

Eagle One Etching Mag Wheel Cleaner

Version number: 1.0

Date of compilation: 2016-09-22

SECTION 1: Identification

1.1 Product identifier

Trade name **Eagle One Etching Mag Wheel Cleaner**

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Consumer uses

1.3 Details of the supplier of the safety data sheet

American Covers, Inc. dba Handstands
102 West 12200 South
84020 Draper
United States

Telephone: 1-800-228-8987 Hours: 8AM-5PM MST
E-mail: Info@handstands.com

1.4 Emergency telephone number

(800) 255-3924 USA, Canada, Puerto Rico, and US Virgin Islands, +1 (813) 248-0585 International

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Substance or mixture corrosive to metals.	Met. Corr. 1.	H290.
Skin corrosion/irritation.	Skin Corr. 1B.	H314.
Serious eye damage/eye irritation.	Eye Dam. 1.	H318.
Carcinogenicity.	Carc. 1A.	H350.

For full text of abbreviations: see SECTION 16.

Skin corrosion produces an irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis.

Additional information

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200) Labeling:

- Signal word **Danger**

- Pictograms



- Hazard statements

H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H350	May cause cancer.

Eagle One Etching Mag Wheel Cleaner

Version number: 1.0

Date of compilation: 2016-09-22

- Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P201	Obtain special instructions before use.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P264	Wash thoroughly after handling.
P280	Wear protective gloves/eye protection/face protection.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

- Hazardous ingredients for labelling

sulphuric acid ... %, ammonium bifluoride, sodium octane-1-sulphonate monohydrate

2.3 Other hazards

Hazards not otherwise classified

Supplemental hazard information.

May be harmful if swallowed (GHS category 5: acutely toxic - oral).

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Hazardous ingredients acc. to GHS			
Name of substance	Identifier	Wt%	Classification acc. to GHS
phosphoric acid	CAS No 7664-38-2	10 - < 25	Met. Corr. 1 / H290 Skin Corr. 1B / H314 Eye Dam. 1 / H318
sodium octane-1-sulphonate monohydrate	CAS No 5324-84-5	1 - < 5	Skin Irrit. 2 / H315 Eye Dam. 1 / H318
ammonium bifluoride	CAS No 1341-49-7	1 - < 5	Acute Tox. 3 / H301 Skin Corr. 1B / H314 Eye Dam. 1 / H318
sulphuric acid	CAS No 7664-93-9	1 - < 5	Skin Corr. 1A / H314 Eye Dam. 1 / H318 Carc. 1A / H350
Alcohol Ethoxylate	CAS No 68439-46-3	1 - < 5	Acute Tox. 4 / H302 Eye Dam. 1 / H318

Eagle One Etching Mag Wheel Cleaner

Version number: 1.0

Date of compilation: 2016-09-22

Hazardous ingredients acc. to GHS			
Name of substance	Identifier	Wt%	Classification acc. to GHS
Sodium dodecyl sulphate	CAS No 151-21-3	< 1	Flam. Sol. 2 / H228 Acute Tox. 4 / H302 Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Eye Dam. 1 / H318 STOT SE 3 / H335
isopropyl alcohol	CAS No 67-63-0	< 1	Flam. Liq. 2 / H225 Eye Irrit. 2 / H319 STOT SE 3 / H336
prop-2-yn-1-ol	CAS No 107-19-7	< 1	Flam. Liq. 3 / H226 Acute Tox. 3 / H301 Acute Tox. 3 / H311 Acute Tox. 3 / H331 Skin Corr. 1B / H314

For full text of abbreviations: see SECTION 16. For the listed ingredient(s), the identity and exact percentage(s) are being withheld as a trade secret.

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

Eagle One Etching Mag Wheel Cleaner

Version number: 1.0

Date of compilation: 2016-09-22

SECTION 5: Fire-fighting measures**5.1 Extinguishing media**

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO₂)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Substance or mixture corrosive to metals.

Hazardous combustion products

Nitrogen oxides (NO_x), Phosphorus oxides (P_xO_y)**5.3 Advice for firefighters**

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advices on how to contain a spill

Covering of drains

Advices on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: Sawdust, Kieselgur (diatomite), Sand, Universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal precautions: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

Eagle One Etching Mag Wheel Cleaner

Version number: 1.0

Date of compilation: 2016-09-22

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation
Use local and general ventilation. Use only in well-ventilated areas.
- Handling of incompatible substances or mixtures
Do not mix with alkali.
- Keep away from
Caustic solutions

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Corrosive conditions
Store in corrosive resistant container with a resistant inner liner.

Control of the effects

Protect against external exposure, such as

Heat, High temperatures, Frost

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)								
Country	Name of substance	CAS No	Notation	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]
US	isopropyl alcohol	67-63-0		PEL	400	980		
US	phosphoric acid ... %	7664-38-2		PEL		1		
US	sulphuric acid ... %	7664-93-9		PEL		1		

Notation

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period unless otherwise specified

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average

Eagle One Etching Mag Wheel Cleaner

Version number: 1.0

Date of compilation: 2016-09-22

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

Physical state	liquid
Color	colorless
Odor	Pleasant
pH (value)	1, acid
Melting point/freezing point	not determined
Initial boiling point and boiling range	90.6 °C at 1,013 hPa
Flash point	not determined
Evaporation rate	not determined
Flammability (solid, gas)	not relevant (fluid)
Explosive limits	not determined
Vapor pressure	not determined
Density	1.1 g/cm ³ at 20 °C
Vapor density	this information is not available
Relative density	1.1 at 20 °C (air = 1)
Solubility(ies)	not determined
Partition coefficient	not determined
Auto-ignition temperature	not determined
Viscosity	not determined

Eagle One Etching Mag Wheel Cleaner

Version number: 1.0

Date of compilation: 2016-09-22

Explosive properties	none
Oxidizing properties	none

SECTION 10: Stability and reactivity**10.1 Reactivity**

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". Substance or mixture corrosive to metals.

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

Oxidizers

Release of flammable materials with:

Light metals (due to the release of hydrogen in an acid/alkaline medium)

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information**11.1 Information on toxicological effects**

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity of components of the mixture					
Name of substance	CAS No	Exposure route	Endpoint	Value	Species
Sodium dodecyl sulphate	151-21-3	oral	LD50	1,200 mg/kg	rat
Sodium dodecyl sulphate	151-21-3	dermal	LD50	>2,000 mg/kg	rat

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Eagle One Etching Mag Wheel Cleaner

Version number: 1.0

Date of compilation: 2016-09-22

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

May cause cancer.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans

Name of substance	CAS No	Classification	Number
isopropyl alcohol	67-63-0	3	Volume 15, Sup 7, 71
sulphuric acid ... %	7664-93-9	1	Volume 54, 100F

Legend

- 1 Carcinogenic to humans
- 3 Not classifiable as to carcinogenicity in humans

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

12.2 Persistence and degradability

Data are not available

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

Eagle One Etching Mag Wheel Cleaner

Version number: 1.0

Date of compilation: 2016-09-22

12.6 Other adverse effects

Endocrine disrupting potential
None of the ingredients are listed.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Relevant provisions relating to waste

List of wastes

Not assigned

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number	3265
14.2 UN proper shipping name	Corrosive liquid, acidic, organic, n.o.s.
14.3 Transport hazard class(es)	
Class	8 (corrosive substances)
14.4 Packing group	II (substance presenting medium danger)
14.5 Environmental hazards	non-environmentally hazardous acc. to the dangerous goods regulations
14.6 Special precautions for user	
There is no additional information.	
14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code	
The cargo is not intended to be carried in bulk.	

Information for each of the UN Model Regulations**Transport of dangerous goods by road or rail (49 CFR US DOT)**

Index number	3265
Proper shipping name	Corrosive liquid, acidic, organic, n.o.s.
- Particulars in the shipper's declaration	UN3265, Corrosive liquid, acidic, organic, n.o.s., (contains: phosphoric acid ... %, ammonium bifluoride), 8, II
Class	8
Packing group	II

Eagle One Etching Mag Wheel Cleaner

Version number: 1.0

Date of compilation: 2016-09-22

Danger label(s) 8



Special provisions (SP) B2, IB2, T11, TP2, TP27

ERG No 153

International Maritime Dangerous Goods Code (IMDG)

UN number 3265

Proper shipping name CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S.

- Particulars in the shipper's declaration UN3265, CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S., (contains: phosphoric acid ... %, ammonium bifluoride), 8, II

Class 8

Packing group II

Danger label(s) 8



Special provisions (SP) 274

Excepted quantities (EQ) E2

Limited quantities (LQ) 1 L

EmS F-A, S-B

Stowage category B

Segregation group 1 - Acids

International Civil Aviation Organization (ICAO-IATA/DGR)

UN number 3265

Proper shipping name Corrosive liquid, acidic, organic, n.o.s.

- Particulars in the shipper's declaration UN3265, Corrosive liquid, acidic, organic, n.o.s., (contains: phosphoric acid ... %, ammonium bifluoride), 8, II

Class 8

Packing group II

Danger label(s) 8

Special provisions (SP) A3, 274

Excepted quantities (EQ) E2

Limited quantities (LQ) 0,5 L

Eagle One Etching Mag Wheel Cleaner

Version number: 1.0

Date of compilation: 2016-09-22

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

SARA TITLE III (Superfund Amendment and Reauthorization Act)

- List of Extremely Hazardous Substances (40 CFR 355) (EPCRA Section 302 and 304)

The List of Extremely Hazardous Substances and Their Threshold Planning Quantities

Name acc. to inventory	CAS No	Notes	Reportable quantity (pounds)	Threshold planning quantity (pounds)
sulphuric acid	7664-93-9		1,000	1000

- Specific Toxic Chemical Listings (40 CFR 372) (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listings

Name acc. to inventory	CAS No	Remarks	Effective date
propargyl alcohol	107-19-7		1994-12-31
isopropyl alcohol	67-63-0	Only persons who manufacture by the strong acid process are subject, no supplier notification.	1986-12-31
Sulfuric acid	7664-93-9	acid aerosols including mists, vapors, gas, fog, and other airborne forms of any particle size	1986-12-31

CERCLA (Comprehensive Environmental Response, Compensation, and Liability Act)

- Section 102(A) Hazardous Substances (40 CFR 302.4)

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
prop-2-yn-1-ol	107-19-7		4	1000 (454)
ammonium bifluoride	1341-49-7		1	100 (45,4)
phosphoric acid ... %	7664-38-2		1	5000 (2270)
sulphuric acid ... %	7664-93-9		1	1000 (454)

Legend

- 1 "1" indicates that the statutory source is section 311(b)(2) of the Clean Water Act
 4 "4" indicates that the source is section 3001 of the Resource Conservation and Recovery Act (RCRA)

Eagle One Etching Mag Wheel Cleaner

Version number: 1.0

Date of compilation: 2016-09-22

Clean Air Act

none of the ingredients are listed

New Jersey Worker and Community Right to Know Act N.J.S.A. 34:5A-1 et. seq.

Right to Know Hazardous Substance List

Name acc. to inventory	CAS No	Remarks	Classifications
propargyl alcohol	107-19-7		F3 R3
ammonium bifluoride	1341-49-7		CO
isopropyl alcohol	67-63-0		F3
phosphoric acid	7664-38-2		CO
SULFURIC ACID (DIHYDROGEN SULFATE)	7664-93-9		CA CO R2

Legend

CA	Carcinogenic
CO	Corrosive
F3	Flammable - Third Degree
R2	Reactive - Second Degree
R3	Reactive - Third Degree

California Environmental Protection Agency (Cal/EPA): Proposition 65 Chemicals known to the State to cause cancer or reproductive toxicity

WARNING! This product contains a chemical known to the State of California to cause cancer.

SULFURIC ACID
7664-93-9

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	3	major injury likely unless prompt action is taken and medical treatment is given
Flammability	0	material that will not burn under typical fire conditions
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protective equipment	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Eagle One Etching Mag Wheel Cleaner

Version number: 1.0

Date of compilation: 2016-09-22

Category	Degree of hazard	Description
Flammability	1	material that must be preheated before ignition can occur
Health	3	material that, under emergency conditions, can cause serious or permanent injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in chapter 2 and 3)

List of relevant phrases (code and full text as stated in chapter 2 and 3).

Code.	Text.
H225.	Highly flammable liquid and vapor.
H226.	Flammable liquid and vapor.
H228.	Flammable solid.
H290.	May be corrosive to metals.
H301.	Toxic if swallowed.
H302.	Harmful if swallowed.
H311.	Toxic in contact with skin.
H314.	Causes severe skin burns and eye damage.
H315.	Causes skin irritation.
H318.	Causes serious eye damage.
H319.	Causes serious eye irritation.
H331.	Toxic if inhaled.
H332.	Harmful if inhaled.
H335.	May cause respiratory irritation.
H336.	May cause drowsiness or dizziness.
H350.	May cause cancer.

Disclaimer

This SDS has been compiled and is solely intended for this product. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.