ITW Permatex 10 Columbus Blvd. Hartford, CT 06106 USA Telephone: 1-87-Permatex (877) 376-2839 Emergency: 800-255-3924 (ChemTel) International Emergency: 00+ 1+ 813-248-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION Product Name: 765-3181 NAPA ULTRA DISC BRAKE CALIPER LUBE (PTX20353) 2 FL.OZ Item No: 21238 Product Type: Lubricant

2. COMPOSITION/INFORMATION ON INGREDIENTS				
Component:	Weight%	ACGIH; TLV-TWA	OSHA PEL	
SYNTHETIC BASE OILS (TRADE SECRET)	>90	Not listed	Not listed	

3. HAZARDS IDENTIFICAT	ION
Toxicity:	May cause eye and skin irritation.
Primary Routes of Entry:	Eye and skin contact, ingestion, inhalation
Signs and Symptoms of Exposure:	Overexposure may cause eye and skin redness.
Aggravated Medical Condition:	Preexisting skin disorders.
4. FIRST AID MEASURES	
Ingestion:	If swallowed, do not induce vomiting - seek medical advice. Never give anything by mouth to an unconscious person.
Inhalation:	Move to fresh air in case of accidental inhalation of vapours. Get medical attention/advice if you feel unwell.
Skin Contact:	Wash off with soap and water. If skin irritation persists, call a physician. Wash contaminated clothing before re-use.
Eye Contact:	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point °F(C°): Recommended Extinguishing Media: Special Fire-Fighting Procedures: Hazardous Products of Combustion: Unusual Fire/Explosion Hazards:

>500°F COC Carbon Dioxide, Dry Chemicals, Foam.

Treat as oil fire. Firefighters should wear self-contained breathing apparatus. Oxides of carbon None.

Lower Explosive Limit: Upper Explosive Limit: Not determined. Not determined.

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures:

Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

7. HANDLING AND STORAGE

Storage: Handling: Store away from heat.

Avoid contact with skin and eyes. Wash thoroughly after handling. Product may cause surfaces to become slippery.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes:	
Skin:	
Ventilation:	

Safety glasses. Neoprene or nitrile gloves recommended. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory Protection:

An approved organic vapor respirator should be worn when exposures are expected to exceed the applicable limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Green semi-solid
Odor:	Mild
Boiling Point:	Not determined.
pH:	Does not apply
Solubility in Water:	Insoluble
Specific Gravity:	0.89
VOC(Wt.%):	0
Vapor Pressure:	Not Determined
Vapor Density (Air=1):	> 1 (air = 1)
Evaporation Rate:	<1 (butyl acetate = 1)

10. STABILITY AND REACTIVITY

Chemical Stability: Hazardous Polymerization: Incompatabilities: Conditions to Avoid: Hazardous Products of Combustion: Stable at normal conditions Will not occur Strong oxidizers Excessive heat, Welding Oxides of carbon

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal:Disposal should be made in accordance with federal, state and local regulations.US EPA Waste Number:NH - Not a RCRA Hazardous Waste Material

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

U.S. Department of Transportation - DOT - 49 CFR (Ground)				
DOT Shipping Name:	Not regulated			
Hazard Class:	None			
UN/ID Number:	None			
IATA (Air)				
Proper Shipping Name:	Not regulated			
Class or Division:	None			
UN/ID Number:	None			
IMDG (Vessel)				
Proper Shipping Name:	Not regulated			
Hazard Class:	None			
UN Number:	None			
Marine Pollutant:	None			

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

NONE

California Proposition 65: No California Prop 65 chemicals are known to be present.

TSCA Inventory Status: All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

 Estimated NFPA Rating:
 HEALTH 1, FLAMMABILITY 1, REACTIVITY 0.

 Estimated HMIS Classification:
 HEALTH 1, FLAMMABILITY 1, PHYSICAL HAZARD 0

 (NFPA is a registered trademark of the National Fire Protection Association)
 HEALTH 1, FLAMMABILITY 1, PHYSICAL HAZARD 0

 (HMIS is a registered trademark of the National Fire Protection Association)
 HEALTH 1, FLAMMABILITY 1, PHYSICAL HAZARD 0

Prepared By:	Denise Boyd, Manager-Environmental, Health & Safety	Revision Date: May 05, 2014
Company:	ITW Permatex 10 Columbus Blvd. Hartford, CT USA 06106	Revision Number: 8
Telephone No.:	1-87-Permatex (877) 376-2839	