

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Date of issue: 01/06/2016 Revision date: 01/06/2016 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : FIC Fuel Injector Cleaner

Product code : 16-FIC

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Gasoline additive

1.3. Details of the supplier of the safety data sheet

The Blaster Corporation 8500 Sweet Valley Drive Valley View, Ohio 44125 - USA T (216) 901-5800 - F (216) 901-5801

www.blasterproducts.com

1.4. Emergency telephone number

Emergency number : Chemtrec (800) 424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flammable liquid 3
Eye irritation 2A
Carcinogenicity 2
Specific target organ toxicity - Single exposure 3
Aspiration toxicity 1

2.2. Label elements

GHS-US labelling

This product is a consumer product and is labeled in accordance with the US Consumer Product Safety Commission regulations which take precedence over OSHA Hazard Communication labeling. The actual container label will not include the label elements below. The labeling below applies to industrial/professional products.

Hazard pictograms (GHS-US)



 \Diamond



GHS02 GHS07

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : Flammable liquid and vapor. Causes serious eye irritation. Suspected of causing cancer. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.

Precautionary statements (GHS-US)

Keep away from heat/sparks/open flames/hot surfaces.— No smoking. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash hands thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/ eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. If exposed or concerned: Get medical advice/attention. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easyto do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3. Other hazards

No additional information available.

2.4. Unknown acute toxicity (GHS-US)

2 % of the mixture consists of ingredient(s) of unknown acute toxicity.

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable.

01/06/2016 EN (English) Page 1



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

3.2 **Mixture**

Name	Product identifier	%	GHS-US classification
Petroleum distillates, hydrotreated light	(CAS No) 64742-47-8	60 - 100	Flam. Liq. 3 Asp. Tox. 1
Isopropyl alcohol	(CAS No) 67-63-0	7 - 13	Flam. Liq. 2 Eye Irrit. 2A STOT SE 3
Solvent naphtha, petroleum, light aromatic	(CAS No) 64742-95-6	1 - 5	Flam. Liq. 3 Skin Irrit. 2 Eye Irrit. 2A Asp. Tox. 1
Cumene	(CAS No) 98-82-8	0.1 - 1	Flam. Liq. 3 Carc. 2 STOT SE3 Asp. Tox. 1

^{*} The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

SECTION 4: First aid measures

Description of first aid measures

First-aid measures afterinhalation

: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical advice/attention if you feel unwell.

First-aid measures after skin contact

: In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.

First-aid measures after eye contact

: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to

do, remove contact lenses, if worn. If irritation persists, get medical attention.

First-aid measures afteringestion

: IDo NOT induce vomiting. Never give anything by mouth to an unconscious person. Get

immediate medical advice/attention.

Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation

: May cause drowsiness, dizziness and central nervous system depression. May cause respiratory tract irritation.

Symptoms/injuries after skin contact

: May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.

Symptoms/injuries after eye contact

Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

Symptoms/injuries afteringestion

: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea orvomiting.

Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media : Dry chemical, foam, carbon dioxide. Unsuitable extinguishing media : Do not use a heavy water stream.

Special hazards arising from the substance or mixture 5.2.

Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon, oxides of nitrogen.

5.3. Advice for firefighters

Methods for cleaning up

: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory Protection during firefighting protection (SCBA). Use water spray to keep fire-exposed containers cool.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

General measures

: Use personal protection recommended in Section 8. Isolate the hazard area and deny entryto unnecessary and unprotected personnel. Eliminate sources ofignition.

Methods and material for containment and cleaning up

For containment

: Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

: Scoop up material and place in a disposal container. Provide ventilation.

01/06/2016 EN (English) 2/6



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

6.3. Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Keep away from sources of ignition - No smoking. Avoid contact with skin and eyes. Avoid breathing gas/mist/vapours/spray. Do not swallow. Handle and open container with care. Use only non-sparking tools. When using do not eat, drink or smoke. Use only outdoors or in a well-ventilated area.

Hygiene measures : Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Keep out of the reach of children. Keep container tightly closed and in a well-ventilated place. Store locked up. Keep cool. Keep away from heat, sparks, and flame.

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personalprotection

8.1. Control parameters

Petroleum distillates, hydrotreated light (64742-47-8)		
USA ACGIH	ACGIH TWA	Not applicable
USA OSHA	OSHA PEL (TWA)	Not applicable
Isopropyl alcohol (67-63-0)		
1104 400111	A O O H L T \ A \ A \ (= = = =)	000

Isopropyl alcohol (67-63-0)		
USA ACGIH	ACGIH TWA (ppm)	200 ppm
USA ACGIH	ACGIH STEL (ppm)	400 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	980 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	400 ppm

Solvent naphtha, petroleum, light aromatic (64742-95-6)		
USA ACGIH	ACGIH TWA	Not applicable
USA OSHA	OSHA PEL (TWA)	Not applicable

Cumene (98-82-8)		
USA ACGIH	ACGIH TWA (ppm)	50 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	245 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	50 ppm

8.2. Exposure controls

Appropriate engineering controls : Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below

recommended exposure limits.

Hand protection : Wear chemically resistant protective gloves.

Eye protection : Wear eye protection.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment; Respirator selection

must be based on known or anticipated exposure levels, the hazards of the product and the

safe working limits of the selected respirator.

Environmental exposure controls : Maintain levels below Community environmental protection thresholds.

Other information : Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid.Appearance: Clear.Colour: Red.

01/06/2016 EN (English) 3/6



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Odour Codour threshold : Aromatic.

Ddour threshold : No data available.

pH : No data available.

Relative evaporation rate (butylacetate=1) : >1

Melting point : No data available. Freezing point : No data available. Boiling point : 76 °C (168.8 °F) : 25 °C (77 °F) [TCC] Flash point Auto-ignition temperature : No data available. Decomposition temperature : No data available. Flammability (solid, gas) : Flammable. Vapour pressure : No data available. Relative vapour density at 20 °C : >1 (Air = 1)Relative density : 0.815 Solubility : Slight.

Log Pow : No data available.

Log Kow : No data available.

Viscosity, kinematic : No data available.

Viscosity, dynamic : No data available.

Explosive properties : No data available.

Oxidising properties : No data available.

Explosive limits : No data available.

9.2. Other information

No additional information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reaction known under conditions of normaluse.

10.2. Chemical stability

Stable under normal storage conditions. May form flammable/explosive vapour-air mixture.

10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normaluse.

10.4. Conditions to avoid

Heat. Excessive water. Incompatible materials.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon, oxides of nitrogen.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Fuel Injector Cleaner		
LD50 oral rat	> 2000 mg/kg	
LD50 dermal rabbit	> 2000 mg/kg	
LC50 inhalation rat	Not available	

Petroleum distillates, hydrotreated light (64742-47-8)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	> 5.2 mg/l/4h



Fuel Injector Cleaner Safety Data Sheet

Safety Data Sheet according to the Hazard Communication Standard (CFR2	9 1910.1200) HazCom 2012.	
Isopropyl alcohol (67-63-0)		
LD50 oral rat	4396 mg/kg	
LD50 dermal rabbit	12870 mg/kg	
LD50 dermal rat	12800 mg/kg	
LC50 inhalation rat	72.6 mg/l/4h	
Solvent naphtha, petroleum, light aromatic (64742-95-6)		
LD50 oral rat	8400 mg/kg	
LD50 dermal rabbit	> 2000 mg/kg	
LC50 inhalation rat	> 5.2 mg/l/4h	
Cumene (98-82-8)		
LD50 oral rat	1400 mg/kg	
LD50 dermal rabbit	> 3160 mg/kg	
LC50 inhalation rat	39000 mg/m³/4h	
Skin corrosion/irritation	: Based on available data, the classification criteria are not met.	
Serious eye damage/irritation	: Causes serious eye irritation.	
Respiratory or skin sensitisation	Based on available data, the classification criteria are not met.	
Germ cell mutagenicity	Based on available data, the classification criteria are not met.	
Carcinogenicity	: Suspected of causing cancer.	
Isopropyl alcohol (67-63-0)		
IARC group	3 - Not classifiable	
Cumene (98-82-8)		
IARC group	2B - Possibly carcinogenic to humans	
National Toxicity Program (NTP) Status	1 - Evidence of Carcinogenicity	
	: Based on available data, the classification criteria are not met.	
Reproductive toxicity Specific target organ toxicity (single exposure)	May cause drowsiness or dizziness.	
	·	
Specific target organ toxicity (repeated exposure)	: Based on available data, the classification criteria are not met.	
Aspiration hazard	: May be fatal if swallowed and enters airways.	
Symptoms/injuries after inhalation	: May cause drowsiness, dizziness and central nervous system depression. May cause respiratory tract irritation.	
Symptoms/injuries after skin contact	: May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.	
Symptoms/injuries after eye contact	: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.	
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea orvomiting.	
SECTION 12: Ecological information	n de la companya de	
12.1. Toxicity		
Ecology - general	: May cause long-term adverse effects in the aquatic environment.	
12.2. Persistence and degradability		
Fuel Injector Cleaner		

Fuel Injector Cleaner	
Persistence and degradability	Not established.

12.3. **Bioaccumulative potential**

Fuel Injector Cleaner	
Bioaccumulative potential	Not established.

12.4. **Mobility in soil**

No additional information available.

Other adverse effects

Effect on ozone layer : No additional information available.

Effect on the global warming : No known ecological damage caused by this product.

01/06/2016 EN (English) 5/6



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

SECTION 13: Disposal considerations

Waste treatment methods

Waste disposal recommendations : This material must be disposed of in accordance with all local, state, provincial, and federal

regulations. The generation of waste should be avoided or minimized wherever possible. Additional information

: Handle empty containers with care because residual vapours are flammable.

SECTION 14: Transport information

In accordance with DOT

14.1. **UN** number

Not regulated for transport

UN-No.(DOT) UN1993

UN proper shipping name

Proper Shipping Name (DOT) Flammable liquids, n.o.s. (Petroleum distillates) LTD QTY

Department of Transportation (DOT) Hazard Classes

Hazard labels (DOT)



Packing group (DOT) Ш

14.3. Additional information

Other information : No supplementary information available.

Special transport precautions : Do not handle until all safety precautions have been read and understood.

SECTION 15: Regulatory information

15.1. US Federal regulations

Isopropyl alcohol (67-63-0)	
Listed on the United States TSCA (Toxic Substan Listed on United States SARA Section 313	ces Control Act) inventory
EPA TSCA Regulatory Flag T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.	
SARA Section 313 - Emission Reporting	1.0 % (only if manufactured by the strong acid process, no supplier notification)

Cumene (98-82-8)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on United States SARA Section 313	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
SARA Section 313 - Emission Reporting	1.0 %

15.2. US State regulations

Fuel Injector Cleaner	
State or local regulations	This product contains a chemical known to the State of California to cause cancer.

SECTION 16: Other information

Indication of changes : None. Date of issue : 01/06/2016 Other information None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

