

Product Name:

SAFETY DATA SHEET

PPE

Idemitsu ATF Type TLS-LV, 12 x 1 Quart Case	
Revision Date: 11-May-2017	Revision Number: 4
1. IDENTIFICATION OF THE SUBSTANCE/PF COMPANY/UNDERTAKING	REPARATION AND OF THE
1.1 Product Identifier	
Product Name:	Idemitsu ATF Type TLS-LV, 12 x 1 Quart Case
Other means of identification	
Product Code:	30040096-75000C020
Synonyms	Not available
1.2 Recommended use of the chemical and restrictions	on use
Recommended Use	Automotive Lubricant
Uses advised against	No information available
1.3. Details of the supplier of the safety data sheet	
Manufactured by	Idemitsu Lubricants America Corporation, 701 Port Rd., Jeffersonville, IN. 47130 Telephone: 812-285-8234, Fax: 812-285-8243, Contact Name: Robin Hutchens, Email: sds@ilacorp.com
24 Hour Emergency Phone Number:	Within USA and Canada: 1 800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

accepted)

2. HAZARDS IDENTIFICATION

2.1 Classification

This material is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) and WHMIS 2015

Acute toxicity - Oral	Not classified
Acute toxicity - Dermal	Not classified
Acute toxicity - Inhalation (Gases)	Not classified
Acute toxicity - Inhalation (Vapors)	Not classified
Acute toxicity - Inhalation (Dusts/Mists)	Not classified
Skin corrosion/irritation	Not classified
Serious eye damage/eye irritation	Not classified
Respiratory sensitization	Not classified
Skin sensitization	Category 1
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Not classified
Specific target organ toxicity (single exposure)	Not classified
Specific target organ toxicity (repeated exposure)	Not classified
Aspiration toxicity	Not classified
Physical hazards	None

2.2. Label elements



Signal word	Warning
Hazard statements	H317 - May cause an allergic skin reaction
Precautionary Statements - Prevention:	P261 - Avoid breathing dust, fume, gas, mist, vapors or spray P280 - Wear protective gloves P272 - Contaminated work clothing should not be allowed out of the workplace
Precautionary Statements - Response:	P321 - Specific treatment (see supplemental first aid instructions on this label) P362 + P364 - Take off all contaminated clothing and wash it before reuse
Skin	P302 + 352 - IF ON SKIN: Wash with plenty of soap and water P363 - Wash contaminated clothing before reuse P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention
Precautionary Statements - Disposal:	P501 - Dispose of contents/ container to an approved waste disposal plant
Hazards not otherwise classified (HNOC)	Not applicable
2.3 Other information	

Other hazards

- May be harmful in contact with skin
- Toxic to aquatic life
- Harmful to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances Not applicable

3.2 Mixtures

Hazardous Components

Chemical Name	CAS No.	Weight-%	US GHS Classification	Notes
Alkyl ester carboxylic acid	68015-93-0	<1	Skin Irrit. 2 (H315)	
			Eye Dam. 1 (H318)	
			Skin Sens. 1 (H317)	

Non-Hazardous Components

Chemical Name	CAS No.	Weight-%
Lubricating Base Stocks	Mixture	85-95

4. FIRST AID MEASURES

4.1 4.1 First Aid Measures

General Advice	If symptoms persist, call a physician. Take a copy of the Safety Data Sheet when going for medical treatment.
Eye Contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If eye irritation persists: Get medical advice/attention.
Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Wash contaminated clothing before re-use. Call a physician immediately.
Inhalation	Move to fresh air in case of accidental inhalation of vapors. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Call a physician immediately.
Ingestion	Do not induce vomiting without medical advice. If vomiting occurs naturally, have casualty lean forward to reduce the risk of aspiration. If symptoms persist, call a physician.
Protection of First-aiders	Use personal protective equipment. Avoid contact with eyes, skin and clothing.
4.2 4.2 Most important symptoms	and effects, both acute and delayed
Symptoms	No information available.
4.3 4.3 Indication of any immediate	e medical attention and special treatment needed
Notes to Physician	Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Flammable Properties	NFPA: Class IIIB Combustible Liquid
5.1 Suitable Extinguishing Media:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment
Unsuitable Extinguishing Media:	Do not use a solid water stream as it may scatter and spread fire.
5.2 Specific Hazards Arising from the Chemical	Keep product and empty container away from heat and sources of ignition.
Hazardous combustion products:	During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and / or irritating. Combustion products may include and are not limited to: Carbon oxides Calcium Oxides (CaOx) Nitrogen oxides (NOx) Oxides of Phosphorus Sulphur oxides
5.3 Protective Equipment and Precautions for Firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists. Use personal protection recommended in Section 8. Ensure adequate ventilation. Remove all sources of ignition.
6.2 Environmental Precautions	
Environmental Precautions	See section 12 for additional ecological information. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not allow material to contaminate ground water system. Do not flush into surface water or sanitary sewer system. Large Spills: Dike far ahead of liquid spill for later recovery and disposal. Prevent entry into waterways, sewers, basements or confined areas.
6.3 Methods and material for conta	inment and cleaning up
Methods for Clean-up	Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceus earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Spill Management	
LARGE SPILLS	Eliminate sources of ignition. Prevent additional discharge of material if possible to do so without hazard. For small spills implement cleanup procedures; for large spills implement cleanup procedures and, if in public area, keep public away and advise authorities. Also, if this product is subject to CERCLA reporting (see Section 15 Regulatory Information) notify the National Response Center.
WATER SPILLS	Prevent liquid entering sewers, watercourses, or low areas. Contain spilled liquid with sand or earth. Recover by pumping or with suitable absorbent. If liquid is too viscous for pumping, scrape up. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.

7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Handling	Do not breathe dusts or mists. Avoid contact with eyes, skin and clothing. Wear protective gloves/protective clothing/eye protection/face protection. Use personal protection recommended in Section 8. Wash hands thoroughly after handling. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product. Should not be released into the environment.
Safe Handling Advice	Wear personal protective equipment. Do not breathe vapors or spray mist. Use product only in closed system.
7.2. Conditions for safe storage, including any incompatibilities	
Storage	Keep in properly labeled containers. Keep container tightly closed in a dry and well-ventilated place.
Technical measures/Precautions	Ensure adequate ventilation. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.
Incompatible Materials and/or Coatings	No information available

B. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Exposure Guidelines

This product does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies.

Other Exposure Guidelines (If Generated)

Chemical Name	OSHA PEL	ACGIH TLV	ACGIH OEL (STEL)	NIOSHT REL TWA	ILA IHG	ILA ROEG	ILA Internal Exposure Limit
Oil mist, mineral	TWA: 5 mg/m ³	TWA: 5 mg/m ³		TWA 5 mg/m ³ ST 10 mg/m ³			

8.2 Exposure controls

Appropriate engineering controls Ensure adequate ventilation, especially in confined areas. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal Protective Equipment

Eye/face protection	Safety glasses equipped with side shields are recommended as minimum protection in
---------------------	--

	industrial settings. If splashes are likely to occur wear tight fitting safety goggles and/or face-shield.
Skin protection	Wear protective gloves/clothing. Long sleeved clothing. Choose the appropriate protective clothing / gloves based on the tasks being performed to avoid exposed skin surfaces. Glove Type: Neoprene, Nitriles
Respiratory protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.
General Hygiene Considerations	When using, do not eat, drink or smoke. Clean equipment, work area and clothing regularly.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance Physical State Odor
Odor Threshold
рН
Melting point / melting range
Boiling point / boiling range
Flash Point
Evaporation Rate
Flammability Limit in Air
Explosion Limits
Vapor Pressure
Vapor Density (Air)
Density
Solubility
Partition Coefficient (n-octanol/water)
Autoignition Temperature
Decomposing Temperature
Viscosity

Red / Clear Liquid Strong No information available Not applicable Not applicable No information available > 165 °C / 329 °F COC ASTM D92 No information available 0.85 g/cm 3 @15°C No information available No information available No information available No information available @ 40C = 22.80 cSt; @ 100C = 5.26 cSt

Other Information

10. STABILITY AND REACTIVITY	
10.1 Reactivity	
Reactivity	The product is chemically stable
10.2 Chemical stability	
Chemical Stability	Stable under recommended storage conditions.
10.3 Possibility of Hazardous Reactions	
Possibility of Hazardous Reactions	None under normal processing.
Hazardous Polymerization	Hazardous polymerisation does not occur.
10.4 Conditions to Avoid	
Conditions to Avoid	Heat, flames and sparks.

10.5 Incompatible Materials

Incompatible Materials

10.6 Hazardous Decomposition Products

Hazardous decomposition products

Thermal decomposition can lead to release of irritating gases and vapors.

11. TOXICOLOGICAL INFORMATION

11.1 Information on likely routes of exposure

May cause irritation of respiratory tract.
May cause slight irritation.
May cause an allergic skin reaction.
May be harmful if swallowed.

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Alkyl ester carboxylic acid	> 2,000 mg/kg (Rat)	> 3,160 mg/kg (Rabbit)	
68015-93-0			

Strong oxidizing agents.

11.2 Information on toxicological effects

Symptoms

No information available

11.3 Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Not classified.
Serious eye damage/eye irritation	Not classified.
Sensitization	May cause an allergic skin reaction.
Mutagenic effects	Not classified.

11.4 Carcinogenicity

Carcinogenicity No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, OSHA or ACGIH.

Legend:

NTP (National Toxicology Program) ACGIH (American Conference of Governmental Industrial Hygienists) IARC (International Agency for Research on Cancer) OSHA (Occupational Safety and Health Administration of the US Department of Labor)

Reproductive Effects	Not classified.
STOT - single exposure	Not classified.
STOT - repeated exposure	Not classified
Aspiration hazard	Not classified.

11.5 Acute Toxicity

The following values are calculated based on chapter 3.1 of the GHS document _.

Product Information (Estimated):

ATEmix (oral)	> 5,000 mg/kg
ATEmix (dermal)	> 2,000 mg/kg
ATEmix (inhalation-dust/mist)	> 5 mg/l

12. ECOLOGICAL INFORMATION

12.1 Ecotoxicity Ecotoxicity effects	Toxic to aquatic life. Harmful to aquatic life with long lasting effects. Plants and animals may experience harmful or fatal effects when coated with petroleum products. Petroleum-based (mineral) lubricating oils normally will float on water. In stagnant or slow-flowing waterways, an oil layer can cover a large surface area. As a result, this oil layer might limit or eliminate natural atmospheric oxygen transport into the water. With time, if not removed, oxygen depletion in the waterway may be sufficient to cause a fish kill or create an anaerobic environment.		
Unknown aquatic toxicity	8.99 % of the mixture consists of component(s) of unknown hazards to the aquatic environment		
12.2 Persistence and degradability	No information available.		
12.3 Bioaccumulation/Accumulation No information available			
12.4. Mobility in soil	No information available		
PBT and vPvB assessment	No information available		
12.5 Other adverse effects:	No information available		

13. DISPOSAL CONSIDERATIONS

Hazard characteristic and regulatory waste stream classification can change with product use. Accordingly, it is the responsibility of the user to determine the proper storage, transportation, treatment and/or disposal methodologies for spent materials and residues at the time of disposition.

Waste Disposal Method	This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.		
Contaminated packaging	Dispose of in accordance with local regulations.		
14. TRANSPORT INFORMATION			
DOT - Non bulk	Not regulated		
<u>DOT - Bulk</u>	Not regulated		

IATA Not regulated

IMDG/IMO

Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA	All ingredients are o	on the inventory or exempt fro	m listing
DSL	All ingredients are on the inventory or exempt from listing		
NDSL	There are ingredients listed on the NDSL Inventory List		
Chemical Name	<u>NDSL</u>	CAS No.	Weight-%
Alkenyl dicarboxylamide	Х	ACC 147376	1-5
Alkyl Phosphites	Х	AAC 151872	<1
ELINCS	Contains an ELINCS substance		
ENCS	All ingredients are on the inventory or exempt from listing		
CHINA	All ingredients are on the inventory or exempt from listing		
KECL	All ingredients are on the inventory or exempt from listing		
PICCS	All ingredients are o	on the inventory or exempt fro	m listing
AICS		Does not comply	
NZIoC		Does not comply	
REACH	All ingredients are o	on the inventory or exempt fro	m listing

USA

Federal Regulations		
	Federal Regulations	

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazardous Categorization

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

CERCLA/SARA 302 & 304

Section 302 & 304 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 355.

Chemical Name	CAS No.	Weight-%	RQ	TPQ
Methyl methacrylate	80-62-6	<0.1	1000 lb final RQ	
			454 kg final RQ	
Benzene	71-43-2	<0.001	10 lb final RQ	
			4.54 kg final RQ	

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

Chemical Name	CAS No.	Weight-%	HAPS data
Methyl methacrylate	80-62-6	<0.1	Х
Benzene	71-43-2	<0.001	Х

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CAS No.	Weight-%	U.S CWA (Clean Water Act)
Methyl methacrylate	80-62-6	<0.1	Х
Benzene	71-43-2	<0.001	Х

State Regulations

California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm

Chemical Name	CAS No.	Weight-%	California Prop. 65		Safe Harbor Limits for Cancer-causing Chemicals (NSRLs)
Benzene	71-43-2	<0.001	Carcinogen Developmental Male Reproductive	24µg/dayoral 49µg/dayinhalation	6.4 μg/day oral 13 μg/day inhalation

State Right-to-Know

Chemical Name	CAS No.	New Jersey
distillates (petroleum), hydrotreated light	64742-55-8	Х
paraffinic		
Petroleum distillates, hydrotreated heavy	64742-54-7	Х
paraffinic		
Alkenyl dicarboxylamide	ACC 147376	Х
Petroleum distillates, solvent dewaxed heavy	64742-65-0	Х
paraffinic		

Chemical Name	CAS No.	Massachusetts
distillates (petroleum), hydrotreated light	64742-55-8	Х
paraffinic		

Chemical Name	CAS No.	Pennsylvania
distillates (petroleum), hydrotreated light paraffinic	64742-55-8	Х
Alkenyl dicarboxylamide	ACC 147376	Х
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0	Х
Amines, polyethylenepoly-, reaction products with succinic anhydride polybutenyl derivitives	68439-80-5	Х

New Jersey Worker and Community Right-to-Know Act:

Under the New Jersey Right-to-Know Act L. 1983 Chapter 315 N.J.S.A. 34:5A-1 et. seq., the product is to be identified as follows: PETROLEUM OIL (Automatic Transmission Fluid)

Canada

This material has been classified in accordance with the WHMIS 2015 regulation

Chemical Name	CAS No.	Weight-%	NPRI
Petroleum distillates, hydrotreated light	64742-47-8	<0.1	Listed
Methyl methacrylate	80-62-6	<0.1	Listed

Diphenylamine	122-39-4	<0.01	Listed
Benzene	71-43-2	<0.001	Listed

Legend

NPRI - National Pollutant Release Inventory

16. OTHER INFORMATI	16. OTHER INFORMATION			
	_ Health: 2	Flammability: 1	Instability: 0	
Prepared By	Lakyn Neumeyer			
Revision Date:	11-May-2017	11-May-2017		
Revision Summary:	New GHS Classification NFPA Code Change PPE Global Inventory Status change SARA 311/312 Hazard change			

Disclaimer:

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet



Product Name:

SAFETY DATA SHEET

PPE

Idemitsu ATF Type TLS-LV, 4 x 5 Quart Case	
Revision Date: 11-May-2017	Revision Number: 4
1. IDENTIFICATION OF THE SUBSTANCE/PRE COMPANY/UNDERTAKING	PARATION AND OF THE
1.1 Product Identifier	
Product Name:	Idemitsu ATF Type TLS-LV, 4 x 5 Quart Case
Other means of identification	
Product Code:	30040096-95300C020
Synonyms	Not available
1.2 Recommended use of the chemical and restrictions or	n use
Recommended Use	Automotive Lubricant
Uses advised against	No information available
1.3. Details of the supplier of the safety data sheet	
Manufactured by	Idemitsu Lubricants America Corporation, 701 Port Rd.,

24 Hour Emergency Phone Number:

Jeffersonville, IN. 47130 Telephone: 812-285-8234, Fax: 812-285-8243, Contact Name: Robin Hutchens, Email: sds@ilacorp.com

Within USA and Canada: 1 800-424-9300 Outside USA and Canada: + 1 703-741-5970 (collect calls accepted)

2. HAZARDS IDENTIFICATION

2.1 Classification

This material is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) and WHMIS 2015

Acute toxicity - Oral	Not classified
Acute toxicity - Dermal	Not classified
Acute toxicity - Inhalation (Gases)	Not classified
Acute toxicity - Inhalation (Vapors)	Not classified
Acute toxicity - Inhalation (Dusts/Mists)	Not classified
Skin corrosion/irritation	Not classified
Serious eye damage/eye irritation	Not classified
Respiratory sensitization	Not classified
Skin sensitization	Category 1
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Not classified
Specific target organ toxicity (single exposure)	Not classified
Specific target organ toxicity (repeated exposure)	Not classified
Aspiration toxicity	Not classified
Physical hazards	None

2.2. Label elements



Signal word	Warning
Hazard statements	H317 - May cause an allergic skin reaction
Precautionary Statements - Prevention:	P261 - Avoid breathing dust, fume, gas, mist, vapors or spray P280 - Wear protective gloves P272 - Contaminated work clothing should not be allowed out of the workplace
Precautionary Statements - Response:	P321 - Specific treatment (see supplemental first aid instructions on this label) P362 + P364 - Take off all contaminated clothing and wash it before reuse
Skin	P302 + 352 - IF ON SKIN: Wash with plenty of soap and water P363 - Wash contaminated clothing before reuse P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention
Precautionary Statements - Disposal:	P501 - Dispose of contents/ container to an approved waste disposal plant
Hazards not otherwise classified (HNOC)	Not applicable
2.3 Other information	

Other hazards

- May be harmful in contact with skin
- Toxic to aquatic life
- Harmful to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances Not applicable

3.2 Mixtures

Hazardous Components

Chemical Name	CAS No.	Weight-%	US GHS Classification	Notes
Alkyl ester carboxylic acid	68015-93-0	<1	Skin Irrit. 2 (H315)	
			Eye Dam. 1 (H318)	
			Skin Sens. 1 (H317)	

Non-Hazardous Components

Chemical Name	CAS No.	Weight-%
Lubricating Base Stocks	Mixture	85-95

4. FIRST AID MEASURES

4.1 4.1 First Aid Measures

General Advice	If symptoms persist, call a physician. Take a copy of the Safety Data Sheet when going for medical treatment.
Eye Contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If eye irritation persists: Get medical advice/attention.
Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Wash contaminated clothing before re-use. Call a physician immediately.
Inhalation	Move to fresh air in case of accidental inhalation of vapors. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Call a physician immediately.
Ingestion	Do not induce vomiting without medical advice. If vomiting occurs naturally, have casualty lean forward to reduce the risk of aspiration. If symptoms persist, call a physician.
Protection of First-aiders	Use personal protective equipment. Avoid contact with eyes, skin and clothing.
4.2 4.2 Most important symptoms	and effects, both acute and delayed
Symptoms	No information available.
4.3 4.3 Indication of any immediate	e medical attention and special treatment needed
Notes to Physician	Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Flammable Properties	NFPA: Class IIIB Combustible Liquid
5.1 Suitable Extinguishing Media:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment
Unsuitable Extinguishing Media:	Do not use a solid water stream as it may scatter and spread fire.
5.2 Specific Hazards Arising from the Chemical	Keep product and empty container away from heat and sources of ignition.
Hazardous combustion products:	During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and / or irritating. Combustion products may include and are not limited to: Carbon oxides Calcium Oxides (CaOx) Nitrogen oxides (NOx) Oxides of Phosphorus Sulphur oxides
5.3 Protective Equipment and Precautions for Firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists. Use personal protection recommended in Section 8. Ensure adequate ventilation. Remove all sources of ignition.
6.2 Environmental Precautions	
Environmental Precautions	See section 12 for additional ecological information. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not allow material to contaminate ground water system. Do not flush into surface water or sanitary sewer system. Large Spills: Dike far ahead of liquid spill for later recovery and disposal. Prevent entry into waterways, sewers, basements or confined areas.
6.3 Methods and material for conta	inment and cleaning up
Methods for Clean-up	Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceus earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Spill Management	
LARGE SPILLS	Eliminate sources of ignition. Prevent additional discharge of material if possible to do so without hazard. For small spills implement cleanup procedures; for large spills implement cleanup procedures and, if in public area, keep public away and advise authorities. Also, if this product is subject to CERCLA reporting (see Section 15 Regulatory Information) notify the National Response Center.
WATER SPILLS	Prevent liquid entering sewers, watercourses, or low areas. Contain spilled liquid with sand or earth. Recover by pumping or with suitable absorbent. If liquid is too viscous for pumping, scrape up. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.

7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Handling	Do not breathe dusts or mists. Avoid contact with eyes, skin and clothing. Wear protective gloves/protective clothing/eye protection/face protection. Use personal protection recommended in Section 8. Wash hands thoroughly after handling. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product. Should not be released into the environment.
Safe Handling Advice	Wear personal protective equipment. Do not breathe vapors or spray mist. Use product only in closed system.
7.2. Conditions for safe storage, including any incompatibilities	
Storage	Keep in properly labeled containers. Keep container tightly closed in a dry and well-ventilated place.
Technical measures/Precautions	Ensure adequate ventilation. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.
Incompatible Materials and/or Coatings	No information available

B. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Exposure Guidelines

This product does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies.

Other Exposure Guidelines (If Generated)

Chemical Name	OSHA PEL	ACGIH TLV	ACGIH OEL (STEL)	NIOSHT REL TWA	ILA IHG	ILA ROEG	ILA Internal Exposure Limit
Oil mist, mineral	TWA: 5 mg/m ³	TWA: 5 mg/m ³		TWA 5 mg/m ³ ST 10 mg/m ³			

8.2 Exposure controls

Appropriate engineering controls Ensure adequate ventilation, especially in confined areas. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal Protective Equipment

Eye/face protection	Safety glasses equipped with side shields are recommended as minimum protection in
Eye/face protection	Safety glasses equipped with side shields are recommended as minimum protection

	industrial settings. If splashes are likely to occur wear tight fitting safety goggles and/or face-shield.
Skin protection	Wear protective gloves/clothing. Long sleeved clothing. Choose the appropriate protective clothing / gloves based on the tasks being performed to avoid exposed skin surfaces. Glove Type: Neoprene, Nitriles
Respiratory protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.
General Hygiene Considerations	When using, do not eat, drink or smoke. Clean equipment, work area and clothing regularly.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance Physical State Odor
Odor Threshold
pH Malificana a international and a second
Melting point / melting range
Boiling point / boiling range
Flash Point
Evaporation Rate
Flammability Limit in Air
Explosion Limits
Vapor Pressure
Vapor Density (Air)
Density
Solubility
Partition Coefficient (n-octanol/water)
Autoignition Temperature
Decomposing Temperature
Viscosity
Viscosity

Red / Clear Liquid Strong No information available Not applicable Not applicable No information available > 165 °C / 329 °F COC ASTM D92 No information available 0.85 g/cm 3 @15°C No information available No information available No information available No information available @ 40C = 22.80 cSt; @ 100C = 5.26 cSt

Other Information

10. STABILITY AND REACTIVITY	
10.1 Reactivity	
Reactivity	The product is chemically stable
10.2 Chemical stability	
Chemical Stability	Stable under recommended storage conditions.
10.3 Possibility of Hazardous Reactions	
Possibility of Hazardous Reactions	None under normal processing.
Hazardous Polymerization	Hazardous polymerisation does not occur.
10.4 Conditions to Avoid	
Conditions to Avoid	Heat, flames and sparks.

10.5 Incompatible Materials

Incompatible Materials

10.6 Hazardous Decomposition Products

Hazardous decomposition products

Thermal decomposition can lead to release of irritating gases and vapors.

11. TOXICOLOGICAL INFORMATION

11.1 Information on likely routes of exposure

Inhalation	May cause irritation of respiratory tract.
Eye contact	May cause slight irritation.
Skin Contact	May cause an allergic skin reaction.
Ingestion	May be harmful if swallowed.

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Alkyl ester carboxylic acid	> 2,000 mg/kg (Rat)	> 3,160 mg/kg (Rabbit)	
68015-93-0			

Strong oxidizing agents.

11.2 Information on toxicological effects

Symptoms

No information available

11.3 Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Not classified.
Serious eye damage/eye irritation	Not classified.
Sensitization	May cause an allergic skin reaction.
Mutagenic effects	Not classified.

11.4 Carcinogenicity

Carcinogenicity No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, OSHA or ACGIH.

Legend:

NTP (National Toxicology Program) ACGIH (American Conference of Governmental Industrial Hygienists) IARC (International Agency for Research on Cancer) OSHA (Occupational Safety and Health Administration of the US Department of Labor)

Reproductive Effects	Not classified.
STOT - single exposure	Not classified.
STOT - repeated exposure	Not classified
Aspiration hazard	Not classified.

11.5 Acute Toxicity

The following values are calculated based on chapter 3.1 of the GHS document _

Product Information (Estimated):

ATEmix (oral)	> 5,000 mg/kg
ATEmix (dermal)	> 2,000 mg/kg
ATEmix (inhalation-dust/mist)	> 5 mg/l

12. ECOLOGICAL INFORMATION

12.1 Ecotoxicity Ecotoxicity effects	Toxic to aquatic life. Harmful to aquatic life with long lasting effects. Plants and animals may experience harmful or fatal effects when coated with petroleum products. Petroleum-based (mineral) lubricating oils normally will float on water. In stagnant or slow-flowing waterways, an oil layer can cover a large surface area. As a result, this oil layer might limit or eliminate natural atmospheric oxygen transport into the water. With time, if not removed, oxygen depletion in the waterway may be sufficient to cause a fish kill or create an anaerobic environment.
Unknown aquatic toxicity	8.99 % of the mixture consists of component(s) of unknown hazards to the aquatic environment
12.2 Persistence and degradability	No information available.
12.3 Bioaccumulation/Accumulation	n No information available
12.4. Mobility in soil	No information available
PBT and vPvB assessment	No information available
12.5 Other adverse effects:	No information available

13. DISPOSAL CONSIDERATIONS

Hazard characteristic and regulatory waste stream classification can change with product use. Accordingly, it is the responsibility of the user to determine the proper storage, transportation, treatment and/or disposal methodologies for spent materials and residues at the time of disposition.

Waste Disposal Method	This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.		
Contaminated packaging	Dispose of in accordance with local regulations.		
14. TRANSPORT INFORMATION			
DOT - Non bulk	Not regulated		
DOT - Bulk	Not regulated		

IATA Not regulated

IMDG/IMO

Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA	All ingredients are on the inventory or exempt from listing		
DSL	All ingredients are on the inventory or exempt from listing		
NDSL	There are ingredients listed on the NDSL Inventory List		
Chemical Name	NDSL	CAS No.	Weight-%
Alkenyl dicarboxylamide	Х	ACC 147376	1-5
Alkyl Phosphites	Х	AAC 151872	<1
ELINCS	Contains an ELINCS substance		
ENCS	All ingredients are on the inventory or exempt from listing		
CHINA	All ingredients are on the inventory or exempt from listing		
KECL	All ingredients are on the inventory or exempt from listing		
PICCS	All ingredients are on the inventory or exempt from listing		
AICS	Does not comply		
NZIoC	Does not comply		
REACH	All ingredients are on the inventory or exempt from listing		

USA

Federal Regulations		
	Federal Regulations	

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazardous Categorization

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

CERCLA/SARA 302 & 304

Section 302 & 304 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 355.

Chemical Name	CAS No.	Weight-%	RQ	TPQ
Methyl methacrylate	80-62-6	<0.1	1000 lb final RQ	
			454 kg final RQ	
Benzene	71-43-2	<0.001	10 lb final RQ	
			4.54 kg final RQ	

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

Chemical Name	CAS No.	Weight-%	HAPS data
Methyl methacrylate	80-62-6	<0.1	Х
Benzene	71-43-2	<0.001	Х

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CAS No.	Weight-%	U.S CWA (Clean Water Act)
Methyl methacrylate	80-62-6	<0.1	Х
Benzene	71-43-2	<0.001	Х

State Regulations

California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm

Chemical Name	CAS No.	Weight-%	California Prop. 65		Safe Harbor Limits for Cancer-causing Chemicals (NSRLs)
Benzene	71-43-2	<0.001	Carcinogen Developmental Male Reproductive	24µg/dayoral 49µg/dayinhalation	6.4 μg/day oral 13 μg/day inhalation

State Right-to-Know

Chemical Name	CAS No.	New Jersey
distillates (petroleum), hydrotreated light	64742-55-8	Х
paraffinic		
Petroleum distillates, hydrotreated heavy	64742-54-7	Х
paraffinic		
Alkenyl dicarboxylamide	ACC 147376	Х
Petroleum distillates, solvent dewaxed heavy	64742-65-0	Х
paraffinic		

Chemical Name	CAS No.	Massachusetts
distillates (petroleum), hydrotreated light	64742-55-8	Х
paraffinic		

Chemical Name	CAS No.	Pennsylvania
distillates (petroleum), hydrotreated light paraffinic	64742-55-8	Х
Alkenyl dicarboxylamide	ACC 147376	X
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0	Х
Amines, polyethylenepoly-, reaction products with succinic anhydride polybutenyl derivitives	68439-80-5	X

New Jersey Worker and Community Right-to-Know Act:

Under the New Jersey Right-to-Know Act L. 1983 Chapter 315 N.J.S.A. 34:5A-1 et. seq., the product is to be identified as follows: PETROLEUM OIL (Automatic Transmission Fluid)

Canada

This material has been classified in accordance with the WHMIS 2015 regulation

Chemical Name	CAS No.	Weight-%	NPRI	
Petroleum distillates, hydrotreated light	64742-47-8	<0.1	Listed	
Methyl methacrylate	80-62-6	<0.1	Listed	

Diphenylamine	122-39-4	<0.01	Listed
Benzene	71-43-2	<0.001	Listed

Legend

NPRI - National Pollutant Release Inventory

16. OTHER INFORMATION					
200	NFPA_	Health: 2	Flammability: 1	Instability: 0	
Prepared By		Lakyn Neumeyer			
Revision Date:		11-May-2017			
Revision Summary:		New GHS Classification NFPA Code Change PPE Global Inventory Status change SARA 311/312 Hazard change			

Disclaimer:

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet