Mastercool Inc.

# A/C Quick Flush Aerosol can

Rev. 2 dated 14<sup>st</sup> September, 2017

Code: 91050, 91051

### **1** IDENTIFICATION OF PREPARATION AND SOCIETY

# 1.1 Product identifier

A/C Quick Flush Code: 91050, 91051

# **1.2** Relevant identified uses of the substance or mixture and uses advised against Type of use: descaling and flushing fluid for air conditioning systems Industry Sector: automotive and refrigeration Application: industrial and professional

1.3 Details of the supplier of the Satety Data Sheet

Mastercool Inc. 1 Aspen Drive Randolph, NJ 07869 USA

# 1.4 Emergency telephone number

+ 39 0322 838319 Hours: 8.30 am - 12.30 pm / 1.30 pm - 5.30 pm Anti-Poison National Centre (24 h /24)

# 2 HAZARDS IDENTIFICATION

## 2.1 Classification of the substance or mixture

This product has classified as dangerous under (CE) 1272/2008 (CLP) Directives and subsequent amendments. Therefore, this preparation requires a safety data sheet according to the (CE) 1907/2006 Regulation and subsequent amendments.

Further information on health and/or environmental hazards can be found in section 11 and 12 of this safety data sheet.

Classification and hazards:

Aerosol 2 H223 Flammable aerosol

H229 Pressurized container: may burst if heated

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways

Skin Sens. 1 H317 May cause an allergic skin reaction

# 2.2 Label elements

Hazard labelling under (EC) 1272/2008 (CLP) Regulation and subsequent amendments



| Dangerous pictograms:         |                                                                                                                           |
|-------------------------------|---------------------------------------------------------------------------------------------------------------------------|
| Signal word                   | Warning                                                                                                                   |
| Hazard statements (H):        | H229 Pressurized container: may burst if heated                                                                           |
|                               | H304 May be fatal if swallowed and enters airways                                                                         |
|                               | H317 May cause an allergic skin reaction                                                                                  |
|                               | EUH066 Repeated exposure may cause skin dryness or cracking                                                               |
| Precautionary statements (P): | P251 Pressurized container – Do not pierce or burn, even after use                                                        |
|                               | P261 Avoid breathing dust/fume/gas/mist/vapours/spray                                                                     |
|                               | P280 Wear protective gloves/protective clothing/eye protection/face protection                                            |
|                               | P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician                                             |
|                               | P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower |
|                               | P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing                |
|                               | P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F                                     |
| Contents:                     | Hydrocarbons C11-C14 cyclic isoalkanes <2% aromatic                                                                       |
|                               | Essences mix                                                                                                              |

# 2.3 Other hazards

Based on available data, the product does not contain any PBT or vPvB substances in percentage greater than 0.1%.

Rev. 2 dated 14<sup>st</sup> September, 2017

### 3 COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous   | ingredients: |
|-------------|--------------|
| 11azai uous | ingreulents. |

| CAS<br>Number | CE<br>Number | Index<br>Number | REACH<br>Registration Number | %<br>[weight] | Name                                                   | Classification                                                  |
|---------------|--------------|-----------------|------------------------------|---------------|--------------------------------------------------------|-----------------------------------------------------------------|
|               | 927-285-2    |                 | 01-2119480162-45-xxxx        | 86-90         | Hydrocarbons C11-C14 cyclic isoalkanes <2%<br>aromatic | Asp. Tox. 1 H304,<br>EUH066                                     |
| 108-65-6      | 203-603-9    | 607-195-00-7    | 01-2119475791-29-xxxx        | 9-10,5        | Acetate of 1-methyl-2-methoxyethyl                     | Flam. Liq. 3 H226                                               |
|               |              |                 |                              | 2-2,5         | Essence mix                                            | Asp. Tox. 1 H304<br>Skin Sens. 1 H317<br>Aquatic Chronic 2 H411 |
| Propellant    |              |                 |                              |               |                                                        |                                                                 |
| 7727-37-9     | 231-783-9    |                 |                              | 11 bar        | Nitrogen                                               | Press. Gas H280                                                 |
|               |              |                 |                              |               |                                                        |                                                                 |

## 4 FIRST AID MEASURES

#### 4.1 Description of first aid measures

EYE CONTACT: Remove contact lenses, if present. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.

SKIN CONTACT: In case of contact with skin, wash immediately with plenty of water. Remove contaminated clothing. If irritation or blistering occurs, call a physician.

INAHLATION: Remove patience from exposure to fresh air. Administer oxygen if necessary. Obtain immediate medical attention. INGESTION: Unlikely route of exposure. As this product is a gas, refer to the section "Inhalation". Do not induce vomiting without medical advice. Obtain immediate medical attention.

# 4.2 Most important symptoms and effects, both acute and delayed

For symptoms and effects caused by the contained substances, see chap. 11

# 4.3 Indication of any immediate medical attention and special treatment needed

In case of accident or if you feel unwell, seek medical advice immediately.

#### 5 FIREFIGHTING MEASURES

### 5.1 Extinguishing media

#### SUITABLE EXTINGUISHING MEDIA

The fire fighting to the conventional kind: carbon dioxide, foam, dry chemical. For leakage and spillage that have not caught fire, nebulized water may be used to disperse the flammable vapours and protect the people involved in stopping the leakage.

#### UNSUITABLE EXTINGUISHING MEDIA

Do not use water jets. Water is not effective to extinguish the fire, nevertheless it can be used to cool closed containers exposed to flames to prevent bursts and explosions.

## 5.2 Special hazards arising from the substance or mixture

#### HAZARDS CAUSED BY EXPOSURE IN CASE OF FIRE

Sealed containers exposed to fire heat may generate overpressure and explode. Avoid breathing products of combustion.

# 5.3 Advice for firefighters

# GENERAL INFORMATION

Cool down with water jets the containers to prevent product decomposition and the development of substances potentially hazardous to health. Always wear full fire prevention. Collect extinguishing water to prevent it from draining into the drain. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

EQUIPMENT

Normal clothing to fight the fire, like a compressed air breathing apparatus open circuit (EN 137), full flame retardant (EN 469), flame-resistant gloves (EN 659) and boots for firefighters (HO A29 or A30).

## 6 ACCIDENTAL RELEASE MEASURE

#### 6.1 Personal precautions, protective equipment and emergency procedures

Eliminate any sources of ignition (cigarettes, flames, sparks, etc.) from the air in which the leak occurred.

If aerosol or vapour are released into the air, use breathing equipment.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures. Do not handle damaged containers or leaked product before donning appropriate protective gear. Block the leakage if there is no hazard.

#### 6.2 Environmental precautions

Provide adequate ventilation in warehouse or closed storage area. Ensure adequate ventilation to the leak affected area. The product must not penetrate the sewers, surface water, ground water and neighbouring areas.

#### 6.3 Methods and material for containment and cleaning up

For liquid products, suck into a suitable container (made of material compatible with the product) and soak up any leaked product with absorbent inert material (sand, vermiculite, diatomeous earth, etc.).

Collect the majority of the remaining material and deposit in containers for disposal.

Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4 Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

## 7 HANDLING AND STORAGE

#### 7.1 Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

### 7.2 Conditions for safe storage, including

Store only in the original container. Store in a well-ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials see section 10 for details.

# 7.3 Specific end use(s)

Descaling and flushing fluid for air conditioning systems.

## 8 EXPOSURE CONTROL / PERSONAL PROTECTION

#### 8.1 Control parameters

# ACETATE OF 1-METHYL-2-METHOXYETHYL

| Threshold | Limit Value | e (TLV)         |     |                     |     |      |                |                                                                                   |
|-----------|-------------|-----------------|-----|---------------------|-----|------|----------------|-----------------------------------------------------------------------------------|
| Туре      | State       | TWA/8h<br>mg/m3 | ррт | STEL/15min<br>mg/m3 | ррт | Note |                |                                                                                   |
| AGW       | DEU         | 270             | 50  | 270                 | 50  |      | Cormonu        | MAK und DAT Worth Listo 2012                                                      |
| MAK       | DEU         | 270             | 50  | 270                 | 50  |      | Germany        | MAK-ullu BAT-Wei le-Liste 2012                                                    |
| VLA       | ESP         | 275             | 50  | 550                 | 100 | skin | Spain          | INSHT - Límites de exposición profesional para agentes<br>químicos en España 2015 |
| VLEP      | FRA         | 275             | 50  | 550                 | 100 | skin | France         | JORF n°0109 du 10 mai 2012 page 8773 texte n° 102                                 |
| WEL       | GRB         | 274             | 50  | 548                 | 100 |      | United Kingdom | EH40/2005 Workplace exposure limits                                               |
| TLV       | GRC         | 275             | 50  | 550                 | 100 |      | Greece         | ΕΦΗΜΕΡΙΣ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ -ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου                                 |
|           |             |                 |     |                     |     |      | (Ελλάδα)       | 19 - 9 Φεβρουαρίου 2012                                                           |
| TLV       | ITA         | 275             | 50  | 550                 | 100 | skin | Italy          | Legislative decree 9 April 2008, n.81                                             |
| OEL       | NLD         | 550             | 50  |                     |     |      | The Nederland  | Databank of the social and Economic Concil of Netherlands                         |
|           |             |                 |     |                     |     |      |                | (SER) Values, AF 2011:18                                                          |
| NDS       | POL         | 260             |     | 520                 |     |      | Poland         | ROZPORZĄDZENIE MINISTRA PRACY I POLITYKI SPOŁECZNEJ z                             |
|           |             |                 |     |                     |     |      |                | dnia 16 grudnia 2011r                                                             |
| NPHV      | SVK         | 275             | 50  | 550                 |     | skin | Slovenia       | NARIADENIE VLÁDY Slovenskej republiky z 20. júna 2007                             |
| ESD       | TUR         | 275             | 50  | 550                 | 100 | skin | Turkey         | 2000/39/EC sayılı Direktifin ekidir                                               |
| OEL       | EU          | 275             | 50  | 550                 | 100 | skin | Europe         | Directive 2009/161/UE; Directive 2006/15/CE; Directive                            |
|           |             |                 |     |                     |     |      |                | 2004/37/CE; Directive 2000/39/CE                                                  |

### 8.2 Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, ensure good ventilation in the workplace through effective local aspiration or bad air vent. Personal protection equipment must comply with the rules in force indicated here below. Provide emergency shower pan with visoculare.

# HAND PROTECTION

Protect your hands with work gloves, category III (see Standard EN 374).

Selection of glove materials, the following factors should be considered: compatibility, degradation, breakthrough time and permeation rate.

In the case of preparations, glove resistance should be tested before use because it is not foreseeable. The gloves have a durability that depends on the duration of exposure and method of use.

SKIN PROTECTION

Use protective working wear with long and safe shoes for professional use of category II (see Directive 89/686/CEE and EN ISO 20344). Wash with water and soap after removal of protective clothes.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion. EYES PROTECTION

Wear airtight protective goggles (see Standard EN 166).

### **RESPIRATORY PROTECTION**

If you exceed threshold value (e.g. TLV-TWA) of one or more of the substances in the preparation, wear filter half face mask "A" type which class (1, 2 or 3) should be chosen according to the limit concentration of use (refer to Standard EN 14387).

In the presence of gases or vapours of various kinds and/or gases or vapours with particles (aerosols, fumes, mists, etc.) combined filters should be provided. Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited. If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in case of emergency, wear open-circuit compressed air-breathing apparatus (in compliance with Standard EN 137) or external airintake breathing apparatus (in compliance with Standard EN 138). For a correct choice of respiratory protection device, see standard EN 529. ENVIRONMENTAL EXPOSURE CONTROLS.

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

# 9 PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

| -  | information on passe physical and electrical ph |                                                                                          |
|----|-------------------------------------------------|------------------------------------------------------------------------------------------|
|    | Appearance                                      | Liquid                                                                                   |
|    | Colour                                          | Colourless                                                                               |
|    | Odour                                           | Orange                                                                                   |
|    | Odour threshold                                 | Not available                                                                            |
|    | рН                                              | Not available                                                                            |
|    | Melting point / Freezing point                  | -60 °C (- 76 °F) @ 101.325 kPa [hydrocarbons c11-c14 cyclic isoalkanes <2% essences mix] |
|    |                                                 | -66 °C (- 87 °F) @ 101.325 kPa [acetate of 1-methyl-2-methoxyethyl]                      |
|    | Initial boiling point                           | 143 °C (289 °F)                                                                          |
|    | Boiling range                                   | 143 - 173 °C (289 – 343 °C)                                                              |
|    | Flash point                                     | 51 °C (124 °F)                                                                           |
|    | Evaporation rate                                | Not available                                                                            |
|    | Flammability of solids and gases                | Not applicable                                                                           |
|    | Lower inflammability limit                      | Not available                                                                            |
|    | Upper inflammability limit                      | Not available                                                                            |
|    | Lower explosive limit                           | 0,6 % (V/V)                                                                              |
|    | Upper explosive limit                           | 7 % (V/V)                                                                                |
|    | Vapour pressure                                 | 0,035 kPa at 20 °C (68 °F) [Hydrocarbons c11-c14 cyclic isoalkanes <2% essences mix]     |
|    |                                                 | 355 Pa at 20 °C (68 °F) [ACETATE OF 1-METHYL-2-METHOXYETHYL]                             |
|    | Vapour density (air = 1)                        | Not available                                                                            |
|    | Relative density                                | 0,755-0,765 g/cc a 20 °C                                                                 |
|    | Solubility                                      | Not available data for mixture                                                           |
|    | Partition coefficient: n-octanol/water:         | Not available data for mixture                                                           |
|    | Auto-ignition temperature                       | 232 °C (450 °F) @ 101.325 kPa [hydrocarbons c11-c14 cyclic isoalkanes <2% essences mix]  |
|    |                                                 | 333 °C (631 °F) @ 101.325 kPa [1,2-dichloropropane]                                      |
|    | Decomposition temperature                       | Not available                                                                            |
|    | Viscosity                                       | 1.75 mm <sup>2</sup> /s [hydrocarbons c11-c14 cyclic isoalkanes <2% essences mix]        |
|    |                                                 | 1.13 - 1.23 mm <sup>2</sup> /s [ACETATE OF 1-METHYL-2-METHOXYETHYL]                      |
|    | Explosive properties                            | Not available data                                                                       |
|    | Oxidizing properties                            | No oxidizing properties                                                                  |
| .2 | Other information                               |                                                                                          |
|    | VOC (Directive 2010/75/CE) :                    | 98,00 % - 744,80 g/litre                                                                 |
|    | VOC (volatile carbon)                           | 80,12 % - 608,87 g/litre                                                                 |

#### 10 STABILITY AND REACTIVITY

#### 10.1 Reactivity

9

There are no particular risks of reaction with other substances in normal conditions of use. ACETATE OF 1-METHYL-2-METHOXYETHYL: stable but with the air it may slowly develop peroxides that explode with an increase in temperature.

### 10.2 Chemical stability

The product is stable in normal conditions of use and storage.

## 10.3 Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air. ACETATE OF 1-METHYL-2-METHOXYETHYL: may react violently with oxidising agents and strong acids and alkaline metals.

## 10.4 Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition. ACETATE OF 1-METHYL-2-METHOXYETHYL: store in an inert atmosphere, sheltered from moisture because it hydrolysis easily.

# 10.5 Incompatible materials

ACETATE OF 1-METHYL-2-METHOXYETHYL: copper, aluminium and their alloys.

# 10.6 Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

# 11 TOXICOLOGICAL INFORMATION

#### 11.1 Information on toxicological effects

In the absence of experimental toxicological data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

The introduction of even small quantities of this liquid into the respiratory system in case of ingestion or vomit may cause bronchopneumonia and pulmonary edema.

Upon contact with the skin causes sensitization (dermatitis). Dermatitis derives as a result of an inflammation of the skin, that begins in the skin areas which repeatedly come into contact with the sensitizing agent. The skin lesions may include erythema, edema, papules, vesicles, pustules, scales, ulcerations and exudative phenomena, which vary depending on the stage of the disease and the affected areas. In the acute phase prevail erythema, edema and exudation. In the chronic stages prevail scales, dryness, ulcerations and skin thickening.

ACETATE OF 1-METHYL-2-METHOXYETHYL: the main way of entry is the skin, whereas the respiratory way is less important owing to the low vapour tension of the product. Concentrations above 100 ppm cause eye irritation, nose and oropharynx. At 1000 ppm disturbance in the equilibrium and severe eye irritation is observed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and ocular irritation on direct contact. No chronic effects have been reported in man.

a) Acute toxicity

| Substance                                           | LD50                     | LD50                       | LC50                       |
|-----------------------------------------------------|--------------------------|----------------------------|----------------------------|
| Substance                                           | (Oral)                   | (Skin)                     | (Inhalation)               |
| Hydrocarbons C11-C14 cyclic isoalkanes <2% aromatic | 5000 - 15000 mg/kg (rat) | 3160 - 5000 mg/kg (rabbit) | (8 h) 41 - 4467 ppm (rat)  |
| Acetate of 1-methyl-2-methoxyethyl                  | 8530 mg/kg (rat)         | > 5000 mg/kg (rat)         | LC0 (3 h) 2000 ppm (mouse) |

#### b) Skin corrosion / skin irritation

<u>Hydrocarbons C11-C14 cyclic isoalkanes <2% aromatic</u>. Method: OECD Guideline 404 - Result: non-irritating <u>Acetate of 1-methyl-2-methoxyethyl</u>. Method: OECD Guideline 404 - Result: non-irritating

c) Serious eyes damages / eyes irritation

<u>Hydrocarbons C11-C14 cyclic isoalkanes <2% aromatic</u>. Method: OECD Guideline 405 - Result: non-irritating <u>Acetate of 1-methyl-2-methoxyethyl</u>. Method: OECD Guideline 405 - Result: non-irritating

d) Respiratory or skin sensitization

<u>Hydrocarbons C11-C14 cyclic isoalkanes <2% aromatic</u>. Method: OECD Guideline 406 (Skin Sensitisation) - Result: non-sensitizing <u>Acetate of 1-methyl-2-methoxyethyl</u>. Method: OECD Guideline 406 (Skin Sensitisation) - Result: sensitizing

e) Germ cell mutagenicity

<u>Hydrocarbons C11-C14 cyclic isoalkanes <2% aromatic</u>. Not classified. Data are conclusive but insufficient for classification <u>Acetate of 1-methyl-2-methoxyethyl</u>. Reverse mutation test - S. typhimurium - Result: negative

f) Cancerogenicity

<u>Hydrocarbons C11-C14 cyclic isoalkanes <2% aromatic</u>. Not classified. Data are conclusive but insufficient for classification <u>Acetate of 1-methyl-2-methoxyethyl</u>. Not identified as a known or anticipated carcinogen by IARC

g) Reproductive toxicity

<u>Hydrocarbons C11-C14 cyclic isoalkanes <2% aromatic</u>. Not classified. Data are conclusive but insufficient for classification <u>Acetate of 1-methyl-2-methoxyethyl</u>. No data available

## h) Specific target organ toxicity (STOT) – single exposure

<u>Hydrocarbons C11-C14 cyclic isoalkanes <2% aromatic</u>. Not classified. Data are conclusive but insufficient for classification <u>Acetate of 1-methyl-2-methoxyethyl</u>. No data available

#### i) Specific target organ toxicity (STOT) - repeated exposure

Hydrocarbons C11-C14 cyclic isoalkanes <2% aromatic. Not classified. Data are conclusive but insufficient for classification Acetate of 1-methyl-2-methoxyethyl. No data available

j) Aspiration hazard

May be fatal if swallowed and enters airways

# 12. ECOLOGICAL INFORMATION

### 12.1 Toxicity

No specific information available, use according to good working practices. Avoid release into the environment. Prevent contamination of soil and water. Inform the competent authorities, should the product reach waterways or sewers or contaminate soil or vegetation. Take measures to reduce or prevent effects on ground water.

| Hydrocarbons C11-C14 cyclic isoalkanes <2% aromatic |                                                   |
|-----------------------------------------------------|---------------------------------------------------|
| LL50 - Fish                                         | > 1000 mg/l/24h                                   |
| LLO – Shellfish                                     | > 1000 mg/l/48h                                   |
| EC50 - Seaweed                                      | > 1000 mg/l/72h (Pseudokirchneriella subcapitata) |
| Acetate of 1-methyl-2-methoxyethyl                  |                                                   |
| LC50 - Fish.                                        | 96 ore: > 100 mg/l                                |
| EC50 – Shellfish                                    | 408 mg/l/48h (Daphnia magna)                      |
| EC50 - Seaweed                                      | > 1000 mg/l/96h (Pseudokirchneriella subcapitata) |

Rev. 2 dated 14<sup>st</sup> September, 2017

#### 12.2 Persistence and degradability

<u>Hydrocarbons C11-C14 cyclic isoalkanes <2% aromatics</u>. Readily biodegradable. <u>Acetate of 1-methyl-2-methoxyethyl</u>. Readily biodegradable.

#### 12.3 Bioaccumulative potential

| Substance                                           | Partition coefficient n-octanol/water | BCF |
|-----------------------------------------------------|---------------------------------------|-----|
| Hydrocarbons C11-C14 cyclic isoalkanes <2% aromatic | No data available                     |     |
| Acetate of 1-methyl-2-methoxyethyl                  | 1,2                                   |     |

## 12.4 Mobility in soil

No data available

## 12.5 Results of PBT and vPvB assessment

Based on available data, the product does not contain any PBT or vPvB substances as a percentage greater than 0.1%.

### 12.6 Other adverse effects

None known

# 13 DISPOSAL CONSIDERATIONS

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations. Avoid littering. Do not contaminate soil, sewers and waterways. Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

#### 14 TRANSPORT INFORMATION

People loading and unloading dangerous goods must be trained on all the risks deriving from these substances and on all actions that must be taken in case of emergencies.

| 14.1 | <b>UN number</b><br>ADR / RID, IMDG, I             | ATA:         | 1950                           |        |                       |                              |
|------|----------------------------------------------------|--------------|--------------------------------|--------|-----------------------|------------------------------|
| 14.2 | UN proper shipping<br>ADR / RID:<br>IMDG:<br>IATA: | name         | AEROSOL<br>AEROSOLS<br>Aerosol |        |                       |                              |
| 14.3 | Transport hazard cla                               | iss(es)      |                                |        |                       |                              |
|      | ADR / RID, IMDG:                                   |              | Class 2.2                      | Label  | $\diamond$            |                              |
|      | IATA:                                              |              | Class 2.2                      | Label  | <b>(Y</b> )           |                              |
| 14.4 | Packing group<br>ADR / RID, IMDG, I                | ATA:         | n.a.                           |        | •                     |                              |
| 14.5 | Environmental haza                                 | rds          |                                |        |                       |                              |
|      | ADR / RID, IMDG, I                                 | ATA:         | NO                             |        |                       |                              |
| 14.6 | Special precautions<br>ADR / RID:<br>IMDG          | for user     | 5-U.                           | Limite | ed quantity 1 L       | Tunnel restriction code (D)  |
|      |                                                    | Storage and  | d handling                     | SW1    | - SW22                | Segregation code: SG69       |
|      | ΙΑΤΑ                                               | Cargo:       |                                | Maxir  | num quantity: 150 kg  | Packaging instructions: 203  |
|      |                                                    | Pass.:       |                                | Maxir  | num quantity: 30 kg G | Packaging instructions: Y203 |
|      |                                                    | Special inst | ructions:                      | A145   | - A167 - A802         |                              |
|      |                                                    |              |                                | /      |                       |                              |

## 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code Not applicable

Rev. 2 dated 14<sup>st</sup> September, 2017

#### 15 REGULATORY INFORMATION

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Seveso category: P3b

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation (CE) 1907/2006: Product point 3-40

Substances in Candidate List (Art. 59 REACH): none

Substances subject to authorisation (Annex XIV REACH)): none

Substances subject to exportation reporting pursuant to (EC) Reg. 689/2008: none

Substances subject to the Rotterdam Convention: none

Substances subject to the Stockholm Convention: none

Healthcare controls: workers exposed to this chemical agent must not undergo health checks according to article 41 of Legislative Decree no. 81 of April 9, 2008, unless the risks related to the workers' health and safety are modest and the article 224 comma 2 is respected.

# 15.2 Chemical safety assessment

No chemical safety assessment has been processed for the mixture and the substances it contains.

#### 16 OTHER INFORMATION

This Material Safety Data Sheet has been made in compliance with the (EU) Directive 2015/830. The information included in this document are based on data reported by the supplier of the mixture on its SDS "500TB9 - K5100" Version 8 dated 21<sup>st</sup> January 2016 and have been integrated based on current and reliable knowledge.

| Classification in accordance with Regulation (CE) n. 1272/2008 | Classification procedure |                              |  |
|----------------------------------------------------------------|--------------------------|------------------------------|--|
| Apropal 2                                                      | H223                     | Bridging principle "Aprocel" |  |
| Aerosol 2                                                      | H229                     | Bridging principle Aerosol   |  |
| Asp. Tox. 1                                                    | H304                     | Method of calculation        |  |
| Skin Sens. 1                                                   | H317                     | Method of calculation        |  |

### Text of H phrases (Hazard statements) and P phrases (Precautionary statements) in section 2 - 3

| Asp. Tox. 1 – H304<br>Skin Sens. 1 – H317<br>Flam. Liq. 3 – H225<br>Acute Tox. Cat. 4 – H302<br>Acute Tox. Cat. 4 – H332<br>Aquatic Chronic 2 – H41<br>Press. Gas – H280<br>H411 | <ul> <li>May be fatal if swallowed and enters airways</li> <li>May cause an allergic skin reaction</li> <li>Highly flammable liquid and vapour</li> <li>Acute toxicity, oral</li> <li>Acute toxicity, inhalation</li> <li>Toxic to aquatic life with long lasting effects</li> <li>Contains gas under pressure; may explode if heated</li> <li>Toxic to aquatic life with long-lasting effects</li> </ul>                                                                                                                                                                                                                                                                                              |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| P210<br>P211<br>P251<br>P261<br>P301+P310<br>P303+P361+P353<br>P304+P340<br>P410+P412                                                                                            | Keep away from heat/sparks/open flames/hot surfaces – No smoking<br>Do not spray on an open flame or other ignition source<br>Pressurized container – Do not pierce or burn, even after use<br>P261 Avoid breathing dust/fume/gas/mist/vapours/spray<br>Wear protective gloves/protective clothing/eye protection/face protection<br>IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician<br>IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower<br>IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing<br>Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F |
| Date of revision                                                                                                                                                                 | 03/2016                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |

New Version prepared by Mariel Srl Print date: 03/2016

#### Abbreviations and acronyms

- ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
- CAS NUMBER: Chemical Abstract Service number
- CE50: Effective concentration (required to induce a 50% effect)
- CLP: Classification Packaging and Labelling (Regulation CE 1272/2008)
- DNEL: Derived No Effect Level
- EC NUMBER: ESIS identificative number (European List of Notified Chemical Substances)
- EmS: Emergency Medical Service
- GHS: Globally Harmonized System of classification and labelling of chemicals
- IC50: Inhibitory Concentration Firfty (50)
- IMDG: International Maritime Dangerous Goods
- INDEX NUMBER: Identificative number included in the Annex VI of the CLP
- LC50: Letal Concentration 50%
- LD50: Letal Dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, Bioaccumalate and Toxic (according to REACH)

Rev. 2 dated 14<sup>st</sup> September, 2017

- PEC: Predicted Environmental Concentration
- PEL: Predicted Exposure Level
- PNEC: Predicted No Effect Concentration
- REACH: Registration Evaluation and Authorisation of Chemicals (Regulation CE 1907/2006)
- RID: Regulation relating to International carriage of Dangerous goods by rail
- TLV: Threshold Limit Value
- TLV-C: Threshold Limit Value Ceiling. The concentration in air that should not be exceeded during any part of the working exposure.
- TWA: Time Weighted Average
- TWA STEL: Time-Weighted Average Short-Term Exposure Limits
- VOC: Volatile Organic Compounds
- vPvB: very Persistent and very Bioaccumulative (according to REACH)
- WGK: Toxic to aquatic organisms (Germany)

# **General Bibliography**

- Regulation (UE) 1907/2006 of the European Parliament (REACH)
- Regulation (UE) 1272/2008 of the European Parliament (CLP)
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- ECHA Agency website

# Notice of liability

This information should not constitute a guarantee for any specific product properties. This information are only a guidance for safe handling, use, processing, storage, transportation, disposal and release and are not to be considered a warranty or a quality specification.

The information contained in the safety data sheet are based on our current knowledge and EU and national laws; they describe the product only with regard to safety requirements. The conditions of the user are beyond our knowledge and control. The product should not be used for purpose other than those specified. It is always the responsibility of the user to take all the necessary measures to comply with the requirements of current legislation. The information contained in this form should not considered as a guarantee of its properties.