

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Product name : Herculiner Truck Bed Liner

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Roll-on Truck Bed Liner

1.3. Details of the supplier of the safety data sheet

Old World Industries, LLC 4065 Commercial Ave. Northbrook, IL 60062 - USA T (847) 559-2000 www.oldworldind.com

1.4. Emergency telephone number

Emergency number : (800) 424-9300; (703) 527 3887 (International)

Chemtrec

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Liq. 3 H226
Acute Tox. 4 (Inhalation:dust,mist) H332
Skin Irrit. 2 H315
Resp. Sens. 1 H334
Skin Sens. 1 H317
Carc. 2 H351
STOT RE 2 H373

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US)





GHS02

GHS07

GHS08

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H226 - Flammable liquid and vapor

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H332 - Harmful if inhaled

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled

H351 - Suspected of causing cancer

H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US) : P201 - Obtain special instructions before use

P202 - Do not handle until all safety precautions have been read and understood P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking

P233 - Keep container tightly closed P242 - Use only non-sparking tools

P260 - Do not breathe fume, mist, spray, vapors P264 - Wash affected areas thoroughly after handling P271 - Use only outdoors or in a well-ventilated area P280 - Wear personal protective equipment as required

P284 - [In case of inadequate ventilation] wear respiratory protection

P303 + P361 + P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower

P304 + P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

P312 - Call a doctor/physician or poison center if you feel unwell

P321 - Specific treatment (see label elements and supplemental first aid instructions on this

10/24/2014 EN (English) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

label)

P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention

P342 + P311 - If experiencing respiratory symptoms: Call a doctor/physician or poison center

P362 - Take off contaminated clothing and wash before reuse

P370 + P378 - In case of fire: Use foam/dry powder/carbon dioxide to extinguish

P403 + P235 - Store in a well-ventilated place. Keep cool

P405 - Store locked up

P501 - Dispose of contents/container, in a safe manner, to to appropriate waste disposal facility,

in accordance with local/regional/national/international regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	% by wt	GHS-US classification
xylene, mixture of isomers	(CAS No) 1330-20-7	<= 29.4	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315
polymethylene polyphenyl isocyanate	(CAS No) 9016-87-9	<= 5	Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general

: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Suspected of causing cancer. Symptoms of poisoning may not appear for several hours. medical observation is recommended for at least 48 hours after accident.

First-aid measures after inhalation

: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Assure fresh air breathing, Call a POISON CENTER/doctor/physician if you feel unwell. Call a POISON CENTER or doctor/physician. Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor/physician if you feel unwell. Provide oxygen treatment if affected person has difficulty breathing. In case of irregular breathing or respiratory arrest provide artificial respiration.

First-aid measures after skin contact

: Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact

: Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for several minutes. Get medical advice/attention. If eye irritation persists: Get medical advice/attention

First-aid measures after ingestion

Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Drink plenty of water. A person vomitting while laying on their back should be turned onto their side.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries

: Causes damage to organs.

Symptoms/injuries after inhalation

 May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause respiratory irritation. Danger of impaired breathing. Danger of pulmonary oedema.

Symptoms/injuries after skin contact

: Causes skin irritation.

Symptoms/injuries after eye contact

: Causes serious eye irritation.

Symptoms/injuries after ingestion

: Nausea. Gastrointestinal complaints. Dizziness.

10/24/2014 EN (English) 2/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.3. Indication of any immediate medical attention and special treatment needed

If swallowed or in case of vomitting, danger of entering the lungs. Severe allergic skin reaction, bronchial spasms and anaphylactic shock are possible. In cases of irritation to the lungs, initial treatement with cortical steroid inhalants. If necessary oxygen respiration treatment. Treat skin and mucous membrane with anithistamine and corticoid preparations. Contains diphenylmethanediisocyanate, isomers and homologues. May produce an allergic reaction.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapor. During heating or in case of fire poisonous gases are produced.

Explosion hazard : May form flammable/explosive vapor-air mixture.

Reactivity : Cures with exposure to water vapor.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No

smoking. Isolate area and prevent access.

6.1.1. For non-emergency personnel

Protective equipment : Use respiratory protective device against the effects of fumes, dust, aerosol.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection. Refer to section 8.2.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Allow to solidify. Pick up mechanically. Dispose contaminated material as wasted according to

Section 13. Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents.

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect

spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Hygiene measures

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor

: Wash affected areas thoroughly after handling. Contaminated work clothing should not be

allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical, lighting, ventilating

container and receiving equipment. Ose explosion-proof electrical, lighting, ventilating

equipment.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Direct sunlight.,

Heat sources. Keep container tightly closed. Store in a dry place. Store away from foodstuffs.

Protect from humidity and water.

Incompatible products : Keep away from strong acids, strong bases and oxidizing agents.

10/24/2014 EN (English) 3/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Herculiner Truck Bed Liner		
SUPPLIER	TWA (mg/m³)	0.045 mg/m³ Limits not to be exceeded at any time.
SUPPLIER	TWA (ppm)	0.005 ppm Limits not to be exceeded at any time.
SUPPLIER	Remark	Contains Isocyanate (as - NCO) which is an ingredient with limit values that require monitoring at the workplace

xylene, mixture of isomers (1330-20-7)		
USA ACGIH	ACGIH TWA (ppm)	100.00 ppm
USA ACGIH	ACGIH STEL (ppm)	150.00 ppm
USA ACGIH	Remark (ACGIH)	Upper Respiratory Tract & eye irritant; Central Nervous System impairment
USA OSHA	OSHA PEL (TWA) (mg/m³)	435.00 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	100.00 ppm

8.2. Exposure controls

Personal protective equipment : Avoid all unnecessary exposure. Gloves. Safety glasses. High gas/vapor concentration: gas mask.







Hand protection : Wear protective gloves.

Eye protection : Chemical goggles or safety glasses.
Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Combined Organic Vapor and Particulate Respirator is recommended for use during all

processing activities.

Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Pigment.
Color : Black

Odor : Petroleum-like odor
Odor threshold : No data available
Relative evaporation rate (butylacetate=1) : No data available
Freezing point : No data available
Boiling point : 154 °C (309 °F)
Flash point : 27 °C (81 °F (TCC))

Auto-ignition temperature : 400 °C

Decomposition temperature : No data available Flammability (solid, gas) : No data available

Vapor pressure : $8 - 9 \text{ mm Hg (at } 25 \,^{\circ}\text{C} / 77 \,^{\circ}\text{F})$

Relative vapor density at 20 °C : 3 (at 68 °F)

Specific Gravity : 1.06 (.865 Xylene Only)

Density : 1.03 g/cm³

Solubility : Water: Forms solid gel
Log Pow : No data available

10/24/2014 EN (English) 4/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Log Kow : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidizing properties : No data available
Explosive limits : 1 - 7 vol %

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Cures with exposure to water vapor.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Germ cell mutagenicity

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Strong acids. Strong bases. Oxidizing agent. water.

10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide. May release flammable gases. fume. Isocyanates. Nitrogen oxides. Hydrogen cyanide (prussic acid).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Harmful if inhaled.

xylene, mixture of isomers (1330-20-7)	
LD50 oral rat	3523 - 8600 mg/kg (3523 mg/kg bodyweight; >4000 mg/kg bodyweight; Rat; Rat; Rat; Experimental value; Experimental value)
LD50 dermal rabbit	> 4,200 mg/kg bodyweight (Rabbit; Experimental value,Rabbit; Experimental value)
LC50 inhalation rat (mg/l)	29 mg/l/4h (27.57 mg/l/4h; Rat; Rat; Experimental value; Experimental value,27.57 mg/l/4h; Rat; Rat; Experimental value; Experimental value)
ATE US (oral)	3,523 mg/kg bodyweight
ATE US (dermal)	1,100 mg/kg bodyweight
ATE US (gases)	4,500 ppmv/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust,mist)	2 mg/l/4h

polymethylene polyphenyl isocyanate (9016-87-9)	
LD50 oral rat	> 10,000 mg/kg (Rat; Literature study)
LD50 dermal rabbit	> 5,000 mg/kg (Rabbit; Literature study)
ATE US (gases)	4,500 ppmv/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust,mist)	2 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Not classified

Respiratory or skin sensitisation : May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic

skin reaction.

: Not classified

Carcinogenicity : Suspected of causing cancer.

xylene, mixture of isomers (1330-20-7)	
IARC group	3 - Not classifiable

10/24/2014 EN (English) 5/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

polymethylene polyphenyl isocyanate (9016-87-9)		
IARC group	3 - Not classifiable	
Reproductive toxicity	· Not classified	

Reproductive toxicity : Not classified Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated

exposure)

: May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

Potential Adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met.

Symptoms/injuries after inhalation : May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic

skin reaction. May cause respiratory irritation. Danger of impaired breathing. Danger of

pulmonary oedema.

Symptoms/injuries after skin contact : Causes skin irritation.

Symptoms/injuries after eye contact : Causes serious eye irritation.

Symptoms/injuries after ingestion : Nausea. Gastrointestinal complaints. Dizziness.

SECTION 12: Ecological information

12.1. Toxicity

xylene, mixture of isomers (1330-2	20-7)
LC50 fish 1	14 mg/l (96 h; Lepomis macrochirus; Lethal)
EC50 Daphnia 1	150 mg/l (24 h; Daphnia magna)
LC50 fish 2	4 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
EC50 Daphnia 2	7 mg/l (48 h; Daphnia magna)
Threshold limit algae 1	72 mg/l (336 h; Selenastrum capricornutum; Growth)
Threshold limit algae 2	10 mg/l (72 h; Skeletonema costatum)

polymethylene polyphenyl isocyanate (9016-87-9)	
LC50 other aquatic organisms 1	> 1,000 mg/l (96 h)
Threshold limit other aquatic organisms 1	> 1,000 mg/l (96 h)

12.2. Persistence and degradability

xylene, mixture of isomers (1330-20-7)		
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Photolysis in the air.	
polymethylene polyphenyl isocyanate (9016-87-9)		
Persistence and degradability	Not readily biodegradable in water. Hydrolysis in water. No (test)data on mobility of the substance available.	

12.3. Bioaccumulative potential

xylene, mixture of isomers (1330-20-7)		
BCF fish 1	15 8 weeks; Salmo gairdneri (Oncorhynchus mykiss)	
BCF fish 2	7 - 26 (8 weeks; Oncorhynchus mykiss)	
Log Pow	3.2 (20 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).	

polymethylene polyphenyl isocyanate (9016-87-9)	
BCF fish 1	1 (Pisces)
Bioaccumulative potential	Not bioaccumulative.

12.4. Mobility in soil

xylene, mixture of isomers (1330-20-7)	
Ecology - soil	May be harmful to plant growth, blooming and fruit formation.

12.5. Other adverse effects

Effect on ozone	layer	:	No	additional	informatio	n av	/ailab	le
-----------------	-------	---	----	------------	------------	------	--------	----

10/24/2014 EN (English) 6/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Effect on global warming : No known ecological damage caused by this product.

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of

contents/container, in a safe manner, to an approved waste disposal site in accordance with

local/regional/national regulations.

Additional information : Handle empty containers with care because residual vapors are flammable.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with DOT

Not a dangerous good in sense of transport regulations

Other information : DOT Consumer Commodity Exemption (Part 172,150) Outer Packaging: "Consumer Commodity

- ORM-D" and ISO orientation arrows. Pallets: If "Consumer Commodity" on outer packaging is visibile lableling not required. Otherwise label as "Consumer Commodity." Container/Trailer:

None required.

ADR

No additional information available

Transport by sea

Limited quantities (IMDG) : IMDG Exemption for Limited Quantities (IMDG 18.3, 3.26)

Outer Packaging: (No requirements)

Pallets: Dangerous Goods in Limited Quantities (Class 3 Flammable)

Container: "Limited Quantities'

Air transport

Instruction "passenger" - Limited quantities

(ICAO)

: IATA Limited Quantities Exemption (Part 2.8) For Shipping of product 10 Liters and Under in one Package: Packing Instruction Y309 (No UN Packaging Required). Labels Required:Paint, Flammable Liquid, 3, ISO orientation arrows, shipper and consignee information, and the statement "LTD. QTY". For Shipping of product over 10 Liters in one Package:Packing Instruction 309 or 310 dependent aircraft type (UN Packaging Required). Labels Required: Paint, Flammable Liquid, 3, ISO orientation arrows (cargo only aircraft label if applicable), shipper and consignee information.

SECTION 15: Regulatory information

15.1. US Federal regulations

Herculiner Truck Bed Liner	
EPA TSCA Regulatory Flag	9016-87-9 diphenylmethanediisocyanate, isomers and homologues CBD
SARA Section 302 Threshold Planning Quantity (TPQ)	No
SARA Section 311/312 Hazard Classes	Section 311 Yes, Section 312 Yes
SARA Section 313 - Emission Reporting	9016-87-9 diphenylmethanediisocyanate, isomers and homologues

15.2. International regulations

CANADA

WHMIS Classification



Class B Division 3 -Combustible Liquid

Herculiner Truck Bed Liner	
WHMIS Classification	Class B Division 3 - Combustible Liquid

10/24/2014 EN (English) 7/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC or 1999/45/EC

Not classified

15.2.2. National regulations

No additional information available

15.3. US State regulations

xylene, mixture of isomers (1330-20-7)

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Massachusetts - Right To Know List

SECTION 16: Other information

Full text of H-phrases:

Acute toxicity (dermal), Category 4		
Acute toxicity (inhal.), Category 4		
Acute toxicity (inhalation:dust,mist) Category 4		
Carcinogenicity, Category 2		
Serious eye damage/eye irritation, Category 2A		
Flammable liquids, Category 3		
Sensitisation — Respiratory, category 1		
Skin corrosion/irritation, Category 2		
Sensitisation — Skin, category 1		
Specific target organ toxicity — Repeated exposure, Category 2		
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation		
Flammable liquid and vapor		
Harmful in contact with skin		
Causes skin irritation		
May cause an allergic skin reaction		
Causes serious eye irritation		
Harmful if inhaled		
May cause allergy or asthma symptoms or breathing difficulties if inhaled		
May cause respiratory irritation		
Suspected of causing cancer		
May cause damage to organs through prolonged or repeated exposure		

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt

medical attention is given.

NFPA fire hazard : 3 - Liquids and solids that can be ignited under almost all

ambient conditions.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.



HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 3 Serious Hazard
Physical : 0 Minimal Hazard

SDS GHS US (GHS HazCom 2012) OWI

10/24/2014 EN (English) 8/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Old World Industries, LLC makes no warranty, representation or guarantee as to the accuracy, sufficiency or completeness of the material set forth herein. It is the user's responsibility to determine the safety, toxicity and suitability of his own use, handling and disposal of this product. Since actual use by others is beyond our control, no warranty, expressed or implied, is made by Old World Industries, LLC as to the effects of such use, the results to be obtained or the safety and toxicity of this product, nor does Old World Industries, LLC assume liability arising out of the use by others of this product referred to herein. The data in this SDS relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.

10/24/2014 EN (English) 9/9