



TURTLE WAX, INC.
2250 W. Pinehurst Blvd., STE 150
Addison, IL 60101

SAFETY DATA SHEET

1. Product and Company Identification

1.1 Product Identifier

Product Name: Turtle Wax ICE Premium Car Care Paste Wax
Product Code (SKU): T465R (50300)

1.2 Relevant Identified Uses Of The Substance

Product Use: Automotive Wax, Polish, Sealant & Glaze – Hard Paste Wax

1.3 Details of the Supplier of the SDS

Company Name: Turtle Wax, Inc.
Street Address: 2250 W. Pinehurst Blvd., Suite 150
City, State, Zip Code: Addison, IL 60101

1.4 Emergency Telephone Numbers

Phone Number: 1(630)455-3700
Fax Number: 1(630)455-3868
Transportation: 1(800)424-9300 (CHEMTREC)
Medical Assistance: Call your local Poison Control Center

2. Hazard Identification:

2.1 Classification of the Substance or Mixture

Hazard Classification: Flammable Solid 1
Skin Irritation 2
Eye Irritation 2A
Skin Sensization 2

2.2 Label Elements



Pictogram:

Signal Word: Danger
Hazard Statement: Flammable Solid. Causes skin irritation. Causes serious eye irritation.

Precautionary Statement: Keep away from heat, sparks, open flames, or hot surfaces. No smoking. Ground container and receiving equipment. Wear protective gloves, glasses, and face protection to avoid contact. Wash hands thoroughly after handling. Avoid breathing fumes and vapors. If on skin, wash thoroughly with soap and water. Remove contaminated clothing and footwear, and launder before re-use. If skin irritation or rash occurs, seek medical attention. If in eyes, rinse thoroughly with water for 15 minutes. Remove contact lenses if present. If eye irritation persists, seek medical

attention. Dispose of containers in accordance with local, state, and federal regulations.

2.3 Other Hazards

Description of additional HNOC: none

3. Information on Ingredients:

3.1 Substance not applicable

3.2 Mixture

<u>Component</u>	<u>CAS Number</u>	<u>Concentration (wt%)</u>
Petroleum Distillates (Hydrotreated Light Distillates - Spirits)	64742-47-8	30-60%
Petroleum Distillates (Hydrotreated Light Distillates - Solvent)	64742-47-8	10-30%
Polydimethyl Siloxanes	63148-62-9	5-15%
Cyclopentasiloxane	541-02-6	5-15%
Aminofunctional Siloxanes	67923-07-3	0.5-1.5%

4. First Aid Measures:

4.1 Description of First Aid Measures

Inhalation: Remove to fresh air and promote deep breathing. Get medical attention if effects persist.

Skin: In case of skin contact, wash thoroughly with soap and water. Remove contaminated clothing and foot wear. Wash clothing before re-use. If irritation persists, get medical attention.

Eyes: In case of eye contact, immediately flush eyes with plenty of water for 15 minutes. Remove contact lenses if worn. If irritation persists, get medical attention

Ingestion: If swallowed, do not induce vomiting. Never give anything by mouth to an unconscious person. Call a poison control facility of physician immediately.

4.2 Most important symptoms and effects – acute and chronic

Inhalation: May cause respiratory tract irritation.

Skin: Cause skin irritation. Symptoms may include redness, drying, de-fatting, cracking, or dermatitis.

Eyes: Cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with redness and swelling.

Ingestion: May be harmful if swallowed. May cause stomach distress, nausea, and vomiting.

4.3 Indication of any immediate medical attention and special treatment

Symptoms may not appear immediately. Seek medical attention if effects persist and you feel unwell.

5. Fire Fighting Measures:

5.1 Extinguishing media

Water spray, carbon dioxide, dry chemical, and alcohol foam

5.2 Special hazards arising from the substance or mixture

CO₂, CO, and hydrocarbons

5.3 Advice for Fire Fighters

Keep up wind of fire. Wear full firefighting turn out gear (full bunker gear) and respiratory protection (SCBA). See Section 8 for personal protection.

6. Accidental Release Measures:

6.1 Personal precautions, protective equipment, and emergency procedures

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.2 Methods and materials for containment and clean up

For containment: Contain and absorb spill with inert material. Place in suitable container for disposal. Spilled material may be slippery.

For clean up: Take up material and place in a suitable container. Provide adequate ventilation. Spilled material may be slippery.

7. Handling and Storage

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Do not swallow. Do not eat, drink or smoke while handling. Wash hands with soap and water after handling. Launder all clothing and foot wear before re-use. Residual vapors are flammable.

7.2 Conditions for safe storage including incompatibilities

Keep out of reach of children. Keep container tightly closed. Store in a well ventilated place. Do not store above 49°C (120°F). Keep open material grounded.

7.3 Specific end uses

Shelf Life: Shelf life is considered to be 7 – 10 years when properly stored and kept closed.

8. Exposure Control/Personal Protection:

8.1 Control parameters

<u>Exposure Limits</u>	<u>8 hr TWA:</u>	<u>(OSHA PEL)</u>	<u>(ACGIH TWA)</u>
Petroleum Distillates Stoddard solvent		500 ppm	200 ppm
Petroleum Distillates Hydrotreated Light		100 ppm	200 ppm
Polydimethyl Siloxanes		not applicable	not applicable
Cyclopentasiloxane		not applicable	not applicable
Aminofunctional Siloxanes		not applicable	not applicable

8.2 Exposure controls

Use adequate ventilation to keep exposure below recommended limits. Ensure that eye wash station and safety shower are close to work station.

Hand Protection Equipment: Wear chemical resistant gloves, face shield, and clothing to prevent skin contact.

Eye Protection Equipment: Wear safety glasses or splash goggles to prevent eye contact.

Skin and Body Protection: Wear suitable protective clothing.

Respiration/Ventilation Protection Requirements: Provide good ventilation.

Ingestion Protection Requirements: Do not eat, drink or smoke while handling. Wash hands with soap and water after handling. Launder all clothing and foot wear before re-use.

9. Physical And Chemical Properties:

9.1 Information of basic chemical and physical properties

Physical Form:	hard cake paste wax
Color:	tan opaque
Odor:	typical fruity
Odor Threshold:	not available
pH:	none (anhydrous)
Melting Point/Freeze Point:	80°C (175°F)
Initial Boiling Point:	163°C (320°F)
Flash Point (Seta Closed Cup):	>93°C (200°F)
Flammability Limits:	Explosive Limits: Upper: 6.0% Lower: 0.6%
Evaporation Rate:	not available
Flammability Solid/Gas:	not applicable
Vapor Pressure:	not available
Vapor Density:	not available
Specific Gravity:	0.816
Solubility in Water:	insoluble
Auto Ignition Temperature:	not available
Partition coefficient (n/octonol/water):	not available
Viscosity:	paste structure

9.2 Other information

%NVM by Weight:	39.0%
%VOC Content (California):	40.0%

10. Stability and Reactivity:

10.1 Reactivity

Does not react under normal conditions

10.2 Chemical stability

Stable

10.3 Possibility of hazardous reactions

Does not react under normal conditions

10.4 Conditions to avoid

Heat and incompatible materials

10.5 Incompatible materials

Strong oxidizers such as bleach and peroxides

10.6 Hazardous decomposition products

CO₂, CO and hydrocarbons

11. Toxicological Information:

11.1 Information on Toxicological effects

Turtle Wax ICE Premium Car Care Paste Wax

LD50 – Oral Rat >2000 mg/Kg
LD50 – Dermal Rat >2000 mg/Kg
LC50 – Inhalation Rat >20 mg/L (4 hr)

Petroleum Distillate Stoddard Solvent (8052-41-3)

LD50 – Dermal Rat >3000 mg/Kg
LC50 – Inhalation Rat 5.5 mg/L (8 hr)

Petroleum Distillate Hydrotreated Light (64742-47-8)

LD50 – Oral Rat >5000 mg/Kg
LD50 – Dermal Rat >2000 mg/Kg
LC50 – Inhalation Rat 5.2 mg/L (4 hr)

Cyclopentasiloxane (541-02-6)

LD50 – Oral Rat >20000 mg/Kg
LD50 – Dermal Rat >10 ml/Kg
LC50 – Inhalation Rat 8.67 mg/L (4 hr)

Skin corrosion/irritation	Causes skin irritation
Serious eye damage/irritation	Causes serious eye irritation
Respiratory or skin sensitization	May cause an allergic skin reaction
Germ cell mutagenicity	Based on available data, classification data are not met
Carcinogenicity	Based on available data, classification data are not met
Reproductive toxicity	Based on available data, classification data are not met
Specific target organs – single exposure	Based on available data, classification data are not met
Specific target organs – repeated exposure	Based on available data, classification data are not met
Aspiration hazard	Based on available data, classification data are not met
Symptoms/injuries after inhalation	May cause respiratory tract irritation
Symptoms/injuries after skin contact	Cause skin irritation. Symptoms may include redness, drying, de-fatting, cracking, or dermatitis
Symptoms/injuries after eye contact	Cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with redness and swelling.
Symptoms/injuries after ingestion	May be harmful if swallowed. May cause stomach distress, nausea, and vomiting.

12. Ecological Information:

12.1 Toxicity

Not recommended for release into aquatic systems without treatment

12.2 Persistence and degradability

Not established

12.3 Bioaccumulative potential

Not established

12.4 Mobility in soil

Not established

12.5 Other adverse effects

None known

13. Disposal Considerations:**13.1 Waste treatment methods****RCRA Hazardous Waste:**

Classified as a RCRA hazardous waste – D-001 (ignitable)

Waste Disposal Method:

Dispose of in accordance with local, state and federal regulations

Waste Disposal Vessel:

Metal drums.

14. Transportation Information:**14.1 UN number**

UN1325

14.2 UN Proper shipping name

Flammable solid, Organic, N.O.S., (Hydrotreated Light Distillates)

14.3 Transport Hazard class

4.1

14.4 Packaging group

PG-II

14.5 Marine Pollutant

No

14.6 Transportation in Bulk

Not applicable

14.7 Special precautions

Read and understand all safety and hazard instructions.

15. Regulatory Information:**15.1 US Federal Regulations**

TSCA Status: All ingredients are commercially available and listed by the manufacturer under TSCA.

15.2 Foreign Regulations

Canadian Status: All materials contained in this product are listed on the Canadian Domestic Substance List (DSL). Consult Turtle Wax, Inc. regarding status of ingredients.

European Union: All materials contained in this product are listed on EINECS.

AICS: All materials are registered for AICS (Australia) except for the following:
Alkyl Modified Silicone Polymer Wax – 192390-10-6

15.3 State Regulations

State Regulatory Information:

The following chemicals are specifically listed by individual states; other product specific health and safety data in other sections of the SDS may also be applicable for state requirements. For details on your regulatory requirements, contact the appropriate agency in your state.

California Prop 65:

<u>CAS Number</u>	<u>Concentration</u>	<u>State Code</u>
None		

15.4 HMIS & NFPA Classifications

HMIS Classification:	Health	2
	Flammability	2
	Reactivity	0
NFPA Classification:	Health	2
	Flammability	2
	Reactivity	0

16. Other Information:

Reason For Issue	Address Update
Prepared By	James Heidel
Preparer's Title	Technical Director, R&D
SDS Administrator	Jean Mayszak - Technical Compliance Manager, R&D
Approval Date	February 10, 2017
Supersedes Date	September 17, 2015
Revision Number	A – 5

This information is, to the best of Turtle Wax, Inc.'s knowledge and belief, accurate and reliable. However, no representation, warranty, or guarantee is made to its accuracy, reliability or completeness.

It is the user's responsibility to satisfy oneself as to the suitability and completeness of such information for their own particular use.