



Revision Number: 005.0

Issue date: 08/06/2014

**1. PRODUCT AND COMPANY IDENTIFICATION**

|                               |   |                     |                |
|-------------------------------|---|---------------------|----------------|
| <b>Product name:</b>          | <b>LOCTITE PC 7226 A RESIN known as Nordbak Pneu Wear RESIN</b> | <b>IDH number:</b>  | 702258         |
| <b>Product type:</b>          | Epoxy resin   | <b>Item number:</b> | 98383_10241000 |
| <b>Restriction of Use:</b>    | None identified   | <b>Region:</b>      | United States  |
| <b>Company address:</b>       | <b>Contact information:</b>                                     |                     |                |
| Henkel Corporation            | Telephone: (860) 571-5100                                       |                     |                |
| One Henkel Way                | MEDICAL EMERGENCY Phone: Poison Control Center                  |                     |                |
| Rocky Hill, Connecticut 06067 | 1-877-671-4608 (toll free) or 1-303-592-1711                    |                     |                |
|                               | TRANSPORT EMERGENCY Phone: CHEMTREC                             |                     |                |
|                               | 1-800-424-9300 (toll free) or 1-703-527-3887                    |                     |                |
|                               | Internet: www.henkelna.com                                      |                     |                |

**2. HAZARDS IDENTIFICATION****EMERGENCY OVERVIEW**

**WARNING:** CAUSES SKIN IRRITATION.  
MAY CAUSE AN ALLERGIC SKIN REACTION.  
CAUSES SERIOUS EYE IRRITATION.

| HAZARD CLASS       | HAZARD CATEGORY |
|--------------------|-----------------|
| SKIN IRRITATION    | 2               |
| EYE IRRITATION     | 2A              |
| SKIN SENSITIZATION | 1               |

**PICTOGRAM(S)****Precautionary Statements**

|                    |   |
|--------------------|---|
| <b>Prevention:</b> | Avoid breathing vapors, mist, or spray. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear eye and face protection. Wear protective gloves.  |
| <b>Response:</b>   | IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing. |
| <b>Storage:</b>    | Not prescribed  |
| <b>Disposal:</b>   | Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.   |

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

IDH number: 702258

Product name: LOCTITE PC 7226 A RESIN known as Nordbak Pneu Wear RESIN

Page 1 of 6

| Hazardous Component(s)            | CAS Number  | Percentage* |
|-----------------------------------|-------------|-------------|
| Aluminum oxide, fibrous           | 1344-28-1   | 30 - 60     |
| Epoxy resin                       | Proprietary | 10 - 30     |
| Silicon carbide                   | 409-21-2    | 5 - 10      |
| Silicon dioxide                   | 7631-86-9   | 1 - 5       |
| Magnesium oxide                   | 1309-48-4   | 1 - 5       |
| Treated fumed silica              | 67762-90-7  | 1 - 5       |
| Neopentyl glycol diglycidyl ether | 17557-23-2  | 1 - 5       |
| Titanium dioxide                  | 13463-67-7  | 0.1 - 1     |
| Substituted silane                | Proprietary | 0.1 - 1     |

\* Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

#### 4. FIRST AID MEASURES

|                      |   |
|----------------------|---|
| <b>Inhalation:</b>   | Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.  |
| <b>Skin contact:</b> | Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. If symptoms develop and persist, get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse. |
| <b>Eye contact:</b>  | Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.   |
| <b>Ingestion:</b>    | DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If symptoms develop and persist, get medical attention.  |
| <b>Symptoms:</b>     | See Section 11.   |

#### 5. FIRE FIGHTING MEASURES

|   |   |
|---|---|
| <b>Extinguishing media:</b>               | Foam, dry chemical or carbon dioxide.   |
| <b>Special firefighting procedures:</b>   | Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.  |
| <b>Unusual fire or explosion hazards:</b> | In case of fire, keep containers cool with water spray. Closed containers may rupture (due to build up of pressure) when exposed to extreme heat. |
| <b>Hazardous combustion products:</b>     | Oxides of carbon. Aldehydes. Irritating vapors.   |

#### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

|                                   |  |
|-----------------------------------|--|
| <b>Environmental precautions:</b> | Do not allow product to enter sewer or waterways.  |
| <b>Clean-up methods:</b>          | Ensure adequate ventilation. Wear appropriate personal protective equipment. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up spilled material and place in a closed container for disposal. |

## 7. HANDLING AND STORAGE

**Handling:**

Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Use only with adequate ventilation. Keep container closed.

**Storage:**

Store in original container until ready to use. Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials. Keep away from heat, spark and flame.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s)            | ACGIH TLV  | OSHA PEL   | AIHA WEEL | OTHER                               |
|-----------------------------------|--|--|-----------|-------------------------------------|
| Aluminum oxide, fibrous           | 1 mg/m3 TWA<br>Respirable fraction.  | 5 mg/m3 PEL<br>Respirable fraction.<br>15 mg/m3 PEL Total<br>dust. | None      | None                                |
| Epoxy resin                       | None   | None   | None      | None                                |
| Silicon carbide                   | 10 mg/m3 TWA<br>Inhalable fraction.<br>3 mg/m3 TWA<br>Respirable fraction.<br>0.1 FIBERS/CM3<br>TWA Fiber. | 5 mg/m3 PEL<br>Respirable fraction.<br>15 mg/m3 PEL Total<br>dust. | None      | None                                |
| Silicon dioxide                   | 6 mg/m3 TWA  | 20 MPPCF TWA<br>0.8 mg/m3 TWA                                      | None      | 3 mg/m3 TWA<br>Respirable fraction. |
| Magnesium oxide                   | 10 mg/m3 TWA<br>Inhalable fraction.  | 15 mg/m3 PEL Total<br>particulate.                                 | None      | None                                |
| Treated fumed silica              | 10 mg/m3 TWA<br>Inhalable dust.<br>3 mg/m3 TWA<br>Respirable fraction.                                     | 15 mg/m3 TWA Total<br>dust.<br>5 mg/m3 TWA<br>Respirable fraction. | None      | None                                |
| Neopentyl glycol diglycidyl ether | None   | None   | None      | None                                |
| Titanium dioxide                  | 10 mg/m3 TWA   | 15 mg/m3 PEL Total<br>dust.  | None      | None                                |
| Substituted silane                | None   | None   | None      | None                                |

**Engineering controls:**

Use local ventilation if general ventilation is insufficient to maintain vapor concentration below established exposure limits.

**Respiratory protection:**

Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

**Eye/face protection:**

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists.

**Skin protection:**

Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Physical state:**

Liquid

**Color:**

Dark grey

**Odor:**

Epoxy

**Odor threshold:**

Not available.

**pH:**

Not available.

**Vapor pressure:**

Not available.

**Boiling point/range:**

Not available.

**Melting point/ range:**

Not available.

|   |   |
|---|---|
| <b>Specific gravity:</b>                        | Not available.  |
| <b>Vapor density:</b>                           | Not available.  |
| <b>Flash point:</b>                             | > 93 °C (> 199.4 °F) ; Estimated                                      |
| <b>Flammable/Explosive limits - lower:</b>      | Not available.  |
| <b>Flammable/Explosive limits - upper:</b>      | Not available.  |
| <b>Autoignition temperature:</b>                | Not available.  |
| <b>Evaporation rate:</b>                        | Not available.  |
| <b>Solubility in water:</b>                     | Not available.  |
| <b>Partition coefficient (n-octanol/water):</b> | Not available.  |
| <b>VOC content:</b>                             | < 1.0 %; < 10 g/l (value for resin and hardener together) (estimated) |
| <b>Viscosity:</b>                               | Not available.  |
| <b>Decomposition temperature:</b>               | Not available.  |

## 10. STABILITY AND REACTIVITY

|  |   |
|--|---|
| <b>Stability:</b>                        | Stable under normal conditions of storage and use.  |
| <b>Hazardous reactions:</b>              | None under normal processing.   |
| <b>Hazardous decomposition products:</b> | Oxides of carbon. Aldehydes. Irritating vapors.   |
| <b>Incompatible materials:</b>           | Strong acids and strong bases. Strong oxidizing agents.   |
| <b>Reactivity:</b>                       | Not available.  |
| <b>Conditions to avoid:</b>              | Heat, flames, sparks and other sources of ignition. Excessive heat. Store away from incompatible materials. |

## 11. TOXICOLOGICAL INFORMATION

|                                     |                                   |
|-------------------------------------|-----------------------------------|
| <b>Relevant routes of exposure:</b> | Skin, Inhalation, Eyes, Ingestion |
|-------------------------------------|-----------------------------------|

### Potential Health Effects/Symptoms

**Inhalation:** Inhalation of vapors or mists of the product may be irritating to the respiratory system.  
**Skin contact:** Causes skin irritation. May cause allergic skin reaction.  
**Eye contact:** Causes serious eye irritation.  
**Ingestion:** May cause gastrointestinal tract irritation if swallowed.

| Hazardous Component(s)            | LD50s and LC50s                  | Immediate and Delayed Health Effects                                |
|-----------------------------------|----------------------------------|---|
| Aluminum oxide, fibrous           | None                             | Irritant, Nuisance dust, Corrosive                                  |
| Epoxy resin                       | None                             | Allergen, Irritant  |
| Silicon carbide                   | None                             | Nuisance dust   |
| Silicon dioxide                   | Oral LD50 (RAT) = > 22,500 mg/kg | Nuisance dust   |
| Magnesium oxide                   | None                             | Blood, Central nervous system, Immune system, Irritant              |
| Treated fumed silica              | None                             | Irritant  |
| Neopentyl glycol diglycidyl ether | None                             | Allergen, Blood, Bone Marrow, Immune system, Irritant, Reproductive |
| Titanium dioxide                  | None                             | Irritant, Respiratory, Some evidence of carcinogenicity             |
| Substituted silane                | None                             | Allergen, Irritant  |

| Hazardous Component(s)            | NTP Carcinogen | IARC Carcinogen | OSHA Carcinogen<br>(Specifically Regulated) |
|-----------------------------------|----------------|-----------------|---|
| Aluminum oxide, fibrous           | No             | No              | No  |
| Epoxy resin                       | No             | No              | No  |
| Silicon carbide                   | No             | No              | No  |
| Silicon dioxide                   | No             | No              | No  |
| Magnesium oxide                   | No             | No              | No  |
| Treated fumed silica              | No             | No              | No  |
| Neopentyl glycol diglycidyl ether | No             | No              | No  |
| Titanium dioxide                  | No             | Group 2B        | No  |
| Substituted silane                | No             | No              | No  |

## 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Follow all local, state, federal and provincial regulations for disposal.

**Hazardous waste number:** Not a RCRA hazardous waste.

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

### U.S. Department of Transportation Ground (49 CFR)

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

### International Air Transportation (ICAO/IATA)

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

**Water Transportation (IMO/IMDG)**

|                           |               |
|---------------------------|---------------|
| Proper shipping name:     | Not regulated |
| Hazard class or division: | None          |
| Identification number:    | None          |
| Packing group:            | None          |

**15. REGULATORY INFORMATION****United States Regulatory Information**

|   |  |
|---|--|
| <b>TSCA 8 (b) Inventory Status:</b>     | All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.  |
| <b>TSCA 12 (b) Export Notification:</b> | None above reporting de minimis  |
| <b>CERCLA/SARA Section 302 EHS:</b>     | None above reporting de minimis  |
| <b>CERCLA/SARA Section 311/312:</b>     | Immediate Health, Delayed Health   |
| <b>CERCLA/SARA Section 313:</b>         | This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Aluminum oxide, fibrous (CAS# 1344-28-1). |
| <b>California Proposition 65:</b>       | This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.                            |

**Canada Regulatory Information**

|                             |   |
|-----------------------------|---|
| <b>CEPA DSL/NDL Status:</b> | All components are listed on or are exempt from listing on the Canadian Domestic Substances List. |
|-----------------------------|---|

**16. OTHER INFORMATION**

**This safety data sheet contains changes from the previous version in sections:** New Safety Data Sheet format.

**Prepared by:** Rena Petrides, Regulatory Affairs Specialist

**Issue date:** 08/06/2014

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.