	Page: 1
<b>SAFETY DATA SHEET</b>	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0367943
Maxlife™ DEX/MERC SYNTHETIC AUTOMATIC TRANSMISSION FLUID ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 773775	Version: 1.4

29 CFR 1910.1200 (OSHA HazCom 2012)

## SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

### Product identifier

Trade name : Maxlife™ DEX/MERC  
SYNTHETIC AUTOMATIC TRANSMISSION FLUID  
™ Trademark, Valvoline or its subsidiaries, regisred in various countries

### Recommended use of the chemical and restrictions on use

<b>Details of the supplier of the safety data sheet</b>  Valvoline LLC 3499 Blazer Parkway Lexington, KY 40509 United States of America  SDS@valvoline.com	<b>Emergency telephone number</b> 1-800-VALVOLINE  <b>Regulatory Information Number</b> 1-800-TEAMVAL  <b>Product Information</b> 1-800-TEAMVAL
---	--

## SECTION 2. HAZARDS IDENTIFICATION

### GHS Classification

Skin sensitization : Category 1

### GHS Label element

Hazard pictograms :



Signal Word : Warning

Hazard Statements : May cause an allergic skin reaction.

Precautionary Statements : If medical advice is needed, have product container or label at hand.


Keep out of reach of children.

Read label before use.

### Prevention:

Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

Contaminated work clothing must not be allowed out of the workplace.

	Page: 2
<b>SAFETY DATA SHEET</b>	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0367943
Maxlife™ DEX/MERC SYNTHETIC AUTOMATIC TRANSMISSION FLUID ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 773775	Version: 1.4

Wear protective gloves.

**Response:**

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/ attention.

Wash contaminated clothing before reuse.

**Disposal:**

Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS


Substance / Mixture : Mixture

Chemical nature : Defatter


**Hazardous components**

Chemical Name	CAS-No.	Classification	Concentration (%)
HEAVY PARAFFINIC DISTILLATE	64742-54-7	Asp. Tox. 1; H304	73.23
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	Asp. Tox. 1; H304	1.91
Acetamide, 2-hydroxy-, N,N-dicoco alkyl derivs.	866259-61-2	Skin Sens. 1; H317	0.89
DODECYL HYDROXYPROPYL SULFIDE	67124-09-8	Skin Sens. 1; H317	0.25
BENZENE, POLYPROPENE DERIVATIVES, SULFONATED, CALCIUM SALTS		Eye Irrit. 2A; H319 Skin Sens. 1; H317	0.14

### SECTION 4. FIRST AID MEASURES

		Page: 3
<b>SAFETY DATA SHEET</b>		Revision Date: 07/31/2016
		Print Date: 11/1/2016
		SDS Number: R0367943
Maxlife™ DEX/MERC SYNTHETIC AUTOMATIC TRANSMISSION FLUID ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 773775		Version: 1.4

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : If breathed in, move person into fresh air.  
If unconscious place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.  
If on skin, rinse well with water.  
First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.  
Wash contaminated clothing before re-use.
- In case of eye contact : Flush eyes with water as a precaution.  
Remove contact lenses.  
Protect unharmed eye.  
If eye irritation persists, consult a specialist.
- If swallowed : Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.
- Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:  
acne  
stomach or intestinal upset (nausea, vomiting, diarrhea)  
irritation (nose, throat, airways)  
May cause an allergic skin reaction.
- Notes to physician : No hazards which require special first aid measures.

		Page: 4
<b>SAFETY DATA SHEET</b>		Revision Date: 07/31/2016
		Print Date: 11/1/2016
		SDS Number: R0367943
Maxlife™ DEX/MERC SYNTHETIC AUTOMATIC TRANSMISSION FLUID ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 773775		Version: 1.4


## SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Water spray  
Foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : carbon dioxide and carbon monoxide  
Hydrocarbons
- Specific extinguishing methods :
- Product is compatible with standard fire-fighting agents.
- Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.
- Other information : Comply with all applicable federal, state, and local regulations.

## SECTION 7. HANDLING AND STORAGE

	Page: 5
<b>SAFETY DATA SHEET</b>	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0367943
Maxlife™ DEX/MERC SYNTHETIC AUTOMATIC TRANSMISSION FLUID ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 773775	Version: 1.4

- Advice on safe handling : Do not breathe vapours/dust.  
Do not smoke.  
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Container hazardous when empty.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
Smoking, eating and drinking should be prohibited in the application area.  
For personal protection see section 8.  
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Electrical installations / working materials must comply with the technological safety standards.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	REL	5 mg/m3 Mist.	NIOSH/GUID E
		STEL	10 mg/m3 Mist.	NIOSH/GUID E
		PEL	5 mg/m3 Mist.	OSHA_TRA NS

- Engineering measures** : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.


### Personal protective equipment

#### Hand protection

- Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

#### Eye protection

- : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed

	Page: 6
<b>SAFETY DATA SHEET</b>	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0367943
Maxlife™ DEX/MERC SYNTHETIC AUTOMATIC TRANSMISSION FLUID ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 773775	Version: 1.4

into eyes.

Skin and body protection : Wear as appropriate:  
impervious clothing  
Safety shoes  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.  
Discard gloves that show tears, pinholes, or signs of wear.  
Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures : Wash hands before breaks and at the end of workday.

---

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid

Colour : red

Odour : mild

Odour Threshold : No data available

pH : No data available

: No data available

Boiling point/boiling range : > 424 °F / 218 °C  
(1013 hPa)

Flash point : > 390 °F / > 199 °C  
Method: Closed Cup

Evaporation rate : < 1  
Ethyl Ether

Flammability (solid, gas) : No data available

Upper explosion limit : No data available


Lower explosion limit : No data available

Vapour pressure : 1 hPaCalculated Vapor Pressure

Relative vapour density : > 1AIR=1

Relative density : No data available

Density : 0.8518 g/cm3 (15.56 °C)

		Page: 7
<b>SAFETY DATA SHEET</b>		Revision Date: 07/31/2016
		Print Date: 11/1/2016
		SDS Number: R0367943
Maxlife™ DEX/MERC SYNTHETIC AUTOMATIC TRANSMISSION FLUID ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 773775		Version: 1.4

Solubility(ies)  
Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Thermal decomposition : No data available

Viscosity  
Viscosity, dynamic : No data available

Viscosity, kinematic : 28.8 mm<sup>2</sup>/s (40 °C)

Oxidizing properties : No data available

---

## SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Product will not undergo hazardous polymerization.

Conditions to avoid : excessive heat

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : carbon dioxide and carbon monoxide  
Hydrocarbons

---


## SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation  
Skin contact  
Eye Contact  
Ingestion

### Acute toxicity

Not classified based on available information.

### Components:

	Page: 8
<b>SAFETY DATA SHEET</b>	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0367943
Maxlife™ DEX/MERC SYNTHETIC AUTOMATIC TRANSMISSION FLUID ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 773775	Version: 1.4

**HEAVY PARAFFINIC DISTILLATE:**

Acute oral toxicity : LD 50 (Rat): > 15 g/kg

Acute dermal toxicity : LD 50 (Rabbit): > 5 g/kg

**DODECYL HYDROXYPROPYL SULFIDE:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
GLP: yes

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

**Skin corrosion/irritation**

Not classified based on available information.

**Product:**

Remarks: May cause skin irritation in susceptible persons.

Result: Repeated exposure may cause skin dryness or cracking.

**Components:**

**HEAVY PARAFFINIC DISTILLATE:**

Result: Mildly irritating to skin

**HYDROTREATED LIGHT PARAFFINIC DISTILLATE:**

Result: Mildly irritating to skin

**DODECYL HYDROXYPROPYL SULFIDE:**

Species: Rabbit

Result: Not irritating to skin

**BENZENE, POLYPROPENE DERIVATIVES, SULFONATED, CALCIUM SALTS:**

Result: Possibly irritating to skin

**Serious eye damage/eye irritation**

Not classified based on available information.

**Product:**

Result: Slightly irritating to eyes

Remarks: Expected based on components.

Remarks: Unlikely to cause eye irritation or injury.

**Components:**

**HEAVY PARAFFINIC DISTILLATE:**

Result: Not irritating to eyes

**HYDROTREATED LIGHT PARAFFINIC DISTILLATE:**


Result: Mildly irritating to eyes

**DODECYL HYDROXYPROPYL SULFIDE:**

Species: Rabbit

Result: Not irritating to eyes



	Page: 9
<b>SAFETY DATA SHEET</b>	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0367943
Maxlife™ DEX/MERC SYNTHETIC AUTOMATIC TRANSMISSION FLUID ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 773775	Version: 1.4

BENZENE, POLYPROPENE DERIVATIVES, SULFONATED, CALCIUM SALTS:

Result: Irritating to eyes

**Respiratory or skin sensitisation**

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

**Components:**

Acetamide, 2-hydroxy-, N,N-dicoco alkyl derivs.:

Assessment: May cause sensitisation by skin contact.

Result: May cause sensitisation by skin contact.

DODECYL HYDROXYPROPYL SULFIDE:

Assessment: May cause sensitization by skin contact.

Result: May cause sensitization by skin contact.

BENZENE, POLYPROPENE DERIVATIVES, SULFONATED, CALCIUM SALTS:

Assessment: May cause sensitization by skin contact.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.

**Reproductive toxicity**

Not classified based on available information.

**STOT - single exposure**

Not classified based on available information.

**STOT - repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

**Product:**

No aspiration toxicity classification

**Components:**

HEAVY PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

**Further information**

**Product:**

Remarks: No data available


**Carcinogenicity:**

**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA**

No component of this product present at levels greater than or

	Page: 10
<b>SAFETY DATA SHEET</b>	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0367943
Maxlife™ DEX/MERC SYNTHETIC AUTOMATIC TRANSMISSION FLUID ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 773775	Version: 1.4

equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

#### NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

##### HEAVY PARAFFINIC DISTILLATE:

- Toxicity to fish : LL50 (Fish): > 100 mg/l
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Aquatic invertebrates): > 10,000 mg/l
- Toxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l
- Toxicity to fish (Chronic toxicity) : NOEC (Fish): 10 mg/l
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Aquatic invertebrates): 10 mg/l


##### DODECYL HYDROXYPROPYL SULFIDE:

- Toxicity to fish : LC 50 (Oncorhynchus mykiss (rainbow trout)): 0.75 mg/l  
Exposure time: 96 h  
Test Type: semi-static test  
Method: OECD Test Guideline 203  
GLP: yes
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC 50 (Daphnia magna (Water flea)): 0.5 mg/l  
Exposure time: 21 d  
End point: see user defined free text  
Test Type: see user defined free text  
Method: OECD Test Guideline 211  
GLP: yes

### Persistence and degradability

#### Components:

No data available

	Page: 11
<b>SAFETY DATA SHEET</b>	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0367943
Maxlife™ DEX/MERC SYNTHETIC AUTOMATIC TRANSMISSION FLUID ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 773775	Version: 1.4

#### Bioaccumulative potential

##### Components:

No data available

##### **Mobility in soil**

##### Components:

No data available

##### **Other adverse effects**

No data available

##### Product:

Additional ecological information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life with long lasting effects.

##### Components:

### SECTION 13. DISPOSAL CONSIDERATIONS

#### **Disposal methods**

General advice

: The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging

: Empty remaining contents.  
Dispose of as unused product.  
Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Do not re-use empty containers.

### SECTION 14. TRANSPORT INFORMATION


#### **International transport regulations**

##### **REGULATION**

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

#### **U.S. DOT - ROAD**

Not dangerous goods

		Page: 12
<b>SAFETY DATA SHEET</b>		Revision Date: 07/31/2016
		Print Date: 11/1/2016
		SDS Number: R0367943
Maxlife™ DEX/MERC SYNTHETIC AUTOMATIC TRANSMISSION FLUID ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 773775		Version: 1.4

**CFR\_RAIL\_C**

Not dangerous goods

**U.S. DOT - INLAND WATERWAYS**

Not dangerous goods

**TDG\_ROAD\_C**

Not dangerous goods

**TDG\_RAIL\_C**

Not dangerous goods

**TDG\_INWT\_C**

Not dangerous goods

**INTERNATIONAL MARITIME DANGEROUS GOODS**

Not dangerous goods

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO**

Not dangerous goods

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER**

Not dangerous goods

**MX\_DG**


Not dangerous goods

**\*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

**SECTION 15. REGULATORY INFORMATION**

	Page: 13
<b>SAFETY DATA SHEET</b>	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0367943
Maxlife™ DEX/MERC SYNTHETIC AUTOMATIC TRANSMISSION FLUID ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 773775	Version: 1.4

**SARA 311/312 Hazards** : Acute Health Hazard

**SARA 313 Component(s)** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**Pennsylvania Right To Know**

HEAVY PARAFFINIC DISTILLATE	64742-54-7	70.00 - 90.00 %
HYDROTREATED HEAVY PARAFFINIC BASE OIL	64742-54-7	10.00 - 20.00 %
LUBRICANT ADDITIVE	Not Assigned	5.00 - 10.00 %
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	1.00 - 5.00 %

**New Jersey Right To Know**


HEAVY PARAFFINIC DISTILLATE	64742-54-7	70.00 - 90.00 %
HYDROTREATED HEAVY PARAFFINIC BASE OIL	64742-54-7	10.00 - 20.00 %
LUBRICANT ADDITIVE	Not Assigned	5.00 - 10.00 %
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	1.00 - 5.00 %
PROPRIETARY POLYMER	Not Assigned	1.00 - 5.00 %

**California Prop 65** Proposition 65 warnings are not required for this product based on the results of a risk assessment.

**The components of this product are reported in the following inventories:**

TSCA	: On TSCA Inventory
DSL	: All components of this product are on the Canadian DSL.
AUSTR	: On the inventory, or in compliance with the inventory
KECL	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: Contact your sales representative for additional information.
ENCS	: Contact your sales representative for additional information.

**Inventories**


	Page: 14
<b>SAFETY DATA SHEET</b>	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0367943
Maxlife™ DEX/MERC SYNTHETIC AUTOMATIC TRANSMISSION FLUID ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 773775	Version: 1.4

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

## SECTION 16. OTHER INFORMATION

### Further information

Revision Date: 07/31/2016

NFPA:	HMIS III:						
<p>Flammability</p> <p>Health</p> <p>Instability</p>  <p>Special hazard.</p>	<table border="1"> <tr> <td><b>HEALTH</b></td><td><b>2</b></td></tr> <tr> <td><b>FLAMMABILITY</b></td><td><b>1</b></td></tr> <tr> <td><b>PHYSICAL HAZARD</b></td><td><b>0</b></td></tr> </table> <p>0 = not significant, 1 =Slight,  2 = Moderate, 3 = High  4 = Extreme, * = Chronic</p>	<b>HEALTH</b>	<b>2</b>	<b>FLAMMABILITY</b>	<b>1</b>	<b>PHYSICAL HAZARD</b>	<b>0</b>
<b>HEALTH</b>	<b>2</b>						
<b>FLAMMABILITY</b>	<b>1</b>						
<b>PHYSICAL HAZARD</b>	<b>0</b>						

### NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB


### Full text of H-Statements referred to under sections 2 and 3.

H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H401	Toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

### Further information

Sources of key data used to compile the Safety Data Sheet  
Valvoline internal data including own and sponsored test reports  
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-825-8654).

	Page: 15
<b>SAFETY DATA SHEET</b>	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0367943
Maxlife™ DEX/MERC SYNTHETIC AUTOMATIC TRANSMISSION FLUID ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 773775	Version: 1.4

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act

DOT : Department of Transportation

FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act

HMIRC : Hazardous Materials Information Review Commission

HMIS : Hazardous Materials Identification System

NFPA : National Fire Protection Association

NIOSH : National Institute for Occupational Safety and Health

OSHA : Occupational Safety and Health Administration

PMRA : Health Canada Pest Management Regulatory Agency

RTK : Right to Know

WHMIS : Workplace Hazardous Materials Information System