



SAFETY DATA SHEET

Valvoline™ VR1 Racing™ SAE 60 Racing Oil

Version: 1.5

Revision Date: 04/30/2020

Print Date:
11/20/2020

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Valvoline™ VR1 Racing™ SAE 60
Racing Oil

Product code : 822403


Details of the supplier of the safety data sheet Valvoline LLC 100 Valvoline Way Lexington, KY 40509 United States of America (USA) 1-800-TEAMVAL (1-800-832-6825) SDS@valvoline.com	Emergency telephone number 1-800-VALVOLINE (1-800-825-8654) Regulatory Information Number 1-800-TEAMVAL (1-800-832-6825) Product Information 1-800-TEAMVAL (1-800-832-6825)
---	---

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Eye irritation : Category 2A

GHS label elements

Hazard pictograms : 

Signal Word : Warning

Hazard Statements : Causes serious eye irritation.

Precautionary Statements : **Prevention:**
Wear eye protection/ face protection.
Wash skin thoroughly after handling.
Response:
If eye irritation persists: Get medical advice/ attention.
IF IN EYES: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing.



SAFETY DATA SHEET

Valvoline™ VR1 Racing™ SAE 60 Racing Oil

Version: 1.5

Revision Date: 04/30/2020

Print Date:
11/20/2020

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	Not a hazardous substance or mixture.	≥ 30.00 - < 40.00
Zinc O,O,O',O'-tetrakis(1,3- dimethylbutyl) bis(phosphorodithioate)	2215-35-2	Skin Irrit. 2; H315 Eye Dam. 1; H318	≥ 1.50 - < 5.00

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : Do not leave the victim unattended.
Show this safety data sheet to the doctor in attendance.
Move out of dangerous area.
- If inhaled : If breathed in, move person into fresh air.
If unconscious, place in recovery position and seek medical
advice.
If symptoms persist, call a physician.
- In case of skin contact : Wash contaminated clothing before re-use.
If on skin, rinse well with water.
Remove contaminated clothing. If irritation develops, get
medical attention.
- In case of eye contact : Protect unharmed eye.
Remove contact lenses.
Immediately flush eye(s) with plenty of water.
- If swallowed : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms
and effects, both acute and
delayed : No symptoms known or expected.
Causes serious eye irritation.



SAFETY DATA SHEET

Valvoline™ VR1 Racing™ SAE 60 Racing Oil

Version: 1.5

Revision Date: 04/30/2020

Print Date:
11/20/2020

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the point of release.
- Hazardous combustion products : carbon dioxide and carbon monoxide
- Specific extinguishing methods :
- Product is compatible with standard fire-fighting agents.
- Further information : Standard procedure for chemical fires.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
Use personal protective equipment.
- Environmental precautions : Prevent further leakage or spillage if safe to do so.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.



SAFETY DATA SHEET
Valvoline™ VR1 Racing™ SAE 60 Racing Oil

Version: 1.5

Revision Date: 04/30/2020

Print Date:
11/20/2020

Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Dispose of rinse water in accordance with local and national regulations.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Avoid contact with skin and eyes.
Container hazardous when empty.
Do not smoke.
Do not breathe vapours/dust.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable particulate matter	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment



SAFETY DATA SHEET

Valvoline™ VR1 Racing™ SAE 60 Racing Oil

Version: 1.5

Revision Date: 04/30/2020

Print Date:
11/20/2020

Respiratory protection	:	No personal respiratory protective equipment normally required.
Hand protection Remarks	:	The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection	:	Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.
Skin and body protection	:	Wear resistant gloves (consult your safety equipment supplier). Choose body protection according to the amount and concentration of the dangerous substance at the work place. Safety shoes Impervious clothing Wear as appropriate:
Hygiene measures	:	When using do not smoke. When using do not eat or drink. Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Odour	:	No data available
Odour Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Boiling point/boiling range	:	424.99 °F / 218.33 °C (1,013.333333 hPa) Calculated Phase Transition Liquid/Gas
Flash point	:	> 390 °F / > 199 °C Method: Cleveland open cup
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Self-ignition	:	No data available



SAFETY DATA SHEET

Valvoline™ VR1 Racing™ SAE 60 Racing Oil

Version: 1.5

Revision Date: 04/30/2020

Print Date:
11/20/2020

Upper explosion limit / Upper flammability limit	:	6 %(V) Calculated Explosive Limit
Lower explosion limit / Lower flammability limit	:	1 %(V) Calculated Explosive Limit
Vapour pressure	:	0.0133333 hPa (70.00 °F / 21.11 °C) Calculated Vapor Pressure
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	0.8931 g/cm ³ (60.01 °F / 15.56 °C)
Solubility(ies)		
Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	No data available
Oxidizing properties	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	Stable under recommended storage conditions.
Possibility of hazardous reactions	:	Product will not undergo hazardous polymerization.
Conditions to avoid	:	None known.
Incompatible materials	:	Strong oxidizing agents Acids



SAFETY DATA SHEET

Valvoline™ VR1 Racing™ SAE 60 Racing Oil

Version: 1.5

Revision Date: 04/30/2020

Print Date:
11/20/2020

Hazardous decomposition
products

No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: 4,093 mg/kg
Method: Calculation method

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate):

Acute oral toxicity : LD50 (Rat): 2,230 mg/kg
GLP: no

Acute inhalation toxicity : LC50 (Rat): > 2.3 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: Not classified as acutely toxic by inhalation under GHS.
Remarks: Information given is based on data obtained from similar substances.

Acute dermal toxicity : LD50 (Rabbit): > 3,160 mg/kg
Method: OECD Test Guideline 402
Assessment: Not classified as acutely toxic by dermal absorption under GHS.

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks : May cause skin irritation in susceptible persons.



SAFETY DATA SHEET
Valvoline™ VR1 Racing™ SAE 60 Racing Oil

Version: 1.5

Revision Date: 04/30/2020

Print Date:
11/20/2020

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Assessment : Slight, transient irritation
Result : Slight, transient irritation

Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Irritating to skin.
GLP : yes

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks : Causes serious eye irritation.
Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Result : No eye irritation
Assessment : No eye irritation

Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate:

Result : Corrosive

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate:

Species : Guinea pig
Assessment : Did not cause sensitisation on laboratory animals.
Method : OECD Test Guideline 406
Result : Did not cause sensitisation on laboratory animals.
GLP : yes

Germ cell mutagenicity

Not classified based on available information.

Components:

Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate:

Genotoxicity in vitro : Test Type: Ames test
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Result: negative

Carcinogenicity

Not classified based on available information.



SAFETY DATA SHEET
Valvoline™ VR1 Racing™ SAE 60 Racing Oil

Version: 1.5

Revision Date: 04/30/2020

Print Date:
11/20/2020

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

IARC No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

No aspiration toxicity classification

Further information

Product:

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Not classified based on available information.

Long-term (chronic) aquatic hazard : Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Toxicity to fish : LL50 (Fish): > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EL50 (Aquatic invertebrates): > 10,000 mg/l
Exposure time: 48 h



SAFETY DATA SHEET

Valvoline™ VR1 Racing™ SAE 60 Racing Oil

Version: 1.5

Revision Date: 04/30/2020

Print Date:
11/20/2020

Toxicity to algae	: EL50 (Algae, algal mat (Algae)): > 100 mg/l Exposure time: 72 h
Toxicity to fish (Chronic toxicity)	: NOEC (Fish): 10 mg/l
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Aquatic invertebrates): 10 mg/l
Ecotoxicology Assessment Short-term (acute) aquatic hazard	: Not classified based on available information.
Long-term (chronic) aquatic hazard	: Not classified based on available information.
Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate): Toxicity to fish	: LL50 (Oncorhynchus mykiss (rainbow trout)): 4.5 mg/l Exposure time: 96 h Test Type: semi-static test Method: OECD Test Guideline 203 Remarks: Information given is based on data obtained from similar substances.
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Daphnia magna (Water flea)): 23 mg/l Exposure time: 48 h Method: OECD Test Guideline 202 GLP: yes
Toxicity to algae	: NOEL (Desmodesmus subspicatus (green algae)): 10 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 201 Remarks: Information given is based on data obtained from similar substances.
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia magna (Water flea)): 0.4 mg/l Exposure time: 21 d Test substance: WAF Method: OECD Test Guideline 211 Remarks: Information given is based on data obtained from similar substances.

Persistence and degradability

Components:

Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate):



SAFETY DATA SHEET
Valvoline™ VR1 Racing™ SAE 60 Racing Oil

Version: 1.5

Revision Date: 04/30/2020

Print Date:
11/20/2020

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 1.5 %
Exposure time: 28 d
Method: OECD Test Guideline 301B
Remarks: Information given is based on data obtained from similar substances.

No data available

Bioaccumulative potential

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Partition coefficient: n-octanol/water : log Pow: Expected > 7

No data available

Mobility in soil

Components:

No data available

Other adverse effects

No data available

Product:

Regulation

40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Dispose of in accordance with all applicable local, state and federal regulations.

Send to a licensed waste management company.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Do not dispose of waste into sewer.

Contaminated packaging : Do not re-use empty containers.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Dispose of as unused product.
Empty remaining contents.



SAFETY DATA SHEET
Valvoline™ VR1 Racing™ SAE 60 Racing Oil

Version: 1.5

Revision Date: 04/30/2020

Print Date:
11/20/2020

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

Not regulated as a dangerous good

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Serious eye damage or eye irritation

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Zinc O,O,O',O'- 2215-35-2 >= 1 - < 5 %
tetrakis(1,3-
dimethylbutyl)
bis(phosphorodit
hioate



SAFETY DATA SHEET

Valvoline™ VR1 Racing™ SAE 60 Racing Oil

Version: 1.5

Revision Date: 04/30/2020

Print Date:
11/20/2020

Zinc, bis[O,O- 4259-15-8 >= 0.1 - < 1 %
bis(2-ethylhexyl)
phosphorodithioa
to-S,S']-, (T-4)-

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489).

Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product contains the following toxic pollutants listed under the U.S. Clean Water Act Section 307

Zinc O,O,O',O'- 2215-35-2 >= 1 - < 5 %
tetrakis(1,3-
dimethylbutyl)
bis(phosphorodithioate

This product does not contain any priority pollutants related to the U.S. Clean Water Act

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

ENCS : Contact your sales representative for additional information.

KECI : On the inventory, or in compliance with the inventory

IECSC : q (quantity restricted)

PICCS : On the inventory, or in compliance with the inventory

TCSI : On the inventory, or in compliance with the inventory

TSCA : On TSCA Inventory

TSCA list

No substances are subject to TSCA 12(b) export notification requirements.

Inventories



SAFETY DATA SHEET

Valvoline™ VR1 Racing™ SAE 60 Racing Oil

Version: 1.5

Revision Date: 04/30/2020

Print Date:
11/20/2020

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Internal information : R0173175

NFPA:	HMIS III:						
<p>Flammability</p> <p>Health</p> <p>Instability</p> <p>Special hazard</p>	<table border="1"><tbody><tr><td>HEALTH</td><td>2</td></tr><tr><td>FLAMMABILITY</td><td>1</td></tr><tr><td>PHYSICAL HAZARD</td><td>0</td></tr></tbody></table> <p>0 = not significant, 1 =Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	2	FLAMMABILITY	1	PHYSICAL HAZARD	0
HEALTH	2						
FLAMMABILITY	1						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification
Combustible Liquid Class IIIB

Full text of H-Statements

H315 Causes skin irritation.
H318 Causes serious eye damage.

Sources of key data used to compile the Safety Data Sheet
Valvoline internal data including own and sponsored test reports
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).



SAFETY DATA SHEET

Valvoline™ VR1 Racing™ SAE 60 Racing Oil

Version: 1.5

Revision Date: 04/30/2020

Print Date:
11/20/2020

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act

DOT : Department of Transportation

FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act

HMIRC : Hazardous Materials Information Review Commission

HMIS : Hazardous Materials Identification System

NFPA : National Fire Protection Association

NIOSH : National Institute for Occupational Safety and Health

OSHA : Occupational Safety and Health Administration

PMRA : Health Canada Pest Management Regulatory Agency

RTK : Right to Know

WHMIS : Workplace Hazardous Materials Information System