

Valvoline™ HIGH MILEAGE with MaxLife™ Technology SAE 10W-30 Synthetic Blend Motor Oil

Version: 8.0 Revision Date: 10/23/2020 Print Date: 11/24/2020

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Valvoline™ HIGH MILEAGE with MaxLife™ Technology SAE

10W-30 Synthetic Blend Motor Oil

Product code : 881161

Manufacturer or supplier's details

Company : Valvoline LLC

Address : 100 Valvoline Way

Lexington, KY 40509

United States of America (USA)

E-mail address : SDS@valvoline.com

Emergency telephone number : +1-800-VALVOLINE (+1-800-825-8654)

2. HAZARDS IDENTIFICATION

GHS Classification

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
DISTILLATES (PETROLEUM),	64742-54-7	>= 40 -< 60
HYDROTREATED HEAVY PARAFFINIC		
DISTILLATES (PETROLEUM),	64742-54-7	>= 30 -< 40
HYDROTREATED HEAVY PARAFFINIC		



Valvoline™ HIGH MILEAGE with MaxLife™ Technology SAE 10W-30 Synthetic Blend Motor Oil

Version: 8.0 Revision Date: 10/23/2020 Print Date: 11/24/2020

HYDROTREATED LIGHT PARAFFINIC 64742-55-8 >= 1.5 -< 3
DISTILLATE

4. FIRST AID MEASURES

General advice : No hazards which require special first aid measures.

If inhaled : If breathed in, move person into fresh air.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : First aid is not normally required. However, it is

recommended that exposed areas be cleaned by washing

with soap and water.

In case of eye contact : Remove contact lenses.

Protect unharmed eye.

If swallowed : Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

No symptoms known or expected.

Notes to physician : No hazards which require special first aid measures.

5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray Foam

Carbon dioxide (CO2)

Dry chemical

Specific hazards during

firefighting

Do not allow run-off from fire fighting to enter drains or water

courses.

If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the

point of release.

Hazardous combustion : carbon dioxide and carbon monoxide



Valvoline™ HIGH MILEAGE with MaxLife™ Technology SAE 10W-30 Synthetic Blend Motor Oil

Revision Date: 10/23/2020 Print Date: 11/24/2020 Version: 8.0

products

Specific extinguishing

methods

Standard procedure for chemical fires.

Product is compatible with standard fire-fighting agents.

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Comply with all applicable federal, state, and local regulations.

Prevent further leakage or spillage if safe to do so. **Environmental precautions**

Methods and materials for containment and cleaning up Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.

Materials to avoid : No materials to be especially mentioned.

Further information on

storage stability

No decomposition if stored and applied as directed.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	TWA (Mist)	5 mg/m3	VN OEL



Valvoline™ HIGH MILEAGE with MaxLife™ Technology SAE 10W-30 Synthetic Blend Motor Oil

Version: 8.0 Revision Date: 10/23/2020 Print Date: 11/24/2020

		STEL (Mist)	10 mg/m3	VN OEL	
		TWA	300 mg/m3	VN OEL	
	Further information: Group 2A: Probably carcinogenic to humans				
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	TWA (Mist)	5 mg/m3	VN OEL	
		STEL (Mist)	10 mg/m3	VN OEL	
		TWA	300 mg/m3	VN OEL	
	Further information: Group 2A: Probably carcinogenic to humans				
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	TWA (Mist)	5 mg/m3	VN OEL	
		STEL (Mist)	10 mg/m3	VN OEL	

Engineering measures

General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally

required.

No personal respiratory protective equipment normally

required.

Eye protection : Not required under normal conditions of use. Wear splash-

proof safety goggles if material could be misted or splashed

into eyes.

Skin and body protection : Wear as appropriate:

Safety shoes

Hygiene measures : General industrial hygiene practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : amber

Odour : mild

Odour Threshold : No data available



Valvoline™ HIGH MILEAGE with MaxLife™ Technology SAE 10W-30 Synthetic Blend Motor Oil

Version: 8.0 Revision Date: 10/23/2020 Print Date: 11/24/2020

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : > 218 °C

(1013 hPa)

Flash point : > 199 °C

Method: Cleveland open cup

Evaporation rate : < 1

Flammability (solid, gas) : No data available

Self-ignition : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : < 1.0 mmHg (20 °C)

Relative vapour density : > 1

AIR=1

Relative density : No data available

Density : 0.8687 g/cm3 (15.6 °C)

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : ca. 70 mm2/s (40 °C)

Oxidizing properties : No data available



Valvoline™ HIGH MILEAGE with MaxLife™ Technology SAE 10W-30 Synthetic Blend Motor Oil

Version: 8.0 Revision Date: 10/23/2020 Print Date: 11/24/2020

10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous

reactions

Product will not undergo hazardous polymerization.

Conditions to avoid : excessive heat

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products

No hazardous decomposition products are known.

11. TOXICOLOGICAL INFORMATION

Exposure routes

Inhalation Skin contact Eye Contact Ingestion

Acute toxicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

Skin corrosion/irritation

Not classified based on available information.

Product:

Result : Slight, transient irritation

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:



Valvoline™ HIGH MILEAGE with MaxLife™ Technology SAE 10W-30 Synthetic Blend Motor Oil

Version: 8.0 Revision Date: 10/23/2020 Print Date: 11/24/2020

Assessment : Slight, transient irritation
Result : Slight, transient irritation

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Assessment : Slight, transient irritation
Result : Slight, transient irritation

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Assessment : Slight, transient irritation
Result : Slight, transient irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Result : Slight, transient irritation

Remarks : Expected based on components.

Remarks : Unlikely to cause eye irritation or injury.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Result : No eye irritation
Assessment : No eye irritation

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Result : No eye irritation
Assessment : No eye irritation

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result : Slight, transient irritation
Assessment : Slight, transient irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.



Valvoline™ HIGH MILEAGE with MaxLife™ Technology SAE 10W-30 Synthetic Blend Motor Oil

Version: 8.0 Revision Date: 10/23/2020 Print Date: 11/24/2020

Carcinogenicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

No aspiration toxicity classification

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks : No data available



Valvoline™ HIGH MILEAGE with MaxLife™ Technology SAE 10W-30 Synthetic Blend Motor Oil

Version: 8.0 Revision Date: 10/23/2020 Print Date: 11/24/2020

12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

: Not classified based on available information. Chronic aquatic toxicity

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Toxicity to fish : LL50 (Fish): > 100 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EL50 (Aquatic invertebrates): > 10,000 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

: EL50 (Algae, algal mat (Algae)): > 100 mg/l

Exposure time: 72 h

Toxicity to fish (Chronic

toxicity)

: NOEC (Fish): 10 mg/l

aquatic invertebrates (Chronic toxicity)

Toxicity to daphnia and other : NOEC (Aquatic invertebrates): 10 mg/l

Ecotoxicology Assessment

Acute aquatic toxicity Not classified based on available information.

Chronic aquatic toxicity Not classified based on available information.

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity . Not classified based on available information.

Persistence and degradability

No data available



Valvoline™ HIGH MILEAGE with MaxLife™ Technology SAE 10W-30 Synthetic Blend Motor Oil

Version: 8.0 Revision Date: 10/23/2020 Print Date: 11/24/2020

Bioaccumulative potential

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Partition coefficient: n- : log Pow: Expected > 7

octanol/water

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological

information

: No data available

13. DISPOSAL CONSIDERATIONS

Disposal methods

Contaminated packaging : Empty remaining contents.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

15. REGULATORY INFORMATION



Valvoline™ HIGH MILEAGE with MaxLife™ Technology SAE 10W-30 Synthetic Blend Motor Oil

Version: 8.0 Revision Date: 10/23/2020 Print Date: 11/24/2020

Safety, health and environmental regulations/legislation specific for the substance or mixture

Law on Chemicals No. 06/2007/QH12

Law on Chemicals No. 06/2007/QH12 : Not applicable

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

TCSI : On the inventory, or in compliance with the inventory

TSCA : On TSCA Inventory

16. OTHER INFORMATION

Full text of other abbreviations

VN OEL : Vietnam. Occupational Exposure Limits

VN OEL / TWA : Time weighted average VN OEL / STEL : Short term exposure limit

AICS - Australian Inventory of Chemical Substances; AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); Ecx - Concentration associated with x% response; Elx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety



Valvoline™ HIGH MILEAGE with MaxLife™ Technology SAE 10W-30 Synthetic Blend Motor Oil

Version: 8.0 Revision Date: 10/23/2020 Print Date: 11/24/2020

and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 -Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch -Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS -Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

R0355563 / VN / EN