



Version 1.1	Revision Date: 10/07/2020		DS Number: 00000001311	Date of last issue: 10/03/2019 Date of first issue: 10/03/2019			
SECTION	N 1. IDENTIFICATION						
Prod	luct name	:	AC OZIUM .8OZ	VANILLA 48/6			
Prod	luct code	:	OZ-23				
	ufacturer or supplier's			LC			
Addr	Address		Dallas TX 75225				
Ema	il Address	:	EHS@niteoprodu	ucts.com			
Tele	phone	:	1-844-696-4836				
Eme ber	rgency telephone num-	:	1-800-424-9300 /	/ 1-703-741-5970			
Reco	ommended use of the c	her	nical and restriction	ons on use			
Reco	ommended use	:	AIR FRESHENEI	R			

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accore Flammable aerosols	dan :	ce with 29 CFR 1910.1200 Category 1
Eye irritation	:	Category 2A
Specific target organ toxicity - single exposure	:	Category 3 (Central nervous system)
GHS label elements Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	Extremely flammable aerosol. Causes serious eye irritation. May cause drowsiness or dizziness.
Precautionary statements	:	Prevention: Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.



ersion 1	Revision Date: 10/07/2020	SDS Number: 60000001311	Date of last issue: 10/03/2019 Date of first issue: 10/03/2019				
		Wash skin thor Use only outdo	g dust/ fume/ gas/ mist/ vapours/ spray. oughly after handling. oors or in a well-ventilated area. ection/ face protection.				
		Response: IF INHALED: Remove person to fresh air and keep comfort for breathing. Call a POISON CENTER/doctor if you feel un IF IN EYES: Rinse cautiously with water for several minutes Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention.					
		Store locked up	ventilated place. Keep container tightly closed. p. unlight. Do not expose to temperatures exceedin				
		Disposal: Dispose of con plant.	tents/ container to an approved waste disposal				
Othe	r hazards						
None	known.						

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

CAS-No.	Concentration (% w/w)
67-63-0	>= 30 - < 50
68476-86-8	>= 20 - < 30
75-37-6	>= 5 - < 10
57-55-6	>= 1 - < 5
	67-63-0 68476-86-8 75-37-6

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4. FIRST AID MEASURES

General advice	:	Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	:	Move to fresh air. Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	:	If on skin, rinse well with water.
In case of eye contact	:	Immediately flush eye(s) with plenty of water.



Version 1.1	Revision Date: 10/07/2020		Number: 00001311	Date of last issue: 10/03/2019 Date of first issue: 10/03/2019
		P K		
lf swa	llowed	N	ever give anyth	or alcoholic beverages. ing by mouth to an unconscious person. sist, call a physician.
	important symptoms ffects, both acute and ed		auses serious e lay cause drows	eye irritation. siness or dizziness.
			-	

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Water spray Carbon dioxide (CO2) Dry chemical Alcohol-resistant foam
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during fire- fighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion prod- ucts	:	Carbon oxides Halogenated compounds
Specific extinguishing meth- ods	:	Product is compatible with standard fire-fighting agents.
Further information	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Use a water spray to cool fully closed containers.
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Use personal protective equipment. Remove all sources of ignition. Ensure adequate ventilation. Avoid breathing dust. Beware of vapours accumulating to form explosive concentra- tions. Vapours can accumulate in low areas. Evacuate personnel to safe areas. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
Environmental precautions	:	Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.



Version 1.1	Revision Date: 10/07/2020		Number: 000001311	Date of last issue: 10/03/2019 Date of first issue: 10/03/2019			
		Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inforr respective authorities.					
SECTION	7. HANDLING AND ST	ORAC	9E				
	e on protection against nd explosion	(which might caus Keep away from o gnition. Jse only explosic	action to avoid static electricity discharge se ignition of organic vapours). open flames, hot surfaces and sources of on-proof equipment. a naked flame or any incandescent material.			
Advic	e on safe handling	F [[7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	Provide sufficient Do not breathe va Do not smoke. Fake precautiona Avoid contact with Dispose of rinse v egulations. Container hazard Smoking, eating a blication area.	ry measures against static discharges.			
Cond	itions for safe storage	e c r ł () ł	exposure and ten or throw into fire e ed-hot objects. Keep container tig place.				
	er information on stor-	: 1	No decomposition	n if stored and applied as directed.			

age stability

bility

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Isopropanol	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m3	NIOSH REL
		ST	500 ppm 1,225 mg/m3	NIOSH REL
		TWA	400 ppm	OSHA Z-1



	Revision Date: 10/07/2020			umber:)001311		Date of las Date of firs				
							980 mg/r	n3	1	
					T۷	VA	400 ppm 980 mg/r		05	SHA P0
					ST	ΓEL	500 ppm 1,225 mg		05	SHA P0
-	ifluoroethane		75-3			VA	1,000 pp			6 WEEL
Propy	/lene glycol		57-5	55-6	T٧	VA	10 mg/m	3	US	S WEEL
Biolo	gical occupational	l expos	ure li	mits						
Comp	ponents	CAS-	No.	Control paramete	rs	Biological specimen	Sam- pling time	Permissi concentr tion		Basis
Isopro	opanol	67-63	-0	Acetone		Urine	End of shift at end of work- week	40 mg/l		ACGIF BEI
	iratory protection	:	pro In t	he case of ved filter. he case of proved filte	dus	our formatio			th ar	
Hand					r.		Tormation	use respira	ator	
	protection				r.		Tormation	use respira	ator	
Re	protection emarks	:	er).	ar resistan The suital	t glo pility	oves (consul oves for a specif roducers of	lt your safe ïc workplac	ty equipme	ent s be di	with an suppli-
		:	er). cus We	ear resistan The suitat sed with th ear chemica	t glo pility ne p al sp	oves (consul / for a specif	It your safe ic workplac the protecti s when the	ty equipme ce should b ive gloves. ere is the p	ent s oe di	with an suppli- is-
Eye p	emarks	:	er). cus We exp Cho cer We Imp Fla	ear resistan The suitat sed with the ear chemicate oosure of the cose body	t glo pility ne p al sp ne e prot he c opri-	oves (consul / for a specif roducers of blash goggle yes to liquid tection acco dangerous s ate: ng	It your safe ic workplac the protect s when the , vapor or r rding to the	ty equipme ce should t ive gloves. ere is the p nist. e amount a	ent s be di oten	with an suppli- is- itial for

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	aerosol
------------	---	---------

Colour

: colourless



Version 1.1	Revision Date: 10/07/2020		S Number: 0000001311	Date of last issue: 10/03/2019 Date of first issue: 10/03/2019
Odo	ur	:	pleasant	
Odo	ur Threshold	:	not determined	
pН		:	not determined	
Melt	ing point/freezing point	:	not determined	
Boili	ng point/boiling range	:	not determined	
Flas	h point	:	32 °C Method: closed c	sup
Eva	poration rate	:	not determined	
Flam	nmability (solid, gas)	:	not determined	
Self	f-ignition	:	not determined	
	er explosion limit / Upper mability limit	:	not determined	
	er explosion limit / Lower mability limit	:	not determined	
Vapo	our pressure	:	not determined	
Den	sity	:	not determined	
	bility(ies) Vater solubility	:	completely misci	ble
	ition coefficient: n- nol/water	:	not determined	
Dec	omposition temperature	:	not determined	
	osity /iscosity, dynamic	:	not determined	
V	iscosity, kinematic	:	not determined	
Mole	ecular weight	:	No data available	9
VOC	℃% By Weight	:	69.28 %	

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reac- tions	:	No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.



Version	Revision Date: 10/07/2020	SDS Number:	Date of last issue: 10/03/2019
1.1		600000001311	Date of first issue: 10/03/2019
Condi	itions to avoid	: Heat, flame	es and sparks.
Incom	patible materials	: Strong oxid	lizing agents
Hazaı	rdous decomposition	: Carbon oxi	des
produ	cts	Halogenate	ed compounds

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely route Inhalation Eye contact Skin contact Ingestion	s of	exposure
Acute toxicity		
Not classified based on avail	able	information.
Product:		
Acute oral toxicity	:	Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method
Acute dermal toxicity	:	Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method
		Remarks: Skin absorption of this material (or a component) may be increased through injured skin.
<u>Components:</u>		
Isopropanol:		
Acute oral toxicity	:	LD50 (Rat): 5.84 g/kg
Acute inhalation toxicity	:	LC50 (Rat): 16000 ppm Exposure time: 4 h Test atmosphere: vapour
Acute dermal toxicity	:	LD50 (Rabbit): 12,800 mg/kg
1,1-Difluoroethane: Acute inhalation toxicity	:	LC50 (Rat): 437500 ppm Exposure time: 4 h Test atmosphere: gas
Propylene glycol: Acute oral toxicity	:	LD50 (Rat): 21.0 - 33.7 g/kg
Acute dermal toxicity	:	LD50 (Rabbit): 28 g/kg

Skin corrosion/irritation

Not classified based on available information.





Version	Revision Date:	SDS Number:
1.1	10/07/2020	60000001311

Date of last issue: 10/03/2019 Date of first issue: 10/03/2019

Product:

Remarks: May cause skin irritation in susceptible persons.

Components:

Isopropanol:

Result: Possibly irritating to skin

Propylene glycol:

Assessment: No skin irritation Result: No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:

Isopropanol: Result: Irritating to eyes.

Propylene glycol:

Result: Possibly irritating to eyes

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Components:

1,1-Difluoroethane:

Genotoxicity in vitro

Test Type: Ames test Test system: Salmonella typhimurium Metabolic activation: with and without metabolic activation Result: negative

Carcinogenicity

Not classified based on availab	le information. No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or



ersion 1	Revision Date: 10/07/2020	SDS Number: 600000001311	Date of last issue: 10/03/2019 Date of first issue: 10/03/2019
		equal to 0.1% is c	on OSHA's list of regulated carcinogens.
NTP			this product present at levels greater than or dentified as a known or anticipated carcinogen
-	oductive toxicity lassified based on ava	ailable information.	
	F - single exposure cause drowsiness or c	lizziness.	
Com	ponents:		
-	opanol: ssment: May cause dr	owsiness or dizziness.	
	F - repeated exposur lassified based on ava		
-	r ation toxicity lassified based on ava	ailable information.	
Furth	ner information		
Prod Rema iting.		erexposure may be hea	adache, dizziness, tiredness, nausea and vom-
ECTION	12. ECOLOGICAL IN	IFORMATION	
	city ional ecological nation		ntal hazard cannot be excluded in the event of handling or disposal. atic life.
ECTION	13. DISPOSAL CON	SIDERATIONS	
Dispo	osal methods		
14/			······································

Waste from residues	:	Dispose of in accordance with all applicable local, state and federal regulations.
Contaminated packaging	:	Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.



Version	Revision Date:	SDS Number:	Date of last issue: 10/03/2019
1.1	10/07/2020	60000001311	Date of first issue: 10/03/2019

International Regulations

IATA-DGR UN/ID No. Proper shipping name Class Packing group Labels Packing instruction (cargo aircraft) Packing instruction (passenger aircraft)	:	UN 1950 Aerosols, flammable 2.1 Not assigned by regulation 2.1 203 203
IMDG-Code UN number Proper shipping name Class Packing group Labels EmS Code Marine pollutant		UN 1950 AEROSOLS 2.1 Not assigned by regulation 2.1 F-D, S-U no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR UN/ID/NA number Proper shipping name	-	UN 1950 Aerosols
Class Packing group Labels ERG Code Marine pollutant	:	2.1 Not assigned by regulation 2.1 126 no

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Hydrochloric acid	7647-01-0	5000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Hydrochloric acid	7647-01-0	5000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.




Version 1.1	Revision Date: 10/07/2020	SDS Number: 60000001311	Date of last issue: 10/ Date of first issue: 10/			
SARA 311/312 Hazards		: Flammable (gases, aerosols, liquids, or solids) Serious eye damage or eye irritation Specific target organ toxicity (single or repeated exposure)				
SAR	A 313		The following components are subject to reporting levels es- tablished by SARA Title III, Section 313:			
		Isopropanol	67-63-0	>= 30 - < 50 %		

California Prop. 65

This product contains a chemical that is at or below California Propositions 65's "safe harbor level" as determined via a risk assessment. Therefore, the chemical is not required to be listed as a Prop 65 chemical on the SDS or label.

Proposition 65 warnings are not required for this product based on the results of a risk assessment.

SECTION 16. OTHER INFORMATION



Revision Date : 10/07/2020

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN