

acc. to 29 CFR 1910.1200 App D

Armor All Extreme Shield + Ceramic Wheel Cleaner- Aerosol

Version number: 4.0 Revision: 2020-12-03 Replaces version of: 2020-10-21 (3)

SECTION 1: Identification

1.1 Product identifier

Trade name Armor All Extreme Shield + Ceramic Wheel

Cleaner- Aerosol

Alternative number(s) 070612194084, 67788193812

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses General use

1.3 Details of the supplier of the safety data sheet

Energizer Manufacturing, Inc. 25225 Detroit Rd. Westlake OH 44145 United States

Telephone: 800-383-7323; 314-985-2000 (USA / CANADA)

Website: http://data.energizer.com

Energizer Trading Ltd.

Sword House, Totteridge Road, High Wycombe, HP13 6DG, UK

Telephone: +44(0)8000353376

e-mail: ConsumerServiceEU@energizer.com

1.4 Emergency telephone number

Emergency information service 1-314-985-1511 Int'l: 1-800-526-4727

This number is only available during the following

office hours: Mon-Fri 09:00 AM - 05:00 PM

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard state- ment	
A.3	serious eye damage/eye irritation	2	Eye Irrit. 2	H319	
B.3	flammable aerosol	2	Flam. Aerosol 2	H223	
B.5	gases under pressure	С	Press. Gas C	H280	

For full text of abbreviations: see SECTION 16.

United States: en Page: 1 / 19



acc. to 29 CFR 1910.1200 App D

Armor All Extreme Shield + Ceramic Wheel Cleaner- Aerosol

Version number: 4.0 Revision: 2020-12-03 Replaces version of: 2020-10-21 (3)

The most important adverse physicochemical, human health and environmental effects

Contains gas under pressure; may explode if heated. The mixture contains a substance that was identified as a PBT (persistent, bioaccumulative and toxic). The mixture contains a substance that was identified as vPvB (very persistent and very bioaccumulative).

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Signal word warning

- Pictograms

GHS02, GHS04, GHS07



- Hazard statements

H223 Flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.

- Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children. P103 Read label before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.

P280 Wear eye protection/face protection.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention. P410+P403 Protect from sunlight. Store in a well-ventilated place.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.3 Other hazards

Hazards not otherwise classified

Contains epoxy constituents. May produce an allergic reaction. Harmful to aquatic life (GHS category 3: aquatic toxicity - acute).

Results of PBT and vPvB assessment

Containing a PBT-/vPvB-substance in a concentration of \geq 0,1%. Containing a PBT-substance in a concentration of \geq 0,1%. Containing a vPvB-substance in a concentration of \geq 0,1%.

United States: en Page: 2 / 19



acc. to 29 CFR 1910.1200 App D

Armor All Extreme Shield + Ceramic Wheel Cleaner- Aerosol

Version number: 4.0 Revision: 2020-12-03 Replaces version of: 2020-10-21 (3)

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
Siloxanes and Silicones, di- ME, [[[3-[(2- aminoethyl)amino]propyl] dimethoxysily]oxy]-termin- ated	CAS No 71750-80-6	1-<5	Eye Irrit. 2B / H320	
Polyethylene glycol tri- methylnonyl ether	CAS No 60828-78-6	1-<5	Eye Dam. 1 / H318	
isobutane	CAS No 75-28-5	1-<5	Muta. 1B / H340 Carc. 1A / H350 Flam. Gas 1 / H220 Press. Gas C / H280	
propane	74-98-6 Flam. Ga		sA / OSHA002 Flam. Gas 1 / H220 Press. Gas C / H280	&

For full text of abbreviations: see SECTION 16.

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Thaw frosted parts with lukewarm water. Do not rub affected area.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

United States: en Page: 3 / 19



acc. to 29 CFR 1910.1200 App D

Armor All Extreme Shield + Ceramic Wheel Cleaner- Aerosol

Version number: 4.0 Revision: 2020-12-03 Replaces version of: 2020-10-21 (3)

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Contact with the product can cause burns and/or frostbite. Contains gas under pressure; may explode if heated.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO2)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

United States: en Page: 4 / 19



acc. to 29 CFR 1910.1200 App D

Armor All Extreme Shield + Ceramic Wheel Cleaner- Aerosol

Version number: 4.0 Revision: 2020-12-03 Replaces version of: 2020-10-21 (3)

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Managing of associated risks

- Flammability hazards

Do not spray on an open flame or other ignition source. Protect from sunlight.

Control of the effects

Protect against external exposure, such as

Frost

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)

Coun try	Name of agent	CAS No	Iden- tifier	TWA [ppm]	TWA [mg/ m³]	STEL [ppm]	STEL [mg/ m³]	Ceil- ing-C [ppm]	Ceil- ing-C [mg/ m³]	Nota tion	Sourc e
US	propane	74-98-6	PEL (CA)	1,000	1,800						Cal/ OSHA PEL

United States: en Page: 5 / 19



acc. to 29 CFR 1910.1200 App D

Armor All Extreme Shield + Ceramic Wheel Cleaner- Aerosol

Version number: 4.0 Revision: 2020-12-03 Replaces version of: 2020-10-21 (3)

Occupational exposure limit values (Workplace Exposure Limits)

Coun try	Name of agent	CAS No	Iden- tifier	TWA [ppm]	TWA [mg/ m³]	STEL [ppm]	STEL [mg/ m³]	Ceil- ing-C [ppm]	Ceil- ing-C [mg/ m³]	Nota tion	Sourc e
US	propane	74-98-6	REL	1,000 (10 h)	1,800 (10 h)						NIOSH REL
US	propane	74-98-6	PEL	1,000	1,800						29 CFR 1910.1 000
US	propane	74-98-6	TLV®							oxy- gen, Simpl e Asp., E	AC- GIH® 2019
US	isobutane	75-28-5	REL	800 (10 h)	1,900 (10 h)						NIOSH REL
US	isobutane	75-28-5	TLV®			1,000				Е	AC- GIH® 2019

Notation

Ceiling-C ceiling value is a limit value above which exposure should not occur

explosive

oxygen Adequate oxygen delivery to the tissues is necessary for sustaining life

Simple Asp. simple asphyxiants

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period

(unless otherwise specified)

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-

weighted average (unless otherwise specified

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear protective gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

United States: en Page: 6 / 19



acc. to 29 CFR 1910.1200 App D

Armor All Extreme Shield + Ceramic Wheel Cleaner- Aerosol

Version number: 4.0 Revision: 2020-12-03 Replaces version of: 2020-10-21 (3)

Respiratory protection

During spraying wear suitable respiratory equipment.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	aerosol (spray aerosol)
Color	various
Odor	characteristic

Other safety parameters

pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	-161.5 °C at 1,013 hPa
Flash point	not determined
Evaporation rate	not determined
Flammability (solid, gas)	flammable aerosol in accordance with GHS criteria

Explosive limits

- Lower explosion limit (LEL)	3 vol%
- Upper explosion limit (UEL)	15 vol%
Vapor pressure	not determined
Density	not determined
Vapor density	this information is not available
Relative density	information on this property is not available

United States: en Page: 7 / 19

acc. to 29 CFR 1910.1200 App D

Armor All Extreme Shield + Ceramic Wheel Cleaner- Aerosol

Version number: 4.0 Revision: 2020-12-03 Replaces version of: 2020-10-21 (3)

Solubility(ies)	not determined				
Partition coefficient					
- n-octanol/water (log KOW)	this information is not available				
Auto-ignition temperature	not determined				
Viscosity	not relevant (aerosol)				
Explosive properties	none				
Oxidizing properties	none				
Other information					
Propellant content	5 %				

Propellant content	5 %

SECTION 10: Stability and reactivity

10.1 Reactivity

9.2

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Gas under pressure. Risk of ignition.

Danger of explosion, Gas under pressure, Danger of bursting container

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

Conditions to avoid 10.4

Do not spray on an open flame or other ignition source. Keep away from heat.

Hints to prevent fire or explosion

Protect from sunlight.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

United States: en Page: 8 / 19



acc. to 29 CFR 1910.1200 App D

Armor All Extreme Shield + Ceramic Wheel Cleaner- Aerosol

Version number: 4.0 Revision: 2020-12-03 Replaces version of: 2020-10-21 (3)

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Contains epoxy constituents. May produce an allergic reaction.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Harmful to aquatic life.

United States: en Page: 9 / 19



acc. to 29 CFR 1910.1200 App D

Armor All Extreme Shield + Ceramic Wheel Cleaner- Aerosol

Version number: 4.0 Revision: 2020-12-03 Replaces version of: 2020-10-21 (3)

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
isobutane	75-28-5	LC50	49.9 ^{mg} / _l	fish	96 h
isobutane	75-28-5	EC50	19.37 ^{mg} / _l	algae	96 h
propane	74-98-6	LC50	49.9 ^{mg} / _l	fish	96 h
propane	74-98-6	EC50	19.37 ^{mg} / _l	algae	96 h

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

The substance fulfills the very bioaccumulative criterion.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

The mixture contains a substance that was identified as a PBT (persistent, bioaccumulative and toxic). The mixture contains a substance that was identified as vPvB (very persistent and very bioaccumulative).

12.6 Other adverse effects

Endocrine disrupting potential

None of the ingredients are listed.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

United States: en Page: 10 / 19



acc. to 29 CFR 1910.1200 App D

Armor All Extreme Shield + Ceramic Wheel Cleaner- Aerosol

Version number: 4.0 Revision: 2020-12-03 Replaces version of: 2020-10-21 (3)

SECTION 14: Transport information

14.1 UN number 1950

14.2 UN proper shipping name Aerosols

14.3 Transport hazard class(es)

Class 2.1 (gases) (aerosol) (flammable)

14.4 Packing group not assigned to a packing group

14.5 Environmental hazards non-environmentally hazardous acc. to the danger-

ous goods regulations

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

DOT

Transport of dangerous goods by road or rail (49 CFR US DOT)

Index number 1950
Proper shipping name Aerosols

- Particulars in the shipper's declaration UN1950, Aerosols, 2.1

- Reportable quantity (RQ) 6,662,225 lbs (3,024,650 kg) (acetic acid) (ethylene oxide)

Class 2.1 Danger label(s) 2.1



Special provisions (SP) N82 ERG No 126

International Maritime Dangerous Goods Code (IMDG)

UN number 1950

Proper shipping name AEROSOLS

- Particulars in the shipper's declaration UN1950, AEROSOLS, 2.1

Class 2.1 Marine pollutant -

United States: en Page: 11 / 19



acc. to 29 CFR 1910.1200 App D

Armor All Extreme Shield + Ceramic Wheel Cleaner- Aerosol

Version number: 4.0 Revision: 2020-12-03 Replaces version of: 2020-10-21 (3)

Danger label(s) 2.1



Special provisions (SP) 63, 190, 277, 327, 344, 381, 959

Excepted quantities (EQ) E0
Limited quantities (LQ) 1 L
EmS F-D, S-U

Stowage category -

International Civil Aviation Organization (ICAO-IATA/DGR)

UN number 1950

Proper shipping name Aerosols, flammable

- Particulars in the shipper's declaration UN1950, Aerosols, flammable, 2.1

Class 2.1 Danger label(s) 2.1



Special provisions (SP) A145, A167

Excepted quantities (EQ) E0
Limited quantities (LQ) 30 kg

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Toxic Substance Control Act (TSCA) all ingredients are listed

Clean Air Act

Name of substance	CAS No	Type of registra- tion	Basis for listing	Threshold quantity (lbs)
isobutane	75-28-5	Flammable sub- stance	f	10000
propane	74-98-6	Flammable sub- stance	f	10000

Legend

f Flammable gas.

United States: en Page: 12 / 19





Armor All Extreme Shield + Ceramic Wheel Cleaner- Aerosol

Version number: 4.0 Revision: 2020-12-03 Replaces version of: 2020-10-21 (3)

Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	Name acc. to inventory	CAS No	Functional- ity	Authoritative Lists
Water		7732-18-5	solvents	
Isobutane	Isobutane	75-28-5	propellant	EC Annex VI CMRs - Cat. 1A EC Annex VI CMRs - Cat. 1B
Propane		74-98-6	propellant	
Polyethylene glycol trimethyl- nonyl ether		60828-78-6	surfactant	
Sodium Bicarbonate		144-55-8	foaming agent	
Sodium Carbonate		497-19-8 6132-02-1	cleaning agent	
Acetic acid		64-19-7	biocide	
Alkyl C12-16 Dimethylbenzyl Am- monium Chloride		68424-85-1	preservative	
Water		7732-18-5	solvents	
Ethanol		64-17-5	solvents	
Dodecamethylcyclohexasiloxane	Dodecamethylcyclohexasilox- ane (D6)	540-97-6	emulsifier	Canada PBiTs CECBP - Priority Chemicals EC PBTs
Octamethylcyclotetrasiloxane	Octamethylcyclotetrasiloxane (D4)	556-67-2	emulsifier	Canada PBiTs CECBP - Priority Chemicals EC PBTs
Decamethylcyclopentasiloxane	decamethylcyclopentasiloxane (D5)	541-02-6	emulsifier	Canada PBiTs CECBP - Priority Chemicals EC PBTs
Sodium chloride		7647-14-5	preservative	
1,4-dioxane	1,4-Dioxane	123-91-1	nonfunction- al constitu- ent	CA NLs CA TACs IARC Carcinogens - 2B IRIS Carcinogens - Likely Carcin. NTP 13th RoC - reasonable OEHHA RELs Prop 65

United States: en Page: 13 / 19



acc. to 29 CFR 1910.1200 App D

Armor All Extreme Shield + Ceramic Wheel Cleaner- Aerosol

Version number: 4.0 Revision: 2020-12-03 Replaces version of: 2020-10-21 (3)

Name of substance	Name acc. to inventory	CAS No	Functional- ity	Authoritative Lists
Ethylene oxide	Ethylene oxide	75-21-8	disinfectant	ATSDR Neurotoxicants CA TACs CDC 4th National Exposure Report EC Annex VI CMRs - Cat. 1B IARC Carcinogens - 1 IRIS Carcinogens - Carcin. NTP 13th RoC - known OEHHA RELs Prop 65

- Hazardous Substances List (MN-ERTK)

Name of substance	Name acc. to inventory	CAS No	References	Remarks
isobutane	Alkanes		N	
propane	Propane	74-98-6	A, O	
propane	Alkanes		N	
propane	Gases, Simple Asphyxiants		А	gases

Legend

American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH

gases Refers to displacement of air asphyxiation hazard.
N National Institute for Occupational Safety and Hea

National Institute for Occupational Safety and Health (NIOSH), "Recommendations for Occupational Safety and Health Standards," August 1988, available from NIOSH, Publications Dissemination Office, Division of Standards Development and Technology Transfer

Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division

- Hazardous Substance List (NJ-RTK)

Name of substance	Name acc. to inventory	CAS No	Remarks	Classifications
isobutane	isobutane (propane, 2-methyl-)	75-28-5		F4
propane	propane	74-98-6		F4

Legend

F4 Flammable - Fourth Degree

- Hazardous Substance List (Chapter 323) (PA-RTK)

Name of substance	Name acc. to inventory	CAS No	Classification
isobutane	PROPANE, 2-METHYL-	75-28-5	
propane	PROPANE	74-98-6	

United States: en Page: 14 / 19





Armor All Extreme Shield + Ceramic Wheel Cleaner- Aerosol

Version number: 4.0 Revision: 2020-12-03 Replaces version of: 2020-10-21 (3)

- Hazardous Substance List (RI-RTK)

Name of substance	Name acc. to inventory	CAS No	References
isobutane	Butane	106-97-8	Т, F
propane	liquefied petroleum gas	74-98-6	Т

Legend

F Flammability (NFPA®)
T Toxicity (ACGIH®)

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals

Name acc. to inventory	CAS No	Remarks	Type of the toxicity
1,4-dioxane	123-91-1		cancer
ethylene oxide	75-21-8		cancer
ethylene oxide	75-21-8		female
ethylene oxide	75-21-8		developmental, male
ethanol (ethyl alcohol)	64-17-5	in alcoholic beverages	developmental

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	2	temporary or minor injury may occur
Flammability	4	material that rapidly or completely vaporizes at atmospheric pressure and normal ambient temperature or that is readily dispersed in air and burn readily
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

United States: en Page: 15 / 19



acc. to 29 CFR 1910.1200 App D

Armor All Extreme Shield + Ceramic Wheel Cleaner- Aerosol

Version number: 4.0 Revision: 2020-12-03 Replaces version of: 2020-10-21 (3)

Category	Degree of hazard	Description
Flammability	4	material that rapidly or completely vaporizes at atmospheric pressure and normal ambient temperature or that is readily dispersed in air and burn readily
Health	0	material that, under emergency conditions, would offer no hazard beyond that of or- dinary combustible material
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
AU	AICS	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	not all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed

Legend

AICS Australian Inventory of Chemical Substances CICR Chemical Inventory and Control Regulation

CSCL-ENCS List of Existing and New Chemical Substances (CSCL-ENCS)

DSL

ECSI

Domestic Substances List (DSL)
EC Substance Inventory (EINECS, ELINCS, NLP)
Inventory of Existing Chemical Substances Produced or Imported in China
National Inventory of Chemical Substances
Inventory of Existing and New Chemical Substances (ISHA-ENCS)
Korea Existing Chemicals Inventory **IECSC**

INSQ ISHA-ENCS

KECI New Zealand Inventory of Chemicals NZIoC

Philippine Inventory of Chemicals and Chemical Substances (PICCS) **PICCS**

REACH Reg. REACH registered substances

TCSI Taiwan Chemical Substance Inventory **TSCA** Toxic Substance Control Act

United States: en Page: 16 / 19



acc. to 29 CFR 1910.1200 App D

Armor All Extreme Shield + Ceramic Wheel Cleaner- Aerosol

Version number: 4.0 Revision: 2020-12-03 Replaces version of: 2020-10-21 (3)

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
3.2		Description of the mixture: change in the listing (table)	yes
14.7		Danger label(s): change in the listing (table)	yes
15.1		Cleaning Product Right to Know Act Substance List (CA-RTK): change in the listing (table)	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH®	American Conference of Governmental Industrial Hygienists
ACGIH® 2019	From ACGIH®, 2019 TLVs® and BEIs® Book. Copyright 2019. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
Carc.	Carcinogenicity
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DOT	Department of Transportation (USA)
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule

United States: en Page: 17 / 19



acc. to 29 CFR 1910.1200 App D

Armor All Extreme Shield + Ceramic Wheel Cleaner- Aerosol

Version number: 4.0 Revision: 2020-12-03 Replaces version of: 2020-10-21 (3)

	(-)
Abbr.	Descriptions of used abbreviations
ERG No	Emergency Response Guidebook - Number
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Gas	Flammable gas
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
Muta.	Germ cell mutagenicity
NFPA®	National Fire Protection Association (United States)
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NLP	No-Longer Polymer
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
ppm	Parts per million
Press. Gas	Gas under pressure
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
sA	Simple asphyxiants
STEL	Short-term exposure limit
TLV®	Threshold Limit Values
TWA	Time-weighted average
vPvB	Very Persistent and very Bioaccumulative
	•

United States: en Page: 18 / 19



acc. to 29 CFR 1910.1200 App D

Armor All Extreme Shield + Ceramic Wheel Cleaner- Aerosol

Version number: 4.0 Revision: 2020-12-03 Replaces version of: 2020-10-21 (3)

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H220	Extremely flammable gas.
H223	Flammable aerosol.
H280	Contains gas under pressure; may explode if heated.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H320	Causes eye irritation.
H340	May cause genetic defects.
H350	May cause cancer.
OSHA002	May displace oxygen and cause rapid suffocation.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

United States: en Page: 19 / 19