		Page: 1
SAFETY DATA SHEET		Revision Date: 10/04/2016
		Print Date: 11/1/2016
		SDS Number: 000000091604
Premium Blue™ EXTREME FULL SYNTHETIC HEAVY DUTY DIESEL SAE 5W-40 ENGINE OIL ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 774038		Version: 1.4

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Premium Blue™ EXTREME FULL SYNTHETIC HEAVY DUTY DIESEL SAE 5W-40 ENGINE OIL
 ™ Trademark, Valvoline or its subsidiaries, regisred in various countries

Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Lubricant


Details of the supplier of the safety data sheet Valvoline LLC 3499 Blazer Parkway Lexington, KY 40509 United States of America (USA) 1-800-TEAMVAL	Emergency telephone number 1-800-VALVOLINE Regulatory Information Number 1-800-TEAMVAL Product Information 1-800-TEAMVAL
---	--

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Reproductive toxicity : Category 2

GHS label elements

Hazard pictograms : 

Signal Word : Warning

Hazard Statements : Suspected of damaging fertility or the unborn child.

Precautionary Statements : If medical advice is needed, have product container or label at hand.
 Keep out of reach of children.
 Read label before use.
Prevention:
 Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.

SAFETY DATA SHEET

Revision Date: 10/04/2016

Print Date: 11/1/2016

SDS Number: 000000091604

Version: 1.4

Premium Blue™ EXTREME FULL SYNTHETIC HEAVY DUTY
DIESEL SAE 5W-40 ENGINE OIL

™ Trademark, Valvoline or its subsidiaries, regisred in various
countries
774038

Wear protective gloves/ protective clothing/ eye protection/ face
protection.

Response:

IF exposed or concerned: Get medical advice/ attention.

Storage:

Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal
plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture


Chemical nature : Defatter

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	Asp. Tox. 1; H304	46.0463
ZINC DIALKYL DITHIOPHOSPHATE	68649-42-3	Skin Irrit. 2; H315 Eye Dam. 1; H318	2.1942
TETRAPROPENYLPHENOL	121158-58-5	Skin Irrit. 2; H315 Eye Dam. 1; H318 Repr. 2; H361 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	0.1995

SECTION 4. FIRST AID MEASURES


General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

		Page: 3
SAFETY DATA SHEET		Revision Date: 10/04/2016
		Print Date: 11/1/2016
		SDS Number: 000000091604
Premium Blue™ EXTREME FULL SYNTHETIC HEAVY DUTY DIESEL SAE 5W-40 ENGINE OIL ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 774038		Version: 1.4

- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
If eye irritation persists, consult a specialist.
- If swallowed : Obtain medical attention.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:
acne
stomach or intestinal upset (nausea, vomiting, diarrhea)
irritation (nose, throat, airways)
Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.
- Suspected of damaging fertility or the unborn child.
- Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Foam

		Page: 4
SAFETY DATA SHEET		Revision Date: 10/04/2016
		Print Date: 11/1/2016
		SDS Number: 000000091604
Premium Blue™ EXTREME FULL SYNTHETIC HEAVY DUTY DIESEL SAE 5W-40 ENGINE OIL ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 774038		Version: 1.4

- Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : carbon dioxide and carbon monoxide
Hydrocarbons
Nitrogen oxides (NO_x)
Sulphur oxides
hydrogen sulfide
mercaptans
zinc oxide
Aldehydes
- Specific extinguishing methods :

Product is compatible with standard fire-fighting agents.
- Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.
- Other information : Comply with all applicable federal, state, and local regulations.

SAFETY DATA SHEET

Revision Date: 10/04/2016

Print Date: 11/1/2016

SDS Number: 000000091604

Version: 1.4

Premium Blue™ EXTREME FULL SYNTHETIC HEAVY DUTY DIESEL SAE 5W-40 ENGINE OIL
 ™ Trademark, Valvoline or its subsidiaries, regised in various countries
 774038

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Do not breathe vapours/dust.
 Do not smoke.
 Container hazardous when empty.
 Avoid exposure - obtain special instructions before use.
 Avoid contact with skin and eyes.
 Smoking, eating and drinking should be prohibited in the application area.
 For personal protection see section 8.
 Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.
 Observe label precautions.


SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Contains no substances with occupational exposure limit values.				
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL

Hazardous components without workplace control parameters

Components	CAS-No.
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7
ZINC DIALKYL DITHIOPHOSPHATE	68649-42-3
TETRAPROPENYLPHENOL	121158-58-5

		Page: 6
SAFETY DATA SHEET		Revision Date: 10/04/2016
		Print Date: 11/1/2016
		SDS Number: 000000091604
Premium Blue™ EXTREME FULL SYNTHETIC HEAVY DUTY DIESEL SAE 5W-40 ENGINE OIL ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 774038		Version: 1.4

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

Hand protection
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Wear resistant gloves (consult your safety equipment supplier).
 Wear as appropriate:
 Impervious clothing
 Safety shoes
 Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : Wash hands before breaks and at the end of workday.
 When using do not eat or drink.
 When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid

Odour : No data available

Odour Threshold : No data available

SAFETY DATA SHEET

Revision Date: 10/04/2016

Print Date: 11/1/2016

SDS Number: 000000091604

Version: 1.4

Premium Blue™ EXTREME FULL SYNTHETIC HEAVY DUTY
DIESEL SAE 5W-40 ENGINE OIL
™ Trademark, Valvoline or its subsidiaries, regisred in various
countries
774038

pH	: No data available
Melting point/freezing point	: No data available No data available
Boiling point/boiling range	: 392 °F / 200 °C Calculated Phase Transition Liquid/Gas
Flash point	: > 199 °C
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: 6 %(V) GLP: Calculated Explosive Limit
Lower explosion limit	: 1 %(V) GLP: Calculated Explosive Limit
Vapour pressure	: 1.3333333 hPa (20 °C) Calculated Vapor Pressure
Relative vapour density	: No data available
Relative density	: 0.8556 (20 °C)
Density	: No data available
Solubility(ies)	
Water solubility	: insoluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: 100 mm ² /s (40 °C)
Oxidizing properties	: No data available

SECTION 10. STABILITY AND REACTIVITY

**SAFETY DATA SHEET**

Revision Date: 10/04/2016

Print Date: 11/1/2016

SDS Number: 000000091604

Version: 1.4

Premium Blue™ EXTREME FULL SYNTHETIC HEAVY DUTY
DIESEL SAE 5W-40 ENGINE OIL
™ Trademark, Valvoline or its subsidiaries, regisred in various
countries
774038

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under recommended storage conditions.
Possibility of hazardous reactions	: Product will not undergo hazardous polymerization.
Conditions to avoid	: excessive heat
Incompatible materials	: Acids Strong oxidizing agents
Hazardous decomposition products	Aldehydes carbon dioxide and carbon monoxide Hydrocarbons hydrogen sulfide Nitrogen oxides (NOx) Sulphur oxides zinc oxide mercaptans

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg


ZINC DIALKYL DITHIOPHOSPHATE:

Acute oral toxicity : LD50 (Rat): > 2,000 - 5,000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: Not classified as acutely toxic by dermal
absorption under GHS.

TETRAPROPENYLPHENOL:

Acute oral toxicity :
Assessment: The component/mixture is classified as acute

		Page: 9
SAFETY DATA SHEET		Revision Date: 10/04/2016
		Print Date: 11/1/2016
		SDS Number: 000000091604
Premium Blue™ EXTREME FULL SYNTHETIC HEAVY DUTY DIESEL SAE 5W-40 ENGINE OIL ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 774038		Version: 1.4

oral toxicity, category 5.

Skin corrosion/irritation

Not classified based on available information.

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Result: Slight, transient irritation

ZINC DIALKYL DITHIOPHOSPHATE:

Result: Irritating to skin.

TETRAPROPENYLPHENOL:

Result: Irritating to skin.

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Result: No eye irritation

ZINC DIALKYL DITHIOPHOSPHATE:

Result: Corrosive

TETRAPROPENYLPHENOL:

Result: Risk of serious damage to eyes.

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

Components:

TETRAPROPENYLPHENOL:

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure


Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

		Page: 10
SAFETY DATA SHEET		Revision Date: 10/04/2016
		Print Date: 11/1/2016
		SDS Number: 000000091604
Premium Blue™ EXTREME FULL SYNTHETIC HEAVY DUTY DIESEL SAE 5W-40 ENGINE OIL ™ Trademark, Valvoline or its subsidiaries, regised in various countries 774038		Version: 1.4

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:
 May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Acute aquatic toxicity Category 3; Harmful to aquatic life.

Chronic aquatic toxicity : Chronic aquatic toxicity Category 3; Harmful to aquatic life with long lasting effects.

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Toxicity to fish : LL50 (Fish): > 100 mg/l

Toxicity to daphnia and other aquatic invertebrates : EL50 (Aquatic invertebrates): > 10,000 mg/l

Toxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l

Toxicity to fish (Chronic toxicity) : NOEC (Fish): 10 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Aquatic invertebrates): 10 mg/l

ZINC DIALKYL DITHIOPHOSPHATE:

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

TETRAPROPENYLPHENOL:

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

Persistence and degradability

Components:

No data available



SAFETY DATA SHEET

Revision Date: 10/04/2016

Print Date: 11/1/2016

SDS Number: 000000091604

Version: 1.4

Premium Blue™ EXTREME FULL SYNTHETIC HEAVY DUTY DIESEL SAE 5W-40 ENGINE OIL
™ Trademark, Valvoline or its subsidiaries, regised in various countries
774038

Bioaccumulative potential

Components:

No data available

Mobility in soil

Components:

No data available

Other adverse effects

No data available

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life with long lasting effects.

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

U.S. DOT - ROAD

Not dangerous goods

CFR_RAIL_C

Not dangerous goods



SAFETY DATA SHEET

Revision Date: 10/04/2016

Print Date: 11/1/2016

SDS Number: 000000091604

Version: 1.4

Premium Blue™ EXTREME FULL SYNTHETIC HEAVY DUTY DIESEL SAE 5W-40 ENGINE OIL
 ™ Trademark, Valvoline or its subsidiaries, regised in various countries
 774038

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TDG_ROAD_C

Not dangerous goods

TDG_RAIL_C

Not dangerous goods

TDG_INWT_C

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX_DG

Not dangerous goods

***ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Marine pollutant	no
------------------	----


Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

**EPCRA - Emergency Planning and Community Right-to-Know Act
 CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
ETHYLENEDIAMINE	107-15-3	5000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

		Page: 13
SAFETY DATA SHEET		Revision Date: 10/04/2016
		Print Date: 11/1/2016
		SDS Number: 000000091604
Premium Blue™ EXTREME FULL SYNTHETIC HEAVY DUTY DIESEL SAE 5W-40 ENGINE OIL ™ Trademark, Valvoline or its subsidiaries, regised in various countries 774038		Version: 1.4

SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
ETHYLENEDIAMINE	107-15-3	5000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 311/312 Hazards : Chronic Health Hazard

SARA 313

Phosphorodithioic acid, 113706-15-3 1.08 %
 mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts

California Prop 65

Proposition 65 warnings are not required for this product based on the results of a risk assessment.

The components of this product are reported in the following inventories:

- DSL : All components of this product are on the Canadian DSL
- AICS : On the inventory, or in compliance with the inventory
- ENCS : Not in compliance with the inventory
- KECI : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- IECSC : Not in compliance with the inventory
- TSCA : On TSCA Inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 10/04/2016

NFPA:	HMIS III:
--------------	------------------

SAFETY DATA SHEET


Revision Date: 10/04/2016

Print Date: 11/1/2016

SDS Number: 000000091604

Version: 1.4

Premium Blue™ EXTREME FULL SYNTHETIC HEAVY DUTY DIESEL SAE 5W-40 ENGINE OIL
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 774038

<p>Flammability</p>  <p>Health</p> <p>Instability</p> <p>Special hazard.</p>	<table border="1"> <tr> <td style="background-color: blue; color: white;">HEALTH</td> <td style="text-align: center;">0*</td> </tr> <tr> <td style="background-color: red; color: white;">FLAMMABILITY</td> <td style="text-align: center;">1</td> </tr> <tr> <td style="background-color: yellow;">PHYSICAL HAZARD</td> <td style="text-align: center;">0</td> </tr> </table> <p>0 = not significant, 1 =Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	0*	FLAMMABILITY	1	PHYSICAL HAZARD	0
HEALTH	0*						
FLAMMABILITY	1						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements

- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H361 Suspected of damaging fertility or the unborn child.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists


BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

	Page: 15
SAFETY DATA SHEET	Revision Date: 10/04/2016
	Print Date: 11/1/2016
	SDS Number: 000000091604
Premium Blue™ EXTREME FULL SYNTHETIC HEAVY DUTY DIESEL SAE 5W-40 ENGINE OIL ™ Trademark, Valvoline or its subsidiaries, regised in various countries 774038	Version: 1.4

H-statement : Hazard Statement
 IATA : International Air Transport Association.
 IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization
 ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
 IMDG : International Maritime Code for Dangerous Goods
 ISO : International Organization for Standardization
 logPow : octanol-water partition coefficient
 LCxx : Lethal Concentration, for xx percent of test population
 LDxx : Lethal Dose, for xx percent of test population.
 ICxx : Inhibitory Concentration for xx of a substance
 Ecxx : Effective Concentration of xx
 N.O.S.: Not Otherwise Specified
 OECD : Organization for Economic Co-operation and Development
 OEL : Occupational Exposure Limit
 P-Statement : Precautionary Statement
 PBT : Persistent , Bioaccumulative and Toxic
 PPE : Personal Protective Equipment
 STEL : Short-term exposure limit
 STOT : Specific Target Organ Toxicity
 TLV : Threshold Limit Value
 TWA : Time-weighted average
 vPvB : Very Persistent and Very Bioaccumulative
 WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act
 DOT : Department of Transportation
 FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act
 HMIRC : Hazardous Materials Information Review Commission
 HMIS : Hazardous Materials Identification System
 NFPA : National Fire Protection Association
 NIOSH : National Institute for Occupational Safety and Health
 OSHA : Occupational Safety and Health Administration
 PMRA : Health Canada Pest Management Regulatory Agency
 RTK : Right to Know
 WHMIS : Workplace Hazardous Materials Information System