

		Page: 1
SAFETY DATA SHEET		Revision Date: 11/16/2015
		Print Date: 12/10/2015
		SDS Number: 000000264395
Valvoline™ SYNTHETIC DOT 3&4 BRAKE FLUID 601458		Version: 1.1

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Valvoline™ SYNTHETIC DOT 3&4
BRAKE FLUID

Recommended use of the chemical and restrictions on use

Details of the supplier of the safety data sheet Niteo Products, LLC P.O. Box 191629 Dallas TX 75219 United States of America	Emergency telephone number CHEMTREC DIRECT 1-800-424-9300 Product Information 1-844-696-4836
--	---

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Serious eye damage : Category 1

Reproductive toxicity : Category 2

GHS Label element

Hazard pictograms :



Signal Word : Danger

Hazard Statements : Causes serious eye damage.
Suspected of damaging fertility or the unborn child.

Precautionary Statements : **Prevention:**
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
IF IN EYES: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.

		Page: 2
SAFETY DATA SHEET		Revision Date: 11/16/2015
		Print Date: 12/10/2015
		SDS Number: 000000264395
Valvoline™ SYNTHETIC DOT 3&4 BRAKE FLUID 601458		Version: 1.1

IF exposed or concerned: Get medical advice/ attention.

Storage:

Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Defatter

Hazardous components

Chemical Name	CAS-No.	Classification	Concentration (%)
Triethylene glycol monomethyl ether, borate	30989-05-0	Not a hazardous substance or mixture.	40.00
TRIETHYLENE GLYCOL MONOBUTYL ETHER	143-22-6	Eye Dam. 1; H318	17.99
POLYOXYETHYLENE MONOBUTYL ETHER	9004-77-7	Eye Dam. 1; H318	13.00
TETRAETHYLENE GLYCOL	112-60-7	Not a hazardous substance or mixture.	10.00
TRIETHYLENE GLYCOL	112-27-6	Not a hazardous substance or mixture.	5.00
PENTAETHYLENE GLYCOL	4792-15-8	Not a hazardous substance or mixture.	5.00
DIISOPROPANOLAMINE	110-97-4	Eye Irrit. 2A; H319	1.50
DIETHYLENE GLYCOL MONOMETHYL ETHER	111-77-3	Repr. 2; H361	0.99

		Page: 3
SAFETY DATA SHEET		Revision Date: 11/16/2015
		Print Date: 12/10/2015
		SDS Number: 000000264395
Valvoline™ SYNTHETIC DOT 3&4 BRAKE FLUID 601458		Version: 1.1

--	--	--	--

SECTION 4. FIRST AID MEASURES

General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	: If breathed in, move person into fresh air. If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	: First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
In case of eye contact	: In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Protect unharmed eye.
If swallowed	: Obtain medical attention. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	: Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea) irritation (nose, throat, airways) Causes serious eye damage. Suspected of damaging fertility or the unborn child.
Notes to physician	:

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray Foam Carbon dioxide (CO2) Dry chemical
------------------------------	--

		Page: 4
SAFETY DATA SHEET		Revision Date: 11/16/2015
		Print Date: 12/10/2015
		SDS Number: 000000264395
Valvoline™ SYNTHETIC DOT 3&4 BRAKE FLUID 601458		Version: 1.1

Unsuitable extinguishing media	: High volume water jet
Specific hazards during firefighting	: If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the point of release. Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: carbon dioxide and carbon monoxide Hydrocarbons Alcohols Aldehydes ethers Nitrogen oxides (NOx)
Specific extinguishing methods	: Product is compatible with standard fire-fighting agents.
Further information	: Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for firefighters	: In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Ensure adequate ventilation. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.
Other information	: Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

SAFETY DATA SHEET

Revision Date: 11/16/2015

Print Date: 12/10/2015

SDS Number: 000000264395

Valvoline™ SYNTHETIC DOT 3&4 BRAKE FLUID

Version: 1.1

601458

Advice on safe handling : Do not breathe vapours/dust.
Do not smoke.
Container hazardous when empty.
Avoid contact with skin and eyes.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Triethylene glycol monomethyl ether, borate	30989-05-0	TWA	2 mg/m3 Inhalable fraction.	ACGIH
		STEL	6 mg/m3 Inhalable fraction.	ACGIH
TETRAETHYLENE GLYCOL	112-60-7	TWA	10 mg/m3 Particulate.	WEEL
				WEEL
TRIETHYLENE GLYCOL	112-27-6	TWA	10 mg/m3 Particulate.	WEEL
				WEEL
PENTAETHYLENE GLYCOL	4792-15-8			WEEL
		TWA	10 mg/m3 Particulate.	WEEL
DIISOPROPANOLAMINE	110-97-4	TWA	10 ppm	SUPLR EXP
		TWA	10 ppm	SUPLR EXP
		TWA	10 ppm	SUPLR EXP
		TWA	10 ppm	SUPLR EXP

Hazardous components without workplace control parameters

Components	CAS-No.
TRIETHYLENE GLYCOL MONOBUTYL ETHER	143-22-6
POLYOXYETHYLENE MONOBUTYL ETHER	9004-77-7

		Page: 6
SAFETY DATA SHEET		Revision Date: 11/16/2015
		Print Date: 12/10/2015
		SDS Number: 000000264395
Valvoline™ SYNTHETIC DOT 3&4 BRAKE FLUID 601458		Version: 1.1

DIETHYLENE GLYCOL MONOMETHYL ETHER	111-77-3
---------------------------------------	----------

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Wear chemical splash goggles and face shield when there is potential for exposure of the eyes or face to liquid, vapor or mist.
Maintain eye wash station in immediate work area.

Skin and body protection

: Wear as appropriate:
Impervious clothing
Safety shoes
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures

: Wash hands before breaks and at the end of workday.
When using do not eat or drink.

		Page: 7
SAFETY DATA SHEET		Revision Date: 11/16/2015
		Print Date: 12/10/2015
		SDS Number: 000000264395
Valvoline™ SYNTHETIC DOT 3&4 BRAKE FLUID 601458		Version: 1.1

When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: liquid
Colour	: yellow
Odour	: ammoniacal
Odour Threshold	: No data available
	No data available
pH	: 7.7
Melting point/freezing point	: < -74 °F / < -59 °C
Boiling point/boiling range	: > 469 °F / > 243 °C
Flash point	: 270 °F / 132 °C Method: Closed Cup
Evaporation rate	: No data available
	No data available
Flammability (solid, gas)	: No data available
	No data available
Upper explosion limit	: No data available
	No data available
Lower explosion limit	: No data available
	No data available
Vapour pressure	: Estimated < 0.01 mmHg
Relative vapour density	: > 10AIR=1
Relative density	: No data available
	No data available
Density	: 1.03 - 1.08 g/cm3
Solubility(ies)	
Water solubility	: soluble

		Page: 8
SAFETY DATA SHEET		Revision Date: 11/16/2015
		Print Date: 12/10/2015
		SDS Number: 000000264395
Valvoline™ SYNTHETIC DOT 3&4 BRAKE FLUID 601458		Version: 1.1

Solubility in other solvents : No data available
No data available

Partition coefficient: n-octanol/water : No data available
No data available

Thermal decomposition : No data available
No data available

Viscosity
Viscosity, dynamic : No data available
No data available

Viscosity, kinematic : 1100 mm²/s (40 °C)

Oxidizing properties : No data available
No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.
No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.
Stable under recommended storage conditions.

Possibility of hazardous reactions : Product will not undergo hazardous polymerization.

Conditions to avoid : excessive heat
Do not allow evaporation to dryness.

Incompatible materials : Acids
Alkaline earth metals
aluminum
Bases
Copper
galvanized metals
halogenated hydrocarbons
nitrites
strong alkalis
Strong oxidizing agents
Zinc

		Page: 9
SAFETY DATA SHEET		Revision Date: 11/16/2015
		Print Date: 12/10/2015
		SDS Number: 000000264395
Valvoline™ SYNTHETIC DOT 3&4 BRAKE FLUID 601458		Version: 1.1

Hazardous decomposition products

acetaldehyde
Alcohols
Aldehydes
carbon dioxide and carbon monoxide
dioxolanes
ethers
ethylene glycol monomethyl ether
formaldehyde-like
Nitrogen oxides (NOx)
Organic acids
ketones

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Components:

Triethylene glycol monomethyl ether, borate:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 401
Assessment: No adverse effect has been observed in acute oral toxicity tests.

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

TRIETHYLENE GLYCOL MONOBUTYL ETHER:

Acute oral toxicity : LD 50 (Rat): 5,300 mg/kg

Acute dermal toxicity : LD 50 (Rabbit): 3,502 mg/kg

POLYOXYETHYLENE MONOBUTYL ETHER:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rabbit): 3,540 mg/kg

TETRAETHYLENE GLYCOL:

Acute oral toxicity : LD 50 (Rat): ca. 30,000 mg/kg

Acute dermal toxicity : LD 50 (Rabbit): 22,460 mg/kg

		Page: 10
SAFETY DATA SHEET		Revision Date: 11/16/2015
		Print Date: 12/10/2015
		SDS Number: 000000264395
Valvoline™ SYNTHETIC DOT 3&4 BRAKE FLUID 601458		Version: 1.1

TRIETHYLENE GLYCOL:

Acute oral toxicity : LD 50 (Rat): 15,000 - 22,000 mg/kg

Acute inhalation toxicity : LC 50 (Rat): > 3.9 mg/l
Exposure time: 4 h
Assessment: Not classified as acutely toxic by inhalation under GHS.

Acute dermal toxicity : LD 50 (Rabbit): > 22.6 g/kg

Acute toxicity (other routes of administration) : LD 50 (Rat): 11,700 mg/kg
Application Route: Intravenous

DIISOPROPANOLAMINE:

Acute oral toxicity : LD 50 (Rat): > 2,000 mg/kg
Assessment: No adverse effect has been observed in acute oral toxicity tests.

Acute dermal toxicity : LD 50 (Rabbit): 8,000 mg/kg

DIETHYLENE GLYCOL MONOMETHYL ETHER:

Acute oral toxicity : LD50 (Mouse): > 5,288 mg/kg
Method: OECD Test Guideline 401
GLP: no

Acute inhalation toxicity : LC0 (Rat): > 1.2 mg/l
Exposure time: 6 h
Test atmosphere: vapour
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): 9,404 mg/kg
Method: OECD Test Guideline 402

Skin corrosion/irritation

Not classified based on available information.

Product:

Result: Repeated exposure may cause skin dryness or cracking.

Components:

Triethylene glycol monomethyl ether, borate:
Result: No skin irritation

TRIETHYLENE GLYCOL MONOBUTYL ETHER:

Result: No skin irritation

POLYOXYETHYLENE MONOBUTYL ETHER:

Result: Slightly irritating to skin

TETRAETHYLENE GLYCOL:

Result: No skin irritation

TRIETHYLENE GLYCOL:

		Page: 11
SAFETY DATA SHEET		Revision Date: 11/16/2015
		Print Date: 12/10/2015
		SDS Number: 000000264395
Valvoline™ SYNTHETIC DOT 3&4 BRAKE FLUID 601458		Version: 1.1

Result: No skin irritation

PENTAETHYLENE GLYCOL:
Result: Slightly irritating to skin

DIISOPROPANOLAMINE:
Result: No skin irritation

DIETHYLENE GLYCOL MONOMETHYL ETHER:
Species: Rabbit
Method: OECD Test Guideline 404
Result: No skin irritation

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Remarks: May cause irreversible eye damage.

Components:

Triethylene glycol monomethyl ether, borate:
Result: Slightly irritating to eyes

TRIETHYLENE GLYCOL MONOBUTYL ETHER:
Result: Corrosive

POLYOXYETHYLENE MONOBUTYL ETHER:
Result: Corrosive

TETRAETHYLENE GLYCOL:
Result: Mildly irritating to eyes

TRIETHYLENE GLYCOL:
Result: Mildly irritating to eyes

PENTAETHYLENE GLYCOL:
Result: Slightly irritating to eyes

DIISOPROPANOLAMINE:
Result: Severely irritating to eyes

DIETHYLENE GLYCOL MONOMETHYL ETHER:
Species: Rabbit
Result: Slightly irritating to eyes
Method: OECD Test Guideline 405

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Components:

POLYOXYETHYLENE MONOBUTYL ETHER:
Test Type: Maximisation Test (GPMT)
Species: Guinea pig
Method: OECD Test Guideline 406

		Page: 12
SAFETY DATA SHEET		Revision Date: 11/16/2015
		Print Date: 12/10/2015
		SDS Number: 000000264395
Valvoline™ SYNTHETIC DOT 3&4 BRAKE FLUID 601458		Version: 1.1

Result: Did not cause sensitisation on laboratory animals.

DIETHYLENE GLYCOL MONOMETHYL ETHER:

Test Type: Maximisation Test (GPMT)

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Method: OECD Test Guideline 406

Germ cell mutagenicity

Not classified based on available information.

Components:

PENTAETHYLENE GLYCOL:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Test species: Mouse
Cell type: Bone marrow
Result: negative

DIETHYLENE GLYCOL MONOMETHYL ETHER:

Genotoxicity in vitro : Test Type: Ames test
Test species: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

Components:

DIETHYLENE GLYCOL MONOMETHYL ETHER:

Reproductive toxicity - : Some evidence of adverse effects on development, based on
Assessment animal experiments.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks: No data available

Carcinogenicity:

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential

		Page: 13
SAFETY DATA SHEET		Revision Date: 11/16/2015
		Print Date: 12/10/2015
		SDS Number: 000000264395
Valvoline™ SYNTHETIC DOT 3&4 BRAKE FLUID 601458		Version: 1.1

carcinogen by OSHA.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Acute aquatic toxicity Category 3; Harmful to aquatic life.

Chronic aquatic toxicity : Chronic aquatic toxicity Category 3; Harmful to aquatic life with long lasting effects.

Components:

Triethylene glycol monomethyl ether, borate:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Test Type: semi-static test
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Water flea (Daphnia magna)): >= 500 mg/l
Exposure time: 48 h

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

POLYOXYETHYLENE MONOBUTYL ETHER:

Toxicity to fish : LC50 (Flatfish, flounder (Scophthalmus maximus)): > 1,800 mg/l
Exposure time: 96 h
Test Type: semi-static test
Method: OECD Test Guideline 203

Toxicity to algae : ErC50 (Skeletonema costatum (marine diatom)): 391 mg/l
Exposure time: 72 h

TETRAETHYLENE GLYCOL:

Toxicity to fish : LC 50 (Pimephales promelas (fathead minnow)): > 1,000 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : LC 50 (Water flea (Daphnia magna)): 7,746 mg/l
Exposure time: 48 h

		Page: 14
SAFETY DATA SHEET		Revision Date: 11/16/2015
		Print Date: 12/10/2015
		SDS Number: 000000264395
Valvoline™ SYNTHETIC DOT 3&4 BRAKE FLUID 601458		Version: 1.1

Toxicity to algae : IC50 (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l

TRIETHYLENE GLYCOL:

Toxicity to fish : LC 50 (Bluegill (Lepomis macrochirus)): > 10,000 mg/l
Exposure time: 96 h
Method: Static
Remarks: Mortality

Toxicity to daphnia and other aquatic invertebrates : EC 50 (Water flea (Daphnia magna)): 46,500 mg/l
Exposure time: 48 h
Method: Static
Remarks: Intoxication

DIISOPROPANOLAMINE:

Toxicity to fish : LC 50 (Carassius auratus (goldfish)): 1,100 mg/l
Exposure time: 24 h
Test Type: static test

DIETHYLENE GLYCOL MONOMETHYL ETHER:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 5,741 mg/l
Exposure time: 96 h
Test Type: static test

LC 50 (Bluegill (Lepomis macrochirus)): 7,500 mg/l
Exposure time: 96 h
Method: Static
Remarks: Mortality

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1,192 mg/l
Exposure time: 48 h
Test Type: static test

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l
End point: Biomass
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 201

Persistence and degradability

Components:

Triethylene glycol monomethyl ether, borate:

Biodegradability : Biodegradation: > 70 %
Exposure time: 28 d
Method: OECD Test Guideline 301A

TETRAETHYLENE GLYCOL:

Biodegradability : Biodegradation: 40 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

		Page: 15
SAFETY DATA SHEET		Revision Date: 11/16/2015
		Print Date: 12/10/2015
		SDS Number: 000000264395
Valvoline™ SYNTHETIC DOT 3&4 BRAKE FLUID 601458		Version: 1.1

TRIETHYLENE GLYCOL:

Biodegradability : Result: Readily biodegradable

DIETHYLENE GLYCOL MONOMETHYL ETHER:

Biodegradability : aerobic
Inoculum: activated sludge
Result: Readily biodegradable
Biodegradation: 100 %
Exposure time: 28 d

Bioaccumulative potential

Components:

TETRAETHYLENE GLYCOL:

Partition coefficient: n-octanol/water : log Pow: Estimated -2.30

TRIETHYLENE GLYCOL:

Bioaccumulation : Species: Sheepshead minnow (*Cyprinodon variegatus*)
Bioconcentration factor (BCF): 1,700
Exposure time: 28 d
Concentration: 7.8 mg/l
Method: Flow through

PENTAETHYLENE GLYCOL:

Partition coefficient: n-octanol/water : log Pow: -2.3

DIISOPROPANOLAMINE:

Partition coefficient: n-octanol/water : log Pow: -0.82

Mobility in soil

Components:

No data available

Other adverse effects

No data available

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life with long lasting effects.

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Dispose of in accordance with all applicable local, state and

		Page: 16
SAFETY DATA SHEET		Revision Date: 11/16/2015
		Print Date: 12/10/2015
		SDS Number: 000000264395
Valvoline™ SYNTHETIC DOT 3&4 BRAKE FLUID 601458		Version: 1.1

federal regulations.

The product should not be allowed to enter drains, water courses or the soil.

Do not contaminate ponds, waterways or ditches with chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

TRANSPORT CANADA - INLAND WATERWAYS

Not dangerous goods

TRANSPORT CANADA - RAIL

Not dangerous goods

TRANSPORT CANADA - ROAD

Not dangerous goods

		Page: 17
SAFETY DATA SHEET		Revision Date: 11/16/2015
		Print Date: 12/10/2015
		SDS Number: 000000264395
Valvoline™ SYNTHETIC DOT 3&4 BRAKE FLUID 601458		Version: 1.1

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

U.S. DOT - RAIL

Not dangerous goods

U.S. DOT - ROAD

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
SODIUM HYDROXIDE	1310-73-2	1000	100010.001

SARA 311/312 Hazards : Acute Health Hazard
Chronic Health Hazard

SARA 313 Component(s)

TRIETHYLENE GLYCOL MONOMETHYL ETHER	112-35-6	30.00 %
TRIETHYLENE GLYCOL MONOBUTYL ETHER	143-22-6	17.99 %
DIETHYLENE GLYCOL MONOMETHYL ETHER	111-77-3	0.99 %

California Prop 65 This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

TSCA : On the inventory, or in compliance with the inventory

NiTEO PRODUCTS		Page: 18
SAFETY DATA SHEET		Revision Date: 11/16/2015
		Print Date: 12/10/2015
		SDS Number: 000000264395
Valvoline™ SYNTHETIC DOT 3&4 BRAKE FLUID		Version: 1.1
601458		

DSL : All components of this product are on the Canadian DSL

AICS : Not in compliance with the inventory

ENCS : Not in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 11/16/2015

NFPA:	HMIS III:						
Flammability Health Instability Special hazard. 	<table border="1"> <tr> <td>HEALTH</td><td>3*</td></tr> <tr> <td>FLAMMABILITY</td><td>1</td></tr> <tr> <td>PHYSICAL HAZARD</td><td>0</td></tr> </table> 0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic	HEALTH	3*	FLAMMABILITY	1	PHYSICAL HAZARD	0
HEALTH	3*						
FLAMMABILITY	1						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child.

		Page: 19
SAFETY DATA SHEET		Revision Date: 11/16/2015
		Print Date: 12/10/2015
		SDS Number: 000000264395
Valvoline™ SYNTHETIC DOT 3&4 BRAKE FLUID 601458		Version: 1.1

Sources of key data used to compile the Safety Data Sheet

Internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

Cefic, the European Chemical Industry Council.

ESIS European Chemical Substances Information System

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Niteo's Environmental Health and Safety Department (1-844-696-4836).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act

DOT : Department of Transportation

FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act

HMIRC : Hazardous Materials Information Review Commission

HMIS : Hazardous Materials Identification System

NFPA : National Fire Protection Association

		Page: 20
SAFETY DATA SHEET		Revision Date: 11/16/2015
		Print Date: 12/10/2015
		SDS Number: 000000264395
Valvoline™ SYNTHETIC DOT 3&4 BRAKE FLUID 601458		Version: 1.1

NIOSH : National Institute for Occupational Safety and Health
 OSHA : Occupational Safety and Health Administration
 PMRA : Health Canada Pest Management Regulatory Agency
 RTK : Right to Know
 WHMIS : Workplace Hazardous Materials Information System