		Page: 1
<b>SAFETY DATA SHEET</b>		Revision Date: 11/25/2015
		Print Date: 12/11/2015
		SDS Number: 000000264893
COMPLETE FUEL SYSTEM CLEANER 601456		Version: 1.0

29 CFR 1910.1200 (OSHA HazCom 2012)

## SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

### Product identifier

Trade name : COMPLETE  
FUEL SYSTEM CLEANER

### Relevant identified uses of the substance or mixture and uses advised against

<b>Details of the supplier of the safety data sheet</b> Niteo Products, LLC P.O. Box 191629 Dallas TX 75219 United States of America	<b>Emergency telephone number</b> CHEMTREC DIRECT 1-800-424-9300  <b>Product Information</b> 1-844-696-4836
--	---

## SECTION 2. HAZARDS IDENTIFICATION

### GHS Classification

Flammable liquids : Category 3

Skin irritation : Category 2

Serious eye damage : Category 1

Carcinogenicity : Category 2

Specific target organ systemic toxicity - single exposure : Category 3 (Central nervous system)

Aspiration hazard : Category 1

### GHS Label element


Hazard pictograms :






Signal Word : Danger

Hazard Statements : Flammable liquid and vapor.  
May be fatal if swallowed and enters airways.  
Causes skin irritation.  
Causes serious eye damage.

		Page: 2
<b>SAFETY DATA SHEET</b>		Revision Date: 11/25/2015
		Print Date: 12/11/2015
		SDS Number: 000000264893
COMPLETE FUEL SYSTEM CLEANER		Version: 1.0
601456		

May cause drowsiness or dizziness.  
Suspected of causing cancer.

**Precautionary Statements**

**: Prevention:**

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
Keep container tightly closed.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ ventilating/ lighting/ equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.  
Wash skin thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**

IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.  
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.  
IF exposed or concerned: Get medical advice/ attention. Do NOT induce vomiting.  
If skin irritation occurs: Get medical advice/ attention.  
Take off contaminated clothing and wash before reuse.  
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:**

Store in a well-ventilated place. Keep container tightly closed.  
Store in a well-ventilated place. Keep cool.  
Store locked up.

**Disposal:**

Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

Static Accumulating liquid

---

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture

: Mixture

**SAFETY DATA SHEET**

Revision Date: 11/25/2015

Print Date: 12/11/2015

SDS Number: 000000264893

COMPLETE FUEL SYSTEM CLEANER


Version: 1.0

601456

Chemical nature : Defatter

**Hazardous components**


Chemical Name	CAS-No.	Classification	Concentration (%)
DISTILLATES, SWEETENED MIDDLE	64741-86-2	Flam. Liq. 3; H226 Eye Irrit. 2A; H319 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	35.25
KEROSENE	8008-20-6	Flam. Liq. 3; H226 Skin Irrit. 2; H315 STOT SE 3; H336 Asp. Tox. 1; H304	29.32
POLYETHER AMINE		Skin Irrit. 2; H315 Eye Dam. 1; H318 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	28.18
POLYETHER AMINE POLYMER		Skin Irrit. 2; H315 Eye Dam. 1; H318	3.46
HYDROCARBONS, C10, AROMATICS, >1% NAPHTHALENE		Flam. Liq. 4; H227 Carc. 2; H351 STOT SE 3; H335, H336 Asp. Tox. 1; H304	3.46

		Page: 4
<b>SAFETY DATA SHEET</b>		Revision Date: 11/25/2015
		Print Date: 12/11/2015
		SDS Number: 000000264893
COMPLETE FUEL SYSTEM CLEANER 601456		Version: 1.0

		Aquatic Acute 2; H401  Aquatic Chronic 2; H411	
NAPHTHALENE	91-20-3	Acute Tox. 4; H302  Carc. 2; H351	0.14

#### SECTION 4. FIRST AID MEASURES

General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later. Do not leave the victim unattended.
If inhaled	: Move to fresh air. If unconscious place in recovery position and seek medical advice. Consult a physician after significant exposure.
In case of skin contact	: Remove contaminated clothing. If irritation develops, get medical attention. If on skin, rinse well with water. Wash contaminated clothing before re-use. If on clothes, remove clothes.
In case of eye contact	: In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Protect unharmed eye.
If swallowed	: Obtain medical attention. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	: Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material.


		Page: 5
<b>SAFETY DATA SHEET</b>		Revision Date: 11/25/2015
		Print Date: 12/11/2015
		SDS Number: 000000264893
COMPLETE FUEL SYSTEM CLEANER  601456		Version: 1.0

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:  
 stomach or intestinal upset (nausea, vomiting, diarrhea)  
 irritation (nose, throat, airways)  
 Lung irritation  
 confusion  
 irregular heartbeat  
 Convulsions  
 May be fatal if swallowed and enters airways.  
 Causes skin irritation.  
 Causes serious eye damage.  
 May cause drowsiness or dizziness.  
 Suspected of causing cancer.

Notes to physician : No hazards which require special first aid measures.

## SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
 Water spray  
 Foam  
 Alcohol-resistant foam  
 Carbon dioxide (CO<sub>2</sub>)  
 Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.  
 Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.  
 Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Aldehydes  
 carbon dioxide and carbon monoxide  
 Hydrocarbons  
 Nitrogen oxides (NO<sub>x</sub>)  
 sulfur oxides
- Specific extinguishing methods :  
  
 Product is compatible with standard fire-fighting agents.
- Further information : Fire residues and contaminated fire extinguishing water must

		Page: 6
<b>SAFETY DATA SHEET</b>		Revision Date: 11/25/2015
		Print Date: 12/11/2015
		SDS Number: 000000264893
COMPLETE FUEL SYSTEM CLEANER		Version: 1.0
601456		

be disposed of in accordance with local regulations.  
Use a water spray to cool fully closed containers.


Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.  
Remove all sources of ignition.  
Use personal protective equipment.  
Ensure adequate ventilation.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.  
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
- Other information : Comply with all applicable federal, state, and local regulations.  
Suppress (knock down) gases/vapours/mists with a water spray jet.

## SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Open drum carefully as content may be under pressure.  
Avoid formation of aerosol.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Do not breathe vapours/dust.  
Do not smoke.  
Container hazardous when empty.  
Take precautionary measures against static discharges.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
Smoking, eating and drinking should be prohibited in the application area.  
For personal protection see section 8.  
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

		Page: 7
<b>SAFETY DATA SHEET</b>		Revision Date: 11/25/2015
		Print Date: 12/11/2015
		SDS Number: 000000264893
COMPLETE FUEL SYSTEM CLEANER		Version: 1.0
601456		

place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
No smoking.


## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
KEROSENE	8008-20-6	TWA	200 mg/m3 Non-aerosol (as total hydrocarbon vapor)	ACGIH
		SKIN_DES		ACGIH
				ACGIH
		REL	100 mg/m3	NIOSH/GUID E
NAPHTHALENE	91-20-3	TWA	10 ppm	ACGIH
		REL	10 ppm 50 mg/m3	NIOSH/GUID E
		STEL	15 ppm 75 mg/m3	NIOSH/GUID E
		PEL	10 ppm 50 mg/m3	OSHA_TRAN S
		TWA	10 ppm 50 mg/m3	TN OEL
		STEL	15 ppm 75 mg/m3	TN OEL

### Hazardous components without workplace control parameters

Components	CAS-No.
DISTILLATES, SWEETENED MIDDLE	64741-86-2
POLYETHER AMINE	
POLYETHER AMINE POLYMER	
HYDROCARBONS, C10, AROMATICS, >1% NAPHTHALENE	

		Page: 8
<b>SAFETY DATA SHEET</b>		Revision Date: 11/25/2015
		Print Date: 12/11/2015
		SDS Number: 000000264893
COMPLETE FUEL SYSTEM CLEANER 601456		Version: 1.0

#### Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
------------	---------	--------------------	---------------------	---------------	---------------------------	-------

**Engineering measures** : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

#### Personal protective equipment

**Respiratory protection** : In the case of vapour formation use a respirator with an approved filter.

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

**Hand protection**  
**Remarks** : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

**Eye protection** : Wear chemical splash goggles and face shield when there is potential for exposure of the eyes or face to liquid, vapor or mist.  
Maintain eye wash station in immediate work area.


**Skin and body protection** : Wear as appropriate:  
Impervious clothing  
Safety shoes  
Flame-resistant clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.  
Discard gloves that show tears, pinholes, or signs of wear.  
Wear resistant gloves (consult your safety equipment supplier).

**Hygiene measures** : Wash hands before breaks and at the end of workday.  
When using do not eat or drink.  
When using do not smoke.


## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

**Physical state** : liquid



		Page: 9
<b>SAFETY DATA SHEET</b>		Revision Date: 11/25/2015
		Print Date: 12/11/2015
		SDS Number: 000000264893
COMPLETE FUEL SYSTEM CLEANER 601456		Version: 1.0

Odour	:	No data available
Odour Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Boiling point/boiling range	:	680 °F / 360 °C Calculated Phase Transition Liquid/Gas
Flash point	:	120.00 °F / 48.89 °C Calculated Flash Point
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Flammability (liquids)	:	Static Accumulating liquid
Flammability (liquids)	:	
Upper explosion limit	:	No data available
Lower explosion limit	:	No data available
Vapour pressure	:	10 hPa (37.8 °C) Calculated Vapor Pressure
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	No data available
Solubility(ies)	:	
Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Thermal decomposition	:	No data available
Viscosity	:	
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	No data available
Oxidizing properties	:	No data available

		Page: 10
<b>SAFETY DATA SHEET</b>		Revision Date: 11/25/2015
		Print Date: 12/11/2015
		SDS Number: 000000264893
COMPLETE FUEL SYSTEM CLEANER 601456		Version: 1.0

## SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under recommended storage conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air.
Conditions to avoid	: excessive heat Heat, flames and sparks.
Incompatible materials	: Strong acids Strong oxidizing agents
Hazardous decomposition products	Aldehydes carbon dioxide and carbon monoxide Hydrocarbons Nitrogen oxides (NO <sub>x</sub> ) Sulphur oxides

## SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure	: Inhalation Skin contact Eye Contact Ingestion
--	--

### Acute toxicity

Not classified based on available information.

### Components:

DISTILLATES, SWEETENED MIDDLE:


Acute oral toxicity : LD 50 (Rat): > 5,000 mg/kg

### KEROSENE:

Acute oral toxicity : LD 50 (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 420

Acute inhalation toxicity : LC 50 (Rat): > 5.28 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403  
Assessment: Not classified as acutely toxic by inhalation under GHS.

Acute dermal toxicity : LD 50 (Rabbit): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: Not classified as acutely toxic by dermal

		Page: 11
<b>SAFETY DATA SHEET</b>		Revision Date: 11/25/2015
		Print Date: 12/11/2015
		SDS Number: 000000264893
COMPLETE FUEL SYSTEM CLEANER		Version: 1.0
601456		

absorption under GHS.

**NAPHTHALENE:**

Acute oral toxicity : LD50 (Mouse, male): 533 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 0.4 mg/l  
Exposure time: 4 h  
Assessment: Not classified as acutely toxic by inhalation under GHS.

Acute dermal toxicity : LD50 (Rabbit): > 2.0 g/kg

LD50 (Rat, male and female): > 2,500 mg/kg  
Assessment: Not classified as acutely toxic by dermal absorption under GHS.

**Skin corrosion/irritation**

Causes skin irritation.

**Product:**

Result: Repeated exposure may cause skin dryness or cracking.

Remarks: May cause skin irritation and/or dermatitis.

**Components:**

DISTILLATES, SWEETENED MIDDLE:

Result: Slightly irritating to skin

KEROSENE:

Result: Irritating to skin.

POLYETHER AMINE:

Result: Irritating to skin.

POLYETHER AMINE POLYMER:

Result: Irritating to skin.

HYDROCARBONS, C10, AROMATICS, >1% NAPHTHALENE:

Result: Possibly irritating to skin

NAPHTHALENE:

Result: Slightly irritating to skin

**Serious eye damage/eye irritation**

Causes serious eye damage.


**Product:**

Remarks: May cause irreversible eye damage.

**Components:**

DISTILLATES, SWEETENED MIDDLE:

Result: Irritating to eyes.

		Page: 12
<b>SAFETY DATA SHEET</b>		Revision Date: 11/25/2015
		Print Date: 12/11/2015
		SDS Number: 000000264893
COMPLETE FUEL SYSTEM CLEANER		Version: 1.0
601456		

**KEROSENE:**

Result: Slightly irritating to eyes

**POLYETHER AMINE:**

Result: Risk of serious damage to eyes.

**POLYETHER AMINE POLYMER:**

Result: Risk of serious damage to eyes.

**HYDROCARBONS, C10, AROMATICS, >1% NAPHTHALENE:**

Result: Possibly irritating to eyes

**NAPHTHALENE:**

Result: Slightly irritating to eyes

**Respiratory or skin sensitisation**

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Suspected of causing cancer.

**Components:**

**HYDROCARBONS, C10, AROMATICS, >1% NAPHTHALENE:**

Carcinogenicity - : Limited evidence of carcinogenicity in animal studies  
Assessment

**NAPHTHALENE:**

Carcinogenicity - : Limited evidence of carcinogenicity in inhalation studies with  
Assessment animals.

**Reproductive toxicity**

Not classified based on available information.

**STOT - single exposure**

May cause drowsiness or dizziness.

**Components:**

**KEROSENE:**

Assessment: May cause drowsiness or dizziness.

**HYDROCARBONS, C10, AROMATICS, >1% NAPHTHALENE:**

Assessment: May cause respiratory irritation., May cause drowsiness or dizziness.

**STOT - repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

May be fatal if swallowed and enters airways.


**Components:**

**DISTILLATES, SWEETENED MIDDLE:**

May be fatal if swallowed and enters airways.

**KEROSENE:**

May be fatal if swallowed and enters airways.

		Page: 13
<b>SAFETY DATA SHEET</b>		Revision Date: 11/25/2015
		Print Date: 12/11/2015
		SDS Number: 000000264893
COMPLETE FUEL SYSTEM CLEANER  601456		Version: 1.0

HYDROCARBONS, C10, AROMATICS, >1% NAPHTHALENE:

May be fatal if swallowed and enters airways.

#### Further information

##### Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

##### Components:

KEROSENE:

Remarks: Skin

Remarks: Central nervous system

NAPHTHALENE:

Remarks: Blood

##### Carcinogenicity:

**IARC**

Group 2B: Possibly carcinogenic to humans

NAPHTHALENE

91-20-3

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**NTP**

Reasonably anticipated to be a human carcinogen

NAPHTHALENE

91-20-3

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Acute aquatic toxicity Category 1; Very toxic to aquatic life.

Chronic aquatic toxicity : Chronic aquatic toxicity Category 1; Very toxic to aquatic life with long lasting effects.

#### Components:


DISTILLATES, SWEETENED MIDDLE:

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

KEROSENE:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 2 - 5 mg/l

		Page: 14
<b>SAFETY DATA SHEET</b>		Revision Date: 11/25/2015
		Print Date: 12/11/2015
		SDS Number: 000000264893
COMPLETE FUEL SYSTEM CLEANER  601456		Version: 1.0

Exposure time: 96 h  
 Test Type: semi-static test  
 Test substance: WAF  
 Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Water flea (*Daphnia magna*)): 1.4 mg/l  
 Exposure time: 48 h  
 Test Type: static test  
 Test substance: WAF  
 Method: OECD Test Guideline 202

Toxicity to algae : EL50 (*Pseudokirchneriella subcapitata* (green algae)): 1 - 3 mg/l  
 Exposure time: 72 h  
 Test Type: static test  
 Test substance: WAF  
 Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : (Water flea (*Daphnia magna*)): 0.89 mg/l  
 Exposure time: 21 d  
 End point: Reproduction Test  
 Test Type: semi-static test  
 Test substance: WAF  
 Method: OECD Test Guideline 211

POLYETHER AMINE:  
 Ecotoxicology Assessment  
 Acute aquatic toxicity

: Very toxic to aquatic life.


Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

HYDROCARBONS, C10, AROMATICS, >1% NAPHTHALENE:

Toxicity to fish : LL50 (*Oncorhynchus mykiss* (rainbow trout)): 2 - 5 mg/l  
 Exposure time: 96 h  
 Test Type: semi-static test  
 Test substance: WAF  
 Method: OECD Test Guideline 203  
 Remarks: Information given is based on data obtained from similar substances.

Toxicity to daphnia and other aquatic invertebrates : EL50 (Water flea (*Daphnia magna*)): 10 mg/l  
 Exposure time: 48 h  
 Test Type: static test  
 Test substance: WAF  
 Method: OECD Test Guideline 202  
 Remarks: Information given is based on data obtained from similar substances.

Toxicity to algae : EL50 (*Pseudokirchneriella subcapitata* (green algae)): > 1 - 3 mg/l  
 End point: Growth inhibition  
 Exposure time: 72 h  
 Test Type: static test

		Page: 15
<b>SAFETY DATA SHEET</b>		Revision Date: 11/25/2015
		Print Date: 12/11/2015
		SDS Number: 000000264893
COMPLETE FUEL SYSTEM CLEANER  601456		Version: 1.0

Test substance: WAF  
Method: OECD Test Guideline 201  
Remarks: Information given is based on data obtained from similar substances.

#### Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

#### NAPHTHALENE:

Toxicity to fish : LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss)): 0.91 - 2.82 mg/l  
Exposure time: 96 h  
Test Type: static test

Toxicity to daphnia and other aquatic invertebrates : EC 50 (Water flea (Daphnia magna)): 1.09 - 3.4 mg/l  
Exposure time: 48 h  
Test Type: static test

#### Persistence and degradability

##### Components:

##### KEROSENE:

Biodegradability : Biodegradation: 58.6 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

##### HYDROCARBONS, C10, AROMATICS, >1% NAPHTHALENE:

Biodegradability : Result: Inherently biodegradable

##### NAPHTHALENE:

Biodegradability : Result: Not readily biodegradable.

#### Bioaccumulative potential

##### Components:

##### NAPHTHALENE:

Partition coefficient: n-octanol/water : log Pow: 3.30

#### Mobility in soil

##### Components:


No data available

#### Other adverse effects

No data available

##### Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Very toxic to aquatic life

		Page: 16
<b>SAFETY DATA SHEET</b>		Revision Date: 11/25/2015
		Print Date: 12/11/2015
		SDS Number: 000000264893
COMPLETE FUEL SYSTEM CLEANER		Version: 1.0
601456		

with long lasting effects.

**Components:**

**SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods**

General advice : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

**SECTION 14. TRANSPORT INFORMATION**

**International transport regulations**

**REGULATION**

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

**MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES**

UN	1993	Not dangerous goods	3
----	------	---------------------	---

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER**

UN	1993	Not dangerous goods	3
----	------	---------------------	---

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO**


UN	1993	Not dangerous goods	3
----	------	---------------------	---

**INTERNATIONAL MARITIME DANGEROUS GOODS**

UN	1993	Not dangerous goods	3
----	------	---------------------	---

**TRANSPORT CANADA - INLAND WATERWAYS**



	Page: 17
<b>SAFETY DATA SHEET</b>	Revision Date: 11/25/2015
	Print Date: 12/11/2015
	SDS Number: 000000264893
COMPLETE FUEL SYSTEM CLEANER 601456	Version: 1.0

Not dangerous goods

#### TRANSPORT CANADA - RAIL

Not dangerous goods

#### TRANSPORT CANADA - ROAD

FLAMMABLE LIQUID, N.O.S.	III	MARINE POLLUTANT:( DISTILLATES, SWEETENED MIDDLE)LIMIT ED QUANTITY

#### U.S. DOT - INLAND WATERWAYS

Flammable liquid, n.o.s.	III

#### U.S. DOT - RAIL

Flammable liquid, n.o.s.	III

#### U.S. DOT - ROAD

LIQUIDO INFLAMABLE, N.E.P.	III

**\*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Marine pollutant	yes
------------------	-----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.


### SECTION 15. REGULATORY INFORMATION

#### EPCRA - Emergency Planning and Community Right-to-Know Act

##### CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
NAPHTHALENE	91-20-3	100	70771.408351

**SARA 311/312 Hazards** : Fire Hazard  
Acute Health Hazard  
Chronic Health Hazard

	Page: 18
<b>SAFETY DATA SHEET</b>	Revision Date: 11/25/2015
	Print Date: 12/11/2015
	SDS Number: 000000264893
COMPLETE FUEL SYSTEM CLEANER 601456	Version: 1.0

#### SARA 313 Component(s)

NAPHTHALENE 91-20-3 0.14 %

#### California Prop 65

Proposition 65 warnings are not required for this product based on the results of a risk assessment.

#### The components of this product are reported in the following inventories:

TSCA	: On TSCA Inventory
DSL	: All components of this product are on the Canadian DSL
AICS	: On the inventory, or in compliance with the inventory
ENCS	: Not in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory


#### Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

## SECTION 16. OTHER INFORMATION


#### Further information

Revision Date: 11/25/2015

NFPA:	HMIS III:						
<p>Flammability</p>  <p>Health</p> <p>Instability</p> <p>Special hazard.</p>	<table border="1"> <tr> <td><b>HEALTH</b></td><td><b>3*</b></td></tr> <tr> <td><b>FLAMMABILITY</b></td><td><b>2</b></td></tr> <tr> <td><b>PHYSICAL HAZARD</b></td><td><b>0</b></td></tr> </table> <p>0 = not significant, 1 =Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	<b>HEALTH</b>	<b>3*</b>	<b>FLAMMABILITY</b>	<b>2</b>	<b>PHYSICAL HAZARD</b>	<b>0</b>
<b>HEALTH</b>	<b>3*</b>						
<b>FLAMMABILITY</b>	<b>2</b>						
<b>PHYSICAL HAZARD</b>	<b>0</b>						

#### NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class II

		Page: 19
<b>SAFETY DATA SHEET</b>		Revision Date: 11/25/2015
		Print Date: 12/11/2015
		SDS Number: 000000264893
COMPLETE FUEL SYSTEM CLEANER		Version: 1.0
601456		

#### Full text of H-Statements

H226	Flammable liquid and vapor.
H227	Combustible liquid.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H401	Toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

#### Sources of key data used to compile the Safety Data Sheet

Internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

Cefic, the European Chemical Industry Council.

ESIS European Chemical Substances Information System

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Niteo's Environmental Health and Safety Department (1-844-696-4836).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization


logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

		Page: 20
<b>SAFETY DATA SHEET</b>		Revision Date: 11/25/2015
		Print Date: 12/11/2015
		SDS Number: 000000264893
COMPLETE FUEL SYSTEM CLEANER		Version: 1.0
601456		

N.O.S.: Not Otherwise Specified  
 OECD : Organization for Economic Co-operation and Development  
 OEL : Occupational Exposure Limit  
 P-Statement : Precautionary Statement  
 PBT : Persistent , Bioaccumulative and Toxic  
 PPE : Personal Protective Equipment  
 STEL : Short-term exposure limit  
 STOT : Specific Target Organ Toxicity  
 TLV : Threshold Limit Value  
 TWA : Time-weighted average  
 vPvB : Very Persistent and Very Bioaccumulative  
 WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act  
 DOT : Department of Transportation  
 FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act  
 HMIRC : Hazardous Materials Information Review Commission  
 HMIS : Hazardous Materials Identification System  
 NFPA : National Fire Protection Association  
 NIOSH : National Institute for Occupational Safety and Health  
 OSHA : Occupational Safety and Health Administration  
 PMRA : Health Canada Pest Management Regulatory Agency  
 RTK : Right to Know  
 WHMIS : Workplace Hazardous Materials Information System