

Revision Date 24-Feb-2020

Product identifier

SAFETY DATA SHEET

Version 2

1. IDENTIFICATION

Product Name 84145 BLACK PLASTIC WELDER (ACTIVATOR) Other means of identification Product Code R478-ACT-BL2 Recommended use of the chemical and restrictions on use **Recommended Use** Activator Uses advised against No information available Details of the supplier of the safety data sheet **Manufacturer Address** May Also Be Distributed by: **ITW Permatex** ITW Permatex Canada 6875 Parkland Blvd. 101-2360 Bristol Circle Solon, Ohio 44139 USA Oakville, ON Canada L6H 6M5 Telephone: 1-87-Permatex Telephone: (800) 924-6994 (866) 732-9502 24-hour emergency phone number Chem-Tel: 800-255-3924 International Emergency: 00+1+ 813-248-0585 Contract Number: MIS0003453

E-mail address: mail@permatex.com

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Carcinogenicity	Category 2
Specific target organ toxicity (single exposure)	Category 3

Label elements

Emergency Overview





Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Wash face, hands and any exposed skin thoroughly after handling Avoid breathing dust/fume/gas/mist/vapors/spray Contaminated work clothing should not be allowed out of the workplace Use only outdoors or in a well-ventilated area Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention Specific treatment (see .? on this label)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention IF ON SKIN: Wash with plenty of soap and water Take off contaminated clothing and wash before reuse If skin irritation or rash occurs: Get medical advice/attention IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Precautionary Statements - Storage

Store locked up Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC) Not applicable

Other Information

Harmful to aquatic life with long lasting effects. Harmful to aquatic life.

Unknown acute toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
METHYL METHACRYLATE	80-62-6	60 - 100
CARBON BLACK	1333-86-4	0.1 - 1

4. FIRST AID MEASURES

Description of first aid measures

General advice	Call 911 or emergency medical service. Remove and isolate contaminated clothing and shoes.	
Eye contact	In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.	
Skin contact	Wash skin with soap and water.	
Inhalation	Move victim to fresh air. If breathing is irregular or stopped, administer artificial respiration. Administer oxygen if breathing is difficult.	
Ingestion	IF SWALLOWED:. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician.	
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.	
Most important symptoms and effects, both acute and delayed		
Symptoms	See section 2 for more information.	
Indication of any immediate medical attention and special treatment needed		
Note to physicians	Keep victim warm and quiet.	

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Dry chemical, CO2, water spray or regular foam, Water spray, fog or regular foam, Use water spray or fog; do not use straight streams

Unsuitable extinguishing media

CAUTION: All these products have a very low flash point. Use of water spray when fighting fire may be inefficient

Specific hazards arising from the chemical

Vapors may travel to source of ignition and flash back. Vapors may form explosive mixtures with air. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Those substances designated with a "P" may polymerize explosively when heated or involved in a fire. Runoff to sewer may create fire or explosion hazard. Substance may be transported hot.

Explosion data

Sensitivity to Mechanical Impact	None.
Sensitivity to Static Discharge	None.

Protective equipment and precautions for firefighters

Move containers from fire area if you can do it without risk.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

 Personal precautions
 ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Stop leak if you can do it without risk.

 Other Information
 Water spray may reduce vapor; but may not prevent ignition in closed spaces.

Environmental precautions

Environmental precautions	Prevent entry into waterways, sewers, basements or confined areas.	
Methods and material for containm	ent and cleaning up	
Methods for containment	A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.	
Methods for cleaning up	Use clean non-sparking tools to collect absorbed material. Dike far ahead of liquid spill for later disposal.	
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.	
7. HANDLING AND STORAGE		
Precautions for safe handling		
Advice on safe handling	Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.	
Conditions for safe storage, including any incompatibilities		
Storage Conditions	Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).	
Incompatible materials	Strong oxidizing agents, Reducing agents	

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
METHYL METHACRYLATE	STEL: 100 ppm	TWA: 100 ppm	IDLH: 1000 ppm
80-62-6	TWA: 50 ppm	TWA: 410 mg/m ³	TWA: 100 ppm
		(vacated) TWA: 100 ppm	TWA: 410 mg/m ³
		(vacated) TWA: 410 mg/m ³	_
CARBON BLACK	TWA: 3 mg/m ³ inhalable particulate	TWA: 3.5 mg/m ³	IDLH: 1750 mg/m ³
1333-86-4	matter	(vacated) TWA: 3.5 mg/m ³	TWA: 3.5 mg/m ³
			TWA: 0.1 mg/m ³ Carbon black in
			presence of Polycyclic aromatic
			hydrocarbons PAH

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

.

Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin and body protection	Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.
Respiratory protection	Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physica		
Physical state	Viscous liquid	
Appearance	Black	
Odor	Solvent	
Odor threshold	0.75 ppm	
Property	Values	Remarks • Method
рН	No information available	
Melting point / freezing point	No information available	
Boiling point / boiling range	101 °C / 214 °F	
Flash point	12 °C / 54 °F	Tag Closed Cup
Evaporation rate	>1	Butyl acetate = 1
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	12.5%	
Lower flammability limit:	1.6%	
Vapor pressure	28 mmHg @ 68°F	
Vapor density	>3	Air = 1
Relative density	0.95	
Water solubility	Slightly soluble	
Solubility(ies)	No information available	
Partition coefficient	No information available	
Autoignition temperature	421 °F °C / 790 °F	
Decomposition temperature	No information available	
Kinematic viscosity	No information available	
Dynamic viscosity	No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	
Other Information		
Softening point	No information available	
Molecular weight	No information available	
-	80	
VOC Content (%) Density	No information available	
Bulk density	No information available	
	No information available	
SADT (self-accelerating decomposition temperature)		
decomposition temperature)		

10. STABILITY AND REACTIVITY

Reactivity_____

No information available

Chemical stability

Stable under normal conditions

Possibility of Hazardous Reactions None under normal processing.

None under normal processi

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents, Reducing agents

Hazardous Decomposition Products Carbon oxides

Nitrogen oxides (NOx)

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

hemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Ingestion	Ingestion may cause irritation to mucous membranes.		
Skin contact	May cause skin irritation and/or dermatitis. May cause sensitization by skin contact.		
Eye contact	Contact with eyes may cause irritation. May cause redness and tearing of the eyes.		
Inhalation	May cause irritation of respiratory tract.		

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
METHYL METHACRYLATE	8420 - 10000 mg/kg (Rat) = 7872	5000 - 7500 mg/kg (Rabbit) > 5	= 7093 ppm (Rat)4 h
80-62-6	mg/kg (Rat)	g/kg (Rabbit)	
CARBON BLACK	> 15400 mg/kg (Rat)	> 3 g/kg (Rabbit)	-
1333-86-4			

Information on toxicological effects

Symptoms

No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization Germ cell mutagenicity Carcinogenicity	No informatio No informatio The table be		n agency has listed any ing	gredient as a carcinogen.
Chemical Name	ACGIH	IARC	NTP	OSHA
METHYL METHACRYLATE 80-62-6	-	Group 3	-	-
CARBON BLACK 1333-86-4	A3	Group 2B	-	Х
ACGIH (American Conference of Governmental Industrial Hygienists) A3 - Animal Carcinogen IARC (International Agency for Research on Cancer) Group 2B - Possibly Carcinogenic to Humans Not classifiable as a human carcinogen OSHA (Occupational Safety and Health Administration of the US Department of Labor) X - Present				
Target Organ Effects	Eyes, Respir	atory system, Skin.		
The following values are ATEmix (oral) ATEmix (dermal)	calculated based on cha 7921 mg/kg 5031 mg/kg	•	ument .	

7137.3 mg/l **12. ECOLOGICAL INFORMATION**

Ecotoxicity

9.5 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Persistence and degradability

ATEmix (inhalation-vapor)

No information available.

Bioaccumulation

No information available.

<u>Mobility</u>

No information available.

Chemical Name	Partition coefficient
METHYL METHACRYLATE	0.7
80-62-6	

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes	Disposal should be in accordance with applicable regional, national and local laws and regulations.
Contaminated packaging	Do not reuse container.
US EPA Waste Number	D001, U162

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status	
METHYL METHACRYLATE	Toxic	
80-62-6	Ignitable	

14. TRANSPORT INFORMATION

DOT UN/ID No Proper shipping name: Hazard Class Packing Group Emergency Response Guide Number	1133 Adhesives, Limited Quantity (LQ) 3 II 128
<u>IATA</u> UN/ID No Proper shipping name: Hazard Class ERG Code	ID 8000 Consumer commodity 9 9L
IMDG UN/ID No Proper shipping name: Hazard Class Packing Group EmS-No	1133 Adhesives, Limited Quantity (LQ) 3 II F-E, S-D

15. REGULATORY INFOR	MATION
International Inventories	
TSCA	Complies

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Not determined
ENCS	Not determined

IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

<u>SARA 313</u>

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %		
METHYL METHACRYLATE - 80-62-6	1.0		
SARA 311/312 Hazard Categories			
Acute health hazard	Yes		
Chronic Health Hazard	No		
Fire hazard	Yes		
Sudden release of pressure hazard	No		
Reactive Hazard	No		

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
METHYL METHACRYLATE	1000 lb	-	-	Х
80-62-6				

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
METHYL METHACRYLATE	1000 lb	-	RQ 1000 lb final RQ
80-62-6			RQ 454 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
CARBON BLACK 1333-86-4	*Carcinogen (airborne, unbound particles of respirable size)

• *The asterisked chemical(s) listed are not subject to Proposition 65 because they are not airborne in the finished product U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
METHYL METHACRYLATE	Х	Х	Х
80-62-6			
CARBON BLACK	Х	Х	Х
1333-86-4			
ILS EBA Label Information			

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

B2 - Flammable liquid, D2B - Toxic materials

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

<u>NFPA</u>	Health hazards 2	Flammability 3	Instability 0	-
HMIS	Health hazards 2	Flammability 3	Physical hazards 0	Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date

24-Feb-2020

Disclaimer

Illinois Tool Works Inc. believes the information contained in this data sheet is accurate as of the date compiled. However, Illinois Tool Works Inc. makes no warranty, express or implied, as to the accuracy, reliability or completeness of the information. User is responsible for evaluating whether such information or this product is fit for a particular purpose and suitable for a particular use or application. The information in this data sheet may not be valid if this product is used in combination with other products or in processes for which it was not designed. Illinois Tool Works Inc. disclaims any liability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of this product. Ensure you have the most current version of this data sheet by contacting us or reviewing our web site.

End of Safety Data Sheet