Revision Date: 06/04/2019

SAFETY DATA SHEET

1. Identification

Product identifier: 53016 FS96 14 OZ SUPERIOR COVER ALL TIRE DRESSING LT 12PK

Other means of identification

SDS number: RE1000036602

Recommended restrictions **Product Use: Coating**

Restrictions on use: Not known.

Manufacturer/Importer/Distributor Information

Manufacturer

Company Name: SUPERIOR PRODUCTS CO., INC 6962 STATE HIGHWAY 111 Address:

SOUTH ROXANA, IL 62087

Telephone: 1-800-779-8826

Fax:

Emergency telephone number: 1-866-836-8855

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable aerosol Category 1 Gases under pressure Liquefied gas

Health Hazards

Skin Corrosion/Irritation Category 2 Toxic to reproduction Category 2 Specific Target Organ Toxicity -Category 31.

Single Exposure

Specific Target Organ Toxicity -Category 2

Repeated Exposure

Aspiration Hazard Category 1

Target Organs

Narcotic effect.

Environmental Hazards

Acute hazards to the aquatic Category 2

environment

Revision Date: 06/04/2019

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement: Extremely flammable aerosol.

Causes skin irritation.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

Toxic to aquatic life.

Contains gas under pressure; may explode if heated.

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Use only outdoors or in a well-ventilated area. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid release to the

environment.

Response: IF INHALED: Remove person to fresh air and keep comfortable for

breathing. IF ON SKIN: Wash with plenty of water/... If skin irritation occurs: Get medical advice/attention. IF SWALLOWED: Immediately call a POISON

CENTER/doctor/... Do NOT induce vomiting. Call a POISON

CENTER/doctor if you feel unwell. Specific treatment (see on this label).

Take off contaminated clothing.

Storage: Protect from sunlight. Do not expose to temperatures exceeding

50°C/122°F. Store locked up. Store in a well-ventilated place. Keep

container tightly closed.

Disposal: Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC):

None.

Revision Date: 06/04/2019

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Heptane	142-82-5	25 - <50%
Naphtha (petroleum), hydrotreated light	64742-49-0	10 - <25%
Propane	74-98-6	10 - <20%
Butane	106-97-8	10 - <20%
Hexane	110-54-3	5 - <10%
Benzene, methyl-	108-88-3	0.1 - <1%
Cyclohexane	110-82-7	0.1 - <1%
Benzene	71-43-2	0 - <0.1%

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion: Call a physician or poison control center immediately. Rinse mouth. Never

give liquid to an unconscious person. If vomiting occurs, keep head low so

that stomach content doesn't get into the lungs.

Inhalation: Move to fresh air.

Skin Contact: Immediately flush with plenty of water for at least 15 minutes while

removing contaminated clothing and shoes. Wash contaminated clothing

before reuse. Get medical attention.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. If easy to do,

remove contact lenses. Get medical attention.

Most important symptoms/effects, acute and delayed

Symptoms: No data available.

Hazards: No data available.

Indication of immediate medical attention and special treatment needed

Treatment: No data available.

5. Fire-fighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool. Fight fire from a

protected location. Move containers from fire area if you can do so without

risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Do not use water jet as an extinguisher, as this will spread the fire.

Revision Date: 06/04/2019

Specific hazards arising from

the chemical:

Vapors may travel considerable distance to a source of ignition and flash

back.

Special protective equipment and precautions for firefighters

Special fire fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in

enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Methods and material for containment and cleaning

up:

Absorb spill with vermiculite or other inert material, then place in a container

for chemical waste.

Notification Procedures: Prevent entry into waterways, sewer, basements or confined areas. Stop

the flow of material, if this is without risk. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you

can do so without risk.

Do not contaminate water sources or sewer. Prevent further leakage or **Environmental Precautions:**

spillage if safe to do so. Avoid release to the environment.

7. Handling and storage

Precautions for safe handling:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Avoid contact

with skin. Wash hands thoroughly after handling.

Conditions for safe storage, including any

incompatibilities:

Store locked up. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after

use. Aerosol Level 3

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Туре	Exposure Limit Valu	ies	Source
Heptane	TWA	400 ppm 1,600	mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	STEL	500 ppm 2,000	mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	REL	85 ppm 350	mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	500 ppm 2,000	mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	STEL	500 ppm 2,000	mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000)

Revision Date: 06/04/2019

				(1989)
	TWA	400 ppm		US. ACGIH Threshold Limit Values (02 2012)
	STEL	500 ppm		US. ACGIH Threshold Limit Values (02 2012)
	TWA	400 ppm		US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	ST ESL		10,000 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		2,700 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		2,400 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	Ceil_Time	440 ppm	1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA PEL	400 ppm	1,600 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	STEL	500 ppm	2,000 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	AN ESL		660 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
Naphtha (petroleum), hydrotreated light	PEL	100 ppm	400 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (03 2016)
	TWA PEL	300 ppm	1,350 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (01 2015)
	STEL	400 ppm	1,800 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (01 2015)
	TWA	100 ppm	400 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	REL	100 ppm	400 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	ST ESL		3,500 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		350 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	TWA	100 ppm	400 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Propane	REL	1,000 ppm	1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	1,000 ppm	1,800 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA PEL	1,000 ppm	1,800 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	TWA	1,000 ppm	1,800 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	TWA	1,000 ppm	1,800 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Butane	REL	800 ppm	1,900 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	800 ppm	1,900 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL	1,000 ppm		US. ACGIH Threshold Limit Values (03 2018)
	TWA	800 ppm	1,900 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	AN ESL		3,000 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		7,100 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	TWA PEL	800 ppm		US. Ćalifornia Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	ST ESL		66,000 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)

Revision Date: 06/04/2019

	ST ESL		28,000 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
Hexane	TWA PEL	50 ppm	180 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	TWA	50 ppm	180 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	TWA	50 ppm	180 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	PEL	500 ppm	1,800 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	REL	50 ppm	180 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	50 ppm		US. ACGIH Threshold Limit Values (2008)
	AN ESL		200 μg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		6,200 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		57 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		1,700 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
Benzene, methyl-	STEL	150 ppm	560 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA PEL	10 ppm	37 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (02 2012)
	REL	100 ppm	375 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	100 ppm	375 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	STEL	150 ppm	560 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	Ceiling	300 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	TWA	20 ppm		US. ACGIH Threshold Limit Values (2008)
	Ceiling	500 ppm		US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	AN ESL		1,200 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	TWA	200 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	MAX. CONC	500 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	ST ESL		4,500 μg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	STEL	150 ppm	580 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	ST ESL		1,200 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	TWA	100 ppm	375 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL	150 ppm	560 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	AN ESL		320 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
Cyclohexane	TWA	100 ppm		US. ACGIH Threshold Limit Values (2008)
	ST ESL		3,400 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	TWA	300 ppm	1,050 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	TWA	300 ppm	1,050 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)

Revision Date: 06/04/2019

	REL	300 ppm	1,050 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	300 ppm	1,050 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA PEL	300 ppm	1,050 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	AN ESL		340 μg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		100 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		1,000 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
Benzene	REL	0.1 ppm		US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	1 ppm		US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	Ceiling	25 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	STEL	1 ppm		US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA A LV	0.5 ppm		US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	AN ESL		1.4 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	TWA	0.5 ppm		US. ACGIH Threshold Limit Values (2008)
	STEL	25 ppm		US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL	5 ppm		US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	1 ppm		US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	STEL	5 ppm		US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	TWA PEL	1 ppm		US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	ST ESL		170 μg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	TWA	10 ppm		US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	ST ESL		53 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	STEL	2.5 ppm		US. ACGIH Threshold Limit Values (2008)
	STEL	5 ppm		US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	OSHA_AC T	0.5 ppm		US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	TWA	10 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	MAX. CONC	50 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	AN ESL		4.5 μg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	Ceiling	50 ppm		US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)

Revision Date: 06/04/2019

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Hexane (2,5-Hexanedion, without hydrolysis: Sampling time: End of shift.)	0.5 mg/l (Urine)	ACGIH BEL (03 2018)
Benzene, methyl- (toluene: Sampling time: End of shift.)	0.03 mg/l (Urine)	ACGIH BEL (03 2013)
Benzene, methyl- (o-Cresol, with hydrolysis: Sampling time: End of shift.)	0.3 mg/g (Creatinine in urine)	ACGIH BEL (03 2013)
Benzene, methyl- (toluene: Sampling time: Prior to last shift of work week.)	0.02 mg/l (Blood)	ACGIH BEL (03 2013)
Benzene (t,t-Muconic acid: Sampling time: End of shift.)	500 μg/g (Creatinine in urine)	ACGIH BEL (03 2013)
Benzene (S- Phenylmercapturic acid: Sampling time: End of shift.)	25 μg/g (Creatinine in urine)	ACGIH BEL (03 2013)

Appropriate Engineering Controls

No data available.

Individual protection measures, such as personal protective equipment

General information: Provide easy access to water supply and eye wash facilities. Good general

ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. If exposure limits have not been established, maintain airborne levels

to an acceptable level.

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: No data available.

Other: Wear suitable protective clothing. Wear chemical-resistant gloves, footwear,

and protective clothing appropriate for the risk of exposure. Contact health

and safety professional or manufacturer for specific information.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from

local supervisor.

Hygiene measures: Observe good industrial hygiene practices. When using do not smoke. Do

not handle until all safety precautions have been read and understood. Obtain special instructions before use. Wash contaminated clothing before reuse. Avoid contact with skin. Wash hands before breaks and immediately

after handling the product.

9. Physical and chemical properties

Appearance

Physical state: liquid

Form: Spray Aerosol
Color: No data available.
Odor: No data available.
Odor threshold: No data available.
pH: No data available.

Revision Date: 06/04/2019

Melting point/freezing point:No data available.Initial boiling point and boiling range:No data available.

Flash Point: -104.44 °C

Evaporation rate:No data available. **Flammability (solid, gas):**No data available.

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

Flammability limit - lower (%):

Explosive limit - upper (%):

No data available.

Vapor density:No data available.Density:No data available.Relative density:No data available.

Solubility(ies)

Solubility in water:

Solubility (other):

No data available.

No data available.

No data available.

No data available.

Auto-ignition temperature:No data available.Decomposition temperature:No data available.Viscosity:No data available.

10. Stability and reactivity

Reactivity: No data available.

Chemical Stability: Material is stable under normal conditions.

Possibility of hazardous

reactions:

No data available.

Conditions to avoid: Avoid heat or contamination.

Incompatible Materials: No data available.

Hazardous Decomposition

Products:

No data available.

11. Toxicological information

Information on likely routes of exposure

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: No data available.

Revision Date: 06/04/2019

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

Heptane LD 50 (Rat): > 5,000 mg/kg

Naphtha (petroleum),

hydrotreated light

LD 50 (Rat): > 5,000 mg/kg

Hexane LD 50: > 2,000 mg/kg

Benzene, methyl-LD 50 (Rat): 5,580 mg/kg

Cyclohexane LD 50 (Rat): > 5,000 mg/kg

Benzene LD 50 (Rat): 5,970 mg/kg

Dermal

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

Heptane LD 50 (Rabbit): > 2,000 mg/kg

Naphtha (petroleum),

hydrotreated light

LD 50 (Rabbit): > 3,750 mg/kg

Hexane LD 50 (Rabbit): > 2,000 mg/kg

Benzene, methyl-LD 50 (Rabbit): > 5,000 mg/kg

Cyclohexane LD 50 (Rabbit): > 2,000 mg/kg

Benzene LD 50: > 2,000 mg/kg

Inhalation

Product: Not classified for acute toxicity based on available data.

Revision Date: 06/04/2019

Specified substance(s):

Heptane LC 50 (Rat): > 29.29 mg/l

Naphtha (petroleum), LOAEL (Human): 2,400 mg/m3 hydrotreated light LC 50 (Rat): > 7,630 mg/m3

Propane LC 50 (Mouse): 1,237 mg/l

Butane LC 50 (Mouse): 1,237 mg/l

Hexane LC 50 (Rat): > 31.86 mg/l

Benzene, methyl- LC 50 (Rat): 28.1 mg/l

Cyclohexane LC 50 (Rat): > 32,880 mg/m3

Benzene LC 50 (Rat): 43,767 mg/m3

Repeated dose toxicity

Product: No data available.

Specified substance(s):

Heptane NOAEL (Rat(Male), Inhalation): 12,470 mg/m3 Inhalation Experimental

result, Key study

Naphtha (petroleum), LOAEL (Rat(Female, Male), Oral, 13 Weeks): 1,250 mg/kg Oral Readhydrotreated light across based on grouping of substances (category approach), Key study

NOAEL (Rat(Female, Male), Dermal, 28 d): > 375 mg/kg Dermal

Experimental result, Supporting study

NOAEL (Rat(Female, Male), Inhalation): 10,000 mg/m3 Inhalation

Experimental result, Key study

Propane NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation

Experimental result, Key study

LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation

Experimental result, Key study

Butane NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation

Experimental result, Key study

LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation

Experimental result, Key study

Hexane NOAEL (Mouse(Male), Inhalation, 13 Weeks): 500 ppm(m) Inhalation

Experimental result, Key study

LOAEL (Mouse(Male), Inhalation, 13 Weeks): 1,000 ppm(m) Inhalation

Experimental result, Key study

LOAEL (Rat(Male), Inhalation, 16 Weeks): 3,000 ppm(m) Inhalation

Experimental result, Key study

LOAEL (Mouse(Female), Inhalation, 13 Weeks): 500 ppm(m) Inhalation

Experimental result, Key study

Benzene, methyl- LOAEL (Rat(Female, Male), Oral, 13 Weeks): 1,250 mg/kg (Target

Organ(s): Liver, Kidney) Oral Experimental result, Key study NOAEL (Rat(Female, Male), Inhalation): 625 ppm(m) Inhalation

Experimental result, Key study

NOAEL (Rat(Female, Male), Inhalation - vapor): 2,355 mg/l Inhalation

Revision Date: 06/04/2019

Experimental result, Key study

Cyclohexane NOAEL (Rat(Female, Male), Inhalation, 13 - 18 Weeks): 7,000 ppm(m)

Inhalation Experimental result, Key study

NOAEL (Mouse(Female, Male), Inhalation, 13 - 18 Weeks): 500 ppm(m)

Inhalation Experimental result, Key study

Benzene NOAEL (Rat(Male), Oral, 120 d): 100 mg/kg Oral Experimental result, Key

study

NOAEL (Mouse(Female, Male), Inhalation, 7 - 91 d): 96 mg/m3 Inhalation

Experimental result, Key study

LOAEL (Rat(Female), Oral, 120 d): 25 mg/kg Oral Experimental result, Key

study

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

Heptane in vivo (Rabbit): Irritating Read-across based on grouping of substances

(category approach), Key study

Benzene, methyl- in vivo (Rabbit): Irritating Experimental result, Key study

Cyclohexane Review (Various): Irritating.

in vivo (Rabbit): Not irritant Experimental result, Weight of Evidence study

Benzene in vivo (Rabbit): Irritating Experimental result, Key study

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Heptane Rabbit, 24 - 72 hrs: Not irritating

Naphtha (petroleum), hydrotreated light

Rabbit, 24 - 72 hrs: Not irritating

Hexane Rabbit, 1 - 72 hrs: Not irritating

Benzene, methyl- Rabbit, 24 - 72 hrs: Not irritating

Benzene Rabbit: Irritating

Respiratory or Skin Sensitization

Product: No data available.

Specified substance(s):

Heptane Skin sensitization:, in vivo (Guinea pig): Non sensitising

Naphtha (petroleum), Skin sensitization:, in vivo (Guinea pig): Non sensitising

hydrotreated light

Benzene, methyl-Cyclohexane Skin sensitization:, in vivo (Guinea pig): Non sensitising Skin sensitization:, in vivo (Guinea pig): Non sensitising

Carcinogenicity

Product: No data available.

Specified substance(s):

Benzene Cancer hazard - can cause cancer.

Revision Date: 06/04/2019

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specified substance(s):

Hexane Suspected of damaging fertility or the unborn child. Benzene, methyl-Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity - Single Exposure

Product: Narcotic effect. - Category 3 with narcotic effects.

Specific Target Organ Toxicity - Repeated Exposure

Product: Inhalation - vapor: Nervous System - Category 2

Target Organs

Specific Target Organ Toxicity - Single Exposure: Narcotic effect.

Aspiration Hazard

Product: No data available.

Specified substance(s):

Heptane May be fatal if swallowed and enters airways. Naphtha (petroleum), May be fatal if swallowed and enters airways.

hydrotreated light

Benzene, methylCyclohexane
May be fatal if swallowed and enters airways.
May be fatal if swallowed and enters airways.
Benzene
May be fatal if swallowed and enters airways.
May be fatal if swallowed and enters airways.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Heptane LC 50 (Mozambique tilapia (Tilapia mossambica), 96 h): 375 mg/l Mortality

Naphtha (petroleum), LC 50 (96 h): 8.41 mg/l Experimental result, Key study

SDS US - RE1000036602 13/20

Revision Date: 06/04/2019

hydrotreated light

Propane LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study

Butane LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study

Hexane LC 50 (Fathead minnow (Pimephales promelas), 96 h): 2.101 - 2.981 mg/l

Mortality

Benzene, methyl- LC 50 (Oncorhynchus kisutch, 96 h): 5.5 mg/l Experimental result, Key study

Cyclohexane LC 50 (Pimephales promelas, 96 h): 4.53 mg/l Experimental result, Key

study

Benzene LC 50 (Oncorhynchus mykiss, 96 h): 5.3 mg/l Experimental result, Key study

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Heptane EC 50 (Daphnia magna, 48 h): 1.5 mg/l Experimental result, Key study

Naphtha (petroleum), hydrotreated light

EC 50 (Daphnia magna, 48 h): 4.5 mg/l Experimental result, Key study

Butane LC 50 (Daphnia sp., 48 h): 69.43 mg/l QSAR QSAR, Key study

Hexane EC 50 (Daphnia magna, 48 h): 21.85 mg/l QSAR QSAR, Key study

LC 50 (Water flea (Daphnia magna), 24 h): > 50 mg/l Mortality

Benzene, methyl- LC 50 (Water flea (Daphnia magna), 48 h): 54.6 - 174.7 mg/l Mortality

LC 50 (Ceriodaphnia dubia, 2 d): 3.78 mg/l Experimental result, Key study

Cyclohexane EC 50 (Daphnia magna, 48 h): 0.9 mg/l Experimental result, Key study

Benzene EC 50 (Daphnia magna, 24 h): 10 mg/l Experimental result, Key study

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Heptane NOAEL (Oncorhynchus mykiss): 1.284 mg/l QSAR QSAR, Key study

Naphtha (petroleum), hydrotreated light

EC 50 (Daphnia magna): 10 mg/l Other, Key study NOAEL (Daphnia magna): 2.6 mg/l Other, Key study

Hexane NOAEL (Oncorhynchus mykiss): 2.8 mg/l QSAR QSAR, Key study

Benzene, methyl- NOAEL (Oncorhynchus kisutch): 1.39 mg/l Experimental result, Key study

LOAEL (Oncorhynchus kisutch): 2.77 mg/l Experimental result, Key study

Benzene LOAEL (Pimephales promelas): 1.6 mg/l Experimental result, Key study

LC 50 (Oncorhynchus mykiss): 8.64 mg/l Experimental result, Supporting

study

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Revision Date: 06/04/2019

Heptane NOAEL (Daphnia magna): 0.17 mg/l Read-across based on grouping of

substances (category approach), Key study

EC 50 (Daphnia magna): 0.23 mg/l Read-across based on grouping of

substances (category approach), Key study

Naphtha (petroleum), hydrotreated light

EC 50 (Daphnia magna): 10 mg/l Experimental result, Key study NOAEL (Daphnia magna): 2.6 mg/l Experimental result, Key study

Hexane NOAEL (Daphnia magna): 4.888 mg/l QSAR QSAR, Key study

Benzene, methyl- LOAEL (Ceriodaphnia dubia): 2.76 mg/l Experimental result, Key study

NOAEL (Ceriodaphnia dubia): 0.74 mg/l Experimental result, Key study

Benzene NOAEL (Daphnia magna): 98 mg/l Not specified, Not specified

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

Specified substance(s):

Heptane 70 % Detected in water. Experimental result, Key study

Naphtha (petroleum), hydrotreated light

90.35 % (28 d) Detected in water. Experimental result, Supporting study

Propane 100 % (385.5 h) Detected in water. Experimental result, Key study

50 % (3.19 d) Detected in water. QSAR, Weight of Evidence study

Butane 100 % (385.5 h) Detected in water. Experimental result, Key study

50 % (3.19 d) Detected in water. QSAR, Weight of Evidence study

Hexane 81 % Detected in water. Read-across based on grouping of substances

(category approach), Key study

Benzene, methyl- 100 % (14 d) Detected in water. Experimental result, Weight of Evidence

study

86 % Detected in water. Experimental result, Weight of Evidence study

Cyclohexane 77 % (28 d) Detected in water. Experimental result, Key study

Benzene 4 - 88 % (28 d) Detected in water. Experimental result, Supporting study

81 % Detected in water. Experimental result, Key study

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Specified substance(s):

Heptane Bioconcentration Factor (BCF): 552 Aquatic sediment Estimated by

calculation, Key study

Revision Date: 06/04/2019

Naphtha (petroleum), Bioconcentration Factor (BCF): 10 - 2,500 Aquatic sediment Estimated by

hydrotreated light

coloulation Koy atudy

calculation, Key study

Hexane Pimephales promelas, Bioconcentration Factor (BCF): 501.19 Aquatic

sediment QSAR, Key study

Benzene, methyl- Leuciscus idus, Bioconcentration Factor (BCF): 90 Aquatic sediment

Experimental result, Key study

Cyclohexane Cyprinus carpio, Bioconcentration Factor (BCF): 37 - 129 Aquatic sediment

Experimental result, Supporting study

Benzene Northern anchovy (Engraulis mordax), Bioconcentration Factor (BCF): 505

(Static)

Engraulis mordax; Morone saxatilis, Bioconcentration Factor (BCF): 309

Aquatic sediment Experimental result, Supporting study

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Specified substance(s):

Naphtha (petroleum), Log Kow: > 2.4 - < 5.7 23 °C Yes Experimental result, Key study

hydrotreated light Log Kow: 2.2 - 5.2 23 °C Yes Experimental result, Key study

Log Kow: 2.2 - 6.1 23 °C Yes Experimental result, Key study

Benzene Log Kow: 1.56 - 2.15 25 °C No Not specified, Not specified

Mobility in soil: No data available.

Known or predicted distribution to environmental compartments

Heptane No data available. Naphtha (petroleum), No data available.

hydrotreated light

Propane No data available.
Butane No data available.
Hexane No data available.
Benzene, methyl- No data available.
Cyclohexane No data available.
Benzene No data available.
No data available.

Other adverse effects: Toxic to aquatic organisms.

13. Disposal considerations

Disposal instructions: Discharge, treatment, or disposal may be subject to national, state, or local

laws.

Contaminated Packaging: No data available.

Revision Date: 06/04/2019

14. Transport information

DOT

UN Number: UN 1950

UN Proper Shipping Name: Aerosols, flammable

Transport Hazard Class(es)

Class: 2.1
Label(s): Packing Group: II
Marine Pollutant: No

Environmental Hazards: No Marine Pollutant No

Special precautions for user: Not regulated.

IMDG

UN Number: UN 1950

UN Proper Shipping Name: Aerosols, flammable

Transport Hazard Class(es)

Class: 2 Label(s): –

EmS No.: F-D, S-U

Packing Group: -

Environmental Hazards No Marine Pollutant Yes

Special precautions for user: Not regulated.

IATA

UN Number: UN 1950

Proper Shipping Name: Aerosols, flammable

Transport Hazard Class(es):

Class: 2.1
Label(s): –

Packing Group: –

Environmental Hazards No Marine Pollutant Yes

Special precautions for user: Not regulated.

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Chemical Identity OSHA hazard(s)

Revision Date: 06/04/2019

Benzene respiratory tract irritation

Central nervous system

Blood Skin

Flammability Cancer Aspiration Eye

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity
Heptane	lbs. 100
Propane	lbs. 100
Butane	lbs. 100
Hexane	lbs. 5000
Benzene, methyl-	lbs. 1000
Cyclohexane	lbs. 1000
Benzene	lbs. 10

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Fire Hazard

Immediate (Acute) Health Hazards Delayed (Chronic) Health Hazard

Flammable aerosol Skin Corrosion/Irritation Toxic to reproduction

Specific Target Organ Toxicity - Single Exposure Specific Target Organ Toxicity - Repeated Exposure

Aspiration Hazard

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SARA 304 Emergency Release Notification

Chemical Identity	Reportable quantity
Heptane	lbs. 100
Propane	lbs. 100
Butane	lbs. 100
Hexane	lbs. 5000
Benzene, methyl-	lbs. 1000
Cyclohexane	lbs. 1000
Benzene	lbs. 10

SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
Heptane	10000 lbs
Naphtha (petroleum),	10000 lbs
hydrotreated light	
Propane	10000 lbs
Butane	10000 lbs
Hexane	10000 lbs
Benzene, methyl-	10000 lbs
Cyclohexane	10000 lbs
Benzene	10000 lbs
SARA 313 (TRI Reporting)	

Reporting Reporting threshold for manufacturing and

<u>Chemical Identity</u> <u>other users</u> <u>processing</u>

Revision Date: 06/04/2019

Hexane lbs lbs.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130): Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3) US State Regulations

US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

Hexane Male reproductive toxin. 12 2017
Benzene, methylBenzene Developmental toxin. 03 2008
Developmental toxin. 03 2008

Benzene Carcinogenic. 05 2011

Benzene Male reproductive toxin. 03 2008

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

Heptane

Naphtha (petroleum), hydrotreated light

Propane Butane Hexane

US. Massachusetts RTK - Substance List

Chemical Identity

Benzene

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

Heptane

Naphtha (petroleum), hydrotreated light

Propane Butane

Hexane

US. Rhode Island RTK

No ingredient regulated by RI Right-to-Know Law present.

International regulations

Montreal protocol

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol

Not applicable

Revision Date: 06/04/2019

Inventory Status:

Australia AICS: On or in compliance with the inventory

Canada DSL Inventory List:

On or in compliance with the inventory

EINECS, ELINCS or NLP: Not in compliance with the inventory.

Japan (ENCS) List: On or in compliance with the inventory

China Inv. Existing Chemical Substances: Not in compliance with the inventory.

Korea Existing Chemicals Inv. (KECI): Not in compliance with the inventory.

Canada NDSL Inventory: Not in compliance with the inventory.

Philippines PICCS: On or in compliance with the inventory

US TSCA Inventory: On or in compliance with the inventory

New Zealand Inventory of Chemicals:

On or in compliance with the inventory

Japan ISHL Listing: On or in compliance with the inventory

Japan Pharmacopoeia Listing: Not in compliance with the inventory.

Mexico INSQ: On or in compliance with the inventory

Ontario Inventory: On or in compliance with the inventory

Taiwan Chemical Substance Inventory:

On or in compliance with the inventory

16.Other information, including date of preparation or last revision

Issue Date: 06/04/2019

Revision Information: No data available.

Version #: 1.0

Further Information: No data available.

Disclaimer: This information is provided without warranty. The information is believed to

be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.