



SAFETY DATA SHEET

ZEREX™ G30® 50/50 Antifreeze Coolant

Version: 1.5

Revision Date: 11/03/2021

Print Date:
02/10/2023

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : ZEREX™ G30® 50/50
Antifreeze Coolant

Product code : 877981

Details of the supplier of the safety data sheet

Valvoline LLC
100 Valvoline Way
Lexington, KY 40509
United States of America (USA)
1-800-TEAMVAL (1-800-832-6825)

SDS@valvoline.com

Emergency telephone number

1-800-VALVOLINE (1-800-825-8654)

Regulatory Information Number

1-800-TEAMVAL (1-800-832-6825)

Product Information

1-800-TEAMVAL (1-800-832-6825)

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Acute toxicity (Oral) : Category 4

Specific target organ toxicity
- repeated exposure (Oral) : Category 2 (Kidney, Liver)

GHS label elements

Hazard pictograms :



Signal Word : Warning

Hazard Statements : Harmful if swallowed.
May cause damage to organs (Kidney, Liver) through
prolonged or repeated exposure if swallowed.

Precautionary Statements : **Prevention:**
Do not breathe mist or vapors.
Wash skin thoroughly after handling.



SAFETY DATA SHEET

ZEREX™ G30® 50/50 Antifreeze Coolant

Version: 1.5

Revision Date: 11/03/2021

Print Date:
02/10/2023

Do not eat, drink or smoke when using this product.

Response:

IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.

Get medical advice/ attention if you feel unwell.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
ETHYLENE GLYCOL	107-21-1	Acute Tox. 4; H302 STOT RE 2; H373	>=40.00 - < 50.00

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Induce vomiting immediately and call a physician.
Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.
- Most important symptoms : Effects of acute ethylene glycol poisoning appear in three



SAFETY DATA SHEET

ZEREX™ G30® 50/50 Antifreeze Coolant

Version: 1.5

Revision Date: 11/03/2021

Print Date:
02/10/2023

and effects, both acute and delayed

fairly distinct stages. The initial stage occurs shortly after exposure, lasts 6-12 hours, and is characterized by central nervous system effects (transient exhilaration, nausea, vomiting, and in severe cases, coma, convulsions, and possible death). The second stage lasts from 12-36 hours after exposure and is initiated by the onset of coma. This phase is characterized by tachypnea, tachycardia, mild hypotension, cyanosis, and in severe cases, pulmonary edema, bronchopneumonia, cardiac enlargement, and congestive failure. The final stage occurs 24-72 post-exposure and is characterized by renal failure, ranging from a mild increase in blood urea nitrogen and creatinine followed by recovery, to complete anuria with acute tubular necrosis that can lead to death. Oxaluria is found in most cases. The most significant laboratory finding in ethylene glycol intoxication is severe metabolic acidosis.

Harmful if swallowed.

May cause damage to organs through prolonged or repeated exposure if swallowed.

No symptoms known or expected.

Notes to physician

: This product contains ethylene glycol. Ethanol decreases the metabolism of ethylene glycol to toxic metabolites. Ethanol should be administered as soon as possible in cases of severe poisoning since the elimination half-life of ethylene glycol is 3 hours. If medical care will be delayed several hours, give the patient three to four 1-ounce oral "shots" of 86-proof or higher whiskey before or during transport to the hospital. Fomepizole (4-methylpyrazole) is an effective antagonist of alcohol dehydrogenase, and as such, may be used as an antidote in the treatment of ethylene glycol poisoning. Hemodialysis effectively removes ethylene glycol and its metabolites from the body.

No hazards which require special first aid measures.

Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Unsuitable extinguishing media : High volume water jet

Hazardous combustion products : No hazardous combustion products are known

Specific extinguishing methods :



SAFETY DATA SHEET

ZEREX™ G30® 50/50 Antifreeze Coolant

Version: 1.5

Revision Date: 11/03/2021

Print Date:
02/10/2023

- Further information : Standard procedure for chemical fires.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Do not breathe vapours/dust.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ETHYLENE GLYCOL	107-21-1	TWA	25 ppm Vapour	ACGIH
		STEL	50 ppm Vapour	ACGIH



SAFETY DATA SHEET

ZEREX™ G30® 50/50 Antifreeze Coolant

Version: 1.5

Revision Date: 11/03/2021

Print Date:
02/10/2023

		STEL	10 mg/m3 Inhalable fraction, Aerosol only	ACGIH
		C	50 ppm 125 mg/m3	OSHA P0
		C	40 ppm 100 mg/m3 Vapour	CAL PEL

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Eye wash bottle with pure water
Tightly fitting safety goggles

Skin and body protection

: Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures

: When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

: liquid

Colour

: pink

Odour

: No data available

Odour Threshold

: No data available

pH

: Average 8.3

Melting point/freezing point

: No data available

Boiling point/boiling range

: 225 °F / 107 °C
(1013 hPa)

Flash point

: > 250 °F / > 121 °C



SAFETY DATA SHEET

ZEREX™ G30® 50/50 Antifreeze Coolant

Version: 1.5

Revision Date: 11/03/2021

Print Date:
02/10/2023

Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Self-ignition	:	No data available
Upper explosion limit / Upper flammability limit	:	15.3 %(V) GLP: Calculated Explosive Limit
Lower explosion limit / Lower flammability limit	:	3.2 %(V) GLP: Calculated Explosive Limit
Vapour pressure	:	23.333333 hPa (68 °F / 20 °C) Calculated Vapor Pressure
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	1.0740 g/cm ³ (60.1 °F / 15.6 °C)
Solubility(ies)		
Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	No data available
Oxidizing properties	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed.
Conditions to avoid	:	excessive heat



SAFETY DATA SHEET

ZEREX™ G30® 50/50 Antifreeze Coolant

Version: 1.5

Revision Date: 11/03/2021

Print Date:
02/10/2023

	No data available
Incompatible materials	: Aldehydes Alkali metals Alkaline earth metals Strong acids strong alkalis Strong oxidizing agents Sulphur compounds
	Not applicable
Hazardous decomposition products	No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful if swallowed.

Product:

Acute oral toxicity : Acute toxicity estimate: 1,006 mg/kg
Method: Calculation method

Components:

ETHYLENE GLYCOL:

Acute oral toxicity : LD0 (Human): estimated 1.56 g/kg

Assessment: The component/mixture is moderately toxic after single ingestion.

Acute inhalation toxicity : LC50 (Rat): 10.9 mg/l
Exposure time: 1 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): 9,530 mg/kg

Acute toxicity (other routes of administration) : LD50 (Rat): 5,010 mg/kg
Application Route: Intraperitoneal

LD50 (Rat): 3,260 mg/kg
Application Route: Intravenous

Skin corrosion/irritation

Not classified based on available information.



SAFETY DATA SHEET

ZEREX™ G30® 50/50 Antifreeze Coolant

Version: 1.5

Revision Date: 11/03/2021

Print Date:
02/10/2023

Components:

ETHYLENE GLYCOL:

Species : Rabbit
Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

ETHYLENE GLYCOL:

Result : Slight, transient irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

ETHYLENE GLYCOL:

Test Type : Maximisation Test
Species : Guinea pig
Assessment : Does not cause skin sensitisation.

Germ cell mutagenicity

Not classified based on available information.

Components:

ETHYLENE GLYCOL:

Genotoxicity in vitro : Test Type: Ames test
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Result: negative

Carcinogenicity

Not classified based on available information.

IARC No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

May cause damage to organs (Kidney, Liver) through prolonged or repeated exposure if swallowed.



SAFETY DATA SHEET

ZEREX™ G30® 50/50 Antifreeze Coolant

Version: 1.5

Revision Date: 11/03/2021

Print Date:
02/10/2023

Components:

ETHYLENE GLYCOL:

Exposure routes : Ingestion
Target Organs : Kidney, Liver
Assessment : May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Experience with human exposure

Components:

ETHYLENE GLYCOL:

Ingestion : Target Organs: Kidney

Further information

Product:

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Not classified based on available information.

Long-term (chronic) aquatic hazard : Not classified based on available information.

Components:

ETHYLENE GLYCOL:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 27,540 mg/l
Exposure time: 96 h
Test Type: static test

LC50 (Pimephales promelas (fathead minnow)): 8,050 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Test Type: static test

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 6,500 - 13,000 mg/l
End point: Growth inhibition
Exposure time: 7 Days

Toxicity to fish (Chronic) : NOEC (Pimephales promelas (fathead minnow)): 32,000 mg/l



SAFETY DATA SHEET

ZEREX™ G30® 50/50 Antifreeze Coolant

Version: 1.5

Revision Date: 11/03/2021

Print Date:
02/10/2023

toxicity) Exposure time: 7 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 24,000 mg/l
Exposure time: 7 d

Ecotoxicology Assessment Short-term (acute) aquatic hazard : Not classified based on available information.

Long-term (chronic) aquatic hazard : Not classified based on available information.

Persistence and degradability

Components:

ETHYLENE GLYCOL:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 90 - 100 %
Exposure time: 10 d
Method: OECD Test Guideline 301

No data available

Bioaccumulative potential

Components:

ETHYLENE GLYCOL:

Bioaccumulation : Species: Crayfish (Procambarus)
Bioconcentration factor (BCF): 0.27
Exposure time: 61 d
Concentration: 1000 mg/l
Method: Flow through

Partition coefficient: n-octanol/water : log Pow: -1.36

No data available

Mobility in soil

Components:

No data available

Other adverse effects

No data available

Product:

Regulation

40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Remarks

Additional ecological information : No data available



SAFETY DATA SHEET

ZEREX™ G30® 50/50 Antifreeze Coolant

Version: 1.5

Revision Date: 11/03/2021

Print Date:
02/10/2023

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- General advice : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
- Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

CFR_ROAD

Not regulated as a dangerous good

CFR_ROAD

Not regulated as a dangerous good

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity



SAFETY DATA SHEET

ZEREX™ G30® 50/50 Antifreeze Coolant

Version: 1.5

Revision Date: 11/03/2021

Print Date:
02/10/2023

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
TOLUENE	108-88-3	100	100 (F005)

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Acute toxicity (any route of exposure)
Specific target organ toxicity (single or repeated exposure)

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

ETHYLENE 107-21-1 >= 30 - < 50 %
GLYCOL

Clean Air Act

CAA_90 :

HON_HAP :

HON_SOC : Group I

CAA_111 :

CA AIR Applicable Degree of Accuracy::

WI HAPS A Threshold for emissions from stacks less than 25 ft::

Threshold for emissions from stacks 25 to less than 40 ft::

Threshold for emissions from stacks 40 to less than 75 ft::

Threshold for emissions from stacks greater than or equal to 75 ft::

Ambient air standard::

VOC RE :

VOC DI :

VOC EQ :

VOC AE Reactivity factor::

CA PTACS :



SAFETY DATA SHEET

ZEREX™ G30® 50/50 Antifreeze Coolant

Version: 1.5

Revision Date: 11/03/2021

Print Date:
02/10/2023

SC TAP	MAC Value::
CA TAC	:
CAA_90	:
HON_HAP	:
HON_SOC	: Group I
CAA_111	:
CA AIR	Applicable Degree of Accuracy::
WI HAPS A	Threshold for emissions from stacks less than 25 ft:: Threshold for emissions from stacks 25 to less than 40 ft:: Threshold for emissions from stacks 40 to less than 75 ft:: Threshold for emissions from stacks greater than or equal to 75 ft:: Ambient air standard::
VOC RE	:
VOC DI	:
VOC EQ	:
VOC AE	Reactivity factor::
CA PTACS	:
SC TAP	MAC Value::
CA TAC	:

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).
The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

ETHYLENE GLYCOL	107-21-1	>= 30 - < 50 %
-----------------	----------	----------------

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

ETHYLENE GLYCOL	107-21-1	>= 30 - < 50 %
-----------------	----------	----------------



SAFETY DATA SHEET

ZEREX™ G30® 50/50 Antifreeze Coolant

Version: 1.5

Revision Date: 11/03/2021

Print Date:
02/10/2023

Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

SODIUM HYDROXIDE	1310-73-2	>= 0.1 - < 1 %
ADIPIC ACID	124-04-9	>= 0.1 - < 1 %
POTASSIUM HYDROXIDE	1310-58-3	>= 0 - < 0.1 %
TOLUENE	108-88-3	>= 0 - < 0.1 %

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

SODIUM HYDROXIDE	1310-73-2	>= 0.1 - < 1 %
ADIPIC ACID	124-04-9	>= 0.1 - < 1 %
POTASSIUM HYDROXIDE	1310-58-3	>= 0 - < 0.1 %
TOLUENE	108-88-3	>= 0 - < 0.1 %

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

California Prop. 65

 **WARNING:** Reproductive Harm - www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

TCSI	: On the inventory, or in compliance with the inventory
TSCA	: All substances listed as active on the TSCA inventory
AIIC	: Not in compliance with the inventory
DSL	: All components of this product are on the Canadian DSL
ENCS	: Not in compliance with the inventory
ISHL	: Not in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
NZIoC	: Not in compliance with the inventory
TECI	: Not in compliance with the inventory

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.



SAFETY DATA SHEET

ZEREX™ G30® 50/50 Antifreeze Coolant

Version: 1.5

Revision Date: 11/03/2021

Print Date:
02/10/2023

Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Internal information : 000000091711

NFPA:	HMIS III:						
<p>Flammability</p> <p>Health</p> <p>Instability</p> <p>Special hazard</p>	<table><tr><td>HEALTH</td><td>2*</td></tr><tr><td>FLAMMABILITY</td><td>1</td></tr><tr><td>PHYSICAL HAZARD</td><td>0</td></tr></table> <p>0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	2*	FLAMMABILITY	1	PHYSICAL HAZARD	0
HEALTH	2*						
FLAMMABILITY	1						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements

H302 Harmful if swallowed.
H373 May cause damage to organs through prolonged or repeated exposure if swallowed.

Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).



SAFETY DATA SHEET

ZEREX™ G30® 50/50 Antifreeze Coolant

Version: 1.5

Revision Date: 11/03/2021

Print Date:
02/10/2023

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act

DOT : Department of Transportation

FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act

HMIRC : Hazardous Materials Information Review Commission

HMIS : Hazardous Materials Identification System

NFPA : National Fire Protection Association

NIOSH : National Institute for Occupational Safety and Health

OSHA : Occupational Safety and Health Administration

PMRA : Health Canada Pest Management Regulatory Agency

RTK : Right to Know

WHMIS : Workplace Hazardous Materials Information System