



EDGE High Mileage 10W-40

Strength for Maximum Performance

Description

Castrol® EDGE® High Mileage[™] is part of our strongest and most advanced range of full synthetic engine oils. It is engineered with fluid titanium technology to provide superior motor oil strength and help your vehicle to maximize performance.

As your car ages, its engine can lose performance and efficiency. Proper vehicle maintenance practice is critical to keeping an older engine performing at its best.

Castrol® EDGE® High Mileage[™] is boosted with extra fluid titanium technology to increase its film strength and reduce oil film breakdown and friction.

Application

Exceeds manufacturer's warranty requirements for applications requiring API SN.

Advantages

Castrol® EDGE® High Mileage[™] provides maximum performance in vehicles with 75K+ miles. Boosted with extra fluid TITANIUM technology to increase its film strength and fight power-robbing friction in higher mileage performance engines.

- Maximize short and long term engine performance on high mileage engines
- Reduce leaks, oil burn off and power-robbing deposits

Typical Characteristics

Name	Method	Units	Typical Values
Density @ 15C, Relative	ASTM D4052	g/ml	0.856
Appearance	Visual	-	Clear & Bright
Viscosity, Kinematic 100C	ASTM D445	mm²/s	14.78
Pour Point	ASTM D97	°C	-39
Viscosity, MRV / Yield Stress -30C (10W)	ASTM D4684	mPa.s (cP)	27750
Viscosity, Kinematic 40C	ASTM D445	mm²/s	91.89
Viscosity Index	ASTM D2270	None	159
Noack Volatility	ASTM D5800	% Loss	10.0
Gelation Index	ASTM D5133	-	8.0

• When choosing oil, please refer to your owner's handbook & the product Specifications shown below. May also be suitable for other vehicles.

Product Performance Claims

ACEA A3/B3, A3/B4 API SN

EDGE High Mileage 10W-40 20 Feb 2017 Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road, Wayne, NJ 07470 Telephone: 1,800.462.0835 www.castrol.com/us Email: contactus@bp.com