Permatex.

SAFETY DATA SHEET

Revision Date 07-May-2020 Version 5

1. IDENTIFICATION

Product identifier

Product Name 765-2657 NAPA WATER MIX VALVE GRINDING COMPOUND 4 OZ

Other means of identification

Product Code 39835

Recommended use of the chemical and restrictions on use
Recommended Use Grinding compound
Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address

ITW Permatex 6875 Parkland Blvd. Solon, Ohio 44139 USA Telephone: 1-87-Permatex

(866) 732-9502

24-hour emergency phone number

Chem-Tel: 800-255-3924 International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

E-mail address: mail@permatex.com

May Also Be Distributed by:

ITW Permatex Canada 101-2360 Bristol Circle

Oakville, ON Canada L6H 6M5 Telephone: (800) 924-6994

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Carcinogenicity	Category 1B

Label elements

Emergency Overview

Signal word Danger

Harmful if swallowed May cause cancer



Appearance Gray Physical state Paste Liquid Odor Slight

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

Rinse mouth

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

Not applicable.

Unknown acute toxicity 0% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
SILICON CARBIDE	409-21-2	15 - 40
ETHYLENE GLYCOL	107-21-1	10 - 30

4. FIRST AID MEASURES

Description of first aid measures

General advice Get medical advice/attention if you feel unwell.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

Skin contact IF ON SKIN:. Wash skin with soap and water. If skin irritation persists, call a physician.

Take off contaminated clothing and wash before reuse.

Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If symptoms persist, call a physician.

Ingestion IF SWALLOWED:. Call a POISON CENTER or doctor/physician if you feel unwell. Rinse

mouth.

Self-protection of the first aider Ensure that medical personnel are aware of the material(s) involved and take precautions to

protect themselves.

Most important symptoms and effects, both acute and delayed

Symptoms See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO2), Use dry chemical, Foam

Unsuitable extinguishing media

None

Specific hazards arising from the chemical

None in particular.

Explosion data

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas. Avoid contact with eyes and skin.

Use personal protective equipment as required.

Environmental precautions

Environmental precautions See section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Use personal protective equipment as required. Dam up. Cover liquid spill with sand, earth

or other non-combustible absorbent material. Take up mechanically, placing in appropriate

containers for disposal. Clean contaminated surface thoroughly.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid breathing

vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed in a dry and well-ventilated place. Keep from freezing.

Incompatible materials Strong oxidizing agents

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
SILICON CARBIDE	TWA: 10 mg/m ³ nonfibrous,	TWA: 15 mg/m³ total dust	TWA: 10 mg/m ³ total dust
409-21-2	inhalable particulate matter,	TWA: 5 mg/m³ respirable fraction	TWA: 5 mg/m ³ respirable dust
	particulate matter containing no	(vacated) TWA: 10 mg/m ³ total	
	asbestos and <1% crystalline silica	dust	
		(vacated) TWA: 5 mg/m³ respirable	
	respirable particulate matter,	fraction	
	particulate matter containing no		
	asbestos and <1% crystalline silica		
	TWA: 0.1 fiber/cm3 respirable		
	fibers, including whiskers, length >5		
	μm, aspect ratio >=3:1 as		
	determined by the membrane filter		
	method at 400-450X magnification		
	(4-mm objective), using		
	phase-contrast illumination.		
ETHYLENE GLYCOL	STEL: 50 ppm_vapor fraction	(vacated) Ceiling: 50 ppm	-
107-21-1	STEL: 10 mg/m³ inhalable	(vacated) Ceiling: 125 mg/m ³	
	particulate matter, aerosol only		
	TWA: 25 ppm_vapor fraction		

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

appropriate.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of

equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state Paste Liquid

Appearance Gray
Odor Slight

Odor threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pH No information available

Melting point / freezing point

Boiling point / boiling range
Flash point

No information available

> 100 °C / > 212 °F

> 95 °C / > 203 °F

Evaporation rate <1 Butyl acetate = 1

Flammability (solid, gas) No information available Flammability Limit in Air

Upper flammability limit:
Lower flammability limit:
No information available
No information available
No information available

Vapor density >1

Relative density 1.36

Water solubility Soluble in water

Solubility(ies) No information available Partition coefficient No information available **Autoignition temperature** No information available **Decomposition temperature** No information available Kinematic viscosity No information available No information available **Dynamic viscosity** No information available **Explosive properties Oxidizing properties** No information available

Other Information

Softening point No information available Molecular weight No information available

VOC Content (%) 14.83

DensityNo information availableBulk densityNo information availableSADT (self-accelerating)No information available

decomposition temperature)

10. STABILITY AND REACTIVITY

Air = 1

Reactivity

No information available

Chemical stability

Stable under normal conditions

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Excessive heat.

Incompatible materials

Strong oxidizing agents

Hazardous Decomposition Products

Carbon oxides

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation May cause irritation of respiratory tract.

Eye contact Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

Skin contact May cause skin irritation and/or dermatitis.

Ingestion Harmful if swallowed.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
ETHYLENE GLYCOL	= 4700 mg/kg (Rat)	= 9530 μL/kg (Rabbit) = 10600	-
107-21-1		mg/kg (Rat)	

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

SensitizationNo information available. **Germ cell mutagenicity**No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
SILICON CARBIDE	A2	Group 2A	-	X
409-21-2				

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Not classifiable as a human carcinogen Group 2A - Probably Carcinogenic to Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Target Organ Effects Central nervous system, Eyes, Respiratory system, Skin.

The following values are calculated based on chapter 3.1 of the GHS document ...

ATEmix (oral) 1938 mg/kg ATEmix (dermal) 41087 mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity

1.426 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

Chemical Name	Partition coefficient
ETHYLENE GLYCOL	-1.93
107-21-1	

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number Not applicable

14. TRANSPORT INFORMATION

DOT

Proper shipping name: Not regulated

ATA

Proper shipping name: Not regulated

<u>IMDG</u>

Proper shipping name: Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA Complies **DSL/NDSL** Complies **EINECS/ELINCS** Complies Not determined **ENCS IECSC** Complies **KECL** Complies **PICCS** Complies AICS Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

1.0

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
ETHYLENE GLYCOL	5000 lb	-	RQ 5000 lb final RQ
107-21-1			RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65	
ETHYLENE GLYCOL	Developmental	
107-21-1	<u>'</u>	

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
SILICON CARBIDE	X	X	X
409-21-2			
ETHYLENE GLYCOL	X	X	X
107-21-1			
TRIETHANOLAMINE	X	X	X
102-71-6			

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

D2B - Toxic materials

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 2 Flammability 1 Instability 0

HMIS Health hazards 2 Flammability 1 Physical hazards 0 Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date 07-May-2020

Disclaimer

Illinois Tool Works Inc. believes the information contained in this data sheet is accurate as of the date compiled. However, Illinois Tool Works Inc. makes no warranty, express or implied, as to the accuracy, reliability or completeness of the information. User is responsible for evaluating whether such information or this product is fit for a particular purpose and suitable for a particular use or application. The information in this data sheet may not be valid if this product is used in combination with other products or in processes for which it was not designed. Illinois Tool Works Inc. disclaims any liability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of this product. Ensure you have the most current version of this data sheet by contacting us or reviewing our web site.

End of Safety Data Sheet