CR@

SAFETY DATA SHEET

1. Identification

Product identifier Air Brake Anti-Freeze & Conditioner - 1 gal

Other means of identification

Product Code No. 05528 (Item# 1003820)

Recommended use Air brake anti-freeze

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name CRC Industries, Inc.

Address 885 Louis Dr.

Warminster, PA 18974 US

Telephone

 General Information
 215-674-4300

 Technical Assistance
 800-521-3168

 Customer Service
 800-272-4620

 24-Hour Emergency
 800-424-9300 (US)

(CHEMTREC)

Website www.crcindustries.com

2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 2Health hazardsAcute toxicity, oralCategory 3Acute toxicity, dermalCategory 3Acute toxicity, inhalationCategory 3

Reproductive toxicity

Specific target organ toxicity, single exposure Category 1 (central nervous system, eyes)

Category 1A

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Highly flammable liquid and vapor. Toxic if swallowed. Toxic in contact with skin. Toxic if inhaled.

May damage fertility or the unborn child. Causes damage to organs (central nervous system,

eyes).

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist/vapors. Use only outdoors or in a well-ventilated area. Maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection.

Material name: Air Brake Anti-Freeze & Conditioner - 1 gal
No. 05528 (Item# 1003820) Version #: 01 Issue date: 11-10-2021

Response If swallowed: Immediately call a poison center/doctor. Rinse mouth. If on skin (or hair): Take off

immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor. In case of fire:

Do not use water jet as an extinguisher, as this will spread the fire.

Storage Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Ingestion

Chemical name	Common name and synonyms	CAS number	%
methanol		67-56-1	90 - 100

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or

artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other

proper respiratory medical device. Call a poison center or doctor/physician.

Skin contact

Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical

advice/attention if you feel unwell. Get medical attention if irritation develops and persists. Wash

contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance.

Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other

proper respiratory medical device.

Most important symptoms/effects, acute and delayed

Narcosis. Headache. Dizziness. Nausea, vomiting. Behavioral changes. Decrease in motor functions. Direct contact with eyes may cause temporary irritation.

Indication of immediate

medical attention and special treatment needed

Methanol is metabolized to formic acid and formaldehyde. These metabolites can cause metabolic acidosis, visual disturbances and blindness. Since metabolism is required for these toxic symptoms, their onset may be delayed from 6 to 30 hours following ingestion. Ethanol competes for the same metabolic pathway and has been used to prevent methanol metabolism. Ethanol administration is indicated in symptomatic patients or at blood methanol concentrations above 20 µg/dl. Methanol is effectively removed by hemodialysis. Fomepizole (4-methylpyrazole) is an effective antagonist of alcohol dehydrogenase, and may be used as an antidote in the treatment of methanol poisoning.

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information

Take off immediately all contaminated clothing. IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Alcohol resistant foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Material name: Air Brake Anti-Freeze & Conditioner - 1 gal
No. 05528 (Item# 1003820) Version #: 01 Issue date: 11-10-2021

Specific hazards arising from the chemical

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire-fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

Highly flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. This product is miscible in water. Dike far ahead of spill for later disposal.

Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. Use non-sparking tools and explosion-proof equipment. Do not breathe mist/vapors. Do not taste or swallow. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Wash contaminated clothing before reuse. Observe good industrial hygiene practices. For product usage instructions, see the product label.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Eliminate sources of ignition. Avoid spark promoters. Store in a cool, dry place out of direct sunlight. Keep container tightly closed. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value
methanol (CAS 67-56-1)	PEL	260 mg/m3
		200 ppm

Material name: Air Brake Anti-Freeze & Conditioner - 1 gal
No. 05528 (Item# 1003820) Version #: 01 Issue date: 11-10-2021

US. ACGIH Threshold Limit Valu	es		
Components	Туре	Value	
methanol (CAS 67-56-1)	STEL	250 ppm	
	TWA	200 ppm	
US. NIOSH: Pocket Guide to Che	emical Hazards		
Components	Туре	Value	
methanol (CAS 67-56-1)	STEL	325 mg/m3	
		250 ppm	
	TWA	260 mg/m3	
		200 ppm	

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
methanol (CAS 67-56-1)	15 mg/l	Methanol	Urine	*

^{* -} For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

methanol (CAS 67-56-1)

Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

methanol (CAS 67-56-1) Skin designation applies.

US - Tennessee OELs: Skin designation

methanol (CAS 67-56-1) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

methanol (CAS 67-56-1) Danger of cutaneous absorption

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

methanol (CAS 67-56-1) Can be absorbed through the skin.

Appropriate engineering

controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear protective gloves such as: Nitrile. Rubber.Other Wear appropriate chemical resistant clothing.

Respiratory protection If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a

NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to

determine actual employee exposure levels.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid.
Form Liquid.
Color Colorless.

Odor Pungent. Alcoholic.
Odor threshold Not available.

No. 05528 (Item# 1003820) Version #: 01 Issue date: 11-10-2021 4

Not available. рH

Melting point/freezing point -144 °F (-97.8 °C) estimated Initial boiling point and boiling 147.2 °F (64 °C) estimated

range

Flash point 54.0 °F (12.2 °C) Setaflash

Fast. **Evaporation rate**

Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

2.6 % estimated

(%)

Flammability limit - upper

36.5 % estimated

(%)

144.6 hPa estimated Vapor pressure

Vapor density 1.1 (air = 1)0.79 Relative density

Solubility(ies)

Solubility (water) Completely soluble. Partition coefficient Not available.

(n-octanol/water)

851 °F (455 °C) estimated **Auto-ignition temperature**

Decomposition temperature Not available. Not available. Viscosity Percent volatile 99.9 % estimated

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Material is stable under normal conditions. **Chemical stability**

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Avoid heat, sparks, open flames and other ignition sources. Contact with incompatible materials. Conditions to avoid

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

Carbon oxides. Formaldehyde.

11. Toxicological information

Information on likely routes of exposure

Inhalation Toxic if inhaled. May cause damage to organs by inhalation.

Skin contact Toxic in contact with skin.

Eye contact Direct contact with eyes may cause temporary irritation.

Toxic if swallowed. Even small amounts (30-250 ml methanol) may be fatal. Symptoms are Ingestion

stomach ache, nausea, vomiting, dullness, visual disorder and blindness.

Narcosis. Headache. Dizziness. Nausea, vomiting. Behavioral changes. Decrease in motor

Symptoms related to the physical, chemical and

functions.

toxicological characteristics

Information on toxicological effects

Acute toxicity Toxic if inhaled. Toxic in contact with skin. Toxic if swallowed.

Product Test Results

Air Brake Anti-Freeze & Conditioner - 1 gal

Acute Dermal

ATE 300 mg/kg

Material name: Air Brake Anti-Freeze & Conditioner - 1 gal

Product Species Test Results

Inhalation Vapor

ATE 3 mg/l

Oral

ATE 100 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity May damage fertility or the unborn child.

Specific target organ toxicity -

single exposure

Causes damage to organs (central nervous system, eyes). Even small amounts (30-250 ml

methanol) may be fatal. Symptoms are stomach ache, nausea, vomiting, dullness, visual disorder

and blindness.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

EcotoxicityThe product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

methanol -0.77

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsThis material and its container must be disposed of as hazardous waste. Empty container can be

recycled. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazardous waste code D001: Waste Flammable material with a flash point <140 F

F003: Waste Non-halogenated Solvent - Spent Non-halogenated Solvent

US RCRA Hazardous Waste U List: Reference

methanol (CAS 67-56-1) U154

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN number UN1230

UN proper shipping name Methanol solution

Transport hazard class(es)

3 **Class** Subsidiary risk 3 Label(s) **Packing group** Ш

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions IB2, T7, TP2

Packaging exceptions 150 202 Packaging non bulk Packaging bulk 242

Other information

Passenger and cargo

aircraft

Forbidden

Allowed with restrictions. Cargo aircraft only

IATA

UN number UN1230

UN proper shipping name Methanol solution

Transport hazard class(es)

Class 3 6.1 Subsidiary risk Ш Packing group 3L **ERG Code**

Other information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Forbidden

Cargo aircraft only Allowed with restrictions.

IMDG

UN1230 **UN** number **METHANOL UN proper shipping name**

Transport hazard class(es)

Class 3 Subsidiary risk 6.1 Ш Packing group **Environmental hazards**

Marine pollutant No. F-E, S-D

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

DOT



No. 05528 (Item# 1003820) Version #: 01 Issue date: 11-10-2021



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

CERCLA Hazardous Substance List (40 CFR 302.4)

methanol (CAS 67-56-1)

CERCLA Hazardous Substances: Reportable quantity

methanol (CAS 67-56-1) 5000 LBS

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

methanol (CAS 67-56-1)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Contains component(s) regulated under the Safe Drinking Water Act.

(SDWA)

Food and Drug

Not regulated.

Administration (FDA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Classified hazard

Flammable (gases, aerosols, liquids, or solids)

categories

Acute toxicity (any route of exposure)

Reproductive toxicity

Specific target organ toxicity (single or repeated exposure)

Hazard not otherwise classified (HNOC)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
methanol	67-56-1	90 - 100	

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

methanol (CAS 67-56-1)

US. New Jersey Worker and Community Right-to-Know Act

methanol (CAS 67-56-1)

US. Massachusetts RTK - Substance List

methanol (CAS 67-56-1)

No. 05528 (Item# 1003820) Version #: 01 Issue date: 11-10-2021

US. Pennsylvania Worker and Community Right-to-Know Law

methanol (CAS 67-56-1)

US. Rhode Island RTK

methanol (CAS 67-56-1)

California Proposition 65



WARNING: Reproductive Harm - www.P65Warnings.ca.gov

California Proposition 65 - CRT: Listed date/Developmental toxin

methanol (CAS 67-56-1) Listed: March 16, 2012

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR

51.100(s))

100 %

Consumer products

(40 CFR 59, Subpt. C)

Not regulated

State

Not regulated Consumer products

VOC content (CA) 100 % VOC content (OTC) 100 %

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical	Yes

Substances (EINECS)

Europe European List of Notified Chemical Substances (ELINCS) No Inventory of Existing and New Chemical Substances (ENCS) Japan Yes Existing Chemicals List (ECL) Korea Yes New Zealand New Zealand Inventory Yes Philippines Philippine Inventory of Chemicals and Chemical Substances Yes

(PICCS)

Taiwan Taiwan Chemical Substance Inventory (TCSI) Yes United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

16. Other information, including date of preparation or last revision

Issue date 11-10-2021 Danica Fulmer Prepared by

Version # 01

CRC # 620B/1002661 **Further information**

Disclaimer The information contained in this document applies to this specific material as supplied. It may not

> be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety

professional, or CRC Industries, Inc..

Revision information This document has undergone significant changes and should be reviewed in its entirety.

No. 05528 (Item# 1003820) Version #: 01 Issue date: 11-10-2021

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).