

SAFETY DATA SHEET

1. Identification

Product identifier NAPA® Clean-R-Carb™ Carburetor Cleaner - 1 lb

Other means of identification

No. 091343 (Item# 1007989) **Product Code**

Recommended use Carburetor cleaner Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

CRC Industries. Inc. Company name 885 Louis Dr. **Address**

Warminster, PA 18974 US

Telephone

215-674-4300 **General Information Technical Assistance** 800-521-3168 **Customer Service** 800-272-4620 24-Hour Emergency 800-424-9300 (US)

(CHEMTREC)

Website www.crcindustries.com

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1

> Gases under pressure Compressed gas

Health hazards Acute toxicity, oral Category 3

> Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2A Reproductive toxicity Category 1A

Specific target organ toxicity, single exposure Category 1 (central nervous system, eyes)

Specific target organ toxicity, single exposure Category 3 narcotic effects

Specific target organ toxicity, repeated

exposure

Category 1

Hazardous to the aquatic environment, acute **Environmental hazards**

Aspiration hazard

Category 1 Category 2

hazard

Hazardous to the aquatic environment,

Category 3

long-term hazard

OSHA defined hazards Not classified.

Label elements



Signal word

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Toxic if **Hazard statement**

swallowed. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. May damage fertility or the unborn child. Causes damage to organs (central nervous system, eyes). Causes damage to organs through prolonged or repeated exposure. Toxic to aquatic life. Harmful to aquatic life with long lasting

effects.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe mist/vapors. Extinguish all flames, pilot lights, and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. Avoid release to the environment.

Response

If swallowed: Immediately call a poison center/doctor. Rinse mouth. Do NOT induce vomiting. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or concerned: Get medical advice/attention.

Storage

Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst.

Static accumulating flammable liquid can become electrostatically charged even in bonded and

Dispose of contents/container in accordance with local/regional/national regulations.

Disposal

Hazard(s) not otherwise classified (HNOC)

grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion. None.

Supplemental information

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
methanol		67-56-1	30 - 40
toluene		108-88-3	30 - 40
acetone		67-64-1	20 - 30
carbon dioxide		124-38-9	5 - 10

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.

Skin contact

Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Most important symptoms/effects, acute and delayed

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Narcosis. Headache. Nausea, vomiting. Behavioral changes. Decrease in motor functions. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information

IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Alcohol resistant foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Material name: NAPA® Clean-R-Carb™ Carburetor Cleaner - 1 lb

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may rupture when exposed to heat or flame. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire-fighting equipment/instructions

General fire hazards

In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up.

Extremely flammable aerosol. Contents under pressure. Pressurized container may rupture when exposed to heat or flame.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Remove all possible sources of ignition in the surrounding area. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water. Prevent product from entering drains. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Do not breathe mist/vapors. Do not taste or swallow. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. For product usage instructions, see the product label.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Avoid spark promoters. These alone may be insufficient to remove static electricity. Store in tightly closed container. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limi Components	Тур			lue
acetone (CAS 67-64-1)	PE	_	24	00 mg/m3
			10	00 ppm
carbon dioxide (CAS 124-38-9)	PE	_	9000 mg/m3	
			50	00 ppm
methanol (CAS 67-56-1)	PE	_	26	0 mg/m3
			20	0 ppm
US. OSHA Table Z-2 (29				
Components	Тур	De .	Va	llue
toluene (CAS 108-88-3)	Cei	ling	30	0 ppm
	TW	Α	20	0 ppm
US. ACGIH Threshold Lir	nit Values			
Components	Тур	oe .	Va	lue
acetone (CAS 67-64-1)	STI	ΞL	50	0 ppm
	TW	Α	25	0 ppm
carbon dioxide (CAS 124-38-9)	STI	ΞL	30	000 ppm
	TW	A	50	00 ppm
methanol (CAS 67-56-1)	STI	ΞL	25	0 ppm
	TW	A	20	0 ppm
toluene (CAS 108-88-3)	TW	A	20	ppm
US. NIOSH: Pocket Guide			V -	L
Components	Ту			llue
acetone (CAS 67-64-1)	TW	A		0 mg/m3
				0 ppm
carbon dioxide (CAS 124-38-9)	STI	ΞL	54000 mg/m3	
	T\A.	Λ		000 ppm
	TW	A		00 mg/m3
mothanal (CAS 67 FG 1)	STI	-,		00 ppm 5 mg/m3
methanol (CAS 67-56-1)	311	EL		· ·
	TW	Λ		0 ppm
	IVV	A		0 mg/m3
taluana (CAC 100 00 2)	CT.	-,		0 ppm
toluene (CAS 108-88-3)	STI	EL		0 mg/m3
	T\A:	Λ		0 ppm
	TW	A		5 mg/m3
			10	0 ppm
ogical limit values				
ACGIH Biological Exposi Components	ure Indices Value	Determinant	Specimen	Sampling Time
acetone (CAS 67-64-1)	25 mg/l	Acetone	Urine	*

Biol

acetone (CAS 67-64-1) 25 mg/l Acetone Urine methanol (CAS 67-56-1) 15 mg/l Methanol Urine toluene (CAS 108-88-3) 0.3 mg/g o-Cresol, with Creatinine in hydrolysis urine 0.03 mg/l Toluene Urine

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time	
	0.02 mg/l	Toluene	Blood	*	

^{* -} For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

methanol (CAS 67-56-1) Can be absorbed through the skin. toluene (CAS 108-88-3) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

methanol (CAS 67-56-1) Skin designation applies. toluene (CAS 108-88-3) Skin designation applies.

US - Tennessee OELs: Skin designation

methanol (CAS 67-56-1) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

methanol (CAS 67-56-1) Danger of cutaneous absorption

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

methanol (CAS 67-56-1) Can be absorbed through the skin.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear protective gloves such as: Nitrile. Neoprene. Polyvinyl alcohol (PVA).

Other Wear appropriate chemical resistant clothing.

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a Respiratory protection

NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to

determine actual employee exposure levels.

Wear appropriate thermal protective clothing, when necessary. Thermal hazards

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Liquid. Physical state **Form** Aerosol. Color Colorless. Solvent. Odor **Odor threshold** Not available. Not available.

-144 °F (-97.8 °C) estimated Melting point/freezing point Initial boiling point and boiling 132.9 °F (56.1 °C) estimated

range

Flash point 0 °F (-17.8 °C)

Evaporation rate Fast.

Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

1 % estimated

(%)

Flammability limit - upper

(%)

36 % estimated

4380 hPa estimated Vapor pressure

Vapor density > 1 (air = 1) Relative density 0.87 estimated

Solubility(ies)

Slightly soluble. Solubility (water) Not available. Partition coefficient

(n-octanol/water)

725 °F (385 °C) estimated **Auto-ignition temperature**

Decomposition temperature Not available. **Viscosity** Not available. 93.4 % estimated Percent volatile

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Heat, flames and sparks. Contact with incompatible materials.

Incompatible materials Acids. Strong oxidizing agents. Aluminum.

Hazardous decomposition

products

Carbon oxides. Hydrocarbon fumes and smoke. Aldehydes. Formaldehyde.

11. Toxicological information

Information on likely routes of exposure

May cause damage to organs by inhalation. May cause drowsiness and dizziness. Headache. Inhalation

Nausea, vomiting. Prolonged inhalation may be harmful.

Skin contact Causes skin irritation.

Eve contact Causes serious eve irritation.

Toxic if swallowed. Droplets of the product aspirated into the lungs through ingestion or vomiting Ingestion

may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Narcosis, Headache, Nausea, vomiting, Behavioral changes, Decrease in motor functions, Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin

irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Species Test Results Components acetone (CAS 67-64-1) **Acute**

Dermal

Rabbit LD50 20000 mg/kg

Oral

LD50 Rat 5800 mg/kg

Skin corrosion/irritation Causes skin irritation.

Causes serious eye irritation. Serious eye damage/eye

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Not classifiable as to carcinogenicity to humans. Carcinogenicity

Material name: NAPA® Clean-R-Carb™ Carburetor Cleaner - 1 lb

IARC Monographs. Overall Evaluation of Carcinogenicity

toluene (CAS 108-88-3) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity May damage fertility or the unborn child.

Specific target organ toxicity -

Causes damage to organs (central nervous system, eyes). May cause drowsiness and dizziness.

single exposure

Specific target organ toxicity -

repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful. Causes damage to organs through prolonged or repeated

exposure.

12. Ecological information

Ecotoxicity Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Components **Species Test Results** toluene (CAS 108-88-3) Acute Other EC50 Pseudokirchnerella subcapitata 433 mg/l, 96 hours 12.5 mg/l, 72 hours Aquatic Acute Fish LC50 Coho salmon, silver salmon 5.5 mg/l, 96 hours (Oncorhynchus kisutch)

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

acetone -0.24
methanol -0.77
toluene 2.73

Bioconcentration factor (BCF)
toluene 90

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions This material and its container must be disposed of as hazardous waste. Collect and reclaim or

dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all applicable regulations.

Hazardous waste code D001: Waste Flammable material with a flash point <140 F

F003: Waste Non-halogenated Solvent - Spent Non-halogenated Solvent F005: Waste Non-halogenated Solvent - Spent Non-halogenated Solvent

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN number UN1950

UN proper shipping name Aerosols, flammable, Limited Quantity

Transport hazard class(es)

Class 2.1 Subsidiary risk 6.1(PGIII)

Material name: NAPA® Clean-R-Carb™ Carburetor Cleaner - 1 lb No. 091343 (Item# 1007989) Version #: 01 Issue date: 04-21-2020 **Packing group** Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions N82 306 Packaging exceptions Packaging non bulk None Packaging bulk None

Other information

Passenger and cargo

Allowed with restrictions.

aircraft Cargo aircraft only

Allowed with restrictions.

IATA

UN1950 **UN** number

UN proper shipping name

Aerosols, flammable, containing substances in Division 6.1, Packing Group III

Transport hazard class(es)

Class 2.1 Subsidiary risk 6.1(PGIII) Not applicable. Packing group

ERG Code 10P

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

IMDG

UN1950 **UN** number **AEROSOLS UN** proper shipping name

Transport hazard class(es)

Class 2.1 Subsidiary risk 6.1(PGIII) Not applicable. Packing group


Environmental hazards

Marine pollutant No.

Not available. **EmS**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

DOT



IATA; IMDG



15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

methanol (CAS 67-56-1) toluene (CAS 108-88-3)

CERCLA Hazardous Substance List (40 CFR 302.4)

acetone (CAS 67-64-1) methanol (CAS 67-56-1) toluene (CAS 108-88-3)

CERCLA Hazardous Substances: Reportable quantity

acetone (CAS 67-64-1) 5000 LBS methanol (CAS 67-56-1) 5000 LBS toluene (CAS 108-88-3) 1000 LBS

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

methanol (CAS 67-56-1) toluene (CAS 108-88-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and **Chemical Code Number**

acetone (CAS 67-64-1) 6532 toluene (CAS 108-88-3) 6594

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

acetone (CAS 67-64-1) 35 %WV toluene (CAS 108-88-3) 35 %WV

DEA Exempt Chemical Mixtures Code Number

acetone (CAS 67-64-1) 6532 toluene (CAS 108-88-3) 594

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

acetone (CAS 67-64-1) Low priority

Food and Drug Not regulated.

Administration (FDA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Classified hazard Flammable (gases, aerosols, liquids, or solids)

Gas under pressure categories

Acute toxicity (any route of exposure) Skin corrosion or irritation Serious eye damage or eye irritation

Reproductive toxicity

Specific target organ toxicity (single or repeated exposure)

Aspiration hazard

Hazard not otherwise classified (HNOC)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
methanol	67-56-1	30 - 40	
toluene	108-88-3	30 - 40	

US state regulations

US. New Jersey Worker and Community Right-to-Know Act

acetone (CAS 67-64-1) carbon dioxide (CAS 124-38-9) methanol (CAS 67-56-1) toluene (CAS 108-88-3)

US. Massachusetts RTK - Substance List

acetone (CAS 67-64-1) carbon dioxide (CAS 124-38-9) methanol (CAS 67-56-1) toluene (CAS 108-88-3)

US. Pennsylvania Worker and Community Right-to-Know Law

acetone (CAS 67-64-1) carbon dioxide (CAS 124-38-9) methanol (CAS 67-56-1) toluene (CAS 108-88-3)

US. Rhode Island RTK

acetone (CAS 67-64-1) carbon dioxide (CAS 124-38-9) methanol (CAS 67-56-1) toluene (CAS 108-88-3)

California Proposition 65



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

California Proposition 65 - CRT: Listed date/Carcinogenic substance

acetaldehyde (CAS 75-07-0) Listed: April 1, 1988 benzene (CAS 71-43-2) Listed: February 27, 1987 cumene (CAS 98-82-8) Listed: April 6, 2010 ethylbenzene (CAS 100-41-4) Listed: June 11, 2004 naphthalene (CAS 91-20-3) Listed: April 19, 2002

California Proposition 65 - CRT: Listed date/Developmental toxin

benzene (CAS 71-43-2) Listed: December 26, 1997 methanol (CAS 67-56-1) Listed: March 16, 2012 toluene (CAS 108-88-3) Listed: January 1, 1991

California Proposition 65 - CRT: Listed date/Male reproductive toxin

benzene (CAS 71-43-2) Listed: December 26, 1997

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

acetone (CAS 67-64-1) methanol (CAS 67-56-1) toluene (CAS 108-88-3)

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR 70.1 %

51.100(s))

Compliant **Consumer products**

(40 CFR 59, Subpt. C)

State

This product is regulated as a Carburetor Cleaner. This product is not compliant to be sold for use **Consumer products**

in California, Colorado, Connecticut, Delaware, the District of Columbia, Illinois, Indiana, Maine, Maryland, Massachusetts, Michigan, New Hampshire, New Jersey, New York, Ohio, Pennsylvania, Rhode Island and parts of Utah and Virginia. This product is compliant in all other states.

70.1 % VOC content (CA) VOC content (OTC) 70.1 %

International Inventories

Country(s) or region **Inventory name** On inventory (yes/no)* Australia Australian Inventory of Chemical Substances (AICS) Yes Domestic Substances List (DSL) Canada Yes Country(s) or regionInventory nameOn inventory (yes/no)*CanadaNon-Domestic Substances List (NDSL)NoChinaInventory of Existing Chemical Substances in China (IECSC)YesEuropeEuropean Inventory of Existing Commercial ChemicalYes

Substances (EINECS)

EuropeEuropean List of Notified Chemical Substances (ELINCS)NoJapanInventory of Existing and New Chemical Substances (ENCS)YesKoreaExisting Chemicals List (ECL)YesNew ZealandNew Zealand InventoryYes

Philippine Inventory of Chemicals and Chemical Substances

(PICCS)

Taiwan Chemical Substance Inventory (TCSI)

United States & Puerto Rico

Toxic Substances Control Act (TSCA) Inventory

Yes

16. Other information, including date of preparation or last revision

Issue date04-21-2020Prepared byDustin Kern

Version # 01

Philippines

Further information CRC # 581F/1002603

Disclaimer The information contained in this document applies to this specific material as supplied. It may not

be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety

professional, or CRC Industries, Inc..

Revision information Product and Company Identification: Product and Company Identification

Composition / Information on Ingredients: Component Summary

Fire-fighting measures: Specific methods

Handling and storage: Precautions for safe handling Physical & Chemical Properties: Multiple Properties Disposal considerations: Disposal instructions

Transport Information: Material Transportation Information

Regulatory information: Consumer products

GHS: Qualifiers

Material name: NAPA® Clean-R-Carb™ Carburetor Cleaner - 1 lb No. 091343 (Item# 1007989) Version #: 01 Issue date: 04-21-2020

Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).