

SAFETY DATA SHEET

1. Identification

Product identifier Constant Velocity (CV) Joint Grease - 4 oz

Other means of identification

Product Code No. SL3174 (Item# 1007886)

Recommended use CV joint grease Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name CRC Industries, Inc.

Address 885 Louis Dr.

Warminster, PA 18974 US

Telephone

 General Information
 215-674-4300

 Technical Assistance
 800-521-3168

 Customer Service
 800-272-4620

 24-Hour Emergency
 800-424-9300 (US)

(CHEMTREC)

Website www.crcindustries.com

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Serious eye damage/eye irritation Category 2A

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Causes serious eye irritation.

Precautionary statement

Prevention Wash thoroughly after handling. Wear eye protection/face protection. Use only outdoors or in a

well-ventilated area. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label,

increase ventilation or leave the area.

Response If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Storage Store away from incompatible materials.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
distillates (petroleum),		64742-65-0	70 - 80
solvent-dewaxed heavy para	affinic		

Material name: Constant Velocity (CV) Joint Grease - 4 oz

No. SL3174 (Item# 1007886) Version #: 02 Revision date: 06-15-2021 Issue date: 12-18-2019

Chemical name	Common name and synonyms	CAS number	%
distillates (petroleum), hydrotreated heavy naphthenic	İ	64742-52-5	5 - 10
calcium carbonate		1317-65-3	3 - 5
molybdenum disulphide		1317-33-5	3 - 5
Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts		68457-79-4	1 - 3
potassium orthoborate		20786-60-1	0.475

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

Rinse mouth. Get medical attention if symptoms occur. Ingestion

vision.

Most important

symptoms/effects, acute and

delayed Indication of immediate

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

medical attention and special

treatment needed

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Use fire-extinguishing media appropriate for surrounding materials.

Not established.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire-fighting equipment/instructions

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

The product is immiscible with water and will spread on the water surface.

Small Spills: Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Avoid discharge into drains, water courses or onto the ground. **Environmental precautions**

7. Handling and storage

Precautions for safe handling

Avoid contact with eyes. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. For product usage instructions, see the product label.

Conditions for safe storage, including any incompatibilities Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

Material name: Constant Velocity (CV) Joint Grease - 4 oz

SDS US No. SL3174 (Item# 1007886) Version #: 02 Revision date: 06-15-2021 Issue date: 12-18-2019

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Components	Type	Value	Form
calcium carbonate (CAS 1317-65-3)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
distillates (petroleum), nydrotreated heavy naphthenic (CAS 64742-52-5)	PEL	5 mg/m3	Mist.
		2000 mg/m3	
		500 ppm	
distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	PEL	5 mg/m3	Mist.
paramino (6/16/6/17/12/06/6/		2000 mg/m3	
		500 ppm	
molybdenum disulphide (CAS 1317-33-5)	PEL	15 mg/m3	Total dust.
US. ACGIH Threshold Limit Values			-
Components	Туре	Value	Form
distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.
distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	TWA	5 mg/m3	Inhalable fraction.
molybdenum disulphide (CAS 1317-33-5)	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Inhalable fraction.
US. NIOSH: Pocket Guide to Chem			_
Components	Туре	Value	Form
calcium carbonate (CAS 1317-65-3)	TWA	5 mg/m3	Respirable.
,		10 mg/m3	Total
distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	Ceiling	1800 mg/m3	
	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	Ceiling	1800 mg/m3	
•	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
US. California Code of Regulations Components	s, Title 8, Section 5155. Airborne C Type	ontaminants Value	Form
molybdenum disulphide	PEL	3 mg/m3	Respirable fraction.
(CAS 1317-33-5)		10 mg/m3	Total dust.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Wear protective gloves such as: Neoprene. Nitrile. Hand protection

Other Wear suitable protective clothing.

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a Respiratory protection

NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to

determine actual employee exposure levels.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Solid. **Form** Grease. Color Dark grey. Mild petroleum. Odor **Odor threshold** Not available. pН Not available. Not available. Melting point/freezing point

Initial boiling point and boiling

680 °F (360 °C) estimated

range

455.0 °F (235.0 °C) Flash point

Evaporation rate Not available. Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower Not available.

(%)

Flammability limit - upper Not available.

(%)

0.00001 hPa estimated Vapor pressure

Vapor density Not available.

1.09 Relative density

Solubility(ies)

Not miscible. Solubility (water) Partition coefficient Not available.

(n-octanol/water)

Not available. **Auto-ignition temperature Decomposition temperature** Not available.

68 cSt (104 °F (40 °C)) **Viscosity**

Percent volatile Not available.

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Material name: Constant Velocity (CV) Joint Grease - 4 oz

No. SL3174 (Item# 1007886) Version #: 02 Revision date: 06-15-2021 Issue date: 12-18-2019

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid

Contact with incompatible materials.

Incompatible materials

Strong oxidizing agents.

Hazardous decomposition products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Prolonged inhalation may be harmful. Inhalation

Based on available data, the classification criteria are not met. Skin contact

Causes serious eye irritation. Eye contact

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

Information on toxicological effects

Acute toxicity Not known.

Product Test Results Species

Constant Velocity (CV) Joint Grease - 4 oz

Acute

Dermal

LD50 Rabbit 89888 mg/kg

Inhalation

LC50 Rat 367 mg/l, 4 hours

Oral

LD50 Rat 23938 mg/kg Components **Species Test Results**

distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)

Acute

Dermal

LD50 Rabbit > 2000 mg/kg

Oral

LD50 Rat > 5000 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

This product is not expected to cause skin sensitization. Skin sensitization

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

distillates (petroleum), solvent-dewaxed heavy paraffinic 3 Not classifiable as to carcinogenicity to humans.

(CAS 64742-65-0)

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -Not classified.

single exposure

Material name: Constant Velocity (CV) Joint Grease - 4 oz

No. SL3174 (Item# 1007886) Version #: 02 Revision date: 06-15-2021 Issue date: 12-18-2019

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard

Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

No data available. No data available.

Mobility in soil
Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions

This product is not a RCRA hazardous waste (See 40 CFR Part 261.20 – 261.33). Empty containers may be recycled. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazardous waste code

Not regulated.

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed

CERCLA Hazardous Substance List (40 CFR 302.4)

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts (CAS 68457-79-4)

CERCLA Hazardous Substances: Reportable quantity

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Contains component(s) regulated under the Safe Drinking Water Act.

Food and Drug Not regulated.

Administration (FDA)

Material name: Constant Velocity (CV) Joint Grease - 4 oz

No. SL3174 (Item# 1007886) Version #: 02 Revision date: 06-15-2021 Issue date: 12-18-2019

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Classified hazard

Serious eye damage or eye irritation

categories

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
Phosphorodithioic acid, mixed O,O-bis(iso-Bu and	68457-79-4	1 - 3	
pentyl) esters, zinc salts			

US state regulations

US. New Jersey Worker and Community Right-to-Know Act

calcium carbonate (CAS 1317-65-3)

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts (CAS 68457-79-4)

US. Massachusetts RTK - Substance List

calcium carbonate (CAS 1317-65-3) molybdenum disulphide (CAS 1317-33-5)

US. Pennsylvania Worker and Community Right-to-Know Law

calcium carbonate (CAS 1317-65-3)

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts (CAS 68457-79-4)

US. Rhode Island RTK

calcium carbonate (CAS 1317-65-3)

distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR 92.4 %

51.100(s))

Consumer products (40 CFR 59, Subpt. C)

Not regulated

State

Consumer products Not regulated

VOC content (CA) 0 % VOC content (OTC) 0 %

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes

Country(s) or region Inventory name On inventory (yes/no)*

Philippines Philippine Inventory of Chemicals and Chemical Substances

(PICCS)

Taiwan Chemical Substance Inventory (TCSI)

United States & Puerto Rico

Toxic Substances Control Act (TSCA) Inventory

Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information, including date of preparation or last revision

Issue date12-18-2019Revision date06-15-2021Prepared byAllison Yoon

Version # 02

Disclaimer The information contained in this document applies to this specific material as supplied. It may not

be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety

professional, or CRC Industries, Inc..

Revision information This document has undergone significant changes and should be reviewed in its entirety.

Material Hame. Constant velocity (CV) Joint Grease - 4 02

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).