

# SAFETY DATA SHEET

1 of 7

## Full Timer's Choice Rubber Seal Conditioner

### Section 1- Chemical Product and Company Identification

**Product Name:** Full Timer's Choice Rubber Seal Conditioner

**Supplier:** Camco Manufacturing, Inc.  
121 Landmark Drive  
Greensboro, NC 27409  
1-800-334-2004

**Product Use:** Cleaner

**Product Code:** 41135

**Date of Preparation/Revision:** July 1, 2013

**In case of Emergency:** 1-800-535-5053

### Section 2- Hazards identification

**Physical State:** Aerosol Liquid. [LIQUEFIED COMPRESS GAS WITH YELLOW LIQUID ALIPHATIC ODOR.]

**Emergency overview:** **DANGER!**  
CONTENTS UNDER PRESSURE.



Compressed Gas

Danger keep away from heat, sparks and flame. Do not puncture or incinerate container. Use only with adequate ventilation. Keep container closed. Contact with rapidly expanding gases can cause frostbite. Irritant to Skin, eyes, respiratory tract.

**Target organs:** May cause damage to the following organs: central nervous system (CNS).

**Routes of entry:** Inhalation

#### Potential acute health effects

**Eyes:** Contact with rapidly expanding gas may cause burns or frostbite. Causes irritation, redness, and pain.

**Skin:** Contact with rapidly expanding gas may cause burns or frostbite. Brief contact is not irritating. Prolonged skin contact may cause irritation to skin.

**Inhalation:** Acts as a simple asphyxiant. Causes irritation to the respiratory tract.

**Ingestion:** Ingestion is not a normal route of exposure for gases. May cause irritation to the gastrointestinal tract. Ingestion may cause nausea, vomiting, diarrhea, headache, depending on the amount ingested. Small amounts unlikely to cause irritation.

#### **Potential Chronic**

**Health Effects:** CARCINOGENIC EFFECTS: Not available.  
MUTAGENIC EFFECTS: Not available.  
TERATOGENIC EFFECTS: Not available.

#### **Medical conditions aggravated by overexposure:**

Pre-existing disorders involving any target organs mentioned in this SDS as being at risk may be aggravated by over-exposure to this product.

# SAFETY DATA SHEET

2 of 7

## Full Timer's Choice Rubber Seal Conditioner

**HMIS Ratings: Health: 2 Fire: 1 Reactivity: 0**

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe \* = Chronic hazard

See toxicological information (section 11)

### Section 3 - Composition, Information on Ingredients

<u>Name</u>	<u>CAS Number</u>	<u>% Weight</u>	<u>Exposure limits</u>
Propane / N-Butane	68476-86-8	5 - 10	<b>ACGIH TLV (United States, 2/2010)</b> TWA: 1000 ppm 8 hour(s) <b>NIOSH REL (United States, 6/2009)</b> TWA: 1900 mg/m <sup>3</sup> 10 hour(s) TWA: 800 ppm 10 hour(s) <b>OSHA PEL 1989 (United States, 3/1989)</b> TWA: 1900 mg/m <sup>3</sup> 8 hour(s) TWA: 800 ppm 8 hour(s)
Ethoxylated Nonylphenol	9016-45-9	1 - 5	
Silicone Emulsion	63148-62-9	10 - 20	

### Section 4 - First Aid Measures

- Eye contact:** Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.
- Skin contact:** In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.
- Frostbite:** Try to warm up the frozen tissues and seek medical attention.
- Inhalation:** Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.
- Ingestion:** Do not induce vomiting. Rinse mouth and seek immediate medical attention.

### Section 5 - Fire-Fighting Measures

- Flammability of the Product:** N/A
- Auto-ignition Temperature:** N/A
- Flash Point:** N/A
- Flammable Limits:** Lower: 1.6% Upper: 8.5%
- Products of Combustion:** Decomposition products may include the following materials:  
Carbon Dioxide and Carbon Monoxide
- Fire Hazards in the Presence of Various Substances:** Extremely flammable in the presence of the following materials or conditions: open flames, sparks and static discharge and oxidizing materials.
- Fire-Fighting Media and Instructions:** In case of fire, dry chemical, alcohol foam, alcohol-resistant foam, carbon dioxide and water for large fires. Water spray may be used to keep fire

# SAFETY DATA SHEET

3 of 7

## Full Timer's Choice Rubber Seal Conditioner

exposed containers cool. Cool containers with flooding quantities of water until well after fire is out.

**Special Fire Fighting Procedures:** Use water spray to cool fire exposed containers. Containers can build up pressure if exposed to heat and/or fire. It is always recommended to use SCBA when fighting fires.

**Unusual Fire and Explosion Hazards:** Contents under pressure. Exposure to temperatures above 120 F may cause bursting.

**Hazardous Decomposition Products:** Oxides of Carbon

### Special Protective

**Equipment for Fire-Fighters:** Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

**NFPA Ratings: Health: 1 Fire: 1 Reactivity: 0 Other: none**

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

### Section 6 - Accidental release measures

**Personal Precautions:** Wear recommended protective equipment. mop up, or absorb with an inert dry material and place in an appropriate waste disposal container. Wash area with suitable detergent and thour. Dispose of according to local, state, and federal requirements.

**Environmental Precautions:** Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

**Methods for Cleaning Up:** Immediately contact emergency personnel. Note: see section 1 for emergency contact information and section 13 for waste disposal.

### Section 7- Handling and Storage

**Handling:** Use only with adequate ventilation.  
Store in cool, dry, ventilated area. Exposure to temperatures above 120 F may cause bursting. Protect cylinders from physical damage; do not drag, roll, slide, or drop.

**Storage:** Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame). Segregate from oxidizing materials. Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Cylinder temperatures should not exceed 49 °C (120 °F).

### Section 8 - Exposure Controls / Personal Protection

**Engineering controls:** Use only with adequate ventilation.

#### Personal Protection

**Eyes:** Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.

# SAFETY DATA SHEET

4 of 7

## Full Timer's Choice Rubber Seal Conditioner

**Skin:** Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory:** Use only with adequate ventilation.

**Personal protection in case of a large spill:** Self-contained breathing apparatus (SCBA) should be used to avoid inhalation of the product.

**Product name:**

Propane / Butane

**ACGIH TLV (United States, 2/2010)**

TWA: 1000 ppm 8 hour(s)

**NIOSH REL (United States, 6/2009)**

TWA: 1900 mg/m<sup>3</sup> 10 hour(s)

TWA: 800 ppm 10 hour(s)

**OSHA PEL 1989 (United States, 3/1989)**

TWA: 1900 mg/m<sup>3</sup> 8 hour(s)

TWA: 800 ppm 8 hour(s)

Consult local authorities for acceptable exposure limits.

### **Section 9 - Physical and Chemical Properties**

**Appearance:** Slightly yellow Liquid  
**Odor:** Mild aliphatic  
**Physical State:** Liquid, Spray  
**pH: (@59° F / 15° C)** Not Determined  
**Vapor pressure:** < 17 mmHg @ 75°F (23°C)  
**Vapor density:** > 1 @ 75°F (23°C)  
**Boiling Point:** >212°F (>100° C)  
**Melting Point:** Not Determined  
**Solubility:** 78.1%  
**Specific Gravity: (@70° F / 21° C)** 1.000  
**Evaporation Rate:** < 0.8 @ 75°F (23°C)  
**Percent Volatile:** 6.0% by weight

**Physical Properties: Additional Information**

No additional information available

### **Section 10 - Stability and Reactivity**

**Stability and Reactivity:** The product is stable.  
**Conditions to Avoid (Stability):** Incompatible materials, excess heat.  
**Incompatibility with various Substances:** Strong oxidizing, acids, and reducing agents.  
**Hazardous Decomposition Products:** Oxides of Carbon  
**Hazardous polymerization:** Under normal conditions of storage and use, hazardous polymerization will not occur.

# SAFETY DATA SHEET

5 of 7

## Full Timer's Choice Rubber Seal Conditioner

### Section 11 - Toxicological Information

#### Toxicity Data

Product/Ingredient Name	Result	Species	Dose	Exposure
Butane	LC50 Inhalation	Rat	1.15 mg/L	4 hours
	LD50 Oral	Rat	16,000 mg/kg	
	LD50 Skin	Rabbit	4,490 mg/kg	

**Other toxic effects on humans** No specific information is available in our database regarding the other toxic effects of this material to humans.

#### Specific effects

**Carcinogenic Effects:** No known significant effects or critical hazards.

**Mutagenic Effects:** No known significant effects or critical hazards.

**Reproduction Toxicity:** No known significant effects or critical hazards.

### Section 12 - Ecological Information

**Aquatic Ecotoxicity:** Not available.

**Products of degradation:** Products of degradation: carbon oxides (CO, CO<sub>2</sub>) and water.

**Environmental fate:** Not available.

**Environmental hazards:** No known significant effects or critical hazards.

**Toxicity to the environment:** Not available.

### Section 13 - Disposal Considerations

Comply with federal, state, or local regulations for disposal. Landfill solids at permitted sites. Burn concentrated liquids, diluting with clean, low viscosity fuel. Avoid flameouts and assure that emissions comply with all applicable standards/regulations. Dilute aqueous waste may biodegrade. Assure effluent complies with applicable regulations.

### Section 14 - Transport information

Domestic Ground within the Continental US under 49CFR100-185

Regulatory Information	UN Number	Proper Shipping Name	Class	Packing Group
DOT Classification	UN1950	Aerosol	2.2	

Non-flammable aerosol not over 1 liter

IMDG

UN1057

**Refer to Current IMDG regulations for full shipping description requirements**

IATA

***This material is not prepared or packaged for air transportation***

***International shipping requirements must be determined by the party offering the material for transportation***

# SAFETY DATA SHEET

6 of 7

## Full Timer's Choice Rubber Seal Conditioner

### Section 15 - Regulatory Information

#### U.S. Federal regulations

**United States inventory (TSCA 8b):** This material is listed or exempted.  
**SARA 302/304/311/312 extremely hazardous substances:** No products were found.  
**SARA 302/304 emergency planning and notification:** No products were found.  
**SARA 302/304/311/312 hazardous chemicals:** None  
**SARA 311/312 MSDS distribution - chemical inventory - hazard identification:** None  
**Clean Water Act (CWA) 307:** No products were found.  
**Clean Water Act (CWA) 311:** No products were found.  
**Clean Air Act (CAA) 112 accidental release prevention:** None  
**Clean Air Act (CAA) 112 regulated flammable substances:** None  
**Clean Air Act (CAA) 112 regulated toxic substances:** No products were found.

#### State regulations

**Connecticut Carcinogen Reporting:** This material is not listed.  
**Connecticut Hazardous Material Survey:** This material is not listed.  
**Florida substances:** This material is not listed.  
**Illinois Chemical Safety Act:** This material is not listed.  
**Illinois Toxic Substances Disclosure to Employee Act:** This material is not listed.  
**Louisiana Reporting:** This material is not listed.  
**Louisiana Spill:** This material is not listed.  
**Massachusetts Spill:** This material is not listed.  
**Massachusetts Substances:** This material is listed.  
**Michigan Critical Material:** This material is not listed.  
**Minnesota Hazardous Substances:** This material is not listed.  
**New Jersey Hazardous Substances:** Polydimethylsiloxane – 63148-62-9  
**New Jersey Spill:** This material is not listed.  
**New Jersey Toxic Catastrophe Prevention Act:** This material is not listed.  
**New York Acutely Hazardous Substances:** This material is not listed.  
**New York Toxic Chemical Release Reporting:** This material is not listed.  
**Pennsylvania RTK Hazardous Substances:** Polydimethylsiloxane – 63148-62-9  
**Rhode Island Hazardous Substances:** This material is not listed  
**California Prop 65 Warning:** This material is not listed

### Section 16 - Other information

<b>NFPA CODES:</b> Health	1
Flammability	1
Reactivity	0

Note - NFPA ratings are based on a 0-4 rating scale with 0 representing minimal hazards or risks and 4 representing extreme hazards or risks.

**Date of Preparation/Revision:** July 1, 2013 (Supersedes all previous MSDS)

#### DISCLAIMER

To the best of our knowledge, the information contained herein is accurate, obtained from sources believed by Camco Manufacturing, Inc., to be accurate. However, the information is provided without any representation or warranty, expressed or implied, regarding its accuracy or correctness.

The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and

# SAFETY DATA SHEET

7 of 7

## Full Timer's Choice Rubber Seal Conditioner

expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. It is the responsibility of the user to determine the safety, toxicity and suitability of their own use, handling and disposal of this product.