Page: 1
Revision Date: 09/27/2016
Print Date: 9/27/2016
SDS Number: 000000205480
Version: 1.3

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : NAPA® PREM PERF UFMO SAE 15W40

MOTOR OIL

Relevant identified uses of the substance or mixture and uses advised against

Details of the supplier of the safety data sheet

Valvoline LLC

3499 Blazer Parkway Lexington, KY 40509

United States of America (USA)

1-800-TEAMVAL

Emergency telephone number

1-800-VALVOLINE

Regulatory Information Number

1-800-TEAMVAL

Product Information

1-800-TEAMVAL

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Reproductive toxicity : Category 2

GHS label elements

Hazard pictograms



Signal Word : Warning

Hazard Statements : Suspected of damaging fertility or the unborn child.

Precautionary Statements : **Prevention:**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and

understood.

Wear protective gloves/ protective clothing/ eye protection/ face

protection. **Response:**

IF exposed or concerned: Get medical advice/ attention.

Storage: Store locked up. Disposal:

Dispose of contents/ container to an approved waste disposal

plant.

Valvoline.	Page: 2
SAFETY DATA SHEET	Revision Date: 09/27/2016
	Print Date: 9/27/2016
	SDS Number: 000000205480
NAPA® PREM PERF UFMO SAE 15W40 MOTOR OIL	Version: 1.3
NP75128	

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Defatter

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
MIXTURE OF SEVERELY		Not a hazardous	82.10
HYDROTREATED AND		substance or mixture.	
HYDROCRACKED BASE OIL			
(PETROLEUM)			
Phosphorodithioic acid, mixed	113706-15-3	Skin Irrit. 2; H315	1.08
O,O-bis(sec-Bu and isooctyl)			
esters, zinc salts		Eye Dam. 1; H318	
Dodecylphenol, mixed isomers	74499-35-7	Skin Irrit. 2; H315	0.1449
(branched)		E . I'(0A 11040	
		Eye Irrit. 2A; H319	
		Dong 2: U264	
		Repr. 2; H361	

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : First aid is not normally required. However, it is

recommended that exposed areas be cleaned by washing

with soap and water.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

If eye irritation persists, consult a specialist.

If swallowed : Obtain medical attention.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Valvoline	Page: 3
SAFETY DATA SHEET	Revision Date: 09/27/2016
	Print Date: 9/27/2016
	SDS Number: 000000205480
NAPA® PREM PERF UFMO SAE 15W40 MOTOR OIL	Version: 1.3
NP75128	

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

: Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:

delayed

stomach or intestinal upset (nausea, vomiting, diarrhea)

irritation (nose, throat, airways)

Suspected of damaging fertility or the unborn child.

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray Foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: carbon dioxide and carbon monoxide

Hydrocarbons

Nitrogen oxides (NOx)

Sulphur oxides hydrogen sulfide mercaptans zinc oxide

Specific extinguishing

methods

:

Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and

: Use personal protective equipment.

Ensure adequate ventilation.

Valvoline.	Page: 4
SAFETY DATA SHEET	Revision Date: 09/27/2016
	Print Date: 9/27/2016
	SDS Number: 000000205480
NAPA® PREM PERF UFMO SAE 15W40 MOTOR OIL	Version: 1.3
NP75128	

emergency procedures Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapours/dust.

Do not smoke.

Container hazardous when empty.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes.

Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL

Valvoline	Page: 5
SAFETY DATA SHEET	Revision Date: 09/27/2016
	Print Date: 9/27/2016
	SDS Number: 000000205480
NAPA® PREM PERF UFMO SAE 15W40 MOTOR OIL	Version: 1.3
NP75128	

	ST	10 mg/m3 Mist	NIOSH REL
	PEL	5 mg/m3 particulate	CAL PEL

Hazardous components without workplace control parameters

Components	CAS-No.
------------	---------

Engineering measures : Provide sufficient mechanical (general and/or local exhaust)

ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or

apparent adverse effects.

Personal protective equipment

Respiratory protection : A NIOSH-approved air-purifying respirator with an appropriate

cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by airpurifying respirators is limited. Use a positive pressure, airsupplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not

provide adequate protection.

In the case of vapour formation use a respirator with an

approved filter.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Not required under normal conditions of use. Wear splash-

proof safety goggles if material could be misted or splashed

into eyes.

Skin and body protection : Wear as appropriate:

Impervious clothing

Safety shoes

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Wear resistant gloves (consult your safety equipment

supplier).

Hygiene measures : Wash hands before breaks and at the end of workday.

When using do not eat or drink. When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid

Valvoline	Page: 6
SAFETY DATA SHEET	Revision Date: 09/27/2016
	Print Date: 9/27/2016
	SDS Number: 000000205480
NAPA® PREM PERF UFMO SAE 15W40 MOTOR OIL	Version: 1.3
NP75128	

Odour : No data available

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : No data available

Flash point : > 199 °C

Method: Cleveland open cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit : 6 %(V)

GLP: Calculated Explosive Limit

Lower explosion limit : 1 %(V)

GLP: Calculated Explosive Limit

Vapour pressure : 0.055 hPa (20 °C)

Calculated Vapor Pressure

Relative vapour density : No data available

Relative density : No data available

Density : No data available

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : > 20.5 mm2/s (40 °C)

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Valvoline	Page: 7
SAFETY DATA SHEET	Revision Date: 09/27/2016
	Print Date: 9/27/2016
	SDS Number: 000000205480
NAPA® PREM PERF UFMO SAE 15W40 MOTOR OIL	Version: 1.3
NP75128	

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous

reactions

: Product will not undergo hazardous polymerization.

Conditions to avoid : excessive heat

Incompatible materials : Acids

Oxidizing agents

water

Hazardous decomposition

products

carbon dioxide and carbon monoxide

hydrogen sulfide

Nitrogen oxides (NOx)

Sulphur oxides zinc oxide mercaptans

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of : Inhalation

exposure

: Inhalation Skin contact

> Eye Contact Ingestion

Acute toxicity

Not classified based on available information.

Components:

MIXTURE OF SEVERELY HYDROTREATED AND HYDROCRACKED BASE OIL

(PETROLEUM):

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.2 mg/l

Exposure time: 4 h

Assessment: Not classified as acutely toxic by inhalation

under GHS.

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Assessment: Not classified as acutely toxic by dermal

absorption under GHS.

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts:

Acute oral toxicity : LD50 (Rat): 2,900 mg/kg

Remarks: Information given is based on data obtained from

similar substances.

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Valvoline	Page: 8
SAFETY DATA SHEET	Revision Date: 09/27/2016
	Print Date: 9/27/2016
	SDS Number: 000000205480
NAPA® PREM PERF UFMO SAE 15W40 MOTOR OIL	Version: 1.3
NP75128	

Assessment: Not classified as acutely toxic by dermal absorption under GHS.

Remarks: Information given is based on data obtained from similar substances.

Skin corrosion/irritation

Not classified based on available information.

Product:

Result: Repeated exposure may cause skin dryness or cracking.

Components:

MIXTURE OF SEVERELY HYDROTREATED AND HYDROCRACKED BASE OIL (PETROLEUM):

Result: Slight, transient irritation

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts:

Result: Irritating to skin.

Remarks: Information given is based on data obtained from similar substances.

Dodecylphenol, mixed isomers (branched):

Result: Irritating to skin.

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:

MIXTURE OF SEVERELY HYDROTREATED AND HYDROCRACKED BASE OIL (PETROLEUM):

Result: Slight, transient irritation

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts:

Result: Corrosive

Remarks: Information given is based on data obtained from similar substances.

Dodecylphenol, mixed isomers (branched):

Result: Irritating to eyes.

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information.

Components:

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts:

Test Type: Buehler Test Species: Guinea pig

Assessment: Did not cause sensitisation on laboratory animals.

Germ cell mutagenicity

Not classified based on available information.

Components:

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts:

Valvoline	Page: 9
SAFETY DATA SHEET	Revision Date: 09/27/2016
	Print Date: 9/27/2016
	SDS Number: 000000205480
NAPA® PREM PERF UFMO SAE 15W40 MOTOR OIL	Version: 1.3
NP75128	

Genotoxicity in vitro : Remarks: In vitro tests showed mutagenic effects which were

not observed with in vivo test.

Genotoxicity in vivo : Test Type: chromosome aberration assay

Test species: Mouse

Cell type: peripheral blood cells

Result: negative

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

Components:

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts:

Effects on fertility : Species: Rat

Application Route: Oral Dose: 100 mg/kg bw/day

Symptoms: No effects on reproduction parameters

Effects on foetal : Species: Rat

development Application Route: Oral

Developmental Toxicity: No observed adverse effect level F1:

100 mg/kg body weight

Dodecylphenol, mixed isomers (branched):

Reproductive toxicity - : Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks: No data available

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Valvoline	Page: 10
SAFETY DATA SHEET	Revision Date: 09/27/2016
	Print Date: 9/27/2016
	SDS Number: 000000205480
NAPA® PREM PERF UFMO SAE 15W40 MOTOR OIL	Version: 1.3
NP75128	

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Acute aquatic toxicity Category 3; Harmful to aquatic life.

Chronic aquatic toxicity : Chronic aquatic toxicity Category 3; Harmful to aquatic life

with long lasting effects.

Components:

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 4.5 mg/l

Exposure time: 96 h

Remarks: Information given is based on data obtained from

similar substances.

Dodecylphenol, mixed isomers (branched):

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

Persistence and degradability

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts:

Biodegradability : Result: Not readily biodegradable.

Remarks: Information given is based on data obtained from

similar substances.

No data available

Bioaccumulative potential

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts:

Bioaccumulation : Bioconcentration factor (BCF): 3

Remarks: Information given is based on data obtained from

similar substances.

No data available Mobility in soil No data available Other adverse effects No data available

Product:

Additional ecological

information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life

with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : The product should not be allowed to enter drains, water

courses or the soil.

Valvoline	Page: 11
SAFETY DATA SHEET	Revision Date: 09/27/2016
	Print Date: 9/27/2016
	SDS Number: 000000205480
NAPA® PREM PERF UFMO SAE 15W40 MOTOR OIL	Version: 1.3
NP75128	

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and

federal regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

Empty containers should be taken to an approved waste

handling site for recycling or disposal. Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD	SUBSIDIARY	PACKING	MARINE
		CLASS	HAZARDS	GROUP	POLLUTANT /
					LTD. QTY.

U.S. DOT - ROAD

Not dangerous goods	

CFR_RAIL_C

Not dangerous goods	

U.S. DOT - INLAND WATERWAYS

Not dangerous goods	

TDG_ROAD_C

_	 	
Ī		Not dangerous goods
Ī		

TDG_RAIL_C

Not dangerous goods	

TDG_INWT_C

Not dangerous goods	

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods					

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Valvoline	Page: 12
SAFETY DATA SHEET	Revision Date: 09/27/2016
	Print Date: 9/27/2016
	SDS Number: 000000205480
NAPA® PREM PERF UFMO SAE 15W40 MOTOR OIL	Version: 1.3
NP75128	

Not dangerous goods	

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX DG

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ. SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Chronic Health Hazard

SARA 313

Phosphorodithioic acid, 113706-15-3 1.08 %

mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts

Pennsylvania Right To Know

MIXTURE OF SEVERELY Not Assigned

HYDROTREATED AND HYDROCRACKED

BASE OIL (PETROLEUM)

Proprietary of Infineum D3501L Not Assigned

DISTILLATES (PETROLEUM), 64742-54-7

HYDROTREATED HEAVY PARAFFINIC

New Jersey Right To Know

MIXTURE OF SEVERELY Not Assigned

HYDROTREATED AND HYDROCRACKED

BASE OIL (PETROLEUM)

Proprietary of Infineum D3501L Not Assigned

Valvoline	Page: 13
SAFETY DATA SHEET	Revision Date: 09/27/2016
	Print Date: 9/27/2016
	SDS Number: 000000205480
NAPA® PREM PERF UFMO SAE 15W40 MOTOR OIL	Version: 1.3
NP75128	

DISTILLATES (PETROLEUM), 64742-54-7

HYDROTREATED HEAVY PARAFFINIC

Phosphorodithioic acid, mixed O,O-bis(sec- 113706-15-3

Bu and isooctyl) esters, zinc salts

Distillates (petroleum), solvent-dewaxed 64742-65-0

heavy paraffinic

California Prop 65 WARNING! This product contains a chemical known to the

State of California to cause cancer.
BENZENE 71-43-2

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive

harm.

TOLUENE 108-88-3

BENZENE 71-43-2

The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI: On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : Not in compliance with the inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)


SECTION 16. OTHER INFORMATION

Further information

Revision Date: 09/27/2016

NFPA:	HMIS III:
-------	-----------

Valvoline	Page: 14
SAFETY DATA SHEET	Revision Date: 09/27/2016
	Print Date: 9/27/2016
	SDS Number: 000000205480
NAPA® PREM PERF UFMO SAE 15W40 MOTOR OIL	Version: 1.3
NP75128	



NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements

H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child.

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH: American Conference of Industrial Hygienists

BEI: Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

Valvoline	Page: 15
SAFETY DATA SHEET	Revision Date: 09/27/2016
	Print Date: 9/27/2016
	SDS Number: 000000205480
NAPA® PREM PERF UFMO SAE 15W40 MOTOR OIL	Version: 1.3
NP75128	

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx: Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

OEL: Occupational Exposure Limit
P-Statement: Precautionary Statement
PBT: Persistent, Bioaccumulative and Toxic

PPE: Personal Protective Equipment STEL: Short-term exposure limit STOT: Specific Target Organ Toxicity

TLV : Threshold Limit Value TWA : Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

DOT: Department of Transportation

FIFRA: Federal Insecticide, Fungicide, and Rodenticide Act HMIRC: Hazardous Materials Information Review Commission

HMIS: Hazardous Materials Identification System NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health OSHA: Occupational Safety and Health Administration

PMRA: Health Canada Pest Management Regulatory Agency

RTK: Right to Know

WHMIS: Workplace Hazardous Materials Information System