

	Page: 1
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0257762
Valvoline™ HIGH PERFORMANCE SAE 75W-90 GEAR OIL VV820	Version: 1.1

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Valvoline™ HIGH PERFORMANCE SAE 75W-90
GEAR OIL

Recommended use of the chemical and restrictions on use

Details of the supplier of the safety data sheet Valvoline LLC 3499 Blazer Parkway Lexington, KY 40509 United States of America SDS@valvoline.com	Emergency telephone number 1-800-VALVOLINE Regulatory Information Number 1-800-TEAMVAL Product Information 1-800-TEAMVAL
---	--

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Skin irritation : Category 2

Eye irritation : Category 2A

Skin sensitization : Category 1

GHS Label element

Hazard pictograms : 

Signal Word : Warning

Hazard Statements : Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.

Precautionary Statements : **Prevention:**
Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
Wash skin thoroughly after handling.
Contaminated work clothing must not be allowed out of the

		Page: 2
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 11/1/2016
		SDS Number: R0257762
Valvoline™ HIGH PERFORMANCE SAE 75W-90 GEAR OIL VV820		Version: 1.1

workplace.

Wear eye protection/ face protection.

Wear protective gloves.

Response:

IF ON SKIN: Wash with plenty of soap and water.

IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

If skin irritation or rash occurs: Get medical advice/ attention.

If eye irritation persists: Get medical advice/ attention.

Take off contaminated clothing and wash before reuse.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Defatter

Hazardous components

Chemical Name	CAS-No.	Classification	Concentration (%)
HEAVY PARAFFINIC DISTILLATE	64742-54-7	Asp. Tox. 1; H304	68.25
MINERAL OIL		Not a hazardous substance or mixture.	1.39
ALKYL PHOSPHATE		Skin Corr. 1B; H314 Eye Dam. 1; H318 STOT SE 3; H335	1.02
LONG-CHAIN ALKYL AMINE		Acute Tox. 4; H302 Acute Tox. 2; H330 Acute Tox. 3; H311 Skin Corr. 1B; H314	0.34

		Page: 3
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 11/1/2016
		SDS Number: R0257762
Valvoline™ HIGH PERFORMANCE SAE 75W-90 GEAR OIL VV820		Version: 1.1

		Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	
--	--	---	--

SECTION 4. FIRST AID MEASURES

General advice	: Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	: If breathed in, move person into fresh air. If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	: Remove contaminated clothing. If irritation develops, get medical attention. If on skin, rinse well with water. Wash contaminated clothing before re-use.
In case of eye contact	: Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye.
If swallowed	: Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	: Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

		Page: 4
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 11/1/2016
		SDS Number: R0257762
Valvoline™ HIGH PERFORMANCE SAE 75W-90 GEAR OIL VV820		Version: 1.1

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:

acne
stomach or intestinal upset (nausea, vomiting, diarrhea)
irritation (nose, throat, airways)
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : carbon dioxide and carbon monoxide
Hydrocarbons
Aldehydes
Oxides of phosphorus
- Specific extinguishing methods :

Product is compatible with standard fire-fighting agents.
- Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

		Page: 5
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 11/1/2016
		SDS Number: R0257762
Valvoline™ HIGH PERFORMANCE SAE 75W-90 GEAR OIL VV820		Version: 1.1

- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.
- Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Do not breathe vapours/dust.
Do not smoke.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Container hazardous when empty.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
MINERAL OIL		REL	5 mg/m3 Mist.	NIOSH/GUID E
		STEL	10 mg/m3	NIOSH/GUID

		Page: 6
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 11/1/2016
		SDS Number: R0257762
Valvoline™ HIGH PERFORMANCE SAE 75W-90 GEAR OIL VV820		Version: 1.1

			Mist.	E
		PEL	5 mg/m3 Mist.	OSHA_T RANS
		TWA	5 mg/m3 Mist.	TN OEL
		TWA	5 mg/m3 Inhalable fraction.	ACGIH

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Hand protection

Remarks

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

Skin and body protection

: Wear as appropriate:
impervious clothing
Safety shoes
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Discard gloves that show tears, pinholes, or signs of wear.
Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures

: Wash hands before breaks and at the end of workday.
When using do not eat or drink.
When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid

Odour : No data available

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : 392 °F / 200 °C
(1,013.333333 hPa)
Calculated Phase Transition Liquid/Gas

Flash point : > 390 °F / > 199 °C

		Page: 7
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 11/1/2016
		SDS Number: R0257762
Valvoline™ HIGH PERFORMANCE SAE 75W-90 GEAR OIL VV820		Version: 1.1

Method: Cleveland open cup

Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: 6 %(V) Calculated Explosive Limit
Lower explosion limit	: 1 %(V) Calculated Explosive Limit
Vapour pressure	: 0.1333333 hPa (20 °C) Calculated Vapor Pressure
Relative vapour density	: No data available
Relative density	: No data available
Density	: 0.8613 g/cm3 (15.56 °C)
Solubility(ies)	
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: 99 mm2/s (40 °C)
Oxidizing properties	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under recommended storage conditions.
Possibility of hazardous reactions	: Product will not undergo hazardous polymerization.
Conditions to avoid	: excessive heat
Incompatible materials	: Strong oxidizing agents

		Page: 8
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 11/1/2016
		SDS Number: R0257762
Valvoline™ HIGH PERFORMANCE SAE 75W-90 GEAR OIL VV820		Version: 1.1

Hazardous decomposition
products

carbon dioxide and carbon monoxide
Hydrocarbons

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Components:

HEAVY PARAFFINIC DISTILLATE:

Acute oral toxicity : LD 50 (Rat): > 15 g/kg

Acute dermal toxicity : LD 50 (Rabbit): > 5 g/kg

LONG-CHAIN ALKYL AMINE:

Acute oral toxicity :
Assessment: The component/mixture is classified as acute oral toxicity, category 4.

Acute inhalation toxicity : Assessment: The component/mixture is classified as acute inhalation toxicity, category 2.

Acute dermal toxicity : Assessment: The component/mixture is classified as acute dermal toxicity, category 3.

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks: May cause skin irritation and/or dermatitis.

Components:

HEAVY PARAFFINIC DISTILLATE:

Result: Mildly irritating to skin

MINERAL OIL:

Result: Mildly irritating to skin

ALKYL PHOSPHATE:

Result: Corrosive to skin

LONG-CHAIN ALKYL AMINE:

Result: Corrosive after 3 minutes to 1 hour of exposure

		Page: 9
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 11/1/2016
		SDS Number: R0257762
Valvoline™ HIGH PERFORMANCE SAE 75W-90 GEAR OIL VV820		Version: 1.1

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin., Causes serious eye irritation.

Components:

HEAVY PARAFFINIC DISTILLATE:

Result: Not irritating to eyes

MINERAL OIL:

Result: Mildly irritating to eyes

ALKYL PHOSPHATE:

Result: Corrosive to eyes

LONG-CHAIN ALKYL AMINE:

Result: Corrosive to eyes

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

Components:

LONG-CHAIN ALKYL AMINE:

Assessment: May cause sensitisation by skin contact.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

Components:

ALKYL PHOSPHATE:

Assessment: May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Components:

HEAVY PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

	Page: 10
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0257762
Valvoline™ HIGH PERFORMANCE SAE 75W-90 GEAR OIL VV820	Version: 1.1

Carcinogenicity:
IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

HEAVY PARAFFINIC DISTILLATE:

Toxicity to fish : LL50 (Fish): > 100 mg/l

Toxicity to daphnia and other aquatic invertebrates : EL50 (Aquatic invertebrates): > 10,000 mg/l

Toxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l

Toxicity to fish (Chronic toxicity) : NOEC (Fish): 10 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Aquatic invertebrates): 10 mg/l

LONG-CHAIN ALKYL AMINE:

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

Persistence and degradability

Components:

No data available

Bioaccumulative potential

Components:

No data available

		Page: 11
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 11/1/2016
		SDS Number: R0257762
Valvoline™ HIGH PERFORMANCE SAE 75W-90 GEAR OIL VV820		Version: 1.1

Mobility in soil

Components:

No data available

Other adverse effects

No data available

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life with long lasting effects.

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

U.S. DOT - ROAD

Not dangerous goods

CFR_RAIL_C

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

		Page: 12
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 11/1/2016
		SDS Number: R0257762
Valvoline™ HIGH PERFORMANCE SAE 75W-90 GEAR OIL		Version: 1.1
VV820		

Not dangerous goods

TDG_ROAD_C

Not dangerous goods

TDG_RAIL_C

Not dangerous goods

TDG_INWT_C

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX_DG

Not dangerous goods

***ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards : Acute Health Hazard

	Page: 13
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0257762
Valvoline™ HIGH PERFORMANCE SAE 75W-90 GEAR OIL VV820	Version: 1.1

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
Component(s) SARA 313

Pennsylvania Right To Know

HEAVY PARAFFINIC DISTILLATE	64742-54-7	50.00 - 70.00 %
VISCOSITY MODIFIER	Not Assigned	20.00 - 30.00 %
LUBRICANT ADDITIVE	Not Assigned	5.00 - 10.00 %

New Jersey Right To Know

HEAVY PARAFFINIC DISTILLATE	64742-54-7	50.00 - 70.00 %
VISCOSITY MODIFIER	Not Assigned	20.00 - 30.00 %
LUBRICANT ADDITIVE	Not Assigned	5.00 - 10.00 %
ACRYLIC COPOLYMER	Not Assigned	1.00 - 5.00 %
MINERAL OIL	Not Assigned	1.00 - 5.00 %

California Prop 65 Proposition 65 warnings are not required for this product based on the results of a risk assessment.

The components of this product are reported in the following inventories:

TSCA	: On TSCA Inventory
DSL	: All components of this product are on the Canadian DSL.
AUSTR	: On the inventory, or in compliance with the inventory
ENCS	: On the inventory, or in compliance with the inventory
KECL	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory

Inventories


AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECL (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

	Page: 14
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0257762
Valvoline™ HIGH PERFORMANCE SAE 75W-90 GEAR OIL VV820	Version: 1.1

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 07/31/2016

NFPA:	HMIS III:						
Flammability Health  Instability Special hazard.	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="background-color: blue; color: white; text-align: center;">HEALTH</td><td style="text-align: center;">1</td></tr> <tr> <td style="background-color: red; color: white; text-align: center;">FLAMMABILITY</td><td style="text-align: center;">1</td></tr> <tr> <td style="background-color: yellow; text-align: center;">PHYSICAL HAZARD</td><td style="text-align: center;">0</td></tr> </table> 0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic	HEALTH	1	FLAMMABILITY	1	PHYSICAL HAZARD	0
HEALTH	1						
FLAMMABILITY	1						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements referred to under sections 2 and 3.

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-825-8654).

		Page: 15
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 11/1/2016
		SDS Number: R0257762
Valvoline™ HIGH PERFORMANCE SAE 75W-90 GEAR OIL VV820		Version: 1.1

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists
BEI : Biological Exposure Index
CAS : Chemical Abstracts Service (Division of the American Chemical Society).
CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
FG : Food grade
GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
H-statement : Hazard Statement
IATA : International Air Transport Association.
IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization
ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
IMDG : International Maritime Code for Dangerous Goods
ISO : International Organization for Standardization
logPow : octanol-water partition coefficient
LCxx : Lethal Concentration, for xx percent of test population
LDxx : Lethal Dose, for xx percent of test population.
ICxx : Inhibitory Concentration for xx of a substance
Ecxx : Effective Concentration of xx
N.O.S.: Not Otherwise Specified
OECD : Organization for Economic Co-operation and Development
OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic
PPE : Personal Protective Equipment
STEL : Short-term exposure limit
STOT : Specific Target Organ Toxicity
TLV : Threshold Limit Value
TWA : Time-weighted average
vPvB : Very Persistent and Very Bioaccumulative
WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act
DOT : Department of Transportation
FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act
HMIRC : Hazardous Materials Information Review Commission
HMIS : Hazardous Materials Identification System
NFPA : National Fire Protection Association
NIOSH : National Institute for Occupational Safety and Health
OSHA : Occupational Safety and Health Administration
PMRA : Health Canada Pest Management Regulatory Agency
RTK : Right to Know
WHMIS : Workplace Hazardous Materials Information System