	Page: 1
SAFETY DATA SHEET	Revision Date: 05/22/2017
	Print Date: 6/2/2017
	SDS Number: R0368895
Zerex™ HD EXTENDED LIFE RTU Antifreeze Coolant ZXEDRU1	Version: 1.4

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Zerex™ HD EXTENDED LIFE RTU
Antifreeze Coolant

Relevant identified uses of the substance or mixture and uses advised against

Recommended use : ANTIFREEZE COOLANT

Details of the supplier of the safety data sheet Valvoline LLC 100 Valvoline Way Lexington, KY 40509 United States of America (USA) 1-800-TEAMVAL	Emergency telephone number 1-800-VALVOLINE (1-800-825-8654) Regulatory Information Number 1-800-TEAMVAL Product Information 1-800-TEAMVAL
---	---

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Acute toxicity (Oral) : Category 4

Specific target organ
systemic toxicity - repeated
exposure (Oral) : Category 2 (Kidney, Liver)

GHS label elements

Hazard pictograms :



Signal Word : Warning

Hazard Statements : Harmful if swallowed.
May cause damage to organs (Kidney, Liver) through
prolonged or repeated exposure if swallowed.

Precautionary Statements : **Prevention:**
Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
Wash skin thoroughly after handling.
Do not eat, drink or smoke when using this product.

SAFETY DATA SHEET

Revision Date: 05/22/2017

Print Date: 6/2/2017

SDS Number: R0368895

Zerex™ HD EXTENDED LIFE RTU Antifreeze Coolant

Version: 1.4

ZXEDRU1

Response:

IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.

Get medical advice/ attention if you feel unwell.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
ETHYLENE GLYCOL	107-21-1	Acute Tox. 4; H302 STOT RE 2; H373	49.0056
DIETHYLENE GLYCOL	111-46-6	Acute Tox. 4; H302 STOT RE 2; H373	2.4507
POTASSIUM HYDROXIDE	1310-58-3	Met. Corr. 1; H290 Acute Tox. 4; H302 Skin Corr. 1A; H314 Eye Dam. 1; H318	1.4441

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

If inhaled : If breathed in, move person into fresh air.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.



SAFETY DATA SHEET

Revision Date: 05/22/2017

Print Date: 6/2/2017

SDS Number: R0368895

Zerex™ HD EXTENDED LIFE RTU Antifreeze Coolant

Version: 1.4

ZXEDRU1

- In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
If eye irritation persists, consult a specialist.
- If swallowed : Obtain medical attention.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Effects of acute ethylene glycol poisoning appear in three fairly distinct stages. The initial stage occurs shortly after exposure, lasts 6-12 hours, and is characterized by central nervous system effects (transient exhilaration, nausea, vomiting, and in severe cases, coma, convulsions, and possible death). The second stage lasts from 12-36 hours after exposure and is initiated by the onset of coma. This phase is characterized by tachypnea, tachycardia, mild hypotension, cyanosis, and in severe cases, pulmonary edema, bronchopneumonia, cardiac enlargement, and congestive failure. The final stage occurs 24-72 post-exposure and is characterized by renal failure, ranging from a mild increase in blood urea nitrogen and creatinine followed by recovery, to complete anuria with acute tubular necrosis that can lead to death. Oxaluria is found in most cases. The most significant laboratory finding in ethylene glycol intoxication is severe metabolic acidosis.
- Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:
stomach or intestinal upset (nausea, vomiting, diarrhea)
irritation (nose, throat, airways)
Cough
pain in the abdomen and lower back
cyanosis (causes blue coloring of the skin and nails from lack of oxygen)
lung edema (fluid buildup in the lung tissue)
acute kidney failure (sudden slowing or stopping of urine production)
Convulsions
Harmful if swallowed.
- Notes to physician : This product contains ethylene glycol. Ethanol decreases the metabolism of ethylene glycol to toxic metabolites. Ethanol should be administered as soon as possible in cases of



SAFETY DATA SHEET

Revision Date: 05/22/2017

Print Date: 6/2/2017

SDS Number: R0368895

Zerex™ HD EXTENDED LIFE RTU Antifreeze Coolant

Version: 1.4

ZXEDRU1

severe poisoning since the elimination half-life of ethylene glycol is 3 hours. If medical care will be delayed several hours, give the patient three to four 1-ounce oral "shots" of 86-proof or higher whiskey before or during transport to the hospital. Fomepizole (4-methylpyrazole) is an effective antagonist of alcohol dehydrogenase, and as such, may be used as an antidote in the treatment of ethylene glycol poisoning. Hemodialysis effectively removes ethylene glycol and its metabolites from the body.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Alcohols
Aldehydes
carbon dioxide and carbon monoxide
ethers
toxic fumes
Hydrocarbons
potassium oxide
- Specific extinguishing methods :

Product is compatible with standard fire-fighting agents.
- Further information : Standard procedure for chemical fires.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

SAFETY DATA SHEET

Revision Date: 05/22/2017

Print Date: 6/2/2017

SDS Number: R0368895

Zerex™ HD EXTENDED LIFE RTU Antifreeze Coolant

Version: 1.4

ZXEDRU1

emergency procedures

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapours/dust.
Do not smoke.
Container hazardous when empty.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ETHYLENE GLYCOL	107-21-1	C	100 mg/m3 Aerosol only	ACGIH
		C	50 ppm 125 mg/m3	OSHA P0
		C	40 ppm 100 mg/m3 Vapour	CAL PEL
DIETHYLENE GLYCOL	111-46-6	TWA	10 mg/m3	US WEEL
POTASSIUM HYDROXIDE	1310-58-3	C	2 mg/m3	ACGIH
		C	2 mg/m3	NIOSH REL
		C	2 mg/m3	OSHA P0
		C	2 mg/m3	CAL PEL

SAFETY DATA SHEET

Revision Date: 05/22/2017

Print Date: 6/2/2017

SDS Number: R0368895

Zerex™ HD EXTENDED LIFE RTU Antifreeze Coolant

Version: 1.4

ZXEDRU1

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Wear resistant gloves (consult your safety equipment supplier).
Wear as appropriate:
Impervious clothing
Safety shoes
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : Wash hands before breaks and at the end of workday.
When using do not eat or drink.
When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid

Colour : dark orange

Odour : No data available

Odour Threshold : No data available

pH : 8 - 10

Melting point/freezing point : < -33 °F / < -36 °C

Boiling point/boiling range : 225 °F / 107 °C

Flash point : > 250.00 °F / > 121.11 °C

Evaporation rate : No data available

Flammability (solid, gas) : No data available

SAFETY DATA SHEET

Revision Date: 05/22/2017

Print Date: 6/2/2017

SDS Number: R0368895

Zerex™ HD EXTENDED LIFE RTU Antifreeze Coolant

Version: 1.4

ZXEDRU1

Upper explosion limit	: 15.3 %(V)
Lower explosion limit	: 1 %(V)
Vapour pressure	: 23.333333 hPa (20 °C) Calculated Vapor Pressure
Relative vapour density	: No data available
Relative density	: 1.0745 (15.6 °C)
Density	: 1.0745 g/cm3 (15.6 °C)
Solubility(ies)	
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Oxidizing properties	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under recommended storage conditions.
Possibility of hazardous reactions	: Product will not undergo hazardous polymerization.
Conditions to avoid	: Keep away from heat, flame, sparks and other ignition sources. excessive heat
Incompatible materials	: Acids Alcohols Aldehydes Alkali metals Alkaline earth metals

**SAFETY DATA SHEET**

Revision Date: 05/22/2017

Print Date: 6/2/2017

SDS Number: R0368895

Zerex™ HD EXTENDED LIFE RTU Antifreeze Coolant

Version: 1.4

ZXEDRU1

Amines
Bases
chlorinated solvents
halogenated hydrocarbons
strong alkalis
Strong oxidizing agents
Sulphur compounds
Zinc

Acids
Alcohols
Aldehydes
Alkali metals
Alkaline earth metals
aluminum
Amines
Bases
chlorinated solvents
halogenated hydrocarbons
Metals
strong alkalis
Strong oxidizing agents
Sulphur compounds
water
Zinc

Hazardous decomposition
products

Alcohols
Aldehydes
carbon dioxide and carbon monoxide
ethers
Hydrocarbons
Organic acids
potassium oxide
ketones

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Harmful if swallowed.

Product:

Acute oral toxicity :

Remarks: Ingestion of medications contaminated with diethylene glycol has caused kidney failure and death in

SAFETY DATA SHEET

Revision Date: 05/22/2017

Print Date: 6/2/2017

SDS Number: R0368895

Zerex™ HD EXTENDED LIFE RTU Antifreeze Coolant

Version: 1.4

ZXEDRU1

humans. Products containing diethylene glycol should be considered toxic by ingestion.

Acute dermal toxicity : Remarks: Skin absorption of this material (or a component) may be increased through injured skin.

Components:
ETHYLENE GLYCOL:

Acute oral toxicity : LD0 (Human): Estimated 1.56 g/kg

Assessment: The component/mixture is classified as acute oral toxicity, category 4.

Acute inhalation toxicity : LC50 (Rat): 10.9 mg/l
Exposure time: 1 h
Test atmosphere: dust/mist
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): 9,530 mg/kg

DIETHYLENE GLYCOL:

Acute oral toxicity : LD50 (Human): Expected 1,120 mg/kg
Target Organs: Kidney

Acute inhalation toxicity : LC50 (Rat): > 4.6 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): 13,300 mg/kg

POTASSIUM HYDROXIDE:

Acute oral toxicity : LD50 (Rat): 333 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Product:

Result: No skin irritation

Remarks: Expected based on components.

Components:
ETHYLENE GLYCOL:

Species: Rabbit

Result: No skin irritation

DIETHYLENE GLYCOL:

SAFETY DATA SHEET

Revision Date: 05/22/2017

Print Date: 6/2/2017

SDS Number: R0368895

Zerex™ HD EXTENDED LIFE RTU Antifreeze Coolant

Version: 1.4

ZXEDRU1

Species: Human

Result: Slight, transient irritation

POTASSIUM HYDROXIDE:

Species: Rabbit

Result: Corrosive after 3 minutes or less of exposure

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Result: No eye irritation

Remarks: Expected based on components.

Remarks: Unlikely to cause eye irritation or injury.

Components:

ETHYLENE GLYCOL:

Result: Slight, transient irritation

DIETHYLENE GLYCOL:

Species: Rabbit

Result: Slight, transient irritation

POTASSIUM HYDROXIDE:

Species: Rabbit

Result: Corrosive

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Components:

ETHYLENE GLYCOL:

Test Type: Maximisation Test

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

DIETHYLENE GLYCOL:

Test Type: Maximisation Test

Species: Guinea pig

Method: Directive 67/548/EEC, Annex V, B.6.

Result: Did not cause sensitisation on laboratory animals.

POTASSIUM HYDROXIDE:

Test Type: Maximisation Test

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Germ cell mutagenicity

Not classified based on available information.

SAFETY DATA SHEET

Revision Date: 05/22/2017

Print Date: 6/2/2017

SDS Number: R0368895

Zerex™ HD EXTENDED LIFE RTU Antifreeze Coolant

Version: 1.4

ZXEDRU1

Components:

ETHYLENE GLYCOL:

Genotoxicity in vitro

: Test Type: Ames test
Test species: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Result: negative

DIETHYLENE GLYCOL:

Genotoxicity in vitro

: Test Type: Ames test
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative
GLP: yes

: Test species: Chinese hamster ovary cells
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 479
Result: negative
GLP: yes

Genotoxicity in vivo

: Test Type: In vivo micronucleus test
Test species: Mouse
Method: OECD Test Guideline 474
Result: negative
GLP: yes

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Components:

ETHYLENE GLYCOL:

Exposure routes: Ingestion

Target Organs: Kidney, Liver

Assessment: May cause damage to organs through prolonged or repeated exposure.

DIETHYLENE GLYCOL:

Exposure routes: Ingestion

Target Organs: Kidney

Assessment: May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Experience with human exposure

**SAFETY DATA SHEET**

Revision Date: 05/22/2017

Print Date: 6/2/2017

SDS Number: R0368895

Zerex™ HD EXTENDED LIFE RTU Antifreeze Coolant

Version: 1.4

ZXEDRU1

Components:

DIETHYLENE GLYCOL:

Liver

Further information**Product:**

Remarks: No data available

Components:

POTASSIUM HYDROXIDE:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Product:**

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Components:

ETHYLENE GLYCOL:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 27,540 mg/l
Exposure time: 96 h
Test Type: static test

LC50 (Pimephales promelas (fathead minnow)): 8,050 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Test Type: static test

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 6,500 - 13,000 mg/l
End point: Growth inhibition
Exposure time: 7 Days

Toxicity to fish (Chronic toxicity) : NOEC (Pimephales promelas (fathead minnow)): 32,000 mg/l
Exposure time: 7 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 24,000 mg/l
Exposure time: 7 d

DIETHYLENE GLYCOL:

Toxicity to fish : LC50 (Fathead minnow (Pimephales promelas)): 75,210 mg/l
Exposure time: 96 h
Test Type: flow-through test

SAFETY DATA SHEET

Revision Date: 05/22/2017

Print Date: 6/2/2017

SDS Number: R0368895

Zerex™ HD EXTENDED LIFE RTU Antifreeze Coolant

Version: 1.4

ZXEDRU1

Toxicity to daphnia and other aquatic invertebrates : LC50 (Water flea (Daphnia magna)): > 10,000 mg/l
Exposure time: 24 h
Test Type: static test
Method: DIN 38412

POTASSIUM HYDROXIDE:
Toxicity to fish : LC50 (Gambusia affinis (Mosquito fish)): 80 mg/l
Exposure time: 96 h
Test Type: static test

Ecotoxicology Assessment
Chronic aquatic toxicity : Not expected to cause long-term toxicity to fish., Not expected to cause long-term toxicity to aquatic invertebrates., Not expected to cause long-term toxicity to aquatic plants.

Persistence and degradability
Components:

ETHYLENE GLYCOL:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 90 - 100 %
Exposure time: 10 d
Method: OECD Test Guideline 301

DIETHYLENE GLYCOL:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 70 - 80 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

POTASSIUM HYDROXIDE:

Biodegradability : Result: The methods for determining biodegradability are not applicable to inorganic substances.

No data available

Bioaccumulative potential
Components:

ETHYLENE GLYCOL:

Bioaccumulation : Species: Crayfish (Procambarus)
Bioconcentration factor (BCF): 0.27
Exposure time: 61 d
Concentration: 1000 mg/l
Method: Flow through

Partition coefficient: n-octanol/water : log Pow: -1.36

DIETHYLENE GLYCOL:

Bioaccumulation : Species: Leuciscus idus (Golden orfe)
Bioconcentration factor (BCF): 100

**SAFETY DATA SHEET**

Revision Date: 05/22/2017

Print Date: 6/2/2017

SDS Number: R0368895

Zerex™ HD EXTENDED LIFE RTU Antifreeze Coolant

Version: 1.4

ZXEDRU1

Partition coefficient: n-
octanol/water : log Pow: -1.47

No data available

Mobility in soil**Components:**

No data available

Other adverse effects

No data available

Product:

Additional ecological : No data available
information

Components:

POTASSIUM HYDROXIDE:

Additional ecological : No data available
information

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

General advice : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with
chemical or used container.
Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and
federal regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Empty containers should be taken to an approved waste
handling site for recycling or disposal.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION**International transport regulations****REGULATION**

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

U.S. DOT - ROAD

Not dangerous goods

**SAFETY DATA SHEET**

Revision Date: 05/22/2017

Print Date: 6/2/2017

SDS Number: R0368895

Zerex™ HD EXTENDED LIFE RTU Antifreeze Coolant

Version: 1.4

ZXEDRU1

CFR_RAIL_C

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TDG_ROAD_C

Not dangerous goods

TDG_RAIL_C

Not dangerous goods

TDG_INWT_C

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX_DG

Not dangerous goods

***ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Marine pollutant

no

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know Act**

**SAFETY DATA SHEET**

Revision Date: 05/22/2017

Print Date: 6/2/2017

SDS Number: R0368895

Zerex™ HD EXTENDED LIFE RTU Antifreeze Coolant

Version: 1.4

ZXEDRU1

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
ETHYLENE GLYCOL	107-21-1	5000	10203

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Chronic Health Hazard
Acute Health Hazard

SARA 313

ETHYLENE GLYCOL 107-21-1 49.00 %

California Prop 65 : This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

ENCS : Not in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TSCA : On TSCA Inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION**Further information**

Revision Date: 05/22/2017

NFPA:**HMIS III:**

SAFETY DATA SHEET

Revision Date: 05/22/2017


Print Date: 6/2/2017

SDS Number: R0368895

Zerex™ HD EXTENDED LIFE RTU Antifreeze Coolant

Version: 1.4

ZXEDRU1



NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements

H290	May be corrosive to metals.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H373	May cause damage to organs through prolonged or repeated exposure if swallowed.

Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index


CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

	Page: 18
SAFETY DATA SHEET	Revision Date: 05/22/2017
	Print Date: 6/2/2017
	SDS Number: R0368895
Zerex™ HD EXTENDED LIFE RTU Antifreeze Coolant	Version: 1.4
ZXEDRU1	

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act

DOT : Department of Transportation

FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act

HMIRC : Hazardous Materials Information Review Commission

HMIS : Hazardous Materials Identification System

NFPA : National Fire Protection Association

NIOSH : National Institute for Occupational Safety and Health

OSHA : Occupational Safety and Health Administration

PMRA : Health Canada Pest Management Regulatory Agency

RTK : Right to Know

WHMIS : Workplace Hazardous Materials Information System