



150,000 MILE / 5 YEAR PROTECTION*

EXTENDED LIFE

50/50 PREDILUTED

**ANTIFREEZE
& COOLANT**

DO NOT ADD WATER
FOR ALL MAKES AND MODELS
ADD TO ANY COLOR ANTIFREEZE

P-6196

WARNING: HARMFUL OR FATAL
IF SWALLOWED. CONTAINS
ETHYLENE GLYCOL. Read other
cautionary information on back panel.

1 U.S. Gal (3.78 L)



EXTENDED LIFE 50/50 PREDILUTED ANTIFREEZE & COOLANT

MEETS: ASTM D3306
ASTM D4985

NAPA Extended Life 50/50 PREDILUTED Antifreeze/Coolant features coolant technology that is compatible for use in all automobiles and light duty trucks, regardless of make, model, year or original antifreeze color. Its inhibitors provide maximum cooling protection against damaging rust and corrosion.

NAPA Extended Life 50/50 PREDILUTED Antifreeze/Coolant can be used to top-off cooling systems filled with any automotive antifreeze. However, to realize the 150,000 miles or 5 years of maximum cooling system protection provided by NAPA Extended Life 50/50 PREDILUTED Antifreeze/Coolant, a complete cooling system flush and fill is required*.

CAUTION: DO NOT REMOVE RADIATOR CAP WHEN ENGINE IS HOT.
Check owner's manual for specified antifreeze usage

**Always follow vehicle's owner's manual for top-off requirements and specified maintenance.*

DIRECTIONS:

Top-Off Instructions:

1. Remove radiator cap when engine is cool.
2. Top-off radiator and fill reservoir with NAPA® 50/50 PREDILUTED Antifreeze/Coolant. **DO NOT ADD WATER.**
3. Check fluid level periodically.
4. Check owner's manual for any other recommendations for antifreeze usage.

Flush and Fill Instructions:

1. With engine cold, drain radiator and refill with water. Start engine with heater on high for 10 minutes to recirculate the water.
2. Stop engine and let cool. Once engine is cool, drain radiator.
3. Read owner's manual for cooling system capacity. Refill cooling system with NAPA 50/50 Prediluted Antifreeze & Coolant. **DO NOT ADD WATER.**

DO NOT ADD WATER

Protection Chart (°F) **Using a 15 psi pressure cap.

Concentration	50%
Boiling Point**	265°
Freezing Point	-34°

WARNING

Contains Ethylene Glycol (107-21-1), Water (7732-18-5), Diethylene Glycol (111-46-6), 2-Ethyl Hexanoic Acid, Sodium Salt (19766-89-3). Do not drink antifreeze or solution. Do not store in open or unlabeled containers. Avoid contact with eye, skin and clothing. Wash thoroughly after handling. Avoid breathing vapors or mists. Solution is poisonous to animals. Contains ethylene glycol and diethylene glycol. If swallowed, call a POISON CENTER or go to a hospital emergency room immediately. If inhaled, move to fresh air. Seek medical attention if symptoms persist. In case of contact, wash with water.

KEEP OUT OF REACH OF CHILDREN.



WARNING: Reproductive Harm - www.P65Warnings.ca.gov

DISPOSING OF USED ANTIFREEZE & COOLANT: Dispose of contents and container in accordance with local and national regulations.

RTU1EXT

EMBITTERED FORMULA

P-6196 SDS 504



Made in the U.S.A. with domestic and imported materials

Manufactured for
NAPA Distribution Centers
Atlanta, GA