



GREEN

50/50 PREDILUTED

**ANTIFREEZE
& COOLANT**

DO NOT ADD WATER

FOR USE IN:

FORD & CHRYSLER 2000 AND EARLIER

GM 1995 AND EARLIER

ALL MAKES & MODELS 1989 AND EARLIER

P-6194

WARNING: HARMFUL OR FATAL
IF SWALLOWED, CONTAINS
ETHYLENE GLYCOL. Read other
cautionary information on back panel.

1 U.S. Gal (3.78 L)



GREEN 50/50 PREDILUTED ANTIFREEZE & COOLANT

MEETS: ASTM D-3306
ASTM D-4985
ASTM D-4340
ASTM D-4656
Ford-ESE-M97B44-A
General Motors-GM 1899 M

NAPA 50/50 PREDILUTED Antifreeze/Coolant is a conventional green low silicate antifreeze containing inhibitors providing protection from freezing, overheating, rust and corrosion when used as recommended. NAPA 50/50 PREDILUTED Antifreeze/Coolant has been formulated for use in all conventional automobiles and light duty trucks and protects all cooling system metal surfaces, including aluminum.

CAUTION: DO NOT REMOVE RADIATOR CAP WHEN ENGINE IS HOT.
Check owner's manual for specified antifreeze usage.

DIRECTIONS:

Top-Off Instructions:

1. Remove radiator cap when engine is cool.
2. Top-off radiator and fill reservoir with NAPA® 50/50 Prediluted Antifreeze & Coolant. **DO NOT ADD WATER.**
3. Check fluid level periodically.
4. Check owner's manual for any other recommendations for antifreeze usage.

Flush and Fill Instructions:

1. With engine cold, drain radiator and refill with water. Start engine with heater on high for 10 minutes to recirculate the water.
2. Stop engine and let cool. Once engine is cool, drain radiator.
3. Read owner's manual for cooling system capacity. Refill cooling system with NAPA 50/50 Prediluted Antifreeze & Coolant. **DO NOT ADD WATER.**

WARNING

Contains Ethylene Glycol (107-21-1), Water (7732-18-5), Diethylene Glycol (111-46-6), Sodium Nitrite (7632-00-0). Do not drink antifreeze or solution. Do not store in open or unlabeled containers. Avoid contact with eye, skin and clothing. Wash thoroughly after handling. Avoid breathing vapors or mists. Solution is poisonous to animals. Contains ethylene glycol and diethylene glycol. If swallowed, call a POISON CENTER or go to a hospital emergency room immediately. If inhaled, move to fresh air. Seek medical attention if symptoms persist. In case of contact, wash with water.

KEEP OUT OF REACH OF CHILDREN.

WARNING: Reproductive Harm - www.P65Warnings.ca.gov

DO NOT ADD WATER

Protection Chart (°F) *Using a 15 psi pressure cap.

Concentration	50%
Boiling Point*	265°
Freezing Point	-34°

DISPOSING OF USED ANTIFREEZE & COOLANT: Dispose of contents and container in accordance with local and national regulations.

RTU1GAL
EMBITTERED FORMULA

P-6194 SDS 474



Made in the U.S.A. with domestic and imported materials

Manufactured for
NAPA Distribution Centers
Atlanta, GA