



150,000 MILE / 5 YEAR PROTECTION\*

# EXTENDED LIFE ANTIFREEZE & COOLANT

**FOR ALL MAKES AND MODELS**  
ADD TO ANY COLOR ANTIFREEZE

P-6193

**WARNING:** HARMFUL OR FATAL  
IF SWALLOWED. CONTAINS  
ETHYLENE GLYCOL. Read other  
cautionary information on back panel.

**1 U.S. Gal (3.78 L)**



# EXTENDED LIFE ANTIFREEZE & COOLANT

MEETS: ASTM D3306  
ASTM D4985

NAPA Extended Life Antifreeze/Coolant features coolant technology that is compatible for use in all automobiles and light duty trucks, regardless of make, model, year or original antifreeze color. Its inhibitors provide maximum cooling protection against damaging rust and corrosion.

NAPA Extended Life Antifreeze/Coolant can be used to top-off cooling systems filled with any automotive antifreeze. However, to realize the 150,000 miles or 5 years of maximum cooling system protection provided by NAPA Extended Life Antifreeze/Coolant, a complete cooling system flush and fill is required\*.

*\*Always follow vehicle's owner's manual for top-off requirements and specified maintenance.*

## DIRECTIONS:

**CAUTION: DO NOT REMOVE RADIATOR CAP WHEN ENGINE IS HOT.**  
Check owner's manual for specified maintenance and change intervals.

1. Drain radiator. Fill with fresh water. Flush cooling system for 10 minutes with engine running and heater on high.
2. Let engine cool, drain radiator.
3. Check owner's manual for cooling system capacity. Fill with enough new coolant to achieve a 50/50 antifreeze/water ratio.
4. Run engine 10 minutes with heater on high. When engine has cooled, check freeze protection with an antifreeze tester. Add more antifreeze or water to radiator as necessary to achieve desired freeze protection.
5. Periodically check radiator and reservoir levels. Top off with a 50/50 mixture of NAPA Extended Life Antifreeze/Coolant and water as needed.

## WARNING

Contains Ethylene Glycol (107-21-1), 2-Ethyl Hexanoic Acid, Sodium Salt (19766-89-3), Neodecanoic Acid, Sodium Salt (31548-27-3), Diethylene Glycol (111-46-6). Do not drink antifreeze or solution. Do not store in open or unlabeled containers. Avoid contact with eye, skin and clothing. Wash thoroughly after handling. Avoid breathing vapors or mists. Solution is poisonous to animals. Contains ethylene glycol and diethylene glycol. If swallowed, call a POISON CENTER or go to a hospital emergency room immediately. If inhaled, move to fresh air. Seek medical attention if symptoms persist. In case of contact, wash with water.

**KEEP OUT OF REACH OF CHILDREN.**

**WARNING:** Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

FREEZE/BOIL PROTECTION CHART <small>*Using a 15 PSI Pressure Cap</small>	% of Cooling System Capacity		PROTECTS FROM	
			Freezing Down to	Boiling Up to*
	50		-34°F	265°F
	60		-62°F	270°F
	70		-84°F	276°F

  

Cooling System Capacity In Quarts	Quarts of Antifreeze Required for Protection to Temperatures (°F) Shown										
	3	4	5	6	7	8	9	10	11	For best overall protection solution strengths within the blue color band are recommended.	
8	-7	-34	-69								
9	0	-21	-60	-70							
10	4	-12	-34	-62							
11	8	-6	-23	-47	-65						
12	10	0	-15	-34	-57						
13		3	-9	-25	-45	-64					
14		6	-5	-18	-34	-54	-68				
15		8	0	-12	-26	-43	-62				
16		10	2	-8	-19	-34	-52	-64			
17			5	-4	-14	-27	-42	-58	-69		
18			7	0	-10	-21	-34	-50	-62		
19			9	2	-7	-16	-28	-42	-56		
20			10	4	-3	-12	-22	-34	-48		

DISPOSING OF USED ANTIFREEZE & COOLANT: Dispose of contents and container in accordance with local and national regulations.

1EXT  
**EMBITTERED FORMULA**

P-6193 SDS 503



Made in the U.S.A. with domestic and imported materials

Manufactured for  
NAPA Distribution Centers  
Atlanta, GA