



GREEN ANTIFREEZE & COOLANT

FOR USE IN:

FORD & CHRYSLER 2000 AND EARLIER

GM 1995 AND EARLIER

ALL MAKES & MODELS 1989 AND EARLIER

P-6192

WARNING: HARMFUL OR FATAL
IF SWALLOWED. CONTAINS
ETHYLENE GLYCOL. Read other
cautionary information on back panel.

1 U.S. Gal (3.78 L)



GREEN ANTIFREEZE & COOLANT

MEETS: ASTM D-3306
ASTM D-4985
ASTM D-4340
Ford-ESE-M97B44-A
General Motors-GM 1825 M

NAPA Antifreeze/Coolant is a conventional green low silicate antifreeze containing inhibitors providing protection from freezing, overheating, rust and corrosion when used as recommended. This product has been formulated for use in automobiles and light duty trucks and protects all cooling system metal surfaces, including aluminum.

DIRECTIONS:

CAUTION: DO NOT REMOVE RADIATOR CAP WHEN ENGINE IS HOT.
Check owner's manual for specified maintenance and change intervals.

1. Drain radiator. Fill with fresh water. Flush cooling system for 10 minutes with engine running and heater on high.
2. Let engine cool, drain radiator.
3. Check owner's manual for cooling system capacity. Fill with enough new coolant to achieve a 50/50 antifreeze/water ratio.
4. Run engine 10 minutes with heater on high. When engine has cooled, check freeze protection with an antifreeze tester. Add more antifreeze or water to radiator as necessary to achieve desired freeze protection.
5. Periodically check radiator and reservoir levels. Top off with a 50/50 mixture of NAPA Green Antifreeze/Coolant and water as needed.

WARNING

Contains Ethylene Glycol (107-21-1), Diethylene Glycol (111-46-6), Sodium Nitrite (7632-00-0). Do not drink antifreeze or solution. Do not store in open or unlabeled containers. Avoid contact with eye, skin and clothing. Wash thoroughly after handling. Avoid breathing vapors or mists. Solution is poisonous to animals. Contains ethylene glycol and diethylene glycol. If swallowed, call a POISON CENTER or go to a hospital emergency room immediately. If inhaled, move to fresh air. Seek medical attention if symptoms persist. In case of contact, wash with water.

KEEP OUT OF REACH OF CHILDREN.

WARNING: Reproductive Harm - www.P65Warnings.ca.gov

FREEZE/BOIL PROTECTION CHART	% of Cooling System Capacity	PROTECTS FROM	
		Freezing Down to	Boiling Up to*
*Using a 15 PSI Pressure Cap	50	-34°F	265°F
	60	-62°F	270°F
	70	-84°F	276°F

Cooling System Capacity In Quarts	Quarts of Antifreeze Required for Protection to Temperature (°F) Shown										
	3	4	5	6	7	8	9	10	11	For best overall protection solution strengths within the blue color band are recommended.	
8	-7	-34	-69								
9	0	-21	-50	-70							
10	4	-12	-34	-62							
11	8	-6	-23	-47	-65						
12	10	0	-15	-34	-57						
13		3	-9	-25	-45	-64					
14		6	-5	-18	-34	-54	-68				
15			8	0	-12	-26	-43	-62			
16			10	2	-8	-19	-34	-52	-64		
17				5	-4	-14	-27	-42	-58	-69	
18				7	0	-10	-21	-34	-50	-62	
19				9	2	-7	-16	-28	-42	-56	
20				10	4	-3	-12	-22	-34	-48	

DISPOSING OF USED ANTIFREEZE & COOLANT: Dispose of contents and container in accordance with local and national regulations.

1GAL
EMBITTERED FORMULA

P-6192 SDS 210



Made in the U.S.A. with domestic and imported materials

Manufactured for
NAPA Distribution Centers
Atlanta, GA