



Prestone

COMMAND

PATENTED FORMULA

**HEAVY DUTY
ANTIFREEZE/
COOLANT**

ANTICONGELANTE/REFRIGERANTE
SERVICIO PESADO

CAT EC-1 COMPATIBLE.
For ANY Heavy Duty Engine

with

EXTENDED LIFE
TECHNOLOGY

con TECNOLOGÍA DE LARGA DURACIÓN

600,000 Mile Service Life

when extender added at 300,000 miles

Vida Útil de 600,000 Millas (965,600 km) al
agregar el extensor a las 300,000 millas (482,800 km)



SCAN HERE

P-6170

CONCENTRATE

1 GAL (3.78 L)
3,78 L (1 GALÓN)

WARNING: HARMFUL OR FATAL IF SWALLOWED. Read carefully other cautions on back panel.

ADVERTENCIA: DAÑINO O FATAL SI SE INGIERE. Lea atentamente otras precauciones al reverso.



**PATENTED
FORMULA**

**Prestone Command®
HD Extended Life (ELC)**

Antifreeze/Coolant

is intended for use and compatible with ANY heavy duty antifreeze/coolant in ANY diesel powered commercial vehicle or stationary engine with aluminum or other engine metals. Its patented technologically advanced red formulation is based upon a concentrated blend of premium long-lasting inhibitors designed to guard against temperature extremes, rust, corrosion, scale and premature water pump failure. **Prestone Command HD Extended Life (ELC) Antifreeze/Coolant** is a blend of antifreeze and demineralized water designed to provide up to 600,000 miles/12,000 hours* of protection. When used as directed, **Prestone Command HD Extended Life (ELC) Antifreeze/Coolant** May be added to the antifreeze/coolant of any heavy duty commercial or stationary engine.

**With extender added at 300,000 miles/6,000 hours. Provides extended life protection when flushed and filled according to the directions in the vehicle manufacturer's owner's manual. Maintains extended protection when added to any HD ELC antifreeze/coolant. Is compatible with other ELC heavy duty coolants (users must continue to add extender based upon the treat rates recommended by the engine manufacturer).*

Specifications and Performance: **Prestone Command HD Extended Life (ELC)** meets or exceeds performance requirements of the major engine manufacturer's and the following specifications • **TMC RP329 • ASTM D6210 • ASTM D4985 • ASTM D3306 • SAE J1941**

PROTECTION	FREEZE-UP Protection	BOIL-OVER Protection†	CORROSION Protection
Recommended 50% Prestone Command ELC 50% Water	- 34° F	+265° F	Meets or exceeds ASTM D3306, ASTM D4985, ATSM D6210
Maximum 70% Prestone Command ELC 30% Water	- 84° F	+276° F	

† Using a 15 lb. pressure cap in good condition.

WARNING: CONTAINS ETHYLENE GLYCOL (107-21-1), DIETHYLENE GLYCOL (111-46-6) AND PROPRIETARY INHIBITORS.

DO NOT DRINK ANTIFREEZE OR SOLUTION. DO NOT STORE IN OPEN OR UNLABELED CONTAINERS. AVOID CONTACT WITH EYE, SKIN AND CLOTHING. WASH THOROUGHLY AFTER HANDLING. AVOID BREATHING VAPORS OR MISTS. SOLUTION IS POISONOUS TO ANIMALS. CONTAINS ETHYLENE GLYCOL AND DIETHYLENE GLYCOL. IF SWALLOWED, CALL A POISON CENTER OR GO TO A HOSPITAL EMERGENCY ROOM IMMEDIATELY. IF INHALED, MOVE TO FRESH AIR. SEEK MEDICAL ATTENTION IF SYMPTOMS PERSIST. IN CASE OF CONTACT, WASH WITH WATER.

KEEP OUT OF REACH OF CHILDREN

ADVERTENCIA: CONTIENE ETILENGLICOL (107-21-1), DIETILENGLICOL (111-46-6) E INHIBIDORES PATENTADOS.

NO BEBA LA SOLUCIÓN ANTICONGELANTE. NO ALMACENE EN ENVASES ABIERTOS O SIN ETIQUETA. EVITE EL CONTACTO CON LOS OJOS, LA PIEL Y LA ROPA. LÁVESE BIEN DESPUES DE MANIPULARLO. EVITE RESPIRAR LOS VAPORES O ROCIOS. LA SOLUCIÓN ES TÓXICA PARA LOS ANIMALES. CONTIENE ETILENGLICOL Y DIETILENGLICOL. SI SE INGIERE, LLAME A UN CENTRO DE CONTROL DE ENVENENAMIENTOS O VAYA A LA SALA DE EMERGENCIA DE UN HOSPITAL INMEDIATAMENTE. SI SE INHALA, SALGA AL AIRE FRESCO. OBTENGA ATENCIÓN MÉDICA SI LOS SINTOMAS PERSISTEN. EN CASO DE CONTACTO, LAVE CON AGUA.

MANTÉNGASE FUERA DEL ALCANCE DE LOS NIÑOS.

**HEAVY DUTY
EXTENDED LIFE ELC
ANTIFREEZE/COOLANT**

CAUTION: Do not remove cooling system cap while cooling system is hot. Do not store antifreeze/coolant in open or unlabeled containers. After use, tighten child resistant cap and wash exposed skin with soap and water.

DIRECTIONS: Check the specific maintenance and changeover intervals, antifreeze/coolant to water ratio, cooling system capacity, and service instructions recommended for your vehicle. Start with a cool and clean cooling system. A minimum of 40%, maximum of 60% antifreeze/coolant is recommended to achieve optimal freeze/boil and corrosion protection, never exceed 70%. Follow the cooling system service instructions recommended for your vehicle when Flushing and Filling your cooling system.



For more information, scan this code or visit our website
WWW.PRESTONECOMMAND.COM

TOP OFF - Check coolant level frequently and top off with the desired ratio of Prestone Command HD Extended Life (ELC) Concentrate and quality water as needed.

Mixing Coolant Technology: Diluting the antifreeze/coolant in your cooling system with different coolant technologies has the potential of reducing protection levels. Refer to engine manufacturer or TMC (RP338A and RP362) for recommendations.

DISPOSING OF USED ANTIFREEZE/COOLANT: Dispose of contents and container in accordance with local and national regulations.

Para instrucciones en español, visite www.PrestoneCommand.com

WARNING: Reproductive Harm - www.P65Warnings.ca.gov
ADVERTENCIA: Daño Reproductivo - www.P65Warnings.ca.gov



Recyclable Bottle
This bottle may not be recyclable in your area

PRESTONE PRODUCTS CORPORATION
69 Eagle Road, Danbury, CT 06810
AFC11000 P-6100 SDS 647
Visit WWW.PRESTONECOMMAND.COM
Questions? Call 1-888-269-0750
©2018 Prestone Products Corporation
Made in the U.S.A. with domestic and imported materials
Patents: Prestone.com/patents