



Visit our site or call for specific guarantee requirements and limitations.

1-888-269-0750

Prestone® Concentrate Antifreeze/Coolant is the ideal solution to help your engine last longer. Fortified with patented COR-GUARD[™] corrosion inhibitors, Prestone protects against corrosion and helps keep your cooling system running more efficiently. Keep your entire cooling system, including your radiator and water pump, free from the damaging effects of worn-out antifreeze. Use Prestone, the antifreeze specifically designed for the sophisticated engines in today's cars and light duty trucks.

- All makes, all models of ANY car or light duty truck Works with ANY color antifreeze Will NOT void vehicle manufacturer's warranty Up to 5 years or 150,000 miles of protection"

*Prestone is the number one selling Antifreeze/Coolant brand in North America.

with a complete hush and imper manufacturers recommendations.			
PROTECTION	FREEZE-UP Protection	BOIL-OVER Protection [†]	CORROSION Protection
<i>MINIMUM</i> 50% Antifreeze 50% Water	-34°F	+265°F	Meets or exceeds ASTM D3306, and ASTM D4985.
<i>MAXIMUM</i> 70% Antifreeze 30% Water	-84°F	+276°F	

†Using a 15 lb. pressure cap in good condition.

WARNING: Reproductive Harm - www.P65Warnings.ca.gov

WARNING: Contains ethylene glycol (107-21-1), diethylene glycol (111-46-6), and proprietary inhibitors.

DO NOT drink antifreeze or solution. Do not store in open or unlabeled containers. Avoid contact with eye, skin and clothing. Wash thoroughly after handling. Avoid breathing vapors or mists. Solution is poisonous to animals.

IF SWALLOWED, CALL A POISON CENTER OR GO TO A HOSPITAL EMERGENCY ROOM IMMEDIATELY. If inhaled, move to fresh air. Seek medical attention if symptoms persist. In case of contact, wash with water. **KEEP OUT OF REACH OF CHILDREN AND PETS.**

trusted quality since 1927 CONCENTRATE

ANTIFREEZE/COOLANT

CAUTION: DO NOT OPEN THE COOLING SYSTEM WHEN THE ENGINE IS HOT. Refer to service manual for any special cooling system service instructions. After use, please tighten child-resistant cap and wash hands.

‡Based on lab testing vs. the leading branded competitor.

Flush and Fill

Requires 1-2 gallons of Prestone **Concentrate Antifreeze/Coolant**



Rejuvenates the entire cooling system, protects against corrosion and provides ultimate freeze-up and boil-over protection

For a badly neglected system

You can use Prestone Flush+Cleaner. According to directions; fill half the volume of the cooling system with Prestone Concentrate Antifreeze/ Coolant; top off with distilled water until full.



For more information on how to flush and fill your system, scan this code or visit our website www.prestone.com

DISPOSING OF USED ANTIFREEZE/COOLANT: Dispose of contents and containers in accordance with local and national regulations.



69 Eagle Road, Danbury, CT 06810 AF2000 SDS 501 P-5871

Visit WWW.PRESTONE.COM Questions? Call 1-888-269-0750 ©2018 Prestone Products Corporation Made in the U.S.A. from foreign and domestic material Patents: Prestone.com/patents



Prop65 Warning: www.gov Warning in box:

13pt 8pt 11pt