

Prestone®

Trusted Quality Since 1927



EXTENDED LIFE 50/50 PREDILUTED ANTIFREEZE/COOLANT DO NOT ADD WATER

For use in GM Cars and Trucks Requiring DEX-COOL® Coolant under GMW 3420 (GM6277M).

Compatible with other DEX-COOL approved coolants. Meets GMW 3420 (GM6277M), Ford WSS-M97B44-D2, and property and performance specifications of Chrysler MS12106 (MS-7170 & MS-9769).

DISPOSAL OF USED ANTIFREEZE/COOLANT: OBSERVE LOCAL LAWS AND REGULATIONS. DO NOT DRAIN ONTO THE GROUND OR INTO STORM DRAINAGE SYSTEMS.

ATTENTION: EMPTIED CONTAINER RETAINS VAPOR AND PRODUCT RESIDUE, OBEY ALL LABEL WARNINGS. DO NOT CUT OR WELD ON OR NEAR THE CONTAINER. DO NOT REUSE UNLESS THOROUGHLY CLEANED.

BEFORE USING, READ AND UNDERSTAND THE CURRENT PRESTONE PRODUCTS CORPORATION SAFETY DATA SHEET FOR THIS PRODUCT.

SDS 484

55 GALLONS

PRODUCT CODE

AF850-55/F

DISTRIBUTED BY:
PRESTONE PRODUCTS CORPORATION
69 Eagle Road, Danbury, CT 06810
1-888-269-0750

P-6628

WARNING!: HARMFUL IF SWALLOWED. SUSPECTED OF DAMAGING THE UNBORN CHILD. MAY CAUSE DAMAGE TO KIDNEYS THROUGH PROLONGED OR REPEATED EXPOSURE.

PREVENTION: OBTAIN SPECIAL INSTRUCTIONS BEFORE USE. DO NOT HANDLE UNTIL ALL SAFETY PRECAUTIONS HAVE BEEN READ AND UNDERSTOOD. DO NOT BREATHE MIST OR VAPORS. WASH EXPOSED SKIN THOROUGHLY AFTER HANDLING. DO NOT EAT, DRINK, OR SMOKE WHEN USING THIS PRODUCT. WEAR PROTECTIVE GLOVES AND EYE PROTECTION.

RESPONSE: IF SWALLOWED: CALL A POISON CENTER OR PHYSICIAN IF YOU FEEL UNWELL. RINSE MOUTH. IF EXPOSED OR CONCERNED: GET MEDICAL ADVICE.

DISPOSAL: STORE LOCKED UP. DISPOSE OF CONTENTS AND CONTAINER



PROTECTION	FREEZE-UP Protection	BOILOVER Protection†	CORROSION Protection
Prestone DEXCOOL 50/50 Prediluted antifreeze/coolant	- 34° F	+265° F	Meets or exceeds ASTM D3306, STM D4985 and GMW 3420.

†Using a 15 lb. pressure cap in good condition.

CONTAINS: Ethylene Glycol (107-21-1), Water (7732-18-5), 2-Ethyl Hexanoic Acid, Sodium Salt (19766-89-3), Diethylene Glycol (111-46-6).

SUPPLEMENTAL LABELING: SUDDEN RELEASE OF HOT ORGANIC CHEMICAL VAPORS OR MISTS FROM PROCESS EQUIPMENT OPERATING AT ELEVATED TEMPERATURE AND PRESSURE, OR SUDDEN INGRESS OF AIR INTO VACUUM EQUIPMENT, MAY RESULT IN IGNITIONS WITHOUT ANY OBVIOUS SOURCES OF IGNITION. PUBLISHED "AUTOIGNITION" OR "IGNITION" TEMPERATURES CANNOT BE TREATED AS SAFE OPERATING TEMPERATURES IN CHEMICAL PROCESSES WITHOUT ANALYSIS OF THE ACTUAL PROCESS CONDITIONS. USE OF THIS PRODUCT IN ELEVATED TEMPERATURE APPLICATIONS SHOULD BE THOROUGHLY EVALUATED TO ASSURE SAFE OPERATING CONDITIONS.

FIRST AID: INHALATION: REMOVE THE VICTIM TO FRESH AIR. IF BREATHING HAS STOPPED ADMINISTER ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, HAVE MEDICAL PERSONNEL ADMINISTER OXYGEN. GET MEDICAL ATTENTION.

SKIN CONTACT: REMOVE CONTAMINATED CLOTHING. IMMEDIATELY WASH CONTACTED AREA THOROUGHLY WITH SOAP AND WATER. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION.

EYE CONTACT: IMMEDIATELY FLUSH EYES WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES. GET MEDICAL ATTENTION IF IRRITATION PERSISTS.

INGESTION: SEEK IMMEDIATE MEDICAL ATTENTION. IMMEDIATELY CALL LOCAL POISON CONTROL CENTER OR GO TO AN EMERGENCY DEPARTMENT. NEVER GIVE ANYTHING BY MOUTH TO OR INDUCE VOMITING IN AN UNCONSCIOUS OR DROWSY PERSON. BEFORE USING CONSULT THE SAFETY DATA SHEET FOR THIS PRODUCT.



WARNING: Reproductive Harm - www.P65Warnings.ca.gov

DEX-COOL® and the DEX-COOL™ logo are trademarks of General Motors Corporation

License no.: DC-002

